

REVISIONS

LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Changes in accordance with NOR 5962-R134-94.	94-03-24	M. A. Frye
B	Changes in accordance with NOR 5962-R038-95.	94-11-29	M. A. Frye
C	Redrawn. Add case outline X. Technical and editorial changes throughout.	95-03-24	M. A. Frye
D	Drawing updated to reflect current requirements. - rrp	04-07-19	R. Monnin
E	Redrawn. Update paragraphs to MIL-PRF-38535 requirements. - drw	16-10-03	Charles F. Saffle

THE ORIGINAL FIRST PAGE OF THIS DRAWING HAS BEEN REPLACED.



REV																				
SHEET																				
REV																				
SHEET																				


REV STATUS OF SHEETS	REV	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
	SHEET	1	2	3	4	5	6	7	8	9	10	11	12				

PMIC N/A	PREPARED BY Dan Wonnell	<p align="center">DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990 http://www.landandmaritime.dla.mil</p>															
<p align="center">STANDARD MICROCIRCUIT DRAWING</p> <p>THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE</p> <p align="center">AMSC N/A</p>	CHECKED BY Charles E. Besore																
	APPROVED BY Michael A. Frye	<p align="center">MICROCIRCUIT, LINEAR, MICROPROCESSOR SUPERVISORY CIRCUITS, MONOLITHIC SILICON</p>															
	DRAWING APPROVAL DATE 92-03-26																
	REVISION LEVEL E		SIZE A	CAGE CODE 67268	5962-90712												
		SHEET 1 OF 12															

1. SCOPE

1.1 Scope. This drawing documents two product assurance class levels consisting of high reliability (device class Q and M) and space application (device class V). A choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). When available, a choice of Radiation Hardness Assurance (RHA) levels is reflected in the PIN.

1.2 PIN. The PIN is as shown in the following example:



1.2.1 RHA designator. Device classes Q and V RHA marked devices meet the MIL-PRF-38535 specified RHA levels and are marked with the appropriate RHA designator. Device class M RHA marked devices meet the MIL-PRF-38535, appendix A specified RHA levels and are marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device types. The device types identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	MAX690	Microprocessor watchdog/battery switchover/reset generator
02	MAX692	Microprocessor watchdog/battery switchover/reset generator
03	MAX694	Microprocessor watchdog/battery switchover/reset generator

1.2.3 Device class designator. The device class designator is a single letter identifying the product assurance level as follows:

<u>Device class</u>	<u>Device requirements documentation</u>
M	Vendor self-certification to the requirements for MIL-STD-883 compliant, non-JAN class level B microcircuits in accordance with MIL-PRF-38535, appendix A
Q or V	Certification and qualification to MIL-PRF-38535

1.2.4 Case outlines. The case outlines are as designated in MIL-STD-1835 as follows:

<u>Outline letter</u>	<u>Descriptive designator</u>	<u>Terminals</u>	<u>Package style</u>
P	GDIP1-T8 or CDIP2-T8	8	Dual-in-line
H	GDFP1-F10 or CDFP2-F10	10	Flat pack
X	CDFP3-F10	10	Flat pack
2	CQCC1-N20	20	Square leadless chip carrier

1.2.5 Lead finish. The lead finish is as specified in MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-90712
		REVISION LEVEL E	SHEET 2

1.3 Absolute maximum ratings. 1/

Supply voltage range (V _{CC})	-0.3 V dc to +6.0 V dc
Battery voltage range (V _{BATT})	-0.3 V dc to +6.0 V dc
All other inputs	-0.3 V dc to (V _{OUT} + 0.5 V)
Input current:	
V _{CC}	+200 mA
V _{BATT}	+50 mA
GND	+20 mA
Output current:	
V _{OUT}	Short circuit protected
All other outputs	+20 mA
Rate-of-rise, V _{BATT} , V _{CC}	+100 V/μs
Storage temperature range	-65°C to +160°C
Power dissipation (P _D)	500 mW 2/
Lead temperature (soldering, 10 seconds)	300°C
Thermal resistance, junction-to-case (θ _{JC})	+55°C/W
Thermal resistance, junction-to-ambient (θ _{JA})	+125°C/W

1.4 Recommended operating conditions.

Supply voltage (V _{CC}):	
Device types 01 and 03	4.75 V dc to 5.5 V dc
Device type 02	4.5 V dc to 5.5 V dc
Battery voltage (V _{BATT})	2.8 V
Ambient operating temperature range (T _A)	-55°C to +125°C

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-883 - Test Method Standard Microcircuits.
 MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

DEPARTMENT OF DEFENSE HANDBOOKS

MIL-HDBK-103 - List of Standard Microcircuit Drawings.
 MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these DLA documents are available online at <http://quicksearch.dla.mil> or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.
 2 Derate above +70°C: 8.0 mW/°C for case outline P, 5.26 mW/°C for case outlines H and X, and 9.09 mW/°C for case outline 2.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-90712
		REVISION LEVEL E	SHEET 3

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 as specified herein, or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. The individual item requirements for device class M shall be in accordance with MIL-PRF-38535, appendix A for non-JAN class level B devices and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein for device classes Q and V or MIL-PRF-38535, appendix A and herein for device class M.

3.2.1 Case outlines. The case outlines shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.3 Block diagram. The block diagram shall be as specified on figure 2.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked. For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device. For RHA product using this option, the RHA designator shall still be marked. Marking for device classes Q and V shall be in accordance with MIL-PRF-38535. Marking for device class M shall be in accordance with MIL-PRF-38535, appendix A.

3.5.1 Certification/compliance mark. The certification mark for device classes Q and V shall be a "QML" or "Q" as required in MIL-PRF-38535. The compliance mark for device class M shall be a "C" as required in MIL-PRF-38535, appendix A.

3.6 Certificate of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.6.1 herein). For device class M, a certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-HDBK-103 (see 6.6.2 herein). The certificate of compliance submitted to DLA Land and Maritime-VA prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and herein or for device class M, the requirements of MIL-PRF-38535, appendix A and herein.

3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 or for device class M in MIL-PRF-38535, appendix A shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change for device class M. For device class M, notification to DLA Land and Maritime-VA of change of product (see 6.2 herein) involving devices acquired to this drawing is required for any change that affects this drawing.

3.9 Verification and review for device class M. For device class M, DLA Land and Maritime, DLA Land and Maritime's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

3.10 Microcircuit group assignment for device class M. Device class M devices covered by this drawing shall be in microcircuit group number 105 (see MIL-PRF-38535, appendix A).

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-90712
		REVISION LEVEL E	SHEET 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions ^{1/} -55°C ≤ T _A ≤ +125°C V _{BATT} = 2.8 V unless otherwise specified	Group A subgroups	Device type	Limits ^{2/}		Unit	
					Min	Max		
BATTERY BACKUP SWITCHING								
Operating voltage range	V _{CC}		1, 2, 3	01, 03	4.75	5.5	V	
				02	4.5	5.5		
	V _{BATT}			01, 03	2.0	4.25		
				02	2.0	4.0		
Output voltage	V _{OUT}	I _{OUT} = 1 mA	1, 2, 3	All	V _{CC} -0.3		V	
		I _{OUT} = 50 mA			V _{CC} -0.5			
Battery output voltage backup mode	BATT _{OUT}	I _{OUT} = 250 μA, V _{CC} < V _{BATT} - 0.2 V	1, 2, 3	All	V _{BATT} -0.1		V	
Supply current (excluding I _{OUT})	I _{CC}	I _{OUT} = 1 mA	1	All		5	mA	
			2, 3					7
		I _{OUT} = 50 mA	1					10
			2, 3					15
Supply current in battery backup mode	I _{BATT}	V _{CC} = V, V _{BATT} = 2.8 V	1	All		1	μA	
			2, 3			10		
Battery standby current (- = charge + = discharge)	I _{BATTSB}	5.5 V > V _{CC} > V _{BATT} + 1 V	1	All	-0.1	+0.02	μA	
			2, 3			-1.0		+0.02
Battery switchover threshold V _{CC} - V _{BATT}	BATT _{SWTH}	Power up or power down	1, 2, 3	All	-200	+200	mV	
RESET AND WATCHDOG TIMING								
Reset voltage threshold	R _{TH}		1, 2, 3	01, 03	4.5	4.75	V	
				02	4.25	4.5		
Reset threshold hysteresis	R _{THH}		1, 2, 3	All		250	mV	

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-90712
		REVISION LEVEL E	SHEET 5

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions ^{1/} -55°C ≤ T _A ≤ +125°C V _{BATT} = 2.8 V unless otherwise specified	Group A subgroups	Device type	Limits ^{2/}		Unit
					Min	Max	
RESET AND WATCHDOG TIMING – continued							
Reset timeout delay	R _{DEL}	OSC SEL HIGH V _{CC} = 5 V	9	01, 02	35	70	ms
			10, 11		31	78	
			9	03	140	280	
			10, 11		126	310	
Watchdog timeout period, internal oscillator	WD _{INT}	Long period, V _{CC} = 5 V	9	All	1.0	2.25	s
			10, 11		0.9	2.42	
		Short period, V _{CC} = 5 V	9		70	140	ms
			10, 11		62	154	
Minimum WDI input pulse width	WDI _{PW}	V _{IL} = 0.4 V, V _{IH} = V _{CC} (0.8)	9	All	200		ns
			10, 11		300		
RESET output voltage high	R̄ _{VOH}	I _{SOURCE} = 1 μA, V _{CC} = 5 V	1, 2, 3	All	3.5		V
RESET output voltage low	R̄ _{VOL}	I _{SINK} = 1.6 mA, V _{CC} = 4.25 V	1	All		0.4	V
		I _{SINK} = 800 μA, V _{CC} = 4.25 V	2, 3			0.4	
RESET output short circuit current	R̄ _{Ios}	RESET = 0 V	1, 2, 3	All	1	25	μA
WDI input threshold logic low	WDI _{VIL}	V _{CC} = 5 V ^{3/, 4/}	1	All		0.8	V
			2, 3			0.4	
WDI input threshold logic high	WDI _{VIH}	V _{CC} = 5 V ^{3/, 4/}	1	All	3.5		V
			2, 3		4.0		
WDI input current	WDI _{IN}	WDI = V _{OUT}	1	All		50	μA
			2, 3			80	
		WDI = 0 V	1			-50	
			2, 3			-80	

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-90712
		REVISION LEVEL E	SHEET 6

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions <u>1/</u> -55°C ≤ T _A ≤ +125°C V _{BATT} = 2.8 V unless otherwise specified	Group A subgroups	Device type	Limits <u>2/</u>		Unit
					Min	Max	
POWER FAIL DETECTOR							
PFI input threshold	PFI _{VTH}	V _{CC} = +5 V <u>3/</u>	1, 2, 3	All	1.2	1.4	V
PFI input current	PFI _{IN}		1, 2, 3	All	-25	+25	nA
$\overline{\text{PFO}}$ output voltage high	$\overline{\text{PFO}}$ _{VOH}	I _{SOURCE} = 1 μA, V _{CC} = 5 V	1, 2, 3	All	3.5		V
$\overline{\text{PFO}}$ output voltage low	$\overline{\text{PFO}}$ _{VOL}	I _{SINK} = 3.2 mA	1	All		0.4	V
		I _{SINK} = 1.6 mA	2, 3			0.4	
$\overline{\text{PFO}}$ short circuit source current	$\overline{\text{PFO}}$ _{IOS}	PFI = V _{IH} , $\overline{\text{PFO}}$ = 0 V	1, 2, 3	All	1	25	μA

1/ For device types 01 and 03, V_{CC} = 4.75 V to 5.5 V, unless otherwise specified. For device type 02, V_{CC} = 4.5 V to 5.5 V, unless otherwise specified.

2/ The algebraic convention, whereby the most negative value is a minimum and the most positive a maximum, is used for these limits.

3/ The input voltage limits on PFI and WDI may be exceeded provided the input current is limited to less than 10 mA.

4/ WDI is guaranteed to be in the mid-level (inactive) state if WDI is floating and V_{CC} is in the operating voltage range. WDI is internally biased to 38 percent of V_{CC} with an impedance of approximately 125 kΩ.

**STANDARD
MICROCIRCUIT DRAWING**
DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990

SIZE
A

5962-90712

REVISION LEVEL
E

SHEET
7

Device type	01, 02, 03		
Case outline	H and X	P	2
Terminal number	Terminal symbol		
1	V _{OUT}	V _{OUT}	N/C
2	V _{CC}	V _{CC}	V _{BATT}
3	GND	GND	V _{OUT}
4	NC	PFI	V _{CC}
5	PFI	$\overline{\text{PFO}}$	GND
6	$\overline{\text{PFO}}$	WDI	NC
7	WDI	$\overline{\text{RESET}}$	NC
8	NC	V _{BATT}	NC
9	$\overline{\text{RESET}}$	----	NC
10	V _{BATT}	----	NC
11	----	----	NC
12	----	----	NC
13	----	----	$\overline{\text{PFO}}$
14	----	----	WDI
15	----	----	NC
16	----	----	NC
17	----	----	NC
18	----	----	NC
19	----	----	$\overline{\text{RESET}}$
20	----	----	NC

FIGURE 1. Terminal connections.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-90712
		REVISION LEVEL E	SHEET 8




FIGURE 2. Block diagram.

**STANDARD
MICROCIRCUIT DRAWING**
DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990

SIZE
A

5962-90712

REVISION LEVEL
E

SHEET
9

4. VERIFICATION

4.1 Sampling and inspection. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. For device class M, sampling and inspection procedures shall be in accordance with MIL-PRF-38535, appendix A.

4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection. For device class M, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection.

4.2.1 Additional criteria for device class M.

- a. Burn-in test, method 1015 of MIL-STD-883.
 - (1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.
 - (2) T_A = +125°C, minimum.
- b. Interim and final electrical test parameters shall be as specified in table II herein.

4.2.2 Additional criteria for device classes Q and V.

- a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.
- b. Interim and final electrical test parameters shall be as specified in table II herein.
- c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in MIL-PRF-38535, appendix B.

4.3 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-PRF-38535. Inspections to be performed shall be those specified in MIL-PRF-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4 Conformance inspection. Technology conformance inspection for classes Q and V shall be in accordance with MIL-PRF-38535 including groups A, B, C, D, and E inspections, and as specified herein. Quality conformance inspection for device class M shall be in accordance with MIL-PRF-38535, appendix A and as specified herein. Inspections to be performed for device class M shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-90712
		REVISION LEVEL E	SHEET 10

4.4.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 4, 5, 6, 7, and 8 in table I, method 5005 of MIL-STD-883 shall be omitted.

TABLE II. Electrical test requirements.

Test requirements	Subgroups (in accordance with MIL-STD-883, method 5005, table I)	Subgroups (in accordance with MIL-PRF-38535, table III)	
	Device class M	Device class Q	Device class V
Interim electrical parameters (see 4.2)	1	1	1
Final electrical parameters (see 4.2)	1, 2, 3, 9, 10, 11 <u>1/</u>	1, 2, 3, 9, 10, 11 <u>1/</u>	1, 2, 3, 9, 10, 11 <u>1/</u>
Group A test requirements (see 4.4)	1, 2, 3, 9, 10, 11	1, 2, 3, 9, 10, 11	1, 2, 3, 9, 10, 11
Group C end-point electrical parameters (see 4.4)	1, 9	1, 9	1, 2, 3, 9, 10, 11
Group D end-point electrical parameters (see 4.4)	1, 9	1, 9	1, 9
Group E end-point electrical parameters (see 4.4)	---	---	---

1/ PDA applies to subgroup 1.

4.4.2 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table II herein.

4.4.2.1 Additional criteria for device class M. Steady-state life test conditions, method 1005 of MIL-STD-883:

- a. Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.
- b. $T_A = +125^\circ\text{C}$, minimum.
- c. Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.4.2.2 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-90712
		REVISION LEVEL E	SHEET 11

4.4.3 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table II herein.

4.4.4 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein).

- a. End-point electrical parameters shall be as specified in table II herein.
- b. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535 for the RHA level being tested. For device class M, the devices shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535, appendix A for the RHA level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table I at $T_A = +25^{\circ}\text{C} \pm 5^{\circ}\text{C}$, after exposure, to the subgroups specified in table II herein.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor prepared specification or drawing.

6.1.2 Substitutability. Device class Q devices will replace device class M devices.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

6.3 Record of users. Military and industrial users should inform DLA Land and Maritime when a system application requires configuration control and which SMD's are applicable to that system. DLA Land and Maritime will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DLA Land and Maritime-VA, telephone (614) 692-8108.

6.4 Comments. Comments on this drawing should be directed to DLA Land and Maritime-VA, Columbus, Ohio 43218-3990, or telephone (614) 692-0540.

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535 and MIL-HDBK-1331.

6.6 Sources of supply.

6.6.1 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in MIL-HDBK-103 and QML-38535. The vendors listed in MIL-HDBK-103 and QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DLA Land and Maritime-VA and have agreed to this drawing.

6.6.2 Approved sources of supply for device class M. Approved sources of supply for class M are listed in MIL-HDBK-103. The vendors listed in MIL-HDBK-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DLA Land and Maritime-VA.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-90712
		REVISION LEVEL E	SHEET 12

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 16-10-03

Approved sources of supply for SMD 5962-90712 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DLA Land and Maritime-VA. This information bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535. DLA Land and Maritime maintains an online database of all current sources of supply at <https://landandmaritimeapps.dla.mil/programs/smcr/>.

Standard microcircuit drawing PIN <u>1/</u>	Vendor CAGE number	Vendor similar PIN <u>2/</u>
5962-9071201MHA	<u>3/</u>	MAX690MFB/883B
5962-9071201MXC	<u>3/</u>	MAX690MFB/883B
5962-9071201MPA	1ES66	MAX690MJA/883B
5962-9071201M2C	<u>3/</u>	MAX690MLP/883B
5962-9071202MHA	<u>3/</u>	MAX692MFB/883B
5962-9071202MXC	<u>3/</u>	MAX692MFB/883B
5962-9071202MPA	1ES66	MAX692MJA/883B
5962-9071202M2C	1ES66	MAX692MLP/883B
5962-9071203MHA	<u>3/</u>	MAX694MFB/883B
5962-9071203MXC	<u>3/</u>	MAX694MFB/883B
5962-9071203MPA	1ES66	MAX694MJA/883B
5962-9071203M2C	1ES66	MAX694MLP/883B

- 1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.
- 2/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.
- 3/ Not available from an approved source of supply.

Vendor CAGE
number

1ES66

Vendor name
and address

Maxim Integrated
160 Rio Robles
San Jose, CA 95134

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.