



mm	INCH
0.013	.0005
0.36	.014
2.16	.085
11.94	.470
16.00	.630
36.20	1.425
46.79	1.842
60.45	2.380

NOTES:

1. Dimensions are in millimeters.
2. The US government preferred system of measurement is the metric SI system. However, since this item was originally designed using inch-pound units of measurement, in the event of conflict between the metric and inch-pound units, the inch-pound units shall take precedence.

Figure 1. Connector, receptacle, 24 position, flat cable, locking.

Vibration. The connector, or hardware when assembled to the connector, shall exhibit no evidence of breaking, cracking, or loosening of parts when subjected to vibration of 10-55-10 Hz traversed in 1 minute at 1.52 millimeters (.060 inch) total excursion for 2 hours in each of three mutually perpendicular planes.

Physical shock. The connector or hardware when assembled to the connector, shall exhibit no evidence of breaking, cracking, or loosening of parts when subjected to 50 G's half-sine wave shock of 11 milliseconds duration, 3 shocks in each direction applied along the three mutually perpendicular planes for a total of 18 shocks.

Regulatory requirements. This section is not applicable to this CID.

Quality assurance provisions.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection, examination, and test requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections, examinations, or tests set forth in this description where such inspections, examinations, and tests are deemed necessary to assure supplies and services conform to prescribed requirements.

Contractor certification statement. The contractor shall certify and maintain objective quality evidence that the product offered meets the requirements of this CID, and that the product conforms to the producer's own drawings, specifications, standards, quality assurances practices, and is the same as the product provided as a bid sample. The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Certificate of compliance. A certificate of compliance shall accompany all connectors supplied to this CID.

Packaging.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, labeling, and marking shall be as specified in the contract or purchase order.

Notes. This section contains relevant information which is useful to buyers, users, and suppliers in the process of acquiring the item, but is not mandatory.

Referenced document.

Other Publication

INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS (IEEE)

IEEE 488 - IEEE Standard Digital Interface for Programmable Instrumentation.

(Applications for copies should be addressed to the Institute of Electrical and Electronics Engineers (IEEE), IEEE Service Center, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331.)

Ordering data. Acquisition documents should specify the following:

- a. CID document number and revision and CID PIN.
- b. Quality assurance provisions.
- c. Packaging requirements.

Comments. Comments on this CID should be directed to Defense Electronics Supply Center, 1507 Wilmington Pike, ATTN: DESC-EMT, Dayton, OH 45444-5000, or telephone (513) 296-5391.

A-A-55140

Source of supply. A suggested source of supply is listed in table I. Additional sources will be added as they become available.

TABLE I. Suggested source of supply.

CID PIN A-A-55140-	Vendor commercial PIN	Vendor CAGE number
01	554434-1	00779

Vendor CAGE
number

00779

Vendor name
and address

AMP, Incorporated
470 Friendship Road
Harrisburg, PA 17111-1203

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - 7FXE

PREPARING ACTIVITY:

DLA-ES

(Project 5935-D426)