



| CID PIN AA55500/01 | A Max | B | | C | | D | |
|-----------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| | | Min | Max | Min | Max | Min | Max |
| -001 | 3.05 (.120) | 2.95 (.116) | 3.15 (.124) | 4.25 (.167) | 5.10 (.201) | 1.00 (.039) | 2.00 (.079) |
| -002 | 3.05 (.120) | 2.95 (.116) | 3.15 (.124) | 8.65 (.341) | 9.60 (.378) | 1.00 (.039) | 2.00 (.079) |
| -003 | 2.90 (.114) | 4.40 (.173) | 4.80 (.189) | 8.55 (.337) | 9.25 (.364) | 1.00 (.039) | 1.40 (.055) |

NOTES:

1. Dimensions are in millimeters (inches in parentheses).
2. The US Government preferred system of measurement is the metric SI system. However, this item was originally designed using inch-pound units of measurement. In the event of conflict between the metric and inch-pound units, the inch-pound units shall take precedence.

Figure 1. Configuration and dimensions.

5. PACKAGING. Packaging shall be as specified in A-A-55500.

6. NOTES.

6.1 PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See section 2 for PIN format example.

6.2 CAGE code. For ordering purposes, inventory control, and submission of these shielding beads to DESC under the Military Parts Control Advisory Group (MPCAG) evaluation program, CAGE code 58536 should be used.

TABLE I. DC resistance and impedance.

| CID PIN AA55500/01 | DC resistance max (ohms) | Impedance (ohms) | |
|-----------------------|------------------------------------|------------------|---------|
| | | 25 MHz | 100 MHz |
| -001 | .0006 | 23 min | 47 ±20% |
| -002 | .0009 | 45 min | 95 ±20% |
| -003 | .0009 | 45 min | 95 ±20% |

6.3 Source of documents. This section is not applicable to this CID.

6.4 Ordering data. Ordering data shall be as specified in A-A-55500.

6.5 Commercial products. As part of the market analysis and research effort, this CID was coordinated with the following manufacturers (MFGR) of commercial products. At the time of CID preparation and coordination, these MFGRs were known to have commercial products that would meet the requirements of this CID. (NOTE: This information should not be considered as a list of approved MFGRs or be used to restrict procurement to only the MFGRs shown.)

MFGR's CAGE

34899

MFGR's name and address

Fair-Rite Products Corporation
One Commercial Row
Walkill, NY 12589
(914) 895-2055

6.6 Part number (P/N) suppression data. This CID supersedes the following MFGR's P/Ns as shown. This information is being provided to assist in reducing proliferation in the government inventory system.

| Dash number (see table I) AA55500/01- | MFGR CAGE | MFGR P/N <u>1/</u> |
|---|-----------|-------------------------|
| 001 | 34899 | <u>2/</u> 2743019447 |
| 002 | 34899 | <u>2/ 3/</u> 2743021446 |
| 003 | 34899 | <u>2/</u> 2743037447 |

- 1/ The MFGR's P/N shall not be used for procurement to the requirements of this CID. At the time of preparation of this CID, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown.
- 2/ A "7" in the tenth digit of the manufacturer's part identification number indicates that the items are supplied in a taped and reel configuration. Taped and reel quantities are limited to exact multiples of 2,800 pieces. A "6" in the tenth digit indicates the items shall be provided as loose pieces. Quantities other than multiples of 2,800 pieces will be supplied as loose pieces. For this CID, tape and reel options should be specified in the ordering requirements (see A-A-55500, 6.2d).
- 3/ Manufacturer's part identification number specified above is a single piece part.

6.7 Government users. To acquire information on obtaining these surface mount shielding beads from the Government inventory system, contact Defense Electronics Supply Center, ATTN: DESC-EOP, 1507 Wilmington Pike, Dayton, OH 45444-5765, or telephone (513) 296-6656.

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - 7FXE

Preparing Activity:

DLA-ES

Project 5950-D248