

INCH-POUND

MIL-DTL-17/84C
31 October 2014
SUPERSEDING
MIL-C-17/84B
18 July 1985

DETAIL SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, FLEXIBLE, COAXIAL,
50 OHMS, M17/84-RG223

Inactive for new design after 13 August 1993. For
new design use MIL-DTL-17/194.

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-17.

NOTE: This cable uses PVC material and is not to be used in enclosed environments or shipboard applications. The replacements that are to be used in enclosed areas or shipboard applications are referenced in the following table.

The Air Force has restricted use of PVC in aerospace and ground support applications.

Cables listed on the current QPL may continue to be manufactured and supplied for existing enclosed applications only for a period not to exceed 3 years from the date of this specification.

TABLE I. Supersession and cross reference data.

Current Part or Identifying Number (PIN)	Replacement PIN
M17/84-RG223	M17/194-00001




FIGURE 1. Configuration.

MIL-DTL-17/84C

TABLE II. Description.

Components	Construction details
Inner conductor	Solid silver-coated copper wire. Overall diameter: 0.035 inch \pm 0.001.
Dielectric core	Type A-1: Solid, polyethylene. Diameter: 0.116 inch \pm 0.004.
Outer conductor	Double braid of AWG #36 silver-coated copper wire. Diameter: 0.176 inch maximum.
Inner braid	Coverage: 95.0% nominal Carriers: 16 Ends: 7 Picks/inch: 11.5 \pm 10%
Outer braid	Coverage: 94.2% nominal Carriers: 16 Ends: 7 Picks/inch: 15.0 \pm 10%
Jacket	Type IIa: PVC Diameter: 0.212 inch \pm 0.004.

ENGINEERING INFORMATION

Continuous working voltage: 1,400 V rms, maximum.

Operating frequency: 12.4 GHz, maximum.

Velocity of propagation: 65.9 percent, nominal.

Power rating: See figure 2.

Operating temperature range: -40°C to +85°C.

Inner conductor properties:

DC resistance (maximum at 20°C): 0.897 ohm per 100 feet.

Elongation: 25 percent, minimum.

Tensile strength: Not applicable.

Engineering notes: This cable useful in general purpose, medium low temperature applications.
(See connector series "TNC", "BNC" and "SMA" in accordance with MIL-PRF-39012.)

MIL-DTL-17/84C

REQUIREMENTS

Dimensions, configuration, and description: See figure 1 and table II.

Environmental and mechanical:

Visual and mechanical examination:

Out-of-roundness: Not applicable.

Eccentricity: 10 percent, maximum.

Adhesion of conductors:

Inner conductor to core: 2 pounds, minimum; 20 pounds, maximum.

Aging stability: $+98^{\circ}\text{C} \pm 2^{\circ}\text{C}$.

Stress crack resistance: Not applicable.

Outer conductor integrity: Not applicable.

Cold bend: $-55^{\circ}\text{C} \pm 2^{\circ}\text{C}$.

Dimensional stability: $+85^{\circ}\text{C} \pm 2^{\circ}\text{C}$.

Inner conductor from core: 0.062 inch, maximum.

Inner conductor from jacket: 0.125 inch, maximum.

Contamination: Applicable.

Bendability: Not applicable.

Flammability: Not applicable.

Weight: 0.041 pound per foot, maximum.

Electrical:

Continuity: Applicable.

Spark test: 5,000 V rms, +10%, -0%.

Voltage withstanding: 5,000 V rms, +10%, -0%.

Insulation resistance: Not applicable.

Corona extinction voltage: 1,900 V rms, minimum.

Characteristic impedance: 50 ohms ± 2 .

Attenuation: See figure 2.

MIL-DTL-17/84C

Structural return loss: See figure 3.

Capacitance: 32.2 pF per foot, maximum.

Capacitance stability: Not applicable.

Capacitance unbalance: Not applicable.


Transmission unbalance: Not applicable.

Mechanically induced noise voltage: Not applicable.

Time delay: Not applicable.

PIN: M17/84-RG223. See table I.

MIL-DTL-17/84C



MAXIMUM ATTENUATION ———

MAXIMUM POWER - - - - -

AT 25°C SEA LEVEL

* At 12,400 GHz.

FIGURE 2. Power rating and attenuation.

MIL-DTL-17/84C




FIGURE 3. Structural return loss.

MIL-DTL-17/84C

Revision notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this revision. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-17, this document references the following:

MIL-PRF-39012
MIL-DTL-17/194

CONCLUDING MATERIAL

Custodians:

Army – CR
Navy – EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 6145-2014-039)

Review activities:

Army – AR, AT, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 19, 99
DLA - IS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.