


DETAIL SPECIFICATION SHEET

ADAPTER ASSEMBLY, STRAIGHT, SWIVEL FLANGE TO HOSE

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-27272.



NOTES:

- 1. Dimension A, see table II, is the dimension between the hose end of the socket and the free end of the insert when the socket is assembled on the nipple subassembly.
- 2. Socket may be hex or 2-flat-sides.

FIGURE 1. Adapter assembly illustration.

MS27054E

REQUIREMENTS:

Adapter assembly illustration. See figure 1.

Intended use. This adapter is intended for use with hose conforming to MIL-DTL-27267.

Materials. Material and material codes see table I. See applicable specification sheet and MIL-DTL-27272 for material of other components identified in table II for their material requirements.

TABLE I. Materials and material codes.

Material code	Material
Blank	Combination of aluminum alloy and corrosion-resistant steel (CRES)
C	CRES

TABLE II. Adapter assembly composition. 1/ 2/

Size and material code	Nipple subassembly size and material code	Sleeve size and material code	Socket size and material code	A <u>4/</u> max inch (mm)
	MS27062 <u>3/</u>			
-8C	-8C	-8C	-8C	2.04 (51.8)
-8	-8			
-10C	-10C	-10C	-10C	2.17 (55.1)
-10	-10			
-12C	-12C	-12C	-12C	2.36 (59.9)
-12	-12			
-16C	-16C	-16C	-16C	2.46 (62.5)
-16	-16			
-20C	-20C	-20C	-20C	2.77 (70.4)
-20	-20			
-24C	-24C	-24C	-24C	2.87 (72.9)
-24	-24			

1/ Dimensions are in inches.

2/ Metric equivalents are given for general information only.

3/ MS27062, MS27069 and MS27070 shall be dry film lubricated in accordance with table III, dry film is applied in accordance with MS27062, MS27069 or MS27070 as applicable.

4/ See figure 1.

MS27062, MS27069 and MS27070 parts shall be coated with the same type of dry film lubricant as indicated in the Part or Identifying Number (PIN), no mixing of dry film lubricants shall be used on an assembly unless it is of the types specified by the "blank" designator.

NOTE: Avoid using graphite dry film lubes with aluminum nipples because in a wet environment, graphite becomes corrosive to the aluminum.

MS27054E


TABLE III. Dry film designator.

Dry film designator	SAE class or type designator	Dry film characteristics
Blank	Any SAE class or type below	N/A
SAE-AS1701	SAE-AS1701 class	SAE-AS1701 temperature ranges °F (°C)
4	4	-65° to +1400°F (-54° to 760°C)
5	5	-65° to +850°F (-54° to 454°C)
6	6	-375° to +850°F (-226° to 454°C)
SAE-AS5272	SAE-AS5272 type	SAE-AS5272 temperature ranges. °F (°C)
7	Type I	-90° to 400°F (-68 to 204°C) endurance life of 250 min minimum
8	Type II	-90° to 400°F (-68° to 204°C) endurance life of 450 min minimum
9	Type III	Color 1 - Natural product color -90° to 400°F (-68 to 204°C) low Volatile organic compound with an endurance life of 450 min minimum
10	Type III	Color 2 - Black color -90° to 400°F (-68 to 204°C) low Volatile organic compound with an endurance life of 450 min minimum
Dry film designator	MIL classification	Dry film characteristics
MIL-PRF-46010 <u>1/</u>	---	MIL-PRF-46010 temperature ranges. °F (°C)
11	1	Color 1 natural product color, -90° to 400°F (-68 to 204°C) solvent resisting
12	2	Color 2 - Black color -90° to 400°F (-68 to 204°C) solvent resisting

1/ Not for aerospace usage.

MS27054E

PIN: The PIN consists of prefix "MS", the specification sheet number, dash number for straight adapter assembly size, letter for material, and a blank or number for dry film lubricant. Unassigned PIN's shall not be used.



PIN examples:

- MS27054-10 indicates a straight adapter assembly size 10, a combination of aluminum and CRES, and with dry film class designator "blank".
- MS27054-10C indicates a straight adapter assembly size 10, CRES with dry film class designator "blank".
- MS27054-10C4 indicates a straight adapter assembly size 10, CRES with dry film class designator 4.

Identification of product. The PIN and Government Entity (CAGE) Code or manufacturer's trademark shall be marked on a removable tag securely attached to the adapter.

Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Referenced documents shall be of the issue in effect on date of invitations for bid.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-27272, this document references the following:

MIL-DTL-27267	MS27070
MIL-PRF-46010	MS27077
MS20756	SAE-AS1701
MS27062	SAE-AS5272
MS27069	

MS27054E

CONCLUDING MATETIAL

Custodians:

Army - AV
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:

DLA - CC

(Project 4730-2013-095)

Review activities:

Army - AR, AT, MI
Navy - MC, SA, SH
Air Force - 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.