

INCH-POUND

MIL-DTL-32460  
SUPPLEMENT 1  
22 May 2013

## DETAIL SPECIFICATION

### ADAPTER, HYDRAULIC AND PNEUMATIC, 37° FLARE TUBE FITTING TO ORFS CONNECTORS, 1500 TO 3000 PSI AND -65°F TO 250°F, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-32460, dated 22 May 2013.

## SPECIFICATION SHEETS

- MIL-DTL-32460/1 - Fitting, Adapter, Straight, Hydraulic and Pneumatic,  
37° Flare, Male to ORFS Male
- MIL-DTL-32460/2 - Fitting, Adapter, 45° Elbow, Hydraulic and Pneumatic,  
37° Flare, Male to ORFS Male
- MIL-DTL-32460/3 - Fitting, Adapter, 90° Elbow, Hydraulic and Pneumatic,  
37° Flare, Male to ORFS Male
- MIL-DTL-32460/4 - Fitting, Adapter, Straight, Hydraulic and Pneumatic,  
37° Flare, Male to ORFS Bulkhead
- MIL-DTL-32460/5 - Fitting, Adapter, 45° Elbow, Hydraulic and Pneumatic,  
37° Flare, Male to ORFS Bulkhead
- MIL-DTL-32460/6 - Fitting, Adapter, 90° Elbow, Hydraulic and Pneumatic,  
37° Flare, Male to ORFS Bulkhead
- MIL-DTL-32460/7 - Fitting, Adapter, Straight, Hydraulic and Pneumatic,  
37° Flare, Male to ORFS, Female Swivel
- MIL-DTL-32460/8 - Fitting, Adapter, 45° Elbow, Hydraulic and Pneumatic,  
37° Flare, Male to ORFS, Female Swivel
- MIL-DTL-32460/9 - Fitting, Adapter, 90° Elbow, Hydraulic and Pneumatic,  
37° Flare, Male to ORFS, Female Swivel

## CONCLUDING MATERIAL

Custodians:  
Army – AT  
Navy – AS  
Air Force – 99  
DLA – CC

Preparing activity:  
DLA – CC

(Project 4730-2013-038)

Review activities:  
Army – AR  
Navy – CG, MC, SA, SH  
Air Force – 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.