

INCH-POUND

MIL-PRF-15733/44F
w/AMENDMENT 2
23 November 2015
SUPERSEDING
MIL-PRF-15733/44F
w/AMENDMENT 1
23 November 2005

PERFORMANCE SPECIFICATION SHEET
FILTERS, RADIO FREQUENCY INTERFERENCE,
STYLE FL45

This specification sheet is approved for use by all Departments
and Agencies of the Department of Defense.

The complete requirements for acquiring the filters described herein shall
consist of this specification sheet and the latest issue of MIL-PRF-15733.




FIGURE 1. Case and circuit configuration.



Dash number	A	B	C		D	E		F		G	H		J	K	L	Weight Max (grams)
	Ref	Ref	Min	Max	Max	Min	Max	Min	Max	Max	Min	Max	Max	Ref	Ref	
0001	.600 (15.24)	.336 (8.53)	.097 (2.46)	.167 (4.24)	.030 (0.76)	.079 (2.01)	.109 (2.77)	.177 (4.50)	.222 (5.64)	.030 (0.76)	.173 (4.38)	.203 (5.16)	.211 (5.36)	.030 (0.76)	.060 (1.52)	1.2
0002	A		B	C	D	E		F	G	H		J		K		1.2
	Min	Max	Ref	Min	Min	Min	Max	Ref	Ref	Min	Max	Min	Max	Max		
0003	.390 (9.91)	.430 (10.92)	.200 (5.08)	.050 (1.27)	.050 (1.27)	.213 (5.41)	.263 (6.68)	.125 (3.18)	.062 (1.57)	.039 (0.91)	.045 (1.14)	.185 (4.70)	.191 (4.85)	.211 (5.36)		

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Circuit diagram is for information only.
4. Mounting torque 3 to 5 inch-pounds.
5. Case is ground terminal.
6. Mounting hardware (lockwasher and hex nut) will be supplied with filter.
7. Leads shall be solid, solder coated, AWG 18 (.040 inch).
8. Turret head terminal optional.
9. An undercut or imperfect threads out to a maximum of .052 inch from the hexhead or mounting surface is permissible.

2

FIGURE 1. Case and circuit configuration - Continued.

MIL-PRF-15733/44F
w/AMENDMENT 2

REQUIREMENTS:

Dimensions and configuration: See [figure 1](#).

Weight: See [figure 1](#).

Case and hardware finish: In accordance with [MIL-PRF-15733](#). Pure tin finish is prohibited.

Terminals: Solderable.

Operating temperature range: -55°C to +125°C.

Rated voltage: 125 V dc or 85 V rms, dc to 424 Hz.

Rated current: 15 amperes.

Insertion loss: In accordance with [MIL-PRF-15733](#) and [table I](#).

Voltage conditioning: Applicable to conformance inspection only. 100 percent of each lot of filters shall be subjected to the voltage conditioning test. The test shall be conducted prior to the group A inspection of [MIL-PRF-15733](#), as follows:

Test temperature: 125°C +4°C, -0°C.

Test voltage: 200 percent of rated dc voltage. Charging current shall not exceed 50 mA.

Points of application of test voltage: Between each terminal and the case.

Duration of exposure to test voltage: 100 ±4 hours.

After completion of exposure, and while filters are stabilized at +125°C, insulation resistance shall be measured. Filters shall then be stabilized at +25°C, and insulation resistance shall be measured.

A reject shall be defined as a filter whose insulation resistance does not meet initial requirements when measured at the +125°C and +25°C conditions as specified in this test. If the total rejects from any particular lot exceeds 10 percent, that entire lot shall be rejected.

Thermal shock and immersion: Not applicable.

Moisture resistance: Not applicable.

Capacitance to ground: In accordance with [MIL-PRF-15733](#). Measured capacitance shall be as follows:

<u>Dash no.</u>	<u>Dissipation factor</u>	<u>Measured capacitance</u> <u>-0 percent, +100 percent</u>
-0001	3.0 percent max	3,000 pF
-0002	3.0 percent max	1,500 pF
-0003	3.0 percent max	65 pF

Temperature rise: 25°C, maximum.

Insulation resistance: In accordance with [MIL-PRF-15733](#). The insulation resistance shall be 500 megohms minimum at +25°C and 100 megohms minimum at +125°C.

Voltage drop: In accordance with [MIL-PRF-15733](#) and [table I](#).

Terminal strength: In accordance with [MIL-PRF-15733](#) and [Method 211](#), [MIL-STD-202](#); test condition A.
Applied force: 5 pounds.

MIL-PRF-15733/44F
w/AMENDMENT 2

Salt atmosphere (corrosion): In accordance with MIL-PRF-15733 and Method 101, MIL-STD-202; test condition A, except that the salt solution concentration shall be 20 percent.

TABLE I. Electrical characteristics.

Dash number	Voltage drop maximum		Minimum insertion loss (dB) in accordance with MIL-STD-220, at +25°C.								
	Volts dc	Volts ac rms	4 MHz	10 MHz	100 MHz	150 MHz	500 MHz	1 GHz	5 GHz	1 GHz to 18 GHz	10 GHz to 18 GHz
0001	0.30	0.20	---	10	30	---	55	---	---	65	---
0002	0.10	0.07	3	5	20	---	40	---	---	50	---
0003	0.05	0.03	---	---	---	3	---	16	35	---	42

Dash number	Minimum insertion loss (dB) in accordance with MIL-STD-220, at -55°C and +125°C									
	4 MHz	10 MHz	100 MHz	150 MHz	500 MHz	1 GHz	5 GHz	1 GHz to 18 GHz	10 GHz to 18 GHz	
0001	---	8	28	---	53	---	---	65	---	
0002	---	3	18	---	38	---	---	50	---	
0003	---	---	---	---	---	16	35	---	42	

Shock (specified pulse): In accordance with MIL-PRF-15733 and Method 213, MIL-STD-202; test condition C.

Vibration, high frequency: In accordance with MIL-PRF-15733 and Method 204, MIL-STD-202; test condition D (20 g).

Life: In accordance with MIL-PRF-15733 and method 108, MIL-STD-202; test condition D (1,000 hours) for qualification inspection, test condition B (250 hrs) for group C inspection.

Part or Identifying Number (PIN): M15733/44- (dash number from table I).

Marking: Each filter shall be marked with the PIN, figure 2 shows an example. In addition, full marking in accordance with method I requirements of MIL-STD-1285 shall be marked on each unit package.




FIGURE 2. Hex flats - expanded view.

MIL-PRF-15733/44F
w/AMENDMENT 2

NOTES:

Application note: These nonhermetically sealed filters may be susceptible to moisture intrusion when subjected to repeated thermal cycling. If these items are to be utilized in applications enduring harsh environments, the user should consider placing them within hermetic enclosures.

Extent of qualification: Qualification testing and approval to M15733/44-0001 shall be sufficient to grant qualification approval to M15733/44-0001 through -0003.

Referenced documents. In addition to [MIL-PRF-15733](#), this specification sheet references the following documents:

MIL-STD-1285
MIL-STD-202-101
MIL-STD-202-108
MIL-STD-202-204
MIL-STD-202-211
MIL-STD-202-213
MIL-STD-220

The margins of this specification sheet are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:

Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5915-2016-001)

Review activities:

Army - AR, AT, MI
Navy - AS, MC, OS
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil/>.