

INCH-POUND
MIL-PRF-22097/1J
w/ Amendment 1
31 October 2013
SUPERSEDING
MIL-PRF-22097/1J
17 September 2010

PERFORMANCE SPECIFICATION

RESISTOR, VARIABLE, NONWIREWOUND, ADJUSTMENT TYPE, LEAD SCREW ACTUATED, STYLE RJ11

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist
of this specification sheet and [MIL-PRF-22097](#).

Inactive for new design after 4 November 1970 (see [6.5](#))

1. SCOPE

1.1 Scope. This specification covers the requirements for style RJ11, adjustment type, lead screw actuated, nonwirewound, variable resistors. This style is available in characteristics A.

1.2 Part or Identifying Number (PIN). Resistors covered by this specification is identified by a PIN which consists of the style of this specification and a coded number. The PIN is in following form:

<u>RJ11</u>	<u>AS103</u>
-----	-----
Specification style number	Coded number

2. APPLICABLE DOCUMENTS

* 2.1 General. The documents listed in this section are specified in sections 3, 4 and 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3, 4 and 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation (see [6.2](#)).

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAT, Post Office Box 3990, Columbus, OH 43218-3990, or emailed to Resistor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at <https://assist.dla.mil>.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-22097 - Resistor, Variable, Nonwirewound (Adjustment Type), General Specification For.

* (Copies of these documents are available online at <http://quicksearch.dla.mil> or from the DLA Document Services, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein (except for related specification sheets), the text of this document takes precedence unless otherwise noted. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-22097.

3.2 Interface and physical dimensions. Resistors shall meet the interface and physical dimensions specified on figure 1, as applicable.

3.3 Power rating. The power rating shall be .25 watt for characteristic A.

3.4 Terminals. Available in S-type terminal only.

3.5 Nominal resistance value and maximum rated ac or dc working voltage. Nominal resistance values and maximum rated ac or dc working voltages shall be as specified in table I.

TABLE I. Nominal resistance value and maximum rated ac or dc working voltage.

Nominal resistance value	Maximum rated ac or dc working voltage	Nominal resistance value	Maximum rated ac or dc working voltage
<u>Ohms</u>	<u>Volts</u>	<u>Ohms</u>	<u>Volts</u>
100	5.0	20,000	70.7
200	7.07	25,000	79.0
500	11.1	50,000	111
1,000	15.8	100,000	158
2,000	22.3	250,000	250
5,000	35.4	500,000	300
10,000	50.0	1,000,000	300

3.6 Actual effective electrical travel. Actual effective electrical travel shall be 17 turns minimum, and 27 turns maximum.

3.7 Operating torque. Operating torque shall be a maximum of 8 ounce-inches.


3.8 Pure tin. The use of pure tin, as an underplate or final finish, is prohibited both internally and externally. Tin content of resistor components and solder shall not exceed 97 percent, by mass. Tin shall be alloyed with a minimum of 3 percent lead, by mass (see 6.4).

4. VERIFICATION

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-PRF-22097, and as specified herein.

4.2 Dielectric withstanding voltage. The magnitude of test voltage shall be 900 volts at atmospheric pressure, and 350 volts at reduced barometric pressure.

MIL-PRF-22097/1J
w/ Amendment 1



Inches	mm								
.005	0.13	.020	0.51	.040	0.89	.093	2.36	.275	6.99
.010	0.25	.025	0.64	.047	1.02	.094	2.39	.300	7.62
.011	0.28	.031	0.79	.058	1.19	.125	3.18	.312	7.92
.015	0.38	.032	0.81	.062	1.47	.172	4.37	.375	9.53
.016	0.41	.035	0.89	.078	1.98	.200	5.08	1.000	25.40

NOTES:

1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± 0.005 (.13 mm).
3. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
4. The picturization of the styles above are given as representative of the envelope of the item. Slight deviations from the outline shown, which are contained within the envelope, and do not alter the functional aspects of the device are acceptable.
5. Standoffs and/or eyelets are optional, but shall be contained in the envelope dimensions specified in figure 1.

FIGURE 1. Style RJ11.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Service or Defense Agency, or within the military services system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The notes specified in [MIL-PRF-22097](#) are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must specify the following:

- a. Title, number, and date of this specification, the applicable associated specification, and the complete PIN.
- b. Unless otherwise specified (see 2.1), the versions of the individual documents referenced will be those in effect on the date of release of the solicitation.
- c. Packaging requirements (see 5.1).

* d. Allowable substitution (see paragraph 3.29 of [MIL-PRF-22097](#)).

6.3 Weight. The maximum weight is .012 pound (5.4 grams).

6.4 Tin whisker growth. The use of alloys with tin content greater than 97 percent, by mass, may exhibit tin whisker growth problems after manufacture. Tin whiskers may occur anytime from a day to years after manufacture and can develop under typical operating conditions, on products that use such materials. Conformal coatings applied over top of a whisker-prone surface will not prevent the formation of tin whiskers. Alloys of 3 percent lead, by mass, have shown to inhibit the growth of tin whiskers. For additional information on this matter, refer to [ASTM-B545](#) (Standard Specification for Electrodeposited Coatings of Tin).

6.5 Substitution data. Characteristic A in terminal type P and characteristic B, characteristic C, and characteristic F in terminal types L and P is deleted from this specification. Characteristic A, characteristic B, and characteristic C is replaced by characteristic F of [MIL-PRF-22097/2](#). Characteristic F is replaced by characteristic F of [MIL-PRF-22097/1](#). Terminal types L and P are replaced by terminal types L and Y respectively, of [MIL-PRF-22097/2](#).

* 6.6 Amendment notification. The margins of this specification are marked with asterisk to indicate modification generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship.

MIL-PRF-22097/1J
w/ Amendment 1

Custodians:

Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:

DLA - CC

(Project 5905-2013-024)

Review activities:

Army - AR, AT, AV, CR4, MI
Navy - MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.