

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR124/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and [MIL-PRF-3098](#).

Pertinent characteristics: 2.9 MHz to 3.8 MHz; fundamental; noncontrolled; antiresonance.




FIGURE 1. Crystal unit - CR124/U.

MIL-PRF-3098/101D

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.402	---	10.21
B	---	.183	---	4.65
C	---	.435	---	11.05
D	.184	.200	4.67	5.08
E	---	.530	---	13.46
F	.50	---	12.7	---
G	---	.150	---	3.81
H	.015	.019	0.38	0.48

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with [MIL-PRF-3098](#).

FIGURE 1. Type CR124/U, crystal unit - Continued.

REQUIREMENTS:

Dimensions, marking, and configuration: See [figure 1](#).

Frequency range: 2.9 MHz to 3.8 MHz, inclusive.

Capacitance, shunt: 7 pF, maximum.

Frequency tolerance:

Operating temperature range: ± 50 ppm.

Mode of oscillation: Fundamental.

Rated drive level: 1.0 mW, maximum.

Calibration values:

Resistance: 150 ohms.

Crystal current: 2.7 mA.

Antiresonance, load capacitance: $32.0 \text{ pF} \pm 0.05 \text{ pF}$.

Operating temperature range (noncontrolled): -55°C to $+100^\circ\text{C}$, inclusive.

Operable temperature range: $+65^\circ\text{C}$ to -55°C and $+100^\circ\text{C}$ to $+105^\circ\text{C}$, inclusive.

Equivalent resistance: 450 ohms, maximum.

Shock:

Frequency change permitted: ± 5 ppm.

Equivalent resistance change permitted: ± 15 percent.

Vibration: [Method 204](#), [MIL-STD-202](#), test condition A; 0.10 inch double amplitude or 5 gravity units (55 cps to 500 cps), whichever is less.

Frequency change permitted: ± 5 ppm.

Equivalent resistance change permitted: ± 15 percent.

Thermal shock: ± 50 ppm.

Aging:

Frequency change permitted: ± 5 ppm.

Reference documents. In addition to [MIL-PRF-3098](#), this document references the following:

[MIL-STD-202](#)

| The margins of this specification sheet are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

MIL-PRF-3098/101D

Custodians:

Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:

Army - CR

Agent:

DLA - CC

Review activities:

Air Force - 19, 84, 99

(Project 5955-2012-014)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.