

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR148/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and [MIL-PRF-3098](#).

Pertinent characteristics: 10 MHz to 61 MHz; third mechanical overtone; noncontrolled; series resonance.




FIGURE 1. Crystal unit - CR148/U.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.352	---	8.94
B	---	.725	---	18.42
C	.223	.248	5.66	6.30
D	.030	.037	0.76	0.94
E	.460	.476	11.68	12.09
F	---	.757	---	19.23
G	.030	.040	0.76	1.02
H	.015	.025	0.38	0.64
J	---	.775	---	19.68
K	---	.317	---	8.05
L	.015	.025	0.38	0.64
M	.075	.141	1.90	3.58
N	.048	.052	1.22	1.32

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with [MIL-PRF-3098](#).

FIGURE 1. Crystal unit - CR148/U - Continued.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 10.0 MHz to 61.0 MHz, inclusive.

Capacitance, shunt: 7.0 pF, maximum.

Mode of oscillation: Third mechanical overtone.

Rated drive level: 1.0 mW, maximum.

Calibration values:

Equivalent resistance: 51 ohms.

Resistor voltage drop: 0.32 volt.

Resonance: Series.

Operating temperature range (noncontrolled): -55°C to +105°C, inclusive.

Frequency tolerance: ± 0.0005 percent.

Equivalent resistance: 40 ohms, maximum.

Unwanted modes: Minimum unwanted-to-main mode resistance ratio of 2:1.

Shock:

Frequency change permitted: ± 0.0005 percent.

Equivalent resistance change permitted: ± 15 percent or 2 ohms, whichever is greater.

Vibration: [Method 201, MIL-STD-202](#).

Frequency change permitted: ± 0.0005 percent.

Equivalent resistance change permitted: ± 15 percent or 2 ohms, whichever is greater.

Temperature cycling:

Frequency change permitted: ± 0.0005 percent.

Equivalent resistance change permitted: ± 15 percent or 2 ohms, whichever is greater.

Aging:

Frequency change permitted: ± 0.0005 percent.

Reference documents. In addition to [MIL-PRF-3098](#), this document references the following:

[MIL-STD-202](#)

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - CR
Navy - EC
Air Force - 99
DLA - CC

Preparing activity:

DLA - CC

(Project 5955-2009-039)

Review activities:

Air Force - 19, 84

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <http://assist.daps.dla.mil/>.