


PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR159/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and [MIL-PRF-3098](#).

Pertinent characteristics: 8 MHz to 20 MHz; fundamental; noncontrolled; series resonance.



Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.365	---	9.27
B	---	.265	---	6.73
C	.600	---	15.24	---
D	---	.420	---	10.67
E	.195	.205	4.95	5.21
F	.0175	.0205	0.445	0.521

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. The crystal unit shall not be trimmed after sealing.
4. Marking shall be in accordance with [MIL-PRF-3098](#).

FIGURE 1. Crystal unit - CR159/U.

MIL-PRF-3098/140H

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 8 MHz to 20 MHz, inclusive.

Frequency tolerance : ± 50 ppm.

Equivalent resistance: See table I.

TABLE I Equivalent resistance .

Frequency range, inclusive. MHz	Maximum resistance Ohms
8.0 to 10.0	40
10.0+ to 12.0	30
12.0+ to 15.0	25
15.0+ to 20.0	20

Mode of oscillation: Fundamental.

Operating temperature range (noncontrolled): -55°C to $+105^{\circ}\text{C}$, inclusive.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Capacitance, shunt: 7.0 pF.

Shock:

Frequency change permitted: ± 5 ppm.

Equivalent resistance change permitted: ± 10 percent.

Vibration: [Method 201, MIL-STD-202](#).

Frequency change permitted: ± 10 ppm.

Equivalent resistance change permitted: ± 15 percent.

Temperature cycling:

Frequency change permitted: ± 5 ppm.

Equivalent resistance change permitted: ± 10 percent.

Aging:

Frequency change permitted: ± 5 ppm.

Part or Identifying Number (PIN): For Product Level B, PIN shall be CR159/U or CR159B/U (followed by specified frequency). For Product Level S, PIN shall be CR159S/U (followed by specified frequency, see 1.2 of [MIL-PRF-3098](#)).

Reference documents. In addition to [MIL-PRF-3098](#), this document references the following:

[MIL-STD-202](#)

The margins of this specification sheet are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - CR
Navy - EC
Air Force - 99
DLA - CC

Review activities:

Army - AR, MI, SM
Navy - AS, CG, MC, OS, SH
Air Force - 19, 84

Preparing activity:

Army - CR

Agent:

DLA - CC

(Project 5955-2011-015)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.daps.dla.mil>.