

NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-39012/33A  
AMENDMENT 2  
26 September 1994  
AMENDMENT 1  
21 May 1976

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, COAXIAL, RADIO FREQUENCY, SERIES TNC  
(UNCABLED-RECEPTACLE, SOCKET, RIGHT ANGLE, CLASS 2)

This amendment forms a part of MIL-C-39012/33A, dated 11 January 1973, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1, following ".375-32 UNEF-2A", add "(SEE NOTE 5)". Also add the following new note:

"5. Full threads to within .063 (1.60 mm) of shoulder; 1 1/2 max uneven threads to shoulder."

PAGE 2

\* FIGURE 2: Delete in its entirety.

PAGE 3

TABLE I, add the following new column:

Dash no.	Minimum panel thickness
0001 . . . . .	.045 (1.14)
0002 . . . . .	.045 (1.14)

PAGE 4

\* Under REQUIREMENTS, mating characteristics: Delete "See figure 2 for dimensions" and substitute "See MIL-STD-348."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:  
Army - CR  
Navy - EC  
Air Force - 85  
NASA - NA

Preparing activity:  
DLA - ES

(Project 5935-3932-23)

Review activities:  
Army - AT, AV, EA, MI  
Navy - AS, OS, MC, SH  
Air Force - 11, 19, 99