

INCH-POUND


MIL-PRF-55339/22A
17 September 2004
SUPERSEDING
MIL-PRF-55339/22
6 May 1975

PERFORMANCE SPECIFICATION SHEET

ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE,
(BETWEEN SERIES BNC JACK TO SERIES C PLUG), CLASS 2

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the document described herein shall
consist of this specification sheet and MIL-PRF-55339.



Inches	mm
.781	19.84
1.266	32.16

Reference	Series	Contact
A	BNC	Socket
B	C	Pin

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. All undimensioned pictorial representations are for reference purposes only.
4. Interface dimensions shall be in accordance with MIL-STD-348, series BNC socket contact and series C pin contact.

FIGURE 1. General configuration

DESIGN AND CONSTRUCTION

General configuration: See figure 1.

Impedance: 500 ohms, nom.

Working voltage: Sea level – 500 V rms.
70,000 feet (4.437 kPa) – 125 V rms.

Frequency range: 0 to 4 GHz.

Temperature range: -65° to 165°C.

PERFORMANCE (installation torque is not applicable)

Dimensions: See figure 1 and MIL-STD-348.

Center contact retention:	<u>Series BNC</u>	<u>Series C</u>
Axial force (lb., min)	6 (26.7 N)	6 (26.7 N)
Torque (in. oz., min)	N/A	N/A
Force to engage and disengage:	<u>Series BNC</u>	<u>Series C</u>
Longitudinal force (lb., max)	3.0 (13.3 N)	4.5 (20.02 N)
Torque (in. oz., min)	2.5 (0.34 Nm)	4.0 (0.45 Nm)

Coupling proof torque: Not applicable.

Mating characteristics, series BNC:

Center contact (socket):

 Insertion depth – .125 in. (3.17 mm), min.

 Number of insertions – 1.

Max. test pin (insertion force test), series BNC:

 Steel test pin dia. - .054 in. (1.37 mm), max.

 Pin finish – 16 microinches (0.407 μm).

 Insertion force – 2 lb. (8.89 N), max.

 Number of insertions – 1.

Min. test pin (withdrawal force), series BNC:

 Steel test pin dia. - .052 in. (1.32 mm), max.

 Pin finish – 16 microinches (0.407 μm).

 Withdrawal force – 2 oz. (0.56 N), min.

 Number of withdrawals – 1.

Outer contact, series C:

Min. test ring ID - .411 in. (10.44 mm), max.

 Ring finish – 16 microinches (0.407 μm).

 Insertion force – 7 lb. (31.14 N), max.

 Insertion depth - .125 in. (3.17 mm), min.

 Number of insertions – 1.

Max test ring ID - .419 in. (10.64 mm), min.

 Test ring finish – 16 microinches (0.407 μm).

 Insertion depth - .031 in. (0.79 mm), max.

 Number of insertions – 1.

MIL-PRF-55339/22A

Permeability. <2.0.

Seal: Hermetic – Not applicable.
Pressurized – Not applicable.
Weatherproof – Not applicable.

Insulation resistance: 5000 megohms, min.

VSWR: 1.2:1, max. at .5 to 4 GHz.

RF leakage (total): -55 dB, min, 2 to 3 GHz.

RF insertion loss: .35 dB, max, 3 GHz.
(.020 \sqrt{F} (GHz) dB max tested at 3 GHz).

Durability: 500 cycles minimum at 12 cycles/min maximum. The connector shall meet the mating characteristics and force to engage and disengage requirements.

Dielectric withstanding: Test voltage – 1500 V rms, min (sea level).

Contact resistance (milliohms, max):

<u>Contact</u>	<u>Initial</u>	<u>After</u>
Center	.25	.30
Outer	0.2	N/A
Outer (-70001)	0.4	N/A

Vibration, high frequency: Interruptions – 1 μ s, max.

Shock: Test condition I.

Thermal shock: Test condition C.

Moisture resistance: 200 megohms, min.

Corona level: Voltage – 375 V, min.
Altitude – 70,000 feet (4.437 kPa), min.

RF high potential withstanding voltage: RF voltage – 1000 V rms, min.
Frequency – 5 MHz, min.

Salt spray (corrosion): Applicable.

Coupling mechanism retention force: 100 lb. (444.82 N), min. series C.

Part or Identifying Number (PIN): MS55339/22-00636.

PIN: M55339/22-70001. CAUTION: THIS PART HAS A NICKEL PLATED BODY AND IS NOT FOR USE IN APPLICATIONS WHERE PASSIVE INTERMODULATION GENERATION (PIM) MAY BE A CONCERN.

Cross reference: See table I.

TABLE I. Cross reference of PIN.

PIN	Superseded PIN or type designation <u>1/</u>
M55339/22-00636	MS35283 REB49238 UG-636A/L

1/ The superseded PIN or the type designation is for cross reference only. Where a superseded PIN or type designation is not given, none was assigned or will be assigned. The PIN M55339/22-00636 shall be used in all cases for marking and identifying the adapter.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-PRF-55339, this document references the following:

MIL-STD-348

CONCLUDING MATERIAL

Custodians:

Army – CR
Navy – EC
Air Force – 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4657-021)

Review activities:

Army – AR, AT, EA, MI
Navy – AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <http://assist.daps.dla.mil>.