

INCH-POUND

MIL-PRF-6106/26G
18 September 2012
SUPERSEDING
MIL-PRF-6106/26F
02 December 2011

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 50 AMPERES SPST, NO,
WITH 5 AMPERE SPDT AUXILIARY HERMETICALLY SEALED

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall
consist of this specification sheet and [MIL-PRF-6106](#).





FIGURE 1. Relay, outline drawing.



**CIRCUIT DIAGRAM
(OBSERVE POLARITY)**

Inches	mm	Inches	mm
.005	0.13	.375	9.52
.010	0.25	.38	9.7
.06	1.5	.437	11.10
.100	2.54	.44	11.2
.11	2.8	1.91	48.5
.171	4.34	2.000	50.80
.203	5.16	2.44	62.0
.31	7.9	2.50	63.5

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ± 0.010 (0.25mm) for three place decimals and ± 0.03 (0.8 mm) for two place decimals.
4. Terminal numbers need not appear on the relay header providing there is affixed to the relay a suitable legible circuit diagram that identifies each terminal location specified.
5. Suppression level - the maximum induced transient voltage (back EMF) shall be 50 volts, referenced to zero volts.
6. Terminal studs shall be rated at 171°C.

FIGURE 1. Relay, outline drawing - Continued.

MIL-PRF-6106/26G

TABLE I. Rated contact load (amperes per pole) (case grounded).

Type of load	Life operating cycles X 10 ³	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase			
		Main		Aux		Main		Aux		Main		Aux	
		NO	NC	NO	NC	400	50/60	400	50/60	400	50/60	400	50/60
Resistive	50	50	50	5	5	65	---	5	---	---	---	---	---
Inductive	50	---	---	3	3	65	---	3	---	---	---	---	---
Inductive	20	50	50	---	---	---	---	---	---	---	---	---	---
Motor	---	---	---	---	---	---	---	---	---	---	---	---	---
Lamp	---	---	---	---	---	---	---	---	---	---	---	---	---
Transfer, load	---	---	---	---	---	---	---	---	---	---	---	---	---
Mechanical life	---	---	---	---	---	---	---	---	---	---	---	---	---
Reduced current	---	---	---	---	---	---	---	---	---	---	---	---	---
Intermediate current		APPLICABLE PER SPECIFICATION											

REQUIREMENTS:

COIL DATA:

Nominal operating voltage: 28 V dc.

Maximum operating voltage: 29 V dc.

Pickup voltage: 15 V dc, maximum, at 25°C.

Dropout voltage: 1.5 at 25°C.

Hold voltage: 7 V dc at 25°C.

Duty: continuous.

Coil current: 0.280 ampere, maximum, at 28 V dc, 25°C.

OPERATIONAL DATA:

Operate time: 35 milliseconds maximum with nominal coil voltage.

Dropout time: 25 milliseconds maximum from nominal coil voltage.

Contact load: See [table I](#).

Contact bounce time: 5 milliseconds, maximum.

Contact drop: 150 millivolts, maximum, initially
175 millivolts, maximum, after life test.

Overload current: 400 amperes ac, 125 amperes dc.

Rupture current: 500 amperes ac, 150 amperes dc.

MIL-PRF-6106/26G

PHYSICAL DATA:

Weight: 13 ounces, maximum.

Strength of terminals and mounting studs: Applicable.

Finish: Instrument black.

Seal: Hermetic.

Terminal barriers:

Base cover: Nonconductive. One type of insulator for meeting this requirement is [MIL-I-24768/1](#). The insulator shall enable the product to meet the performance requirements of this specification.

Barrier: Nonconductive. One type of insulator for meeting this requirement is PA110 G43 A99900 KB207 UB090 PA176 E12 in accordance with [ASTM-D4066](#). The insulator shall enable the product to meet the performance requirements of this specification.

ENVIRONMENTAL DATA:

Temperature range: -55°C to +71°C.

Altitude: 60,000 feet.

Dielectric withstanding voltage (sea level):

	Initial	After life tests
Coil to case	1,000 V rms	1,000 V rms
Aux contacts	1,000 V rms	1,000 V rms
All other points	1,500 V rms	1,150 V rms

Dielectric withstanding voltage (altitude):

	60,000 feet	
Coil to case	500 V rms	500 V rms
Aux contacts	500 V rms	500 V rms
All other points	700 V rms	700 V rms

Insulation resistance: 100 megohms, minimum @ 500 volts.

Vibration (sinusoidal): .06 D.A., 10 Hz to 55 Hz, 10 g's 55 Hz to 1,500 Hz, 15 g's, 55 Hz to 1,000 Hz.

Shock: 25 g's for 11 milliseconds.

Acceleration: 10 g's.

Part number: M6106/26-001

Qualification by similarity: See [MIL-PRF-6106](#).

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue

| Referenced documents. In addition to [MIL-PRF-6106](#), this document references the following:

[MIL-I-24768/1](#)

[ASTM-D4066](#)

Custodian:

Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2012-032)

Review activities:

Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil/>.