

REVISIONS			
LT	DESCRIPTION	DATE	APPROVED
A	Add pure tin prohibition, manufacturer eligibility, pulse application paragraphs and table IV. Changes to paragraphs 3.6, 3.12, 3.13, 4.4.1 and table V. Deletion of power conditioning and overload tests. Editorial changes throughout.	2011-01-11	M. Radecki
B	Add QR code. Update per VA SOP 006. Editorial changes throughout.	2019-01-11	M. Radecki

CURRENT DESIGN ACTIVITY CAGE CODE 037Z3
 HAS CHANGED NAMES TO:
 DLA LAND AND MARITIME
 COLUMBUS, OHIO 43218-3990



Prepared in accordance with [ASME Y14.100](#)


Selected item drawing

REV STATUS OF PAGES	REV	B	B	B	B	B	B	B	B	B	B	B	B	B	B				
	PAGES	1	2	3	4	5	6	7	8	9	10	11	12	13	14				
PMIC N/A	PREPARED BY Dennis L. Cross							DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OH											
Original date of drawing 18 July 2002	CHECKED BY Andrew R. Ernst							TITLE: RESISTOR, FIXED, FILM, PRECISION, CHIP 1/8 WATT, STYLE 2012											
	APPROVED BY Kendall A. Cottongim																		
	SIZE A	CAGE CODE 037Z3					DWG NO. 02001												
	REV	B														PAGE	1	OF	14

1. SCOPE

1.1 Scope. This drawing describes the requirements for a fixed, film, chip, 1/8 watt, precision resistor, style 2012.

1.2 Part or Identifying Number (PIN). The complete PIN is as follows:



2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

[MIL-PRF-55342](#) - Resistor, Chip, Fixed, Film, Nonestablished Reliability, Established Reliability, Space Level, General Specification for

* DEPARTMENT OF DEFENSE STANDARDS

- [MIL-STD-202-105](#) - Test Method Standard Method 105, Barometric Pressure (Reduced)
- [MIL-STD-202-107](#) - Test Method Standard Method 107, Thermal Shock
- [MIL-STD-202-108](#) - Test Method Standard Method 108, Life (At Elevated Ambient Temperature)
- [MIL-STD-202-208](#) - Test Method Standard Method 208, Solderability
- [MIL-STD-202-213](#) - Test Method Standard Method 213, Shock (Specified Pulse)
- [MIL-STD-202-215](#) - Test Method Standard Method 215, Resistant to Solvents
- [MIL-STD-202-301](#) - Test Method Standard Method 301, Dielectric Withstanding Voltage
- [MIL-STD-202-302](#) - Test Method Standard Method 302, Insulation Resistance
- [MIL-STD-202-303](#) - Test Method Standard Method 303, DC Resistance
- [MIL-STD-202-304](#) - Test Method Standard Method 304, Resistance-Temperature Characteristic
- [MIL-STD-202-308](#) - Test Method Standard Method 308, Current-Noise Test for Fixed Resistors
- [MIL-STD-690](#) - Failure Rate Sampling Plans and Procedures
- [MIL-STD-790](#) - Established Reliability and High Reliability Qualified Products List (QPL) Systems for Electrical, Electronic, and Fiber Optic Parts Specifications

* (Copies of these documents are available online at <https://quicksearch.dla.mil/>.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

NATIONAL CONFERENCE OF STANDARDS LABORATORIES (NCSL)

[NCSL Z540.3](#) - Requirements for the Calibration of Measuring and Test Equipment.

* (Copies of this document are available from <http://www.ncsli.org/>.)


* 2.3 Order of precedence. Unless otherwise noted herein or in the contract, or in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 2

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be as specified herein.

3.2 Interface and physical dimensions. The chip resistor shall meet the interface and physical dimensions as specified herein (see figure 1).



A	B	C	D	E
0.200 ±0.020	0.096 ±0.015	0.040 ±0.010	0.125 ±0.005	0.050 ±0.010

Inches	mm	Inches	mm
0.005	0.127	0.050	1.270
0.010	0.254	0.096	2.440
0.015	0.381	0.125	3.180
0.020	0.508	0.200	5.080
0.040	1.020		

Notes:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 1. Resistor, fixed, film, precision, chip.

3.3 Electrical characteristics.

3.3.1 Resistance. The nominal resistance is expressed in ohms and identified by five characters, consisting of four digits and a letter. The letter is used simultaneously as a decimal point and as a multiplier. For resistance values:

- a. Greater than or equal to 10 ohms but less than 1 kilohm, the letter "R" is used to represent a decimal point.
- b. Greater than or equal to 1 kilohm but less than 100 kilohms, the letter "K" is used to represent the decimal point.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 3

All digits preceding and following the letters R and K of the group represent significant figures. Minimum and maximum resistance values shall be as specified herein (see 3.5). The standard values for every decade shall follow the sequence specified in table I for the resistance tolerances D and F. The resistance values for tolerances T, Q, A, and B maybe any value within the limits specified herein, but it is preferred that the values be chosen from the tighter tolerance columns of table I.

3.3.2 Resistors tolerance. Resistors are available in tolerances (T) ±0.01 percent, (Q) ±0.02 percent, (A) ±0.05 percent, (B) ±.1 percent, (C) ±.25 percent, (D) ±.5 percent, and (F) ±1.0 percent.

TABLE I. Standard resistance values for the 10 to 100 decade.

Resistance tolerance											
T, Q, A, B, D	F	T, Q, A, B, D	F	T, Q, A, B, D	F	T, Q, A, B, D	F	T, Q, A, B, D	F	T, Q, A, B, D	F
10.0	10.0	14.7	14.7	21.5	21.5	31.6	31.6	46.4	46.4	68.1	68.1
10.1		14.9		21.8		32.0		47.0		69.0	
10.2	10.2	15.0	15.0	22.1	22.1	32.4	32.4	47.5	47.5	69.8	69.8
10.4		15.2		22.3		32.8		48.1		70.6	
10.5	10.5	15.4	15.4	22.6	22.6	33.2	33.2	48.7	48.7	71.5	71.5
10.6		15.6		22.9		33.6		49.3		72.3	
10.7	10.7	15.8	15.8	23.2	23.2	34.0	34.0	49.9	49.9	73.2	73.2
10.9		16.0		23.4		34.4		50.5		74.1	
11.0	11.0	16.2	16.2	23.7	23.7	34.8	34.8	51.1	51.1	75.0	75.0
11.1		16.4		24.0		35.2		51.7		75.9	
11.3	11.3	16.5	16.5	24.3	24.3	35.7	35.7	52.3	52.3	76.8	76.8
11.4		16.7		24.6		36.1		53.0		77.7	
11.5	11.5	16.9	16.9	24.9	24.9	36.5	36.5	53.6	53.6	78.7	78.7
11.7		17.2		25.2		37.0		54.2		79.6	
11.8	11.8	17.4	17.4	25.5	25.5	37.4	37.4	54.9	54.9	80.6	80.6
12.0	12.1	17.6		25.8		37.9		55.6		81.6	
12.1		17.8	17.8	26.1	26.1	38.3	38.3	56.2	56.2	82.5	82.5
12.3	12.4	18.0		26.4		38.8		56.9		83.5	
12.4		18.2	18.2	26.7	26.7	39.2	39.2	57.6	57.6	84.5	84.5
12.6		18.4		27.1		39.7		58.3		85.6	
12.7	12.7	18.7	18.7	27.4	27.4	40.2	40.2	59.0	59.0	86.6	86.6
12.9		18.9		27.7		40.7		59.7		87.6	
13.0	13.0	19.1	19.1	28.0	28.0	41.2	41.2	60.4	60.4	88.7	88.7
13.2		19.3		28.4		41.7		61.2		89.8	
13.3	13.3	19.6	19.6	28.7	28.7	42.2	42.2	61.9	61.9	90.9	90.9
13.5		19.8		29.1		42.7		62.6		92.0	
13.7	13.7	20.0	20.0	29.4	29.4	43.2	43.2	63.4	63.4	93.1	93.1
13.8		20.3		29.8		43.7		64.2		94.2	
14.0	14.0	20.5	20.5	30.1	30.1	44.2	44.2	64.9	64.9	95.3	95.3
14.2		20.8		30.5		44.8		65.7		96.5	
14.3	14.3	21.0	21.0	30.9	30.9	45.3	45.3	66.5	66.5	97.6	97.6
14.5		21.3		31.2		45.9		67.3		98.8	

3.4 Temperature characteristics. Resistors are available with temperature coefficient codes C or F as specified in table II.

TABLE II. Characteristic.

Resistance temperature characteristic (referenced to 25°C) (ppm/°C)								
RTC code	Temperature °C							
	-55		-15		+65		+125	
	Min	Max	Min	Max	Min	Max	Min	Max
C	-10	10	-10	10	-10	10	-10	10
F	-10	10	-5	5	-5	5	-10	10


DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 4

- 3.5 Resistance range. The resistance range shall be from 15 ohms to 100 kilohms.
- 3.6 Reactance. If circuit reactance is critical for your application, contact the sources of supply listed herein (see 6.7) for the circuit reactance characteristics.
- 3.7 Power rating. The power rating shall be 0.125 watt at +85°C. For operation at temperature in excess of +85°C, derate in accordance with figure 2.
- 3.8 Voltage rating. The maximum continuous working voltage shall not exceed 200 volts.
- 3.9 Maximum weight. The maximum weight shall not exceed 0.00221 pound (1 gram).
- 3.10 Termination finish. Termination material shall be in accordance with MIL-PRF-55342 code letter B, except the termination may consist of a solder coated, formed metal lead that egresses from the ends of the body and is formed around the bottom seating area of the device.
- 3.11 Pure tin. The use of pure tin, as an underplate or final finish is prohibited both internally and externally. Tin content of resistor components and solder shall not exceed 97 percent, by mass. Tin shall be alloyed with a minimum of 3 percent lead, by mass (see 6.3).
- 3.12 Thermal shock. When resistors are tested as specified in 4.6, there shall be no evidence of mechanical damage; the change in resistance shall be within the resistance tolerances specified in table IV of the group A tests.
- 3.13 DC resistance. When resistors are tested as specified in 4.5, the dc resistance shall be within the specified tolerance of the nominal resistance (see 3.3.1) except for resistance tolerances ± 0.1 , ± 0.2 , ± 0.5 percent. additional tolerances testing is required on some lots after the group A test to meet the final tolerance limit for all product deliverable on the contract..
- 3.14 Solderability. When resistors are tested as specified in MIL-PRF-55342 and 4.7, the immersed metallized surface shall be at least 95 percent covered with a new clean smooth coating.
- 3.15 Life. When resistors are tested as specified in 4.8, there shall be no evidence of mechanical damage. The change in resistance between the initial measurement and any of the succeeding measurements, up to and including 1,000 hours, shall not exceed ± 1 percent.
- 3.16 Resistance temperature characteristic. When resistors are tested as specified in 4.9, the resistance temperature characteristic, at each of the temperatures specified in 4.9c, referred to 25°C ± 5 °C, and shall not exceed the value specified in table II for the applicable characteristic.
- 3.17 Dielectric withstanding voltage. When resistors are tested as specified in 4.10, there shall be no evidence of flashover, mechanical damage, arcing, or insulation breakdown. The change in resistance shall not exceed $\pm (.05$ percent +.001 ohm).
- 3.18 Insulation resistance. When resistors are tested as specified in 4.11, the insulation resistance shall be not less than 10,000 megohms.
- 3.19 Low temperature operation. When resistors are tested as specified in 4.12, there shall be no evidence of mechanical damage. The change in resistance shall not exceed $\pm (0.05$ percent).
- 3.20 Solder mounting integrity. When resistors are tested as specified in MIL-PRF-55342 and 4.13 herein there shall be no evidence of mechanical damage.
- 3.21 Resistance to bonding exposure. When resistors are tested as specified in 4.14, there shall be no evidence of mechanical damage. The change in resistance shall not exceed $\pm (.075$ percent +.001 ohm).
- 3.22 Moisture resistance. When resistors are tested as specified in 4.15 there shall be no evidence of mechanical damage. The power applied shall be 0.1 watt not to exceed rated voltage as a load voltage on all samples. The change in resistance shall not exceed $\pm (.1$ percent +.001 ohm).
- 3.23 High temperature exposure. When resistors are tested as specified in 4.16, there shall be no evidence of mechanical damage. The change in resistance shall not exceed $\pm (.2$ percent +.001 ohm). Following this test, the dielectric withstanding voltage shall be as specified in 3.17, and the insulation resistance shall be 1,000 megohms minimum.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 5

3.24 Shock (specified pulse). When resistors are tested as specified in 4.17, there shall be no evidence of mechanical or electrical damage. The change in resistance shall not exceed $\pm(.01 \text{ percent} + .001 \text{ ohm})$. There shall be no electrical discontinuity during the test.

3.25 Resistance to solvents. When resistors are tested as specified in 4.18, there shall be no evidence of mechanical damage and the markings shall remain legible.



NOTE: This curve indicates the percentage of nominal wattage to be applied at temperatures higher than 85°C for the same ΔR that would occur at 85°C during life testing. However, at no time shall the applied voltage exceed the maximum rated voltage.

FIGURE 2. Derating curves for various ambient temperatures.

3.26 Current noise. When resistors are tested as specified in 4.19, the current noise index shall not exceed -32dB from 10 ohms to 1 kilohms, -15db from 1.01 kilohms to 10 kilohms, and 0db from 10.1 kilohms to 100 kilohms, unless otherwise specified.

3.27 Visual inspection. Resistors shall be inspected as specified in 4.20, to verify that the interface, physical dimensions, marking, and workmanship are in accordance with the applicable requirements (see 3.2 and 3.31).

3.28 Marking. Due to size limitations, this style resistor shall be marked with the following minimum information:

1K05: - First four characters of the resistance value code.

00TY: - Last two characters of resistance value code, tolerance, and temperature characteristic.

Each unit package shall be marked with the PIN assigned herein (see 1.2) and manufacturer's identification code (CAGE or logo). Where manufacturers are able to provide more information, the following is preferred in the sequence presented: Style, manufacturer's trademark, production lot code, and source code.

* 3.29 Recycled, recovered, environmentally preferable or biobased materials. Recycled, recovered, environmentally preferable or biobased materials should be used to the maximum extent possible provided that the materials meet or exceed the operational and maintenance requirements, and promote economically advantageous life cycle costs.

* 3.30 Manufacturer eligibility. To be eligible for being added as an approved source of supply, a manufacturer shall be listed on the MIL-PRF-55342 Qualified Products List for at least one part, or perform the group A and group C inspections specified herein on a sample agreed upon by the manufacturer and DLA Land and Maritime-VAT.

3.30.1 Certificate of compliance. A certificate of compliance shall be required from manufacturers requesting to be an approved source of supply.

3.31 Workmanship. Resistors shall be uniform in quality and free from defects that will affect life, serviceability, or appearance.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 6

4. VERIFICATION

4.1 Qualification inspection. Qualification inspection is not applicable to this document.

4.2 Reliability assurance program. The reliability assurance provisions specified in MIL-PRF-55342 and maintained in accordance with MIL-STD-790 are not applicable to this document.

4.3 Failure rate qualification. Failure rate qualification specified in MIL-PRF-55342 and MIL-STD-690 are not applicable to this document.

4.4 Conformance inspection.

4.4.1 Inspection of product for delivery. Inspection of product for delivery shall consist of group A and group B inspections:

4.4.1.1 Group A inspection. Group A inspection shall consist of the inspections specified in table III, and shall be made on the same set of sample units, in the order shown.

TABLE III. Group A inspection.

Inspection	Requirement paragraph	Test method paragraph	Number of samples
<u>Subgroup I</u> Thermal shock DC resistance <u>1/</u>	3.12 3.13	4.6 4.5	100 percent
<u>Subgroup II</u> Visual inspection	3.27	4.20	13
<u>Subgroup III</u> Solderability <u>2/</u>	3.14	4.7	5

1/ The resistance measurement made upon completion of the thermal shock test may be used if a measurement has been made which can, without conversion, be directly related to nominal resistance value and tolerance (see table IV).

2/ The manufacturer may request the deletion of the Subgroup III solderability test, provided an in-line or process control system for assessing and assuring the solderability of terminations can be validated and approved by DLA Land and Maritime-VAT. Deletion of the test does not relieve the manufacturer from meeting this test requirement in case of dispute. If the design, material, construction, or processing of the part is changed, or if there are any quality problems, DLA Land and Maritime-VAT may require resumption of the test.

4.4.1.2 Subgroup I. Subgroup I tests shall be performed on 100 percent of the product supplied under this specification. Resistors that are out of resistance tolerance per the requirement of table IV for this test shall be removed from the lot. Lots having more than 5 percent total rejects or one resistor, which ever is greater, shall not be furnished on the contract.

TABLE IV. Group A resistance tolerance limits.

Tolerances (± percent)	Group A initial tolerance limit (percent)	Group A final tolerance limit (percent)
1.0	±0.90	±1.0
0.5	±0.45	±0.50
0.25	±0.20	±0.25
0.10	±0.075	±0.10
0.05	±0.075	±0.10
0.02	±0.075	±0.10
0.01	±0.075	±0.10

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 7

4.4.1.3 Subgroup II. A sample of 13 parts shall be randomly selected, if one or more defects are found, the lot shall be rescreened and defects removed. A new sample of 13 parts shall then be randomly selected. If one or more defects are found in this second sample, the lot shall be rejected and shall not be supplied against this document.

4.4.1.4 Subgroup III (solderability). A sample of 5 parts shall be randomly selected, as an option; the manufacturer may use electrical rejects from subgroup I test for all or part of the sample. If there are one or more defects, the lot is rejected. The manufacturer may use the following for corrective action:

- a. Each lot that was used to form the failed lot shall be individually submitted to the solderability test. Lots that pass the solderability test are available for shipment.
- b. The failed lot is submitted to a 100 percent hot solder dip. A subsequent solderability test shall then be performed. If the lot passes, it is available for shipment; if the lot fails, the manufacturer may perform the hot solder dip one additional time. If the lot fails, the lot is considered rejected and shall not be supplied to this drawing.

4.4.1.4.1 Disposition of samples. The solderability test is considered a destructive test and samples submitted to the solderability test shall not be supplied on the contract.

4.4.2 Group B inspection. Group B inspection shall consist of the inspections specified in [table V](#), in the order shown.

4.4.2.1 Certification. The acquiring activity, at its discretion, may accept a certificate of compliance with group B requirements in lieu of performing group B tests (see [6.2c](#)).

4.4.2.2 Action in case of failure. If any of the subgroups fail Group B testing and an appropriate lot screen can be established the lot shall be screened and a new set of samples (see [table V](#) for number of samples), from the screened lot, shall be submitted to the subgroup(s) that failed. If one or more defects are found in the resubmitted samples, the lot shall be rejected and shall not be supplied to this specification.

4.4.2.3 Disposition of sample units. Sample units which have been subjected to group B inspections shall not be supplied to this specification.

TABLE V. Group B inspection.

Inspection	Requirement Paragraph	Test method paragraph	Number of sample units for inspection	Number of failures allowed
<u>Subgroup I</u> Life	3.15	4.8	5	0
<u>Subgroup II</u> Resistance temperature characteristic Dielectric withstanding voltage Insulation resistance Low temperature operation Solder mounting integrity	3.16 3.17 3.18 3.19 3.20	4.9 4.10 4.11 4.12 4.13	5	0
<u>Subgroup III</u> Resistance to bonding exposure Moisture resistance	3.21 3.22	4.14 4.15	5	0
<u>Subgroup IV</u> High temperature exposure Shock (specified pulse)	3.23 3.24	4.16 4.17	5	0
<u>Subgroup V</u> Resistance to solvents Current noise	3.25 3.26	4.18 4.19	5	0

- * 4.5 DC resistance. (see 3.13). Resistors shall be tested in accordance with [MIL-STD-202-303](#). The following details and exceptions shall apply:
 - a. Measuring apparatus: Different types of measuring test equipment (multimeter, bridges, or equivalent) are permitted to be used on the initial and final readings of this test, provided the equipment is the same style, model, or if it can be shown that the performance of the equipment is equivalent. All test equipment shall be calibrated in accordance with [NCSL Z540.3](#).
 - b. Limit of error of measuring apparatus shall not exceed one-fourth of the resistor tolerance or the resistance change limit for which the measurement is being made. Manufacturers, at their option, may use the apparatus of less accuracy, provided limits are reduced to fully compensate for accuracy deviation.
 - c. Test voltage for bridges: Measurements of resistance shall be made by using the test voltages specified in [table VI](#). The test voltage chosen, whether maximum voltage or a lower voltage which would still provide the sensitivity required, shall be applied across the terminals of the resistor. This same voltage shall be used whenever a subsequent resistance measurement is made.

TABLE VI. DC resistance test voltages.

Resistance, nominal	Maximum test voltage	
	0.5 watt or greater	Less than 0.5 watt
<u>Ohms</u>	<u>Volts</u>	<u>Volts</u>
10 to 98.8 inclusive	1	1
100 to 980 inclusive	3	3
1,000 to 9,800 inclusive	10	3
10,000 to 98,800 inclusive	30	10
0.1 megohm or higher	100	30

- d. Measurement energy for electronic test equipment: The measurement energy applied to the unit under test shall not exceed 10 percent of the +25°C rated wattage times 1 second.
- e. Temperature: The temperature at which subsequent and final resistance measurements are made in each test shall be within $\pm 2^\circ\text{C}$ of the temperature at which the initial resistance measurement was made.
- * 4.6 Thermal shock (see 3.12). Resistors shall be tested in accordance with [MIL-STD-202-107](#). The following details and exceptions shall apply:
 - a. Mounting: Resistors may be mounted or unmounted. Resistors may be placed in metal baskets, vials, or other apparatus as long as resistors are subjected to the specified temperature extremes.
 - b. Measurement before cycling: DC resistance shall be measured as specified in [4.5](#).
 - c. Test condition F (except temperatures shall be +150°C, +10°C, -0°C and -65°C, +0°C, -10°C. These extreme temperatures shall be achieved within 4 minutes.
 - d. Measurement after cycling: After stabilization at room temperature, the dc resistance shall again be measured as specified in [4.5](#) and the resistors shall be examined for evidence of mechanical damage.
- * 4.7 Solderability (see 3.14). Resistors shall be tested in accordance with [MIL-STD-202-208](#). Both leads shall be tested. Steam aging is not applicable.
- * 4.8 Life (see 3.15). Resistors shall be tested in accordance with [MIL-STD-202-108](#). The following details and exceptions shall apply:
 - a. Method of mounting: Resistors shall be mounted per [MIL-PRF-55342](#) on ceramic boards.
 - b. Test temperature: $85^\circ\text{C} \pm 5^\circ\text{C}$.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 9

- c. Initial measurements: Measurements may be made inside or outside the chamber.
 - (1) Inside chamber: When measurements are made inside the chamber, the initial dc resistance shall be measured after mounting at the applicable test temperature, after temperature stabilization, and within 8 hours of exposure of the resistors to the test temperature. This initial measurement shall be used as the reference temperature for all subsequent measurements under the same condition.
 - (2) Outside chamber: When measurements are made outside the chamber, the initial dc resistance shall be measured after mounting at the room temperature. This initial measurement shall be used as the reference temperature for all subsequent measurements under the same condition.
- d. Operating conditions: Rated dc continuous working voltage, or filtered or nonfiltered full wave rectified ac voltage, shall be applied intermittently, 1.5 hours "on" and 0.5 hour "off", for the applicable number of hours (see 4.8f), and at the applicable test temperature. "On time" shall be three quarters of the total elapsed time. During the "on" cycle, the voltage shall be regulated and controlled to maintain ± 5 percent of the rated continuous working voltage.
- e. Test condition: One thousand hours elapsed time for inspection with all samples.
- f. Measurements during test:
 - (1) DC resistance shall be measured at the end of the 30 minutes "off" periods after 250 hours +72 hours, -24 hours; 500 hours +72 hours, -24 hours; and 1,000 hours +96 hours, -24 hours elapsed.
 - (2) Measurements outside of the chamber: When measurements are made outside the chamber, resistors shall be outside of the chamber for a minimum of 45 minutes and stabilized before measurement.
- g. Examination after test: Resistors shall be examined for evidence of mechanical damage.

* 4.9 Resistance temperature characteristic (see 3.16). Resistors shall be tested in accordance with MIL-STD-202-304. The following details and exceptions shall apply:

- a. Resistors shall be mounted per MIL-PRF-55342 using ceramic boards.
- b. Referenced temperature: Room ambient temperature.
- c. Test temperature: In accordance with table VII.
- d. Stability of temperature: Resistors shall be maintained for 30 minutes to 45 minutes within 1°C at each of the test temperatures in table VII. This tolerance shall be maintained at the established test temperatures. Allow resistor to stabilize at the temperature in table VII for a minimum of 5 minutes.
- e. The resistance temperature coefficient will be based on the stabilized temperature.

TABLE VII. Resistance temperature characteristic.

Sequence ^{1/}	Temperature
	Group B acceptance inspection ($^{\circ}\text{C}$)
1	25 ± 3 ^{2/}
2	-55 ± 3
3	25 ± 3 ^{2/}
4	+125 ± 3

^{1/} At the option of the manufacturer, the reverse sequence of table VII may be as follows:

1. 25 ± 3
2. +125 ± 3
3. +25 ± 3
4. -55 ± 3

^{2/} Reference temperature for each of the succeeding temperatures.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 10

4.10 Dielectric withstanding voltage (see 3.17).

* 4.10.1 Atmospheric pressure. Resistors shall be tested in accordance with MIL-STD-202-301. The following details and exceptions shall apply:

- a. Special preparations. Resistors shall be placed in fixtures that short the terminations on the termination side of the resistor together and a second conductive surface that contacts the flat top surface of the resistor (see figure 3).
- b. Initial measurement: DC resistance shall be measured as specified in 4.5.
- c. Magnitude of test potential: Sine wave test potential of magnitude shall be 450 volts.
- d. Nature of potential: An ac supply at commercial-line frequency (not more than 100 Hz) and waveform.
- e. Rate of application of test voltage: One hundred volts per second.
- f. Duration of application of test voltage: One minute.
- g. Points of application of test voltage: Between the resistor terminals connected together and the second conductive surface.
- h. Measurement after test: DC resistance shall be measured as specified in 4.5.
- i. Examination after test: Resistors shall be examined for evidence of flashover, mechanical damage, arcing, and insulation breakdown.

* 4.10.2 Barometric pressure (reduced). Resistors shall be tested in accordance with MIL-STD-202-105. The following details and exception shall apply:

- a. Method of mounting: As specified in 4.10.1a.
- b. Initial measurement: DC resistance shall be measured as specified in 4.5.
- c. Test condition D (100,000 feet).
- d. Magnitude of test voltage: Sine wave test potential of magnitude shall be 200 volts.
- e. Nature of potential: As specified in 4.10.1d.
- f. Rate of application of test voltage: One hundred volts per second.
- g. Duration of test: One minute.
- h. Points of application of test voltage: As specified in 4.10.1g.
- i. Final measurement: DC resistance shall be measured as specified in 4.5.
- j. Examination after test: As specified in 4.10.1i.




FIGURE 3. Mounting for dielectric withstanding voltage and insulation resistance tests.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 11

- * 4.11 Insulation resistance (see 3.18). Resistors shall be tested in accordance with MIL-STD-202-302. The following details and exceptions shall apply:
 - a. Test condition B (500 volts).
 - b. Special preparations: As specified in 4.10.1a.
 - c. Points of application: As specified in 4.10.1g.
- 4.12 Low temperature operation (see 3.19). Following a dc resistance measurement as specified in 4.5, the resistors shall be placed in a cold chamber at -65°C +0°C, -5° C. After 1 hour of stabilization at this temperature, full rated continuous working voltage as specified in 3.8 shall be applied for 45 minutes. The resistors may be loaded individually or in parallel. Fifteen +5, -0 minutes after the removal of the voltage, the temperature in the chamber shall be gradually increased to room temperature within a period of not more than 8 hours. The resistors shall be removed from the chamber and maintained at a temperature of 25°C ±5°C for a period of approximately 24 hours; the dc resistance shall then be measured as specified in 4.5. Resistors shall then be inspected for evidence of mechanical damage.
- 4.13 Solder mounting integrity (see 3.20). Resistors shall be tested in accordance with MIL-PRF-55342, mounting integrity, termination B. The force applied shall be 3 kilograms.
- 4.14 Resistance to bonding exposure (see 3.21). Resistors shall be tested in accordance with MIL-PRF-55342.
- 4.15 Moisture resistance (see 3.22). Resistors shall be tested in accordance with MIL-PRF-55342.
- 4.16 High temperature exposure (see 3.23). Resistors shall be tested in accordance with MIL-PRF-55342.
- * 4.17 Shock, specified pulse (see 3.24). Resistors shall be tested in accordance with MIL-STD-202-213. The following details and exceptions shall apply:
 - a. Mounting: The resistor shall be mounted with the body clamped or cemented to a flat surface. The resistors shall be mounted to insure that they have the same motion as the shock table. In all cases, the resistors shall be mounted in relation to test equipment so that the stress applied is in the direction that would be considered most detrimental.
 - b. Measurement before shock: DC resistance shall be measured as specified in 4.5.
 - c. Number and direction of applied shock: The resistors shall be subjected to a total of 10 shocks in each of three mutually perpendicular planes, two perpendicular and the other parallel to the longitudinal axis of the resistor.
 - d. Test condition I (100 g's, 6 milliseconds (ms) sawtooth).
 - e. Measurement during shock: Each resistor shall be monitored to determine electrical discontinuity by a method that shall at least be sensitive enough to monitor or register, automatically, any electrical discontinuity of 0.1 ms or greater.
 - f. Measurement after shock: DC resistance shall be measured as specified in 4.5.
 - g. Examination after test: Resistors shall be examined for evidence of mechanical and electrical damage.
- * 4.18 Resistance to solvents (see 3.25). Resistors shall be tested in accordance with MIL-STD-202-215. The following details shall apply:
 - a. Mounting: Unmounted.
 - b. The marked portion of the resistor shall be brushed.
 - c. The number of sample units shall be as specified in table V.
 - d. Resistor shall be examined for mechanical damage and legibility of minimum marking.
- * 4.19 Current noise (see 3.26). Current noise shall be measured in accordance with MIL-STD-202-308.
- 4.20 Visual inspection (see 3.27). Resistors shall be examined under 30X to 60X magnification. In case of conflict 30X will be the referee power to verify that the requirements of 3.27 are met.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 12

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature which may be helpful, but is not mandatory.)

6.1 Intended use. The film resistors described herein are intended to be used where high precision and stability are required.

6.2 Ordering data. The contract or purchase order should specify the following:

- a. Complete DLA Land and Maritime CAGE CODE and PIN (see 1.2).
- b. Requirements for delivery: One copy of the conformance inspection data or certification of compliance that parts have passed conformance inspection with each shipment of parts by the manufacturer.
- c. Whether the manufacturer performs the group B tests or provides certification of compliance with group B requirements (see 4.4.2.1).
- d. Requirements for packaging and packing.
- e. Circuit reactance requirements (see 3.6).

6.3 Tin whisker growth. The use of alloys with tin content greater than 97 percent, by mass, may exhibit tin whisker growth problems after manufacture. Tin whiskers may occur anytime from a day to years after manufacture and can develop under typical operating conditions, on products that use such materials. Conformal coatings applied over top of a whisker-prone surface will not prevent the formation of tin whiskers. Alloys of 3 percent lead, by mass, have shown to inhibit the growth of tin whiskers. For additional information on this matter, refer to [ASTM-B545](#) (Standard Specification for Electrodeposited Coatings of Tin).

6.4 Electrostatic charge. Under several combinations of conditions, these resistors can be electrically damaged, by electrostatic charges, and drift from specified value. Users should consider this phenomena when ordering or shipping resistors. Direct shipment to the Government is controlled by [MIL-DTL-39032](#), which specifies a preventive packaging procedure.

6.5 Pulse application. Designers are CAUTIONED on using these resistors in high power pulse applications. Since they have not been qualified nor tested for such applications, damage and premature failure are possible.

6.6 User of record. Coordination of this document for future revisions is coordinated only with the approved source of supply and the users of record of this document. Requests to be added as a recorded user of this drawing may be achieved online at resistor@dla.mil or in writing to: DLA Land and Maritime-VAT, Post Office Box 3990, Columbus, OH 43218-3990 or by telephone (614) 692-0552 or DSN 850-0552.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 13

6.7 Approved source of supply. Approved source of supply is listed herein. Additional sources will be added as they become available. Assistance in the use of this drawing may be obtained online at resistor@dla.mil or contact DLA Land and Maritime-VAT, Post Office Box 3990, Columbus, OH 43218-3990 or by telephone (614) 692-0552 or DSN 850-0552.

DLA Land and Maritime drawing PIN	Vendors similar designation or type number <u>1/</u>	Vendor CAGE	Vendor name and address
02001-*****	PSF2012-1	91637	Vishay Dale Electronics, Inc. P.O. Box 609 Columbus, NE 68602-0609

*

1/ Parts must be purchased to the DLA Land and Maritime CAGE CODE and PIN to assure that all performance requirements and test are met.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 02001
		REV B	PAGE 14