

REVISIONS			
LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Add new vendor. Editorial changes throughout.	10-04-20	Michael A. Radecki
B	Correct paragraph 4.4 example, 2 critical resistance value sign to "≥". Editorial change throughout.	13-02-14	Michael A. Radecki
C	Changes in vendor CAGE code, part number and resistance ohmic values. Editorial changes throughout.	16-04-05	Michael A. Radecki
D	Correct figure 1, dimension table units. Editorial changes throughout.	17-08-18	Michael A. Radecki
E	Update per VA SOP 006. Editorial changes throughout.	18-09-20	Michael A. Radecki
F	Update vendor's supply listing. Editorial changes throughout.	23-01-11	Michael A. Radecki

CURRENT DESIGN ACTIVITY CAGE CODE 037Z3
HAS CHANGED NAMES TO:
DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990



Prepared in accordance with ASME Y14.24

Selected Item Drawing

Revision Status of Sheets													
REV													
SHEET													
REV	F	F	F	F	F	F	F	F					
SHEET	1	2	3	4	5	6	7	8					


PMIC N/A Original date of drawing 2009-02-11	PREPARED BY Andrew R. Ernst				DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990			
	CHECKED BY Andrew R. Ernst				TITLE RESISTOR, CHIP, FIXED, FILM, MOISTURE RESISTANT, MILITARY and SPACE LEVEL, STYLE 0201			
	APPROVED BY Michael Radecki				DWG NO. 07010			
	SIZE A		CAGE CODE 037Z3		PAGE 1 OF 8			

1. SCOPE


1.1 Scope. This drawing describes the requirements for a 0.020 by 0.010 chip resistor, which is resistant to the degrading effects of moisture while under power.

1.2 Part or Identifying Numbers (PIN's). The complete PIN's are shown in the examples below. The first example is for general military applications. The second example is for space type applications and requires adding a code letter to the end of the original PIN.

NOTE: Example of military level PIN.



NOTE: Example of space level PIN (codes A & T).



2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

[MIL-PRF-55342](#) - Resistor, Chip, Fixed, Film, Nonestablished Reliability, Established Reliability, Space Level, General Specification for

DEPARTMENT OF DEFENSE STANDARDS

[MIL-STD-690](#) - Failure Rate Sampling Plans and Procedures
[MIL-STD-790](#) - Standard Practice for Established Reliability and High Reliability Qualified Products List (QPL) Systems for Electrical, Electronic, and Fiber Optic Parts Specifications

* (Copies of these documents are available online at <https://quicksearch.dla.mil/>.)

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 07010
		REV F	PAGE 2

2.2 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein (except for related specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with MIL-PRF-55342, and as specified herein.

3.2 Interface and physical dimensions. The resistor shall meet the interface and physical dimensions as specified in MIL-PRF-55342 and herein (see figure 1).

3.2.1 Design documentation. The design documentation shall be in accordance with MIL-PRF-55342 and unless otherwise specified in the contract or purchase order, shall be retained by the manufacturer and available for review by the acquiring activity or contractor upon request.

3.3 Electrical characteristics.

3.3.1 Resistance temperature characteristic. The resistance temperature characteristic shall be identified by a single letter, as specified in MIL-PRF-55342 and herein (see 6.7).

3.3.2 Resistance. The nominal resistance expressed in ohms is identified by four digits; the first three digits represent significant figures, and the last digit specifies the number of zeros to follow. When the value of resistance is less than 100 ohms, or when fractional values of an ohm are required, the letter "R" shall be substituted for one of the significant figures. The resistance value designations are shown in table I. Minimum and maximum resistance values shall be as specified in MIL-PRF-55342. Resistance values not listed in the "10 to 100" decade table of MIL-PRF-55342 for the appropriate resistance tolerance shall be considered as not conforming to the specification.

TABLE I. Resistance value designations.

Designation	Resistance ohms
10R0 to 98R8 incl.	10.0 to 98.8 Inclusive
1000 to 9880 incl.	100 to 988 Inclusive
1001 to 9881 incl.	1,000 to 9,880 Inclusive
1002 to 9882 incl.	10,000 to 98,800 Inclusive
1003 to 9883 incl.	100,000 to 988,000 inclusive
1004	1,000,000

3.3.2.1 Resistance range. The resistance range shall be 10 ohms to 1 megohms and as specified herein (see 6.7).

3.3.3 Resistance tolerance. Resistors are available in resistance tolerances as specified in table II and herein (see 6.7).

3.3.4 Termination material. Termination material shall be identified by a single letter, as specified in MIL-PRF-55342 and herein (see 6.7).

3.3.4.1 Pure tin. The use of pure tin, as an underplate or final finish is prohibited both internally and externally. Tin content of resistor components and solder shall not exceed 97 percent, by mass. Tin shall be alloyed with a minimum of 3 percent lead, by mass (see 6.3).

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 07010
		REV F	PAGE 3

TABLE II. Resistance tolerance.

Symbol	Resistance tolerance percent
F	±1.0
J	±5.0

3.3.5 Product level testing. The product level testing shall be designated by the military and space level PIN's (see 1.2, 4.3.2, 4.3.3, and 6.7).

3.3.6 Power rating. The power rating for this chip resistor shall be 0.05 watts.

3.3.7 Voltage rating. The maximum continuous working voltage shall be 30 volts.

3.3.8 Power moisture resistance. When resistors are tested as specified in 4.4, there shall be no evidence of mechanical damage; the change in resistance between the initial and final measurements shall not exceed the limits as specified in the moisture resistance requirements of MIL-PRF-55342. Samples subjected to this test shall not be delivered on the contract or order.

3.3.9 Outgassing (space levels A and T). Outgassing shall be performed as specified in MIL-PRF-55342.

3.4 Marking. Marking is not required on the resistor; however, each unit package shall be marked with the PIN assigned herein (see 1.2), vendor CAGE code, and date and lot codes.

3.5 Manufacturers' eligibility (military applications). The approved sources of supply listed on this drawing shall be qualified to at least one product on the Qualified Products List for MIL-PRF-55342. They shall have successfully passed the power moisture resistance test as witnessed and certified by an official company representative with 30 samples (10 low, 10 critical, 10 high) with zero defects. If the manufacturer has already performed the power moisture resistance test to any of the following drawings (94012, 94013, 94014, 94015, 94016, 94017, 94018, 94019, 94025, 94026, 04007, 04008, or 04009) then performance of the power moisture resistance test as a prerequisite for being a source of supply is not required.

3.5.1 Manufacturers eligibility (space levels A and T). Only approved sources of supply qualified to "T" failure rate level of MIL-PRF-55342 and approved to the general military level of this drawing may supply to space level codes A and T. Furthermore, all testing for these levels shall be done on a production lot basis as defined in MIL-PRF-55342. Test deletion or reduction, which may be granted for ER level product, is not allowed for space level codes A and T of this document.

3.5.2 Certificate of compliance. A certificate of compliance shall be required from manufacturers requesting to be listed as an approved source of supply.

3.6 Recycled, recovered, environmentally preferable or biobased materials. Recycled, recovered, environmentally preferable or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements and promotes economically advantageous life cycle costs.



3.7 Workmanship. Resistors shall be uniform in quality and free from any defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Product assurance program. The product assurance program specified in MIL-PRF-55342 and maintained in accordance with MIL-STD-790 is not applicable to this document.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 07010
		REV F	PAGE 4

Configuration A



Configuration B

Configuration	Dimension A mm	Dimension B mm	Dimension C mm	Dimension D mm	Dimension E mm
A	0.6 ±0.05 (0.024 ±0.002)	0.3 ±0.05 (0.012 ±0.002)	0.23 ±0.05 (0.009 ±0.002)	0.15 ±0.05 (0.006 ±0.002)	N/A
B	0.6 ±0.05 (0.024 ±0.002)	0.3 ±0.05 (0.012 ±0.002)	0.23 ±0.05 (0.009 ±0.002)	0.15 ±0.07 (0.006 ±0.003)	0.15 +0.05 -0.10 (0.006 +0.002) -0.004

NOTES:

1. Dimensions are in millimeters.
2. Inches equivalents are given for general information only.
3. The pictorial view of the styles above is given as representative of the envelope of the item. Slight deviations from the outline shown, which are contained within the envelope, and do not alter the functional aspects of the device are acceptable.

FIGURE 1. Chip resistor.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 07010
		REV F	PAGE 5

4.2 Product level qualification. The product level qualification specified in MIL-PRF-55342 and MIL-STD-690 is not applicable to this document.

4.3 Conformance inspection.

4.3.1 Inspection of product for delivery (military level). Inspection of product for delivery for each PIN ordered shall consist of group A inspection and group B inspection of MIL-PRF-55342, ER level. Additionally, 5 samples of each PIN ordered shall be subjected to the power moisture resistance test specified herein with 0 defects allowed.

4.3.1.1 Certification (military level only). The procuring activity may accept a certificate of compliance in lieu of performing group B inspection and the power moisture resistance test (see 6.2d).

4.3.2 Inspection of product for delivery (space level code A). Inspection of product for delivery for each PIN ordered shall consist of group A inspection and group B inspection of MIL-PRF-55342, space level. Additionally, 10 samples of each PIN ordered shall be subjected to the power moisture resistance test specified herein (see 4.4) with 0 defects allowed. The group C life test shall be performed as specified in MIL-PRF-55342 except the test shall be from each production lot for 1000 hours, 22 samples for each value ordered with 0 defects. NOTE: Test samples subjected to Group B, Group C, and the power moisture resistance test herein shall not be delivered on the contract or order.

4.3.3 Inspection of product for delivery (space level code T). Inspection of product for delivery for each PIN ordered (each production lot) shall consist of group A, group B, and group C inspection of MIL-PRF-55342, space level. Resistance to soldering heat and resistance to bonding exposure shall be as specified in MIL-PRF-55342 except 10 samples for each PIN ordered, followed by power moisture resistance as specified herein (see 4.4) performed on the same set of samples with 0 defects for the subgroup. The group C life test shall be performed as specified in MIL-PRF-55342 except the test shall be for 1000 hours, 22 samples for each value ordered with 0 defects. Thermal shock and low temperature operation shall be as specified in MIL-PRF-55342 except 10 samples for each PIN ordered with 0 defects. High temperature exposure shall be as specified in MIL-PRF-55342 except the test shall be for 100 hours, 10 samples with 0 defects. NOTE: Test samples subjected to Group B, Group C, and the power moisture resistance test herein shall not be delivered on the contract or order.

4.3.4 Solder mounting integrity. The solder mounting integrity for group B inspection (all levels) shall be .5 kilograms.

4.4 Power moisture resistance. Power moisture resistance test shall be performed as specified in MIL-PRF-55342 except the loading voltage shall be as follows:

Loading voltage: The loading voltage shall be equal to 10 percent rated power for resistance values less than or equal to the critical resistance value as shown in example number 1. For values greater than or equal to the critical resistance value the loading voltage shall be as shown in example number 2.

EXAMPLE 1

Characteristic: "K"
Rated wattage: 0.050 watts (P)
Value: 2000 ohms (R)

$$\begin{aligned} V &= \sqrt{.1PR} \text{ (for "R" } \leq \text{ critical res.)} \\ &= \sqrt{.1(.05)(2000)} \\ &= \sqrt{10} \\ &= 3.16 \text{ volts} \end{aligned}$$

EXAMPLE 2

Characteristic: "K"
Voltage rating: 30 volts (V)

$$\begin{aligned} V &= \sqrt{.1} \times V \text{ (for "R" } \geq \text{ critical res.)} \\ &= .316 \times 30 \\ &= 9.48 \text{ volts} \end{aligned}$$

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 07010
		REV F	PAGE 6

4.5 Visual and mechanical examination. Resistors shall be examined to verify that the materials, design, construction, physical dimensions, marking, and workmanship are in accordance with the applicable requirements of MIL-PRF-55342.

4.6 Data retention (codes A & T). Data retention for space level products shall be per the requirements of MIL-PRF-55342.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of material is to be performed by DoD or in-house personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system Commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. Chip resistors are intended for use in thick or thin film circuits where microcircuitry is intended. Chip resistors can also be used in surface mount applications.

6.2 Ordering data. The contract or purchase order should specify the following:

- a. Complete DLA Land and Maritime CAGE CODE and PIN (see 1.2).
- b. Requirements for delivery: One copy of the conformance inspection variables and attributes data that parts have passed conformance inspection, with each shipment of parts by the manufacturer.
- c. Packaging requirements (see 5.1).
- d. Whether the manufacturer performs the group B inspection and the moisture resistance test or provides a certificate of compliance (see 4.3.1.1, military level only).

6.3 Tin whisker growth. The use of alloys with tin content greater than 97 percent, by mass, may exhibit tin whisker growth problems after manufacture. Tin whiskers may occur anytime from a day to years after manufacture and can develop under typical operating conditions, on products that use such materials. Conformal coatings applied over top of a whisker-prone surface will not prevent the formation of tin whiskers. Alloys of 3 percent lead, by mass, have shown to inhibit the growth of tin whiskers. For additional information on this matter, refer to ASTM-B545 (Standard Specification for Electrodeposited Coatings of Tin).

6.4 Electrostatic charge. Under several combinations of conditions, these resistors can be electrically damaged, by electrostatic charges, and drift from specified value. Users should consider this phenomenon when ordering or shipping resistors. Direct shipment to the Government is controlled by MIL-DTL-39032, which specifies a preventive packaging procedure.

6.5 Pulse applications. Designers are CAUTIONED on using the above resistors in high power pulse applications. Since they have not been qualified nor tested for such applications, damage and premature failure are possible. These resistors only see a one-time pulse (Short-time overload) as part of the group B inspection of MIL-PRF-55342.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 07010
		REV F	PAGE 7

* 6.6 Users of record. Coordination of this document for future revisions is coordinated only with the approved sources of supply and the users of record of this document. Requests to be added as a recorded user of this drawing may be achieved online at resistor@dla.mil or in writing to: DLA Land and Maritime, Attn: VAT, PO Box 3990, Columbus, OH 43218-3990 or by telephone (614) 400-3997 or DSN 850-0552.

* 6.7 Approved sources of supply. Approved sources of supply are listed herein. Additional sources will be added as they become available. Assistance in the use of this drawing may be obtained online at resistor@dla.mil or contact DLA Land and Maritime, Attn: VAT, PO Box 3990, Columbus, OH 43218-3990 or by telephone (614) 400-3997 or DSN 850-0552.

DLA Land and Maritime drawing PIN's 07010-***** 07010-*****	Vendor similar designation or type number <u>1/</u>	Vendor CAGE	Vendor name and address
Characteristic: L Res. value: 10 ohms thru 47 ohms Res. Tolerance: 5 pct. Termination: B Screen level: blank (military PIN only) Characteristic: K Res. value: 47 ohms thru 1 megohms Res. Tolerance: 1 pct. Termination: B Screen level: blank (military PIN only)	RCWP-0201-**	2799A	Vishay Dale Electronics, Inc. P.O. Box 609 Columbus, NE 68602-0609 <u>Plant:</u> Vishay Israel Hakotzer Street 3 PO Box 2317 Beer Sheva, Israel 84874
Characteristic: L, M Res. value: 1 ohm thru 10 Megohms Res. Tolerance: 1 & 5 pct. Termination: B Military screen level: blank Space screen level: A and T Characteristic: K Res. value: 47 ohms thru 680K ohms Res. Tolerance: 1 & 5 pct. Termination: B Military screen level: blank Space screen level: A and T	MWA96SM-XXXX-X	50316	Mini-Systems, Inc. Thick Film Division PO Box 69 20 David Rd North Attleboro, MA 02761-0069

1/ Parts must be purchased to the DLA Land and Maritime CAGE CODE and PIN to assure that all performance requirements and tests are met.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 037Z3	DWG NO. 07010
		REV F	PAGE 8