

REVISIONS

| LTR | DESCRIPTION  | DATE (YR-MO-DA) | APPROVED          |
|-----|--|-----------------|-------------------|
| A   | Convert to Standard Microcircuit Drawing (SMD) format and update drawing to current requirements. Change CAGE to 67268. Editorial changes throughout.<br>- gap | 09-11-16        | Charles F. Saffle |

**CURRENT CAGE IS 67268**

The original first sheet of this drawing has been replaced.

|       |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|-------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| REV   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| SHEET |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| REV   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| SHEET |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |


|                         |       |   |   |   |   |   |   |   |   |   |  |  |  |  |  |  |  |  |  |
|-------------------------|-------|---|---|---|---|---|---|---|---|---|--|--|--|--|--|--|--|--|--|
| REV STATUS<br>OF SHEETS | REV   | A | A | A | A | A | A | A | A | A |  |  |  |  |  |  |  |  |  |
|                         | SHEET | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |   |  |  |  |  |  |  |  |  |  |

|   |                                   |  |           |                           |              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---|-----------------------------------|--|-----------|---------------------------|--------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| PMIC N/A  | PREPARED BY<br>David W. Queenan   | <p align="center"><b>DEFENSE SUPPLY CENTER COLUMBUS</b><br/> <b>COLUMBUS, OHIO 43218-3990</b><br/> <a href="http://www.dsc.dla.mil">http://www.dsc.dla.mil</a></p> |           |                           |              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| <p align="center"><b>STANDARD<br/>MICROCIRCUIT<br/>DRAWING</b></p> <p align="center">THIS DRAWING IS AVAILABLE<br/>FOR USE BY ALL<br/>DEPARTMENTS<br/>AND AGENCIES OF THE<br/>DEPARTMENT OF DEFENSE</p> | CHECKED BY<br>D. A. DiGenzo       |  |           |                           |              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|   | APPROVED BY<br>N. A. Hauck        | <p align="center">MICROCIRCUIT, DIGITAL, ADVANCED LOW<br/>POWER SCHOTTKY TTL, INVERTER GATE,<br/>BUFFER OUTPUT, MONOLITHIC SILICON</p>                             |           |                           |              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|   | DRAWING APPROVAL DATE<br>84-08-27 |  |           |                           |              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|   | AMSC N/A                          | REVISION LEVEL<br>A  | SIZE<br>A | CAGE CODE<br><b>14933</b> | <b>84061</b> |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|   |                                   | SHEET  |           | 1 OF 8                    |              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

1. SCOPE

1.1 Scope. This drawing describes device requirements for MIL-STD-883 compliant, non-JAN class level B microcircuits in accordance with MIL-PRF-38535, appendix A.

1.2 Part or Identifying Number (PIN). The complete PIN is as shown in the following example:



1.2.1 Device type(s). The device type(s) identify the circuit function as follows:

| <u>Device type</u> | <u>Generic number</u> | <u>Circuit function</u>                  |
|--------------------|-----------------------|--|
| 01                 | 54ALS1004             | Hex 1-input inverter gate, buffer output |

1.2.2 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

| <u>Outline letter</u> | <u>Descriptive designator</u> | <u>Terminals</u> | <u>Package style</u>         |
|-----------------------|-------------------------------|------------------|------------------------------|
| B                     | GDFP4-14                      | 14               | Flat package                 |
| C                     | GDIP1-T14 or CDIP2-T14        | 14               | Dual-in-line package         |
| D                     | GDFP1-F14 or CDFP2-F14        | 14               | Flat package                 |
| 2                     | CQCC1-N20                     | 20               | Square leadless chip carrier |

1.2.3 Lead finish. The lead finish is as specified in MIL-PRF-38535, appendix A.

1.3 Absolute maximum ratings.

|   |                                  |
|---|----------------------------------|
| Supply voltage range .....  | -0.5 V dc to +7.0 V dc           |
| Input voltage range .....   | -1.5 V dc at -18 mA to +7.0 V dc |
| Storage temperature range .....   | -65° to +150°C                   |
| Maximum power dissipation (P <sub>D</sub> ), per device <sup>1/</sup> ..... | 66 mW dc                         |
| Lead temperature (soldering, 10 seconds) .....                              | +300°C                           |
| Thermal resistance, junction to case (θ <sub>JC</sub> ) .....               | See MIL-STD-1835                 |
| Junction temperature (T <sub>J</sub> ) .....                                | 175°C                            |

1.4 Recommended operating conditions.

|   |                                      |
|---|--------------------------------------|
| Supply voltage (V <sub>CC</sub> ) .....                   | 4.5 V dc minimum to 5.5 V dc maximum |
| Maximum low level input voltage (V <sub>IL</sub> ) .....  | 0.8 V dc                             |
| Minimum high level input voltage (V <sub>IH</sub> ) ..... | 2.0 V dc                             |
| Case operating temperature range (T <sub>C</sub> ) .....  | -55° to +125°C                       |

<sup>1/</sup> Must withstand the added P<sub>D</sub> due to short-circuit test (e.g., I<sub>O</sub>).

|   |                  |                            |                   |
|---|------------------|----------------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                            | <b>84061</b>      |
|   |                  | REVISION LEVEL<br><b>A</b> | SHEET<br><b>2</b> |

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-883 - Test Method Standard Microcircuits.  
MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

DEPARTMENT OF DEFENSE HANDBOOKS

MIL-HDBK-103 - List of Standard Microcircuit Drawings.  
MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these documents are available online at <http://assist.daps.dla.mil/quicksearch/> or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with MIL-PRF-38535, appendix A for non-JAN class level B devices and as specified herein. Product built to this drawing that is produced by a Qualified Manufacturer Listing (QML) certified and qualified manufacturer or a manufacturer who has been granted transitional certification to MIL-PRF-38535 may be processed as QML product in accordance with the manufacturers approved program plan and qualifying activity approval in accordance with MIL-PRF-38535. This QML flow as documented in the Quality Management (QM) plan may make modifications to the requirements herein. These modifications shall not affect form, fit, or function of the device. These modifications shall not affect the PIN as described herein. A "Q" or "QML" certification mark in accordance with MIL-PRF-38535 is required to identify when the QML flow option is used.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535, appendix A and herein.

3.2.1 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.2.2 Logic diagram and terminal connections. The logic diagram and terminal connections shall be as specified on figure 1.

3.2.3 Truth table. The truth table shall be as specified on figure 2.

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full case operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are described in table I.

|   |                  |                     |                   |
|---|------------------|---------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                     | <b>84061</b>      |
|   |                  | REVISION LEVEL<br>A | SHEET<br><b>3</b> |

3.5 Marking. Marking shall be in accordance with MIL-PRF-38535, appendix A. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked.

3.5.1 Certification/compliance mark. A compliance indicator "C" shall be marked on all non-JAN devices built in compliance to MIL-PRF-38535, appendix A. The compliance indicator "C" shall be replaced with a "Q" or "QML" certification mark in accordance with MIL-PRF-38535 to identify when the QML flow option is used.

3.6 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-HDBK-103 (see 6.6 herein). The certificate of compliance submitted to DSCC-VA prior to listing as an approved source of supply shall affirm that the manufacturer's product meets the requirements of MIL-PRF-38535, appendix A and the requirements herein.

3.7 Certificate of conformance. A certificate of conformance as required in MIL-PRF-38535, appendix A shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change. Notification of change to DSCC-VA shall be required for any change that affects this drawing.

3.9 Verification and review. DSCC, DSCC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

#### 4. VERIFICATION

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with MIL-PRF-38535, appendix A.

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.

(2)  $T_A = +125^\circ\text{C}$ , minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

|   |                  |                     |                   |
|---|------------------|---------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                     | <b>84061</b>      |
|   |                  | REVISION LEVEL<br>A | SHEET<br><b>4</b> |

TABLE I. Electrical performance characteristics.

| Test   | Symbol           | Conditions<br>-55°C ≤ T <sub>C</sub> ≤ +125°C<br>unless otherwise specified                             | Group A<br>subgroups | Limits |      | Unit |
|--|------------------|---|----------------------|--------|------|------|
|  |                  |   |                      | Min    | Max  |      |
| High level output voltage                    | V <sub>OH</sub>  | V <sub>CC</sub> = 4.5 V, V <sub>IH</sub> = 2.0 V,<br>I <sub>OH</sub> = -1.0 mA, V <sub>IL</sub> = 0.8 V | 1, 2, 3              | 2.4    |      | V dc |
| Low level output voltage                     | V <sub>OL</sub>  | V <sub>CC</sub> = 4.5 V, V <sub>IL</sub> = 0.8 V,<br>I <sub>IN</sub> = 12 mA, V <sub>IH</sub> = 2.0 V   | 1, 2, 3              |        | 0.4  | V dc |
| Input clamp voltage                          | V <sub>IC</sub>  | V <sub>CC</sub> = 4.5 V, I <sub>IN</sub> = -18 mA,<br>T <sub>C</sub> = +25°C                            | 1                    |        | -1.5 | V dc |
| Low level input current                      | I <sub>IL</sub>  | V <sub>CC</sub> = 5.5 V, V <sub>IN</sub> = 0.4 V  | 1, 2, 3              | 0      | -100 | μA   |
| High level input current                     | I <sub>IH1</sub> | V <sub>CC</sub> = 5.5 V, V <sub>IN</sub> = 2.7 V  | 1, 2, 3              |        | 20   | μA   |
|  | I <sub>IH2</sub> | V <sub>CC</sub> = 5.5 V, V <sub>IN</sub> = 7.0 V  | 1, 2, 3              |        | 100  | μA   |
| Output current <u>1/</u>                     | I <sub>O</sub>   | V <sub>CC</sub> = 5.5 V, V <sub>O</sub> = 2.25 V  | 1, 2, 3              | -30    | -112 | mA   |
| Supply current, outputs high                 | I <sub>CCH</sub> | V <sub>CC</sub> = 5.5 V   | 1, 2, 3              |        | 3    | mA   |
| Supply current, outputs low                  | I <sub>CCL</sub> | V <sub>CC</sub> = 5.5 V   | 1, 2, 3              |        | 12.0 | mA   |
| Propagation delay time,<br>low-to-high level | t <sub>PLH</sub> | V <sub>CC</sub> = 5.0 V,<br>C <sub>L</sub> = 50 pF ±10%,<br>R <sub>L</sub> = 500 Ω                      | 9                    | 1      | 7    | ns   |
|  |                  |   | 10, 11               | 1      | 9    |      |
| Propagation delay time,<br>high-to-low level | t <sub>PHL</sub> |   | 9                    | 1      | 6    | ns   |
|  |                  |   | 10, 11               | 1      | 8    |      |

1/ The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I<sub>OS</sub>.

**STANDARD  
MICROCIRCUIT DRAWING**  
DEFENSE SUPPLY CENTER COLUMBUS  
COLUMBUS, OHIO 43218-3990


SIZE  
**A**

**84061**

REVISION LEVEL  
A

SHEET  
**5**

CASES B, C, and D



CASE 2




FIGURE 1. Logic diagram and terminal connections (top view).

|   |                  |                     |                   |
|---|------------------|---------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                     | <b>84061</b>      |
|   |                  | REVISION LEVEL<br>A | SHEET<br><b>6</b> |

Truth table (each gate)

| Input<br>A | Output<br>Y |
|------------|-------------|
| L          | H           |
| H          | L           |

$$Y = \bar{A}$$

FIGURE 2. Truth table.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 4, 5, 6, and 8 in table I, method 5005 of MIL-STD-883 shall be omitted.
- c. Subgroup 7 shall include verification of the truth table.

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test conditions, method 1005 of MIL-STD-883.
  - (1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.
  - (2)  $T_A = +125^\circ\text{C}$ , minimum.
  - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

|   |                  |                     |                   |
|---|------------------|---------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                     | <b>84061</b>      |
|   |                  | REVISION LEVEL<br>A | SHEET<br><b>7</b> |

TABLE II. Electrical test requirements.

| MIL-STD-883 test requirements                                      | Subgroups<br>(in accordance with<br>MIL-STD-883, method 5005,<br>table I) |
|--|---|
| Interim electrical parameters<br>(method 5004)                     | - - -   |
| Final electrical test parameters<br>(method 5004)                  | 1*, 2, 3, 7, 9  |
| Group A test requirements<br>(method 5005)                         | 1, 2, 3, 9, 10**, 11**  |
| Groups C and D end-point<br>electrical parameters<br>(method 5005) | 1, 2, 3   |

\* PDA applies to subgroup 1.

\*\* Subgroups 10 and 11, if not tested, shall be guaranteed to the specified limits in table I.

## 5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535, appendix A.

## 6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

6.4 Record of users. Military and industrial users shall inform Defense Supply Center Columbus (DSCC) when a system application requires configuration control and the applicable SMD. DSCC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronics devices (FSC 5962) should contact DSCC-VA, telephone (614) 692-0544.

6.5 Comments. Comments on this drawing should be directed to DSCC-VA, Columbus, Ohio 43218-3990, or telephone (614) 692-0547.

6.6 Approved sources of supply. Approved sources of supply are listed in MIL-HDBK-103. The vendors listed in MIL-HDBK-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DSCC-VA.

|   |                  |                     |                   |
|---|------------------|---------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                     | <b>84061</b>      |
|   |                  | REVISION LEVEL<br>A | SHEET<br><b>8</b> |

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 09-11-16

Approved sources of supply for SMD 84061 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DSCC-VA. This information bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535. DSCC maintains an online database of all current sources of supply at <http://www.dscclia.mil/Programs/Smcr/>.

| Standard microcircuit drawing PIN <u>1/</u> | Vendor CAGE number | Vendor similar PIN <u>2/</u> | Reference military PIN |
|---|--------------------|------------------------------|------------------------|
| 8406101BA                                   | <u>3/</u>          | SNJ54ALS1004WA               | M38510/38409BBA        |
| 8406101CA                                   | <u>3/</u>          | SNJ54ALS1004J                | M38510/38409BCA        |
| 8406101DA                                   | <u>3/</u>          | SNJ54ALS1004W                | M38510/38409BDA        |
| 84061012A                                   | <u>3/</u>          | SNJ54ALS1004FK               | M38510/38409B2A        |

- 1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.
- 2/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.
- 3/ Not available from an approved source of supply. The last known source of supply is listed below.

Vendor CAGE number

01295

Vendor name and address

Texas Instruments, Inc.  
Semiconductor Group  
8505 Forest Lane  
PO Box 660199  
Dallas, TX 75243

POC U.S. Highway 75 South  
P.O. Box 84, M/S 853  
Sherman, TX 75090-9493

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.