

REVISIONS

LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Correct paragraphs 4.2.a.2. and 4.3.3.b.2. Table I, correct test symbol for Rise time and Fall time.	05-06-24	Raymond Monnin
B	Updated drawing paragraphs. -sld	11-09-02	Charles F. Saffle

REV																				
SHEET																				
REV																				
SHEET																				


REV STATUS	REV	B	B	B	B	B	B	B	B	B	B	B	B	B	B		
OF SHEETS	SHEET	1	2	3	4	5	6	7	8	9	10	11	12				

PMIC N/A	PREPARED BY Gary Zahn	<p align="center">DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990 http://www.landandmaritime.dla.mil</p>															
<p align="center">STANDARD MICROCIRCUIT DRAWING</p> <p align="center">THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE</p> <p align="center">AMSC N/A</p>	CHECKED BY Michael C. Jones																
	APPROVED BY Kendall A. Cottongim	<p align="center">MICROCIRCUIT, HYBRID, DIGITAL, SINGLE CHANNEL, DRIVER-RECEIVER</p>															
	DRAWING APPROVAL DATE 97-10-29																
	REVISION LEVEL B		<table border="1"> <tr> <td>SIZE A</td> <td>CAGE CODE 67268</td> <td rowspan="2">5962-96741</td> </tr> <tr> <td colspan="2">SHEET</td> </tr> </table>	SIZE A	CAGE CODE 67268	5962-96741	SHEET										
SIZE A	CAGE CODE 67268	5962-96741															
SHEET																	
		1 OF 12															

1. SCOPE

1.1 Scope. This drawing documents five product assurance classes as defined in paragraph 1.2.3 and MIL-PRF-38534. A choice of case outlines and lead finishes which are available and are reflected in the Part or Identifying Number (PIN). When available, a choice of radiation hardness assurance levels are reflected in the PIN.

1.2 PIN. The PIN shall be as shown in the following example:



1.2.1 Radiation hardness assurance (RHA) designator. RHA marked devices shall meet the MIL-PRF-38534 specified RHA levels and shall be marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	ACT4455	+5 V, single channel, MIL-STD-1553 transceiver (standby low)
02	ACT4459	+5 V, single channel, MIL-STD-1553 transceiver (standby high)

1.2.3 Device class designator. This device class designator shall be a single letter identifying the product assurance level. All levels are defined by the requirements of MIL-PRF-38534 and require QML Certification as well as qualification (Class H, K, and E) or QML Listing (Class G and D). The product assurance levels are as follows:

<u>Device class</u>	<u>Device performance documentation</u>
K	Highest reliability class available. This level is intended for use in space applications.
H	Standard military quality class level. This level is intended for use in applications where non-space high reliability devices are required.
G	Reduced testing version of the standard military quality class. This level uses the Class H screening and In-Process Inspections with a possible limited temperature range, manufacturer specified incoming flow, and the manufacturer guarantees (but may not test) periodic and conformance inspections (Group A, B, C, and D).
E	Designates devices which are based upon one of the other classes (K, H, or G) with exception(s) taken to the requirements of that class. These exception(s) must be specified in the device acquisition document; therefore the acquisition document should be reviewed to ensure that the exception(s) taken will not adversely affect system performance.
D	Manufacturer specified quality class. Quality level is defined by the manufacturers internal, QML certified flow. This product may have a limited temperature range.

1.2.4 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

<u>Outline letter</u>	<u>Descriptive designator</u>	<u>Terminals</u>	<u>Package style</u>
3	CQCC1-N28	28	Leadless chip carrier

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-96741
		REVISION LEVEL B	SHEET 2

1.2.5 Lead finish. The lead finish shall be as specified in MIL-PRF-38534.

1.3 Absolute maximum ratings. ^{1/}

Supply voltage range (V_{CC})	-0.3 V dc to +7.0 V dc
Logic input voltage range	-0.3 V dc to +5.5 V dc
Receiver differential input voltage	10 V_{p-p}
Driver peak output current	+1.0 A
Power dissipation (P_D):	
Total hybrid (standby)	200 mW
Total hybrid (100% duty cycle)	2 W
Storage temperature range	-65°C to +150°C
Lead temperature (soldering, 10 seconds)	+300°C
Junction temperature (T_J)	+135°C
Thermal resistance, junction-to-case (θ_{JC})	5°C/W
Thermal resistance, junction-to-ambient (θ_{JA})	20°C/W (still air)

1.4 Recommended operating conditions.

Supply voltage range (V_{CC})	+4.75 V dc to +5.5 V dc
Logic input voltage range	0 V dc to +5.0 V dc
Receiver differential input voltage	8.0 V_{p-p}
Driver peak output current	800 mA
Maximum serial data rate	1.0 MHz
Case operating temperature range (T_C)	-55°C to +125°C

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38534 - Hybrid Microcircuits, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-883 - Test Method Standard Microcircuits.
MIL-STD-1835 - Interface Standard for Electronic Component Case Outlines.

DEPARTMENT OF DEFENSE HANDBOOKS

MIL-HDBK-103 - List of Standard Microcircuit Drawings.
MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these documents are available online at <https://assist.daps.dla.mil/quicksearch/> or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

^{1/} Stresses above the absolute maximum ratings may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-96741
		REVISION LEVEL B	SHEET 3

3. REQUIREMENTS

3.1 Item requirements. The individual item performance requirements for device classes D, E, G, H, and K shall be in accordance with MIL-PRF-38534. Compliance with MIL-PRF-38534 may include the performance of all tests herein or as designated in the device manufacturer's Quality Management (QM) plan or as designated for the applicable device class. The manufacturer may eliminate, modify or optimize the tests and inspections herein, however the performance requirements as defined in MIL-PRF-38534 shall be met for the applicable device class. In addition, the modification in the QM plan shall not affect the form, fit, or function of the device for the applicable device class.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38534 and herein.

3.2.1 Case outline(s). The case outline(s) shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.3 Timing waveform(s). The timing waveform(s) shall be as specified on figure 2.

3.2.4 Typical bus connections. The typical bus connections shall be as specified on figure 3.

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full specified operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are defined in table I.

3.5 Marking of device(s). Marking of device(s) shall be in accordance with MIL-PRF-38534. The device shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's vendor similar PIN may also be marked.

3.6 Data. In addition to the general performance requirements of MIL-PRF-38534, the manufacturer of the device described herein shall maintain the electrical test data (variables format) from the initial quality conformance inspection group A lot sample, for each device type listed herein. Also, the data should include a summary of all parameters manually tested, and for those which, if any, are guaranteed. This data shall be maintained under document revision level control by the manufacturer and be made available to the preparing activity (DLA Land and Maritime -VA) upon request.

3.7 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to supply to this drawing. The certificate of compliance (original copy) submitted to DLA Land and Maritime -VA shall affirm that the manufacturer's product meets the performance requirements of MIL-PRF-38534 and herein.

3.8 Certificate of conformance. A certificate of conformance as required in MIL-PRF-38534 shall be provided with each lot of microcircuits delivered to this drawing.

4. VERIFICATION

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with MIL-PRF-38534 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-96741
		REVISION LEVEL B	SHEET 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions 1/ -55°C ≤ T _C ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
RECEIVER							
Output low voltage	V _{OL}	I _{OL} = 4.0 mA	1,2,3	01,02		0.5	V
Output high voltage	V _{OH}	I _{OH} = -0.4 mA	1,2,3	01,02	2.5		V
Threshold voltage	V _{TH}	1 MHz sine wave	4,5,6	01,02	0.56	1.1	V
Receiver delay	t _{DR}	From input <u>zero</u> crossing to DATA or DATA. See figure 2.	9,10,11	01,02		500	ns
RECEIVER STROBE							
Input low voltage	V _{SIL}		1,2,3	01,02		0.7	V
Input high voltage	V _{SIH}		1,2,3	01,02	2.0		V
Input low current	I _{SIL}	V _{SIL} = 0.4 V	1,2,3	01,02	-0.4		mA
Input high current	I _{SIH}	V _{SIH} = 2.7 V	1,2,3	01,02		40.0	μA
Strobe delay	t _{DS}	From strobe rising or falling edge to DATA or DATA. See figure 2.	1,2,3	01,02		200.0	ns
TRANSMITTER							
Input low voltage	V _{IL}		1,2,3	01,02		0.7	V
Input high voltage	V _{IH}		1,2,3	01,02	2.0		V
Input low current	I _{IL}	V _{IL} = 0.4 V	1,2,3	01,02	-0.4		mA
Input high current	I _{IH}	V _{IH} = 2.7 V	1,2,3	01,02		40.0	μA
Differential output voltage	V _O	35Ω load, see point A on figure 3.	4,5,6	01,02	6.5	9.0	V _{P-P}
		140Ω load, see point B on figure 3.			26.0	36.0	
Differential input impedance	Z _{oi}	1 MHz sine wave. In accordance with MIL-STD- 1553B, paragraph 4.5.2.2.3, see figure 3.	4,5,6	01,02	2.0		kΩ
See footnotes at end of table.							
STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990				SIZE A		5962-96741	
				REVISION LEVEL B		SHEET 5	

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions <u>1/</u> -55°C ≤ T _C ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
TRANSMITTER - Continued.							
Differential output noise	V _{ON}	Inhibited	4,5,6	01,02		10.0	mV _{P-P}
Differential offset voltage	V _{OS}	35Ω load, see point A on figure 3.	4,5,6	01,02	-90.0	+90.0	mV-pk
		140Ω load, see point B on figure 3.			-360.0	+360.0	
Rise time	t _R	35Ω load, see figure 2.	9,10,11	01,02	100.0	300.0	ns
Fall time	t _F	35Ω load, see figure 2.	9,10,11	01,02	100.0	300.0	ns
Driver delay	t _{DT}	TX IN to TX OUT, see figure 2.	9,10,11	01,02		250.0	ns
TRANSMITTER INHIBIT							
Input low voltage	V _{IIL}		1,2,3	01,02		0.7	V
Input high voltage	V _{IHH}		1,2,3	01,02	2.0		V
Input low current	I _{IIL}	V _{IIL} = 0.4 V	1,2,3	01,02	-0.4		mA
Input high current	I _{IHH}	V _{IHH} = 2.7 V	1,2,3	01,02		40.0	μA
Inhibit delay	t _{DI-H}	Inhibited output, see figure 2.	9,10,11	01,02		450.0	ns
	t _{DI-L}	Active output, see figure 2.				250.0	
POWER SUPPLY							
Supply current <u>2/</u>	I _{CC1}	Standby, data applied, inhibit high	1,2,3	01,02		30.0	mA
	I _{CC2}	25% duty cycle, 1MHz	4,5,6	01,02		220.0	mA
	I _{CC3}	50% duty cycle, 1MHz	4,5,6	01,02		395.0	mA
	I _{CC4}	100% duty cycle, 1MHz	4,5,6	01,02		745.0	mA

1/ V_{CC} = +5.0 V dc ±0.1 V dc, unless otherwise specified.
2/ Use Technitrol part number 1553-45, turns ratio 1 : 2.5 or equivalent.


STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-96741
		REVISION LEVEL B	SHEET 6

Device types	01 and 02	Device types	01 and 02
Case outline	3	Case outline	3
Terminal number	Terminal symbol	Terminal number	Terminal symbol
1	TX DATA OUT	15	+5 V supply
2	+5 V supply	16	Ground 3
3	+5 V supply	17	No connect
4	TX $\overline{\text{DATA}}$ OUT	18	RX DATA IN
5	TX $\overline{\text{DATA}}$ OUT	19	RX $\overline{\text{DATA}}$ IN
6	Ground 1	20	No connect
7	No connect	21	No connect
8	No connect	22	Ground 4
9	+5 V supply	23	+5 V supply
10	RX DATA OUT	24	INHIBIT
11	Strobe	25	TX DATA IN
12	No connect	26	TX $\overline{\text{DATA}}$ IN
13	RX $\overline{\text{DATA}}$ OUT	27	Ground 2
14	No connect	28	TX DATA OUT

FIGURE 1. Terminal connections.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-96741
		REVISION LEVEL B	SHEET 7

Device type 01.





NOTE: Both inputs "TX DATA IN" and "TX DATA IN" must be in the same logic states during off times.

FIGURE 2. Timing waveforms.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-96741
		REVISION LEVEL B	SHEET 8


Device type 02.



NOTE: Both inputs "TX DATA IN" and "TX DATA IN" must be in the same logic states during off times.

FIGURE 2. Timing waveforms - Continued.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-96741
		REVISION LEVEL B	SHEET 9



NOTE: Transformer is a Technitrol, part number 1553-45 or equivalent.

FIGURE 3. Typical bus connections.

**STANDARD
MICROCIRCUIT DRAWING**
DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990

SIZE
A

5962-96741

REVISION LEVEL
B

SHEET
10

TABLE II. Electrical test requirements.

MIL-PRF-38534 test requirements	Subgroups (in accordance with MIL-PRF-38534, group A test table)
Interim electrical parameters	3, 6, 11
Final electrical parameters	1*, 2, 3, 4, 5, 6, 9, 10, 11
Group A test requirements	1, 2, 3, 4, 5, 6, 9, 10, 11
Group C end-point electrical parameters	1, 2, 3
End-point electrical parameters for radiation hardness assurance (RHA) devices	Not applicable

* PDA applies to subgroup 1.

4.2 Screening. Screening shall be in accordance with MIL-PRF-38534. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

- (1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to either DLA Land and Maritime -VA or the acquiring activity upon request. Also, the test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.
- (2) T_C as specified in the approved manufacturer's QM plan.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Conformance and periodic inspections. Conformance inspection (CI) and periodic inspection (PI) shall be in accordance with MIL-PRF-38534 and as specified herein.

4.3.1 Group A inspection (CI). Group A inspection shall be in accordance with MIL-PRF-38534 and as follows:

- a. Tests shall be as specified in table II herein.
- b. Subgroups 7 and 8 shall be omitted.

4.3.2 Group B inspection (PI). Group B inspection shall be in accordance with MIL-PRF-38534.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-96741
		REVISION LEVEL B	SHEET 11

4.3.3 Group C inspection (PI). Group C inspection shall be in accordance with MIL-PRF-38534 and as follows:

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test, method 1005 of MIL-STD-883.
 - (1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to either DLA Land and Maritime -VA or the acquiring activity upon request. Also, the test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.
 - (2) T_C as specified in the approved manufacturer's QM plan.
 - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.3.4 Group D inspection (PI). Group D inspection shall be in accordance with MIL-PRF-38534.

4.3.5 Radiation Hardness Assurance (RHA) inspection. RHA inspection is not currently applicable to this drawing.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38534.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated as specified in MIL-PRF-38534.

6.4 Record of users. Military and industrial users shall inform DLA Land and Maritime when a system application requires configuration control and the applicable SMD. DLA Land and Maritime will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DLA Land and Maritime -VA, telephone (614) 692-0544.

6.5 Comments. Comments on this drawing should be directed to DLA Land and Maritime -VA, Columbus, Ohio 43218-3990, or telephone (614) 692-1081.

6.6 Sources of supply. Sources of supply are listed in MIL-HDBK-103 and QML-38534. The vendors listed in MIL-HDBK-103 and QML-38534 have submitted a certificate of compliance (see 3.7 herein) to DLA Land and Maritime -VA and have agreed to this drawing.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-96741
		REVISION LEVEL B	SHEET 12

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 11-09-02

Approved sources of supply for SMD 5962-96741 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38534 during the next revisions. MIL-HDBK-103 and QML-38534 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DLA Land and Maritime -VA. This information bulletin is superseded by the next dated revisions of MIL-HDBK-103 and QML-38534. DLA Land and Maritime maintains an online database of all current sources of supply at <http://www.landandmaritime.dla.mil/Programs/Smcr/>.

Standard microcircuit drawing PIN <u>1/</u>	Vendor CAGE number	Vendor similar PIN <u>2/</u>
5962-9674101H3A 5962-9674101H3C	88379 88379	ACT4455-001-2 ACT4455-001-1
5962-9674102H3A 5962-9674102H3C	88379 88379	ACT4459-001-2 ACT4459-001-1

- 1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the Vendor to determine its availability.
- 2/ **Caution.** Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE number

88379

Vendor name and address

Aeroflex Plainview, Incorporated
(Aeroflex Microelectronics Solutions)
35 South Service Road
Plainview, NY 11803-4193

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.