

REVISIONS

LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Update to current requirements. Editorial changes throughout. - gap	06-10-05	Raymond Monnin
B	Remove class M references. Update drawing to MIL-PRF-38535 requirements. - jt	16-03-01	Charles F. Saffle



REV																				
SHEET																				
REV																				
SHEET																				

REV STATUS OF SHEETS	REV	B	B	B	B	B	B	B	B	B	B	B	B			
	SHEET	1	2	3	4	5	6	7	8	9	10	11				

PMIC N/A	PREPARED BY Tuan Nguyen	<p align="center">DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990 http://www.landandmaritime.dla.mil</p>													
<p align="center">STANDARD MICROCIRCUIT DRAWING</p> <p>THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE</p> <p align="center">AMSC N/A</p>	CHECKED BY Larry Shaw														
	APPROVED BY Raymond Monnin	<p align="center">MICROCIRCUIT, DIGITAL, BIPOLAR, TTL, MONOSTABLE MULTIVIBRATOR, MONOLITHIC SILICON</p>													
	DRAWING APPROVAL DATE 97-05-30														
	REVISION LEVEL B	<table border="1"> <tr> <td>SIZE A</td> <td>CAGE CODE 67268</td> <td>5962-97553</td> </tr> </table>	SIZE A	CAGE CODE 67268	5962-97553										
SIZE A	CAGE CODE 67268	5962-97553													
		SHEET 1 OF 11													

1.3 Absolute maximum ratings. 1/

Supply voltage (V _{CC})	+7.0 V dc
Input voltage (V _{IN})	+5.5 V dc
Operating free air temperature range	-55 °C to +125 °C
Maximum power dissipation (P _D)	550 mW
Storage temperature range	-65 °C to +150 °C
Thermal resistance, junction-to-case (θ _{JC})	See MIL-STD-1835
Junction temperature (T _J)	+175 °C

1.4 Recommended operating conditions.

Supply voltage range (V _{CC})	4.5 V dc to 5.5 V dc
High-level output current (I _{OH})	-0.4 mA max
Low-level output current (I _{OL})	16 mA max
Rate of rise or fall of input pulse (dv/dt) 2/	
Schmitt input, B	1 V/s
Logic inputs, A1, A2	1 V/μs
Input pulse width (t _{w(in)})	50 ns min
External timing capacitance (R _{ext})	1.4 kΩ to 30 kΩ 2/
External timing capacitance (C _{ext})	1000 μF 2/
Duty cycle	
R _T = 2 kΩ	67%
R _T = MAX R _{ext}	90%
Case operating temperature range (T _c)	-55 °C to +125 °C

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-883 - Test Method Standard Microcircuits.
MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

DEPARTMENT OF DEFENSE HANDBOOKS

MIL-HDBK-103 - List of Standard Microcircuit Drawings.
MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these documents are available online at <http://quicksearch.dla.mil> or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.

2/ This parameter is not production tested.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-97553
		REVISION LEVEL B	SHEET 3

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 as specified herein, or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein for device classes Q and V.

3.2.1 Case outline. The case outline shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.3 Truth table. The truth table shall be as specified on figure 2.

3.2.4 Switching waveforms and test circuit. The switching waveforms and test circuit shall be as specified on figure 3.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full case operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked. For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device. For RHA product using this option, the RHA designator shall still be marked. Marking for device classes Q and V shall be in accordance with MIL-PRF-38535.

3.5.1 Certification/compliance mark. The certification mark for device classes Q and V shall be a "QML" or "Q" as required in MIL-PRF-38535.

3.6 Certificate of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.6.1 herein). The certificate of compliance submitted to DLA Land and Maritime-VA prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and herein.

3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 shall be provided with each lot of microcircuits delivered to this drawing.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-97553
		REVISION LEVEL B	SHEET 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Test Conditions -55 °C ≤ T _C ≤ +125 °C unless otherwise specified		Group A subgroups	Device type	Limits <u>1/</u>		Unit
						Min	Max	
High-level input voltage at A input	V _{IH}	V _{CC} = 4.5 V		1, 2, 3	01	2		V
Low-level input voltage at A input	V _{IL}	V _{CC} = 4.5 V		1, 2, 3	01		0.8	V
Positive-going threshold voltage at B input	V _{T+}	V _{CC} = 4.5 V			01		2	V
Input clamp voltage	V _{IK}	V _{CC} = 4.5 V, I _I = -12 mA		1, 2, 3	01		-1.5	V
High level output voltage	V _{OH}	V _{CC} = 4.5 V, I _{OH} = -0.4 mA		1, 2, 3	01	2.4		V
Low-level output voltage	V _{OL}	V _{CC} = 4.5 V, I _{OL} = 16 mA		1, 2, 3	01		0.4	V
Input current at maximum input voltage	I _I	V _{CC} = 5.5 V, V _I = 5.5 V		1, 2, 3	01		1	mA
High-level input current	I _{IH}	V _{CC} = 5.5 V, V _I = 2.4 V	A1 or A2	1, 2, 3	01		40	μA
			B	1, 2, 3	01		80	
Low-level input current	I _{IL}	V _{CC} = 5.5 V, V _I = 0.4 V	A1 or A2	1, 2, 3	01		-1.6	mA
			B	1, 2, 3	01		-3.2	
Short-circuit output current	I _{OS} <u>2/</u>	V _{CC} = 5.5 V		1, 2, 3	01	-20	-55	mA
Supply current	I _{CC}	V _{CC} = 5.5 V	Quiescent	1, 2, 3	01		25	mA
			Triggered <u>3/</u>	1, 2, 3	01		40	mA
Functional test		V _{IN} = V _{IH} min or V _{IL} max, Verify output V _O , See 4.4.1b		7, 8	01			

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-97553
		REVISION LEVEL B	SHEET 5

TABLE I. Electrical performance characteristics. – Continued.

Test	Symbol	Conditions -55 °C ≤ T _C ≤ +125 °C unless otherwise specified		Group A subgroups	Device type	Limits ^{1/}		Unit	
						Min	Max		
Propagation delay time, low-to-high level Q output from either A input	t _{PLH}	See figure 3 C _L = 15 pF, R _L = 400Ω	C _{ext} = 80 pF R _{int} to V _{CC}	9	01		70	ns	
Propagation delay time, low-to-high level Q output from B input	t _{PLH}			9	01		55	ns	
Propagation delay time, high- to-low level \bar{Q} output from either A input	t _{PHL}			9	01		80	ns	
Propagation delay time, high-to-low level \bar{Q} output from B input	t _{PHL}			9	01		65	ns	
Pulse width obtained using internal timing resistor	t _{w(out)}			C _{ext} = 80 pF, R _{int} to V _{CC}	9	01	70	150	ns
Pulse width obtained with zero timing capacitance	t _{w(out)}			C _{ext} = 0, R _{int} to V _{CC}	9	01		50	ns
Pulse width obtained using external timing resistor	t _{w(out)}			C _{ext} = 100 pF, R _T = 10 kΩ	9	01	600	800	ns
				C _{ext} = 1 μF, R _T = 10 kΩ ^{3/}	9	01	6	8	ms

^{1/} For negative and positive voltage and current values, the sign designates the potential difference in reference to GND and the direction of current flow, respectively, and the absolute value of the magnitude, not the sign, is relative to the minimum and maximum limits, as applicable, listed herein.

^{2/} Not more than one output should be shorted at a time.

^{3/} This parameter is not production tested.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-97553
		REVISION LEVEL B	SHEET 6



Device type	01
Case outlines	C, D
Terminal number	Terminal symbol
1	\bar{Q}
2	NC
3	A1
4	A2
5	B
6	Q
7	GND
8	NC
9	R _{INT}
10	C _{EXT}
11	R _{EXT} / C _{EXT}
12	NC
13	NC
14	V _{CC}

FIGURE 1. Terminal connections.

INPUTS			OUTPUTS	
A1	A2	B	Q	\bar{Q}
L	X	H	L	H
X	L	H	L \uparrow	H \uparrow
X	X	L	L \uparrow	H \uparrow
H	H	X	L \uparrow	H \uparrow
H	\downarrow	H		
\downarrow	H	H		
\downarrow	\downarrow	H		
L	X	\uparrow		
X	L	\uparrow		

FIGURE 2. Truth table.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-97553
		REVISION LEVEL B	SHEET 7



NOTES:

1. C_L includes probe and jig capacitance. $C_L = 15 \text{ pF}$, $R_L = 400 \text{ } \Omega$.
2. All diodes are 1N3064 or equivalent.

FIGURE 3. Test circuit and switching waveforms.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-97553
		REVISION LEVEL B	SHEET 8

4. VERIFICATION

4.1 Sampling and inspection. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein.

4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection.

4.2.1 Additional criteria for device classes Q and V.

- a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.
- b. Interim and final electrical test parameters shall be as specified in table II herein.
- c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in MIL-PRF-38535, appendix B.

4.3 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-PRF-38535. Inspections to be performed shall be those specified in MIL-PRF-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4 Conformance inspection. Technology conformance inspection for classes Q and V shall be in accordance with MIL-PRF-38535 including groups A, B, C, D, and E inspections, and as specified herein.

4.4.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. For device classes Q and V, subgroups 7 and 8 shall include verifying the functionality of the device.
- c. Subgroups 4, 5, and 6 in table I, method 5005 of MIL-STD-883 shall be omitted.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-97553
		REVISION LEVEL B	SHEET 9

TABLE II. Electrical test requirements.

Test requirements	Subgroups (in accordance with MIL-PRF-38535, table III)	
	Device class Q	Device class V
Interim electrical parameters (see 4.2)		
Final electrical parameters (see 4.2)	<u>1/</u> 1, 2, 3, 7, 8, 9	<u>2/</u> 1, 2, 3, 7, 8, 9
Group A test requirements (see 4.4)	1, 2, 3, 7, 8, 9	1, 2, 3, 7, 8, 9
Group C end-point electrical parameters (see 4.4)	1, 2, 3	1, 2, 3, 7, 8, 9
Group D end-point electrical parameters (see 4.4)	1, 2, 3	1, 2, 3
Group E end-point electrical parameters (see 4.4)	1, 7, 9	1, 7, 9

1/ PDA applies to subgroup 1.

2/ PDA applies to subgroups 1 and 7.

4.4.2 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table II herein.

4.4.2.1 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.

4.4.3 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table II herein.

4.4.4 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein).

- a. End-point electrical parameters shall be as specified in table II herein.
- b. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535 for the RHA level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table I at $T_A = +25^\circ\text{C} \pm 5^\circ\text{C}$, after exposure, to the subgroups specified in table II herein.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-97553
		REVISION LEVEL B	SHEET 10

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535 for device classes Q and V.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor prepared specification or drawing.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

6.3 Record of users. Military and industrial users should inform DLA Land and Maritime when a system application requires configuration control and which SMD's are applicable to that system. DLA Land and Maritime will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DLA Land and Maritime-VA, telephone (614) 692-8108.

6.4 Comments. Comments on this drawing should be directed to DLA Land and Maritime-VA, Columbus, Ohio 43218-3990, or telephone (614) 692-0540.

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535 and MIL-HDBK-1331.

6.6 Sources of supply.

6.6.1 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in MIL-HDBK-103 and QML-38535. The vendors listed in QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DLA Land and Maritime-VA and have agreed to this drawing.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-97553
		REVISION LEVEL B	SHEET 11

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 16-03-01

Approved sources of supply for SMD 5962-97553 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DLA Land and Maritime-VA. This information bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535. DLA Land and Maritime maintains an online database of all current sources of supply at <http://www.landandmaritime.dla.mil/Programs/Smcr/>.

Standard microcircuit drawing PIN <u>1/</u>	Vendor CAGE number	Vendor similar PIN <u>2/</u>
5962-9755301QCA	01295	SNJ54121J
5962-9755301QDA	01295	SNJ54121W

- 1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.
- 2/ **Caution.** Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE
number

01295

Vendor name
and address

Texas Instruments, Inc.
Semiconductor Group
8505 Forest Ln.
PO Box 660199
Dallas, TX 75243

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.