



1. SCOPE

1.1 Scope. This drawing documents the general requirements of a high performance single schmitt trigger inverter microcircuit, with an operating temperature range of -55°C to +125°C.

1.2 Vendor Item Drawing Administrative Control Number. The manufacturers PIN is the item of identification. The vendor item drawing establishes an administrative control number for identifying the item on the engineering documentation:

<u>V62/07626</u>	-	<u>01</u>	<u>X</u>	<u>E</u>
Drawing number		Device type (See 1.2.1)	Case outline (See 1.2.2)	Lead finish (See 1.2.3)

1.2.1 Device type(s).

<u>Device type</u>	<u>Generic</u>	<u>Circuit function</u>
01	SN74LVC1G14-EP	Single schmitt trigger inverter

1.2.2 Case outline(s). The case outline(s) are as specified herein.

<u>Outline letter</u>	<u>Number of pins</u>	<u>JEDEC PUB 95</u>	<u>Package style</u>
X	5	MO-178-AA	Plastics surface mount

1.2.3 Lead finishes. The lead finishes are as specified below or other lead finishes as provided by the device manufacture:

<u>Finish designator</u>	<u>Material</u>
A	Hot solder dip
B	Tin-lead plate
C	Gold plate
D	Palladium
E	Gold flash palladium
Z	Other

<b>DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO</b>	SIZE <b>A</b>	CODE IDENT NO. <b>16236</b>	DWG NO. <b>V62/07626</b>
		REV    A	PAGE    2

1.3 Absolute maximum ratings. 1/

Supply voltage range ( $V_{CC}$ ).....	-0.5 V to 6.5 V
Input voltage range ( $V_I$ ) .....	-0.5 V to 6.5 V 2/
Voltage range applied to any output in the high impedance or power off state ( $V_O$ ) .....	-0.5 V to 6.5 V 2/
Voltage range applied to any output in the high or low state ( $V_O$ ) .....	-0.5 V to $V_{CC} + 0.5$ V 2/ 3/
Input clamp current ( $I_{IK}$ ) ( $V_I < 0$ ) .....	-50 mA maximum
Output clamp current ( $I_{OK}$ ) ( $V_O < 0$ ) .....	-50 mA maximum
Continuous output current ( $I_O$ ) .....	$\pm 50$ mA maximum
Continuous current through $V_{CC}$ or GND .....	$\pm 100$ mA maximum
Package thermal impedance ( $\theta_{JA}$ ) .....	32°C/W maximum 4/
Storage temperature range ( $T_{STG}$ ) .....	-65°C to +150°C

1.4 Recommended operating conditions. 5/

Supply voltage range ( $V_{CC}$ ):	
Operating .....	1.65 V to 5.5 V
Data retention only .....	1.5 V minimum
Input voltage ( $V_I$ ) .....	0 V to 5.5 V
Output voltage ( $V_O$ ) .....	0 V to $V_{CC}$
High level output current ( $I_{OH}$ ):	
$V_{CC} = 1.65$ V .....	-4 mA maximum
$V_{CC} = 2.3$ V .....	-8 mA maximum
$V_{CC} = 3$ V .....	-16 mA maximum
$V_{CC} = 3$ V .....	-24 mA maximum
$V_{CC} = 4.5$ V .....	-32 mA maximum
Low level output current ( $I_{OL}$ ):	
$V_{CC} = 1.65$ V .....	4 mA maximum
$V_{CC} = 2.3$ V .....	8 mA maximum
$V_{CC} = 3$ V .....	16 mA maximum
$V_{CC} = 3$ V .....	24 mA maximum
$V_{CC} = 4.5$ V .....	32 mA maximum
Operating free-air temperature range ( $T_A$ ) .....	-55°C to +125°C

1/ Stresses beyond those listed under “absolute maximum rating” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

2/ The input and output negative voltage ratings may be exceeded if the input and output current ratings are observed.

3/ This value of  $V_{CC}$  is provided in the recommended operating conditions table.

4/ The package thermal impedance is calculated in accordance with JESD 51-2.

5/ All unused inputs of the device must be held at  $V_{CC}$  or GND to ensure proper device operation.

<b>DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO</b>	<b>SIZE A</b>	<b>CODE IDENT NO. 16236</b>	<b>DWG NO. V62/07626</b>
		REV    A	PAGE    3

## 2. APPLICABLE DOCUMENTS

JEDEC PUB 95 – Registered and Standard Outlines for Semiconductor Devices

(Applications for copies should be addressed to the Electronic Industries Alliance, 2500 Wilson Boulevard, Arlington, VA 22201-3834 or online at <http://www.jedec.org>)

## 3. REQUIREMENTS

3.1 Marking. Parts shall be permanently and legibly marked with the manufacturer's part number as shown in 6.3 herein and as follows:

- A. Manufacturer's name, CAGE code, or logo
- B. Pin 1 identifier
- C. ESDS identification (optional)

3.2 Unit container. The unit container shall be marked with the manufacturer's part number and with items A and C (if applicable) above.

3.3 Electrical characteristics. The maximum and recommended operating conditions and electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.4 Design, construction, and physical dimension. The design, construction, and physical dimensions are as specified herein.

3.5 Diagrams.

3.5.1 Case outline. The case outline shall be as shown in 1.2.2 and figure 1.

3.5.2 Terminal connections. The terminal connections shall be as shown in figure 2.

3.5.3 Truth table. The truth table shall be as shown in figure 3.

3.5.4 Logic diagram. The logic diagram shall be as shown in figure 4.

3.5.5 Timing waveforms and test circuit. The timing waveforms and test circuit shall be as shown in figures 5 and 6.

<b>DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO</b>	<b>SIZE A</b>	<b>CODE IDENT NO. 16236</b>	<b>DWG NO. V62/07626</b>
		REV A	PAGE 4

TABLE I. Electrical performance characteristics. 1/

Test	Symbol	Conditions	Temperature, T <sub>A</sub>	Device type	Limits		Unit
					Min	Max	
Electrical characteristics section							
Positive going input threshold voltage	V <sub>T+</sub>	V <sub>CC</sub> = 1.65 V	-55°C to +125°C	01	0.79	1.16	V
		V <sub>CC</sub> = 2.3 V			1.11	1.56	
		V <sub>CC</sub> = 3 V			1.5	1.87	
		V <sub>CC</sub> = 4.5 V			2.16	2.74	
		V <sub>CC</sub> = 5.5 V			2.61	3.33	
Negative going input threshold voltage	V <sub>T-</sub>	V <sub>CC</sub> = 1.65 V	-55°C to +125°C	01	0.39	0.62	V
		V <sub>CC</sub> = 2.3 V			0.58	0.87	
		V <sub>CC</sub> = 3 V			0.84	1.14	
		V <sub>CC</sub> = 4.5 V			1.41	1.79	
		V <sub>CC</sub> = 5.5 V			1.87	2.29	
Hysteresis ( V <sub>T+</sub> - V <sub>T-</sub> )	ΔV <sub>T</sub>	V <sub>CC</sub> = 1.65 V	-55°C to +125°C	01	0.37	0.62	V
		V <sub>CC</sub> = 2.3 V			0.48	0.77	
		V <sub>CC</sub> = 3 V			0.56	0.87	
		V <sub>CC</sub> = 4.5 V			0.71	1.04	
		V <sub>CC</sub> = 5.5 V			0.71	1.11	
High level output voltage	V <sub>OH</sub>	I <sub>OH</sub> = -100 μA, V <sub>CC</sub> = 1.65 to 4.5 V	-55°C to +125°C	01	V <sub>CC</sub> - 0.1		V
		I <sub>OH</sub> = -4 mA, V <sub>CC</sub> = 1.65 V			1.2		
		I <sub>OH</sub> = -8 mA, V <sub>CC</sub> = 2.3 V			1.9		
		I <sub>OH</sub> = -16 mA, V <sub>CC</sub> = 3 V			2.4		
		I <sub>OH</sub> = -24 mA, V <sub>CC</sub> = 3 V			2.3		
		I <sub>OH</sub> = -32 mA, V <sub>CC</sub> = 4.5 V			3.8		

See footnote at end of table.

<b>DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO</b>	<b>SIZE A</b>	<b>CODE IDENT NO. 16236</b>	<b>DWG NO. V62/07626</b>
		<b>REV A</b>	<b>PAGE 5</b>

TABLE I. Electrical performance characteristics – Continued. 1/

Test	Symbol	Conditions	Temperature, T <sub>A</sub>	Device type	Limits		Unit
					Min	Max	
Electrical characteristics section – continued.							
Low level output voltage	V <sub>OL</sub>	I <sub>OL</sub> = 100 μA, V <sub>CC</sub> = 1.65 V to 4.5 V	-55°C to +125°C	01		0.1	V
		I <sub>OL</sub> = 4 mA, V <sub>CC</sub> = 1.65 V				0.45	
		I <sub>OL</sub> = 8 mA, V <sub>CC</sub> = 2.3 V				0.3	
		I <sub>OL</sub> = 16 mA, V <sub>CC</sub> = 3 V				0.4	
		I <sub>OL</sub> = 24 mA, V <sub>CC</sub> = 3 V				0.55	
		I <sub>OL</sub> = 32 mA, V <sub>CC</sub> = 4.5 V				0.55	
Input current, A input	I <sub>I</sub>	V <sub>I</sub> = 5.5 V or GND, V <sub>CC</sub> = 0 to 5.5 V	-55°C to +125°C	01		±5	μA
Off current	I <sub>off</sub>	V <sub>I</sub> or V <sub>O</sub> = 5.5 V, V <sub>CC</sub> = 0 V	-55°C to +125°C	01		±10	μA
Supply current	I <sub>CC</sub>	V <sub>I</sub> = 5.5 V or GND, I <sub>O</sub> = 0, V <sub>CC</sub> = 1.65 V to 5.5 V	-55°C to +125°C	01		19	μA
Quiescent supply current	ΔI <sub>CC</sub>	One input at V <sub>CC</sub> – 0.6 V, other inputs at V <sub>CC</sub> or GND, V <sub>CC</sub> = 3 V to 5.5 V	-55°C to +125°C	01		500	μA
Input capacitance	C <sub>I</sub>	V <sub>I</sub> = V <sub>CC</sub> or GND, V <sub>CC</sub> = 3.3 V	+25°C	01	4.5 typical		pF

See footnote at end of table.

<b>DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO</b>	<b>SIZE A</b>	<b>CODE IDENT NO. 16236</b>	<b>DWG NO. V62/07626</b>
		<b>REV     A</b>	<b>PAGE    6</b>

TABLE I. Electrical performance characteristics – Continued. 1/

Test	Symbol	Conditions	Temperature, T <sub>A</sub>	Device type	Limits		Unit
					Min	Max	
Switching characteristics section.							
Propagation delay time, from input A to output Y	t <sub>pd</sub>	V <sub>CC</sub> = 1.8 V ±0.15 V, C <sub>L</sub> = 15 pF, see figure 5	-55°C to +125°C	01	2.8	9.9	ns
		V <sub>CC</sub> = 2.5 V ±0.2 V, C <sub>L</sub> = 15 pF, see figure 5			1.6	5.5	
		V <sub>CC</sub> = 3.3 V ±0.3 V, C <sub>L</sub> = 15 pF, see figure 5			1.5	4.6	
		V <sub>CC</sub> = 5 V ±0.5 V, C <sub>L</sub> = 15 pF, see figure 5			0.9	4.4	
		V <sub>CC</sub> = 1.8 V ±0.15 V, C <sub>L</sub> = 30 pF or 50 pF, see figure 6			3.8	16	
		V <sub>CC</sub> = 2.5 V ±0.2 V, C <sub>L</sub> = 30 pF or 50 pF, see figure 6			2	7.5	
		V <sub>CC</sub> = 3.3 V ±0.3 V, C <sub>L</sub> = 30 pF or 50 pF, see figure 6			1.8	6.0	
		V <sub>CC</sub> = 5 V ±0.5 V, C <sub>L</sub> = 30 pF or 50 pF, see figure 6			1.2	5	
Operating characteristics section.							
Power dissipation capacitance	C <sub>pd</sub>	f = 10 MHz, V <sub>CC</sub> = 1.8 V	+25°C	01	20 typical		pF
		f = 10 MHz, V <sub>CC</sub> = 2.5 V			21 typical		
		f = 10 MHz, V <sub>CC</sub> = 3.3 V			22 typical		
		f = 10 MHz, V <sub>CC</sub> = 5 V			25 typical		

1/ Testing and other quality control techniques are used to the extent deemed necessary to assure product performance over the specified temperature range. Product may not necessarily be tested across the full temperature range and all parameters may not necessarily be tested. In the absence of specific parametric testing, product performance is assured by characterization and/or design.

<b>DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO</b>	<b>SIZE A</b>	<b>CODE IDENT NO. 16236</b>	<b>DWG NO. V62/07626</b>
		<b>REV A</b>	<b>PAGE 7</b>

Case X




FIGURE 1. Case outline.

<p><b>DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO</b></p>	<p><b>SIZE A</b></p>	<p><b>CODE IDENT NO. 16236</b></p>	<p><b>DWG NO. V62/07626</b></p>
		<p>REV    A</p>	<p>PAGE    8</p>

Case X – continued.

Symbol	Dimensions			
	Inch		Millimeters	
	Min	Max	Min	Max
A	---	.057	---	1.45
A1	.000	.005	0.00	0.15
b	.011	.019	0.30	0.50
c	.003	.008	0.08	0.22
D	.108	.121	2.75	3.05
E	.057	.068	1.45	1.75
E1	.102	.118	2.60	3.00
e	.037 BSC		0.95 BSC	
L	.011	.021	0.30	0.55
L1	.009 BSC		0.25 BSC	
n	5 leads		5 leads	

NOTES:

1. Controlling dimensions are millimeter, inch dimensions are given for reference only.
2. Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 mm (0.006 inch ) per side.
3. Falls with JEDEC MO-178 variation AA.

FIGURE 1. Case outline – Continued.

<b>DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO</b>	<b>SIZE A</b>	<b>CODE IDENT NO. 16236</b>	<b>DWG NO. V62/07626</b>
		REV A	PAGE 9


Device type	01
Case outline	X
Terminal number	Terminal symbol
1	NC
2	A
3	GND
4	Y
5	VCC

FIGURE 2. Terminal connections.

Input	Output
A	Y
H	L
L	H

H = High voltage level  
L = Low voltage level


FIGURE 3. Truth table.



(Positive logic)

FIGURE 4. Logic diagram.

<b>DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO</b>	<b>SIZE A</b>	<b>CODE IDENT NO. 16236</b>	<b>DWG NO. V62/07626</b>
		REV    A	PAGE    10




NOTES:


1.  $C_L$  includes probe and jig capacitance.
2. Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
3. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 10$  MHz,  $Z_O = 50 \Omega$ .
4. The outputs are measured one at a time with one input transition per measurement.
5.  $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .
6.  $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{en}$ .
7.  $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .
8. All parameters and waveforms are not applicable to all devices.

FIGURE 5. Timing waveforms and test circuit.

<p><b>DEFENSE SUPPLY CENTER, COLUMBUS</b> <b>COLUMBUS, OHIO</b></p>	<p>SIZE <b>A</b></p>	<p>CODE IDENT NO. <b>16236</b></p>	<p>DWG NO. <b>V62/07626</b></p>
		<p>REV    <b>A</b></p>	<p>PAGE    <b>11</b></p>



$V_{CC}$	INPUTS		$V_M$	$V_{LOAD}$	$C_L$	$R_L$	$V_{\Delta}$
	$V_I$	$t_r/t_f$					
1.8 V $\pm$ 0.15 V	$V_{CC}$	$\leq 2$ ns	$V_{CC}/2$	$2 \times V_{CC}$	30 pF	1 k $\Omega$	0.15 V
2.5 V $\pm$ 0.2 V	$V_{CC}$	$\leq 2$ ns	$V_{CC}/2$	$2 \times V_{CC}$	30 pF	500 $\Omega$	0.15 V
3.3 V $\pm$ 0.3 V	3 V	$\leq 2.5$ ns	1.5 V	6 V	50 pF	500 $\Omega$	0.3 V
5 V $\pm$ 0.5 V	$V_{CC}$	$\leq 2.5$ ns	$V_{CC}/2$	$2 \times V_{CC}$	50 pF	500 $\Omega$	0.3 V



NOTES:

1.  $C_L$  includes probe and jig capacitance.
2. Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
3. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 10$  MHz,  $Z_O = 50 \Omega$ .
4. The outputs are measured one at a time with one input transition per measurement.
5.  $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .
6.  $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{en}$ .
7.  $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .
8. All parameters and waveforms are not applicable to all devices.

FIGURE 6. Timing waveforms and test circuit.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO	SIZE	CODE IDENT NO.	DWG NO.
	A	16236	V62/07626
	REV	A	PAGE 12

4. VERIFICATION

4.1 Product assurance requirements. The manufacturer is responsible for performing all inspection and test requirements as indicated in their internal documentation. Such procedures should include proper handling of electrostatic sensitive devices, classification, packaging, and labeling of moisture sensitive devices, as applicable.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Preservation, packaging, labeling, and marking shall be in accordance with the manufacturer's standard commercial practices for electrostatic discharge sensitive devices.

6. NOTES

6.1 ESDS. Devices are electrostatic discharge sensitive and are classified as ESDS class 1 minimum.

6.2 Configuration control. The data contained herein is based on the salient characteristics of the device manufacturer's data book. The device manufacturer reserves the right to make changes without notice. This drawing will be modified as changes are provided.

6.3 Suggested source(s) of supply. Identification of the suggested source(s) of supply herein is not to be construed as a guarantee of present or continued availability as a source of supply for the item.

Vendor item drawing administrative control number <u>1/</u>	Device manufacturer CAGE code	Package <u>2/</u>	Top side marking <u>3/</u>	Vendor part number
V62/07626-01XE	01295	Reel of 3000	SBLM	SN74LVC1G14MDBVREP

- 1/ The vendor item drawing establishes an administrative control number for identifying the item on the engineering documentation.
- 2/ For the most current package and ordering information, see the package option addendum at the end of this document, or see the Texas Instruments web site at [www.ti.com](http://www.ti.com).
- 3/ The actual top side marking has one additional character that designates the assembly / test site.

CAGE code

01295

Source of supply

Texas Instruments, Inc.  
 Semiconductor Group  
 8505 Forest Ln.  
 P.O. Box 660199  
 Dallas, TX 75243  
 Point of contact: U.S. Highway 75 South  
 P.O. Box 84, M/S 853  
 Sherman, TX 75090-9493

<b>DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO</b>	<b>SIZE A</b>	<b>CODE IDENT NO. 16236</b>	<b>DWG NO. V62/07626</b>
		<b>REV      A</b>	<b>PAGE    13</b>