

REVISIONS

LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Extended the temperature range from -55°C to +125°C. - phn	14-05-05	Thomas M. Hess
B	Update boilerplate paragraphs to current VID description requirements. - DRH	23-07-24	Muhammad A. Akbar



Prepared in accordance with ASME Y14.24

Vendor Item Drawing

Revision Status of Sheets


REV																				
SHEET																				
REV	B	B	B	B	B	B	B	B	B	B	B	B								
SHEET	1	2	3	4	5	6	7	8	9	10	11	12	13							

PMIC N/A Original date of drawing YY-MM-DD 12-10-09	PREPARED BY Phu H. Nguyen		DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990 https://www.dla.mil/landandmaritime	
	CHECKED BY Phu H. Nguyen		TITLE MICROCIRCUIT, DUAL CHANNEL DIGITAL ISOLATOR, MONOLITHIC SILICON	
	APPROVED BY Thomas M. Hess			
	SIZE A	CAGE CODE 16236	DWG NO. V62/12630	
	REV	B	PAGE	1 OF 13

1. SCOPE

1.1 Scope. This drawing documents the general requirements of a high performance dual channel digital isolator microcircuit, with an operating temperature range of -55°C to +125°C.

1.2 Vendor Item Drawing Administrative Control Number. The manufacturer's PIN is the item of identification. The vendor item drawing establishes an administrative control number for identifying the item on the engineering documentation:



1.2.1 Device type(s).

<u>Device type</u>	<u>Generic</u>	<u>Circuit function</u>
01	ADuM1200-EP	Dual channel digital isolator

1.2.2 Case outline(s). The case outlines are as specified herein.

<u>Outline letter</u>	<u>Number of pins</u>	<u>JEDEC PUB 95</u>	<u>Package style</u>
X	8	JEDEC MS-012-AA	Small Outline Package

1.2.3 Lead finishes. The lead finishes are as specified below or other lead finishes as provided by the device manufacturer:

<u>Finish designator</u>	<u>Material</u>
A	Hot solder dip
B	Tin-lead plate
C	Gold plate
D	Palladium
E	Gold flash palladium
Z	Other

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 2

1.3 Absolute maximum ratings. 1/

Supply voltage, (V _{DD1} , V _{DD2})	-0.5 V to +7.0 V 2/
Input voltage, (V _{IA} , V _{IB})	-0.5 V to V _{DD1} + 0.5 V 2/ 3/
Output voltage, (V _{OA} , V _{OB})	-0.5 V to V _{DD0} +0.5 V 2/ 3/
Average output current per pin (I _o)	-11 mA to +11 mA 4/
Common mode transients (C _{ML} , C _{MH})	-100 kV/μs to +100 kV/μs 5/
Ambient operating temperature, (T _A)	-55°C to +125°C
Storage temperature, (T _{ST})	-55°C to +150°C

1.4 Recommended operating conditions.

Supply voltage, (V _{DD1} , V _{DD2})	3.0 V to 5.5 V 2/
Input signal rise and fall times	1.0 ms
Operating temperature, (T _A)	-55°C to +125°C

1.5 Package characteristics.

Resistance (Input to output), R _{I-O}	10 ¹² Ω 6/
Capacitance (Input to output) C _{I-O}	1.0 pF (at f = 1 MHz)
Input capacitance, C _I	4.0 pF
Junction to case thermal resistance,(Side 1) θ _{JCI}	46 °C/W 7/
Junction to case thermal resistance,(Side 2) θ _{JCO}	41 °C/W

2. APPLICABLE DOCUMENTS

SOLID STATE TECHNOLOGY ASSOCIATION (JEDEC)

- JEDEC PUB 95 – Registered and Standard Outlines for Semiconductor Devices
- JESD 51-7 – High Effective Thermal Conductivity Test Board for Leaded Surface Mount Packages

(Copies of these documents are available online at <https://www.jedec.org>.)

-
- 1/ Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
 - 2/ All voltages are relative to their respective ground.
 - 3/ V_{DD1} and V_{DD0} refer to the supply voltages on the input and output sides of a given channel, respectively.
 - 4/ See FIGURE 6 for maximum rated current values for various temperatures.
 - 5/ Refers to common mode transients exceeding the absolute maximum ratings can cause latch up or permanent damage.
 - 6/ The device is considered a 2-terminal device; Pin1, Pin2, Pin3, and Pin4 are shorted together, and Pin5, Pin6, Pin7, and Pin8 are shorted together.
 - 7/ Thermocouple located at center of package underside.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 3

3. REQUIREMENTS

3.1 Marking. Parts shall be permanently and legibly marked with the manufacturer's part number as shown in 6.3 herein and as follows:

- A. Manufacturer's name, CAGE code, or logo
- B. Pin 1 identifier
- C. ESDS identification (optional)

3.2 Unit container. The unit container shall be marked with the manufacturer's part number and with items A and C (if applicable) above.

3.3 Electrical characteristics. The maximum and recommended operating conditions and electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.4 Design, construction, and physical dimension. The design, construction, and physical dimensions are as specified herein.

3.5 Diagrams.

3.5.1 Case outline. The case outline shall be as shown in 1.2.2 and figure 1.

3.5.2 Terminal connections. The terminal connections shall be as shown in figure 2.

3.5.3 Terminal function. The terminal function shall be as shown in figure 3.

3.5.4 Truth table. The truth table shall be as shown in figure 4.

3.5.5 Functional block diagram. The functional block diagram shall be as shown in figure 5.

3.5.6 Thermal derating curve. The thermal derating curve shall be as shown in figure 6.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 4

TABLE I. Electrical performance characteristics. 1/

Test	Symbol	Test conditions 4.5 V ≤ V _{DD1} ≤ 5.5 V 4.5 V ≤ V _{DD2} ≤ 5.5 V 2/	Device type	Limits			Unit	
				Min	Typ	Max		
5 V OPERATIONS								
DC specifications								
Input supply current per channel, quiescent	I _{DD1(Q)}		All		0.50	0.60	mA	
Output supply current per channel, quiescent	I _{DD0(Q)}				0.19	0.30	mA	
Total supply current, two channels 3/ DC to 2 Mbps							mA	
V _{DD1} supply current	I _{DD1(Q)}	4/			1.1	1.4		
V _{DD2} supply current	I _{DD2(Q)}	4/			0.5	0.8		
10 Mbps								
V _{DD1} supply current	I _{DD1(Q)}	5/			4.3	5.5		
V _{DD2} supply current	I _{DD2(Q)}	5/			1.3	2.0		
25 Mbps								
V _{DD1} supply current	I _{DD1(Q)}	6/			10	13		
V _{DD2} supply current	I _{DD2(Q)}	6/		2.8	3.4			
Input currents	I _{IA} , I _{IB}			-10	+0.01	+10	μA	
Logic high input threshold	V _{IH}			0.7 x 7/			V	
Logic low input threshold	V _{IL}					0.3 x 7/		
Logic high output voltages	V _{OA} H, V _{OB} H	I _{OX} = -20 μA, V _{IX} = V _{IXH} I _{OX} = -20 μA, V _{IX} = V _{IXH}		7/ - 0.1 7/ - 0.5	5.0 4.8			
Logic low output voltages	V _{OAL} , V _{OBL}	I _{OX} = 20 μA, V _{IX} = V _{IXL} I _{OX} = 400 μA, V _{IX} = V _{IXL} I _{OX} = 4 mA, V _{IX} = V _{IXL}			0.0 0.04 0.2	0.1 0.1 0.4		
Switching specifications								
Minimum pulse width 8/	PW		All		20	40	ns	
Maximum data rate 9/					25	50		Mbps
Propagation delay 10/	t _{PHL} , t _{PLH}				20		55	ns
Pulse width distortion, t _{PLH} - t _{PHL} 10/	PWD						3	
Propagation delay skew 11/	t _{PSK}						15	
Channel to channel matching 12/	t _{PSKCD} /t _{PSKOD}						3	
Output rise/fall time (10% to 90%)	t _R /t _F					2.5		
Common mode transient immunity Logic high output 13/	C _{MH}	V _{IX} = V _{DD1} , V _{DD2} , V _{CM} = 1000 V, transient magnitude = 800 V			25	35		kV/μs
Logic low output 13/	C _{ML}	V _{IX} = 0 V, V _{CM} = 1000 V, transient magnitude = 800 V			25	35		
Refresh rate	f _r					1.2		Mbps
Dynamic supply current per channel 14/								
Input	I _{DDI(D)}		All		0.19		mA/	
Output	I _{DDO(D)}				0.05		Mbps	

See footnote at end of table.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 5

TABLE I. Electrical performance characteristics - Continued. 1/

Test	Symbol	Test conditions 2.7 V ≤ V _{DD1} ≤ 3.6 V 2.7 V ≤ V _{DD2} ≤ 3.6 V 15/	Device type	Limits			Unit	
				Min	Typ	Max		
3 V OPERATIONS								
DC specifications								
Input supply current per channel, quiescent	I _{DD1(Q)}		All		0.26	0.35	mA	
Output supply current per channel, quiescent	I _{DD0(Q)}				0.11	0.20	mA	
Total supply current, two channels 3/ DC to 2 Mbps							mA	
V _{DD1} supply current	I _{DD1(Q)}	4/			0.6	1.0		
V _{DD2} supply current	I _{DD2(Q)}	4/			0.2	0.6		
10 Mbps								
V _{DD1} supply current	I _{DD1(Q)}	5/			2.2	3.4		
V _{DD2} supply current	I _{DD2(Q)}	5/			0.7	1.1		
25 Mbps								
V _{DD1} supply current	I _{DD1(Q)}	6/			5.2	7.7		
V _{DD2} supply current	I _{DD2(Q)}	6/			1.5	2.0		
Input currents	I _{IA} , I _{IB}				-10	+0.01	+10	μA
Logic high input threshold	V _{IH}				0.7 x 7/			V
Logic low input threshold	V _{IL}						0.3 x 7/	
Logic high output voltages	V _{OAH} , V _{OBH}	I _{OX} = -20 μA, V _{IX} = V _{IXH} I _{OX} = -20 μA, V _{IX} = V _{IXH}			7/ - 0.1	3.0		
Logic low output voltages	V _{OAL} , V _{OBL}	I _{OX} = 20 μA, V _{IX} = V _{IXL} I _{OX} = 400 μA, V _{IX} = V _{IXL} I _{OX} = 4 mA, V _{IX} = V _{IXL}			7/ - 0.5	2.8		
						0.0	0.1	
						0.04	0.1	
						0.2	0.4	
Switching specifications								
Minimum pulse width 8/	PW		All		20	40	ns	
Maximum data rate 9/					25	50	Mbps	
Propagation delay 10/	t _{PHL} , t _{PLH}				20		55	ns
Pulse width distortion, t _{PLH} - t _{PHL} 10/	PWD						3	
Propagation delay skew 11/	t _{PSK}						16	
Channel to channel matching 12/	t _{PSKCD} /t _{PSKOD}						3	
Output rise/fall time (10% to 90%)	t _R /t _F					2.5		
Common mode transient immunity								kV/μs
Logic high output 13/	CM _H	V _{IX} = V _{DD1} , V _{DD2} , V _{CM} = 1000 V, transient magnitude = 800 V			25	35		
Logic low output 13/	CM _L	V _{IX} = 0 V, V _{CM} = 1000 V, transient magnitude = 800 V			25	35		
Refresh rate	f _r					1.1		Mbps
Dynamic supply current per channel 14/								
Input	I _{DDI(D)}		All		0.10			mA/
Output	I _{DDO(D)}				0.03			Mbps

See footnote at end of table.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 6

TABLE I. Electrical performance characteristics - Continued. 1/

Test	Symbol	Test conditions 16/	Device type	Limits			Unit	
				Min	Typ	Max		
MIXED 5V/3V or 3 V/5 V OPERATION								
DC specifications								
Input supply current per channel, quiescent 5 V/3 V operation 3 V/5 V operation	I _{DD1(Q)}		All		0.50 0.26	0.6 0.35	mA	
Output supply current per channel, quiescent 5 V/3 V operation 3 V/5 V operation	I _{DD0(Q)}				0.11 0.19	0.20 0.25	mA	
Total supply current, two channels 3/ DC to 2 Mbps							mA	
V _{DD1} supply current 5 V/3 V operation 3 V/5 V operation	I _{DD1(Q)}	4/ 4/			1.1 0.6	1.4 1.0		
V _{DD2} supply current 5 V/3 V operation 3 V/5 V operation	I _{DD2(Q)}	4/ 4/			0.2 0.5	0.6 0.8		
10 Mbps								
V _{DD1} supply current 5 V/3 V operation 3 V/5 V operation	I _{DD1(Q)}	5/ 5/			4.3 2.2	5.5 3.4		
V _{DD2} supply current 5 V/3 V operation 3 V/5 V operation	I _{DD2(Q)}	5/ 5/			0.7 1.3	1.1 2.0		
25 Mbps								
V _{DD1} supply current 5 V/3 V operation 3 V/5 V operation	I _{DD1(Q)}	6/ 6/			10 5.2	13 7.7		
V _{DD2} supply current 5 V/3 V operation 3 V/5 V operation	I _{DD2(Q)}	6/ 6/			1.5 2.8	2.0 3.4		
Input currents	I _{IA} , I _{IB}				-10	+0.01	+10	μA
Logic high input threshold	V _{IH}				0.7 x 7/			V
Logic low input threshold	V _{IL}						0.3 x 7/	
Logic high output voltages	V _{OAH} , V _{OBH}	I _{OX} = -20 μA, V _{IX} = V _{IXH} I _{OX} = -20 μA, V _{IX} = V _{IXH}			7/ - 0.1 7/ - 0.5	3.0 2.8		
Logic low output voltages	V _{OAL} , V _{OBL}	I _{OX} = 20 μA, V _{IX} = V _{IXL} I _{OX} = 400 μA, V _{IX} = V _{IXL} I _{OX} = 4 mA, V _{IX} = V _{IXL}				0.0 0.04 0.2	0.1 0.1 0.4	

See footnote at end of table.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 7

TABLE I. Electrical performance characteristics - Continued. 1/

Test	Symbol	Test conditions 16/	Device type	Limits			Unit
				Min	Typ	Max	
MIXED 5V/3V or 3 V/5 V OPERATION – Continued							
Switching specifications							
Minimum pulse width 8/	PW		All		20	40	ns
Maximum data rate 9/				25	50		Mbps
Propagation delay 10/	t _{PHL} , t _{PLH}			20		50	ns
Pulse width distortion, t _{PLH} – t _{PHL} 10/	PWD					3	
Propagation delay skew 11/	t _{PSK}					15	
Channel to channel matching 12/	t _{PSKCD} /t _{PSKOD}					3	
Output rise/fall time (10% to 90%) 5 V/3 V operation 3 V/5 V operation	t _R /t _F				3.0 2.5		
Common mode transient immunity Logic high output 13/ Logic low output 13/	C _{MH}] C _{ML}]	V _{IX} = V _{DD1} , V _{DD2} , V _{CM} = 1000 V, transient magnitude = 800 V V _{IX} = 0 V, V _{CM} = 1000 V, transient magnitude = 800 V			25 25	35 35	kV/μs
Refresh rate 5 V/3 V operation 3 V/5 V operation	f _r				1.2 1.1		
Dynamic supply current per channel 14/							
Input 5 V/3 V operation 3 V/5 V operation	I _{DDI(D)}		All		0.19 0.10		mA/ Mbps
Output 5 V/3 V operation 3 V/5 V operation	I _{DDO(D)}				0.03 0.05		

See footnote at end of table.


DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 8

TABLE I. Electrical performance characteristics – Continued. 1/

- 1/ Testing and other quality control techniques are used to the extent deemed necessary to assure product performance over the specified temperature range. Product may not necessarily be tested across the full temperature range and all parameters may not necessarily be tested. In the absence of specific parametric testing, product performance is assured by characterization and/or design.
- 2/ All voltages are relative to their respective ground; all min/max specifications apply over the entire recommended operating range, unless otherwise noted; all typical specifications are at $T_A = 25^\circ\text{C}$, $V_{DD1} = V_{DD2} = 5\text{ V}$.
- 3/ The supply current values are for both channels combined when running at identical data rates. Output supply current values are specified with no output load present.
- 4/ DC to 1 MHz logic signal frequency.
- 5/ 5 MHz logic signal frequency.
- 6/ 12.5 MHz logic signal frequency.
- 7/ (V_{DD1} or V_{DD2}).
- 8/ The minimum pulse width is the shortest pulse width at which the specified pulse width distortion is guaranteed.
- 9/ The maximum data rate is the fastest data rate at which the specified pulse width distortion is guaranteed.
- 10/ t_{PHL} propagation delay is measure from 50% level of the falling edge of the V_{IX} signal to the 50% level of the falling edge of the V_{OX} signal. t_{PLH} propagation delay is measure from 50% level of the rising edge of the V_{IX} signal to the 50% level of the rising edge of the V_{OX} signal.
- 11/ t_{PSK} is the magnitude of the worst case difference in t_{PHL} and/or t_{PLH} that is measured between units at the same operating temperature, supply voltages, and output load within the recommended operating conditions.
- 12/ Codirectional channel to channel matching is the absolute value of the difference in propagation delays between any two channels with inputs on the same side of the isolation barrier. Opposing directional channel to channel matching is the absolute value on the difference in propagation delays between any two channels with inputs on opposing sides of the isolation barrier.
- 13/ CM_H is the maximum common mode voltage slew rate that can be sustained while maintaining $V_{OX} > 0.8 V_{DD2}$. CM_L is the maximum common mode voltage slew rate that can be sustained while maintaining $V_{OX} < 0.8\text{ V}$. The common mode voltage slew rates apply to both rising and falling common mode voltage edges. The transient magnitude is the range over which the common mode is slewed.
- 14/ Dynamic supply current is the incremental amount of supply current required for a 1 Mbps increase in the signal data rate.
- 15/ All voltages are relative to their respective ground; all min/max specifications apply over the entire recommended operating range, unless otherwise noted; all typical specifications are at $T_A = 25^\circ\text{C}$, $V_{DD1} = V_{DD2} = 3\text{ V}$.
- 16/ All voltages are relative to their respective ground; 5 V/3 V operation: $4.5\text{ V} \leq V_{DD1} \leq 5.5\text{ V}$, $2.7\text{ V} \leq V_{DD2} \leq 3.6\text{ V}$. 3 V/5 V operation: $2.7\text{ V} \leq V_{DD1} \leq 3.6\text{ V}$, $4.5\text{ V} \leq V_{DD2} \leq 5.5\text{ V}$; all min/max specifications apply over the entire recommended operating range, unless otherwise noted; all typical specifications are at $T_A = 25^\circ\text{C}$, $V_{DD1} = 3.0\text{ V}$, $V_{DD2} = 5.0\text{ V}$; or $V_{DD1} = 5.0\text{ V}$, $V_{DD2} = 3.0\text{ V}$.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 9

Case X



Dimensions									
Symbol	Millimeters		Inches		Symbol	Millimeters		Inches	
	Min	Max	Min	Max		Min	Max	Min	Max
A	1.35	1.75	.053	.068	E	3.80	4.00	.149	.157
A1	0.10	0.25	.004	.009	E1	5.80	6.20	.228	.244
b	0.31	0.51	.012	.020	e	1.27 BSC		.050 BSC	
c	0.17	0.25	.006	.009	L	0.40	1.27	.015	.050
D	4.80	5.00	.189	.196					

NOTES:

- Controlling dimensions are in millimeters; inch dimensions (in parentheses) are rounded-off millimeter equivalents for reference only and are not appropriate for use in design.
- Falls within JEDEC MS-012-AA.

FIGURE 1. Case outline.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 10

Case outline X			
Terminal number	Terminal symbol	Terminal number	Terminal symbol
1	V _{DD1}	5	GND ₂
2	V _{IA}	6	V _{OB}
3	V _{IB}	7	V _{OA}
4	GND ₁	8	V _{DD2}

FIGURE 2. Terminal connections.

Case outline X		
Terminal		Description
Number	Mnemonic	
1	V _{DD1}	Supply voltage for isolation side 1
2	V _{IA}	Logic input A.
3	V _{IB}	Logic input B.
4	GND ₁	Ground 1. Ground reference for isolation side 1.
5	GND ₂	Ground 2. Ground reference for isolation side 2.
6	V _{OB}	Logic output B.
7	V _{OA}	Logic output A.
8	V _{DD2}	Supply voltage for isolation side 2

FIGURE 3. Terminal function.

V _{IA} Input	V _{IB} Input	V _{DD1} State	V _{DD2} State	V _{OA} output	V _{OB} output	Notes
H	H	Powered	Powered	H	H	
L	L	Powered	Powered	L	L	
H	L	Powered	Powered	H	L	
L	H	Powered	Powered	L	H	
X	X	Unpowered	Powered	H	H	<u>1/</u>
X	X	Powered	Unpowered	Indeterminate	Indeterminate	<u>2/</u>

1/ Outputs return to the input state within 1 μs of VDD1 power restoration.

2/ Outputs return to the input state within 1 μs of VDD0 power restoration.

3/ H = High, L = Low, X = Undetermined/not relevant.

FIGURE 4. Truth table.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 11




FIGURE 5. Functional block diagram.




FIGURE 6. Thermal derating curve.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 12

4. VERIFICATION

4.1 Product assurance requirements. The manufacturer is responsible for performing all inspection and test requirements as indicated in their internal documentation. Such procedures should include proper handling of electrostatic sensitive devices, classification, packaging, and labeling of moisture sensitive devices, as applicable.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Preservation, packaging, labeling, and marking shall be in accordance with the manufacturer's standard commercial practices for electrostatic discharge sensitive devices.

6. NOTES

6.1 ESDS. Devices are electrostatic discharge sensitive and are classified as ESDS class 1 minimum.

6.2 Configuration control. The data contained herein is based on the salient characteristics of the device manufacturer's data book. The device manufacturer reserves the right to make changes without notice. This drawing will be modified as changes are provided.

6.3 Suggested source(s) of supply. Identification of the suggested source(s) of supply herein is not to be construed as a guarantee of present or continued availability as a source of supply for the item. DLA Land and Maritime maintains an online database of all current sources of supply at <https://landandmaritimeapps.dla.mil/programs/smcr/>.

Vendor item drawing administrative control number <u>1/</u>	Device manufacturer CAGE code	Vendor part number
V62/12630-01XB	24355	ADuM1200UR-EP-RL7

1/ The vendor item drawing establishes an administrative control number for identifying the item on the engineering documentation.

CAGE code

24355

Source of supply

Analog Devices
 1 Technology Way
 P.O. Box 9106
 Norwood, MA 02062-9106

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/12630
		REV B	PAGE 13