

REVISIONS

LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Add footnote <u>4</u> / to DC crosstalk, Output voltage noise density, Output current load capability, and Line regulation tests as specified in Table I. Under Table I, Daisy chain section, delete 1.8 V and replace with 1.62 V on the top of the Limits column. Under Table I, footnote <u>17</u> /, delete 1.8 V and replace with 1.62 V. Delete the numerical limits from Figure 1 case outline and replace with assigned letter symbols. Add dimensions table under figure 1. Update document documents to current requirements. - ro	22-04-06	J. Eschmeyer



Prepared in accordance with ASME Y14.24

Vendor Item Drawing

Revision Status of Sheets																			
REV																			
SHEET																			
REV	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
SHEET	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19

PMIC N/A Original date of drawing YY-MM-DD 17-01-09	PREPARED BY Phu H. Nguyen				DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990 https://www.dla.mil/landandmaritime									
	CHECKED BY Phu H. Nguyen				TITLE MICROCIRCUIT, LINEAR, DUAL, 16-BIT NANODAC+ WITH 4 ppm/°C REFERENCE, SPI INTERFACE, MONOLITHIC SILICON									
	APPROVED BY Thomas M. Hess				DWG NO. V62/14634									
	SIZE A		CAGE CODE 16236		PAGE 1 OF 19									
	REV				A									

1. SCOPE

1.1 Scope. This drawing documents the general requirements of a high performance, Dual, 16-Bit nano DAC+ with 4 ppm/°C Reference, Serial Peripheral Interface (SPI) interface microcircuit, with an operating temperature range of -55°C to +125°C.

1.2 Vendor Item Drawing Administrative Control Number. The manufacturer's PIN is the idem of identification. The vendor item drawing establishes an administrative control number for identifying the item on the engineering documentation:

<u>V62/14634</u> Drawing number	-	<u>01</u> Device type (See 1.2.1)	<u>X</u> Case outline (See 1.2.2)	<u>E</u> Lead finish (See 1.2.3)
---------------------------------------	---	---	---	--

1.2.1 Device type(s).

<u>Device type</u>	<u>Generic</u>	<u>Circuit function</u>
01	AD5689R –EP	Dual, 16-Bit nano DAC+ with 4 ppm/°C Reference, SPI interface

1.2.2 Case outline(s). The case outline(s) are as specified herein.

<u>Outline letter</u>	<u>Number of pins</u>	<u>JEDEC PUB 95</u>	<u>Package style</u>
X	16	JEDEC MO-220-WEED-6	Lead frame chip scale package

1.2.3 Lead finishes. The lead finishes are as specified below or other lead finishes as provided by the device manufacturer:

<u>Finish designator</u>	<u>Material</u>
A	Hot solder dip
B	Tin-lead plate
C	Gold plate
D	Palladium
E	Gold flash palladium
F	Tin-lead alloy (BGA/CGA)
Z	Other

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 2

1.3 Absolute maximum ratings. 1/

VDD to GND	-0.3 V to +7 V
VLOGIC to GND	-0.3 V to +7 V
VOUT to GND	-0.3 V to VDD + 0.3 V
VREF to GND	-0.3 V to VDD + 0.3 V
Digital Input Voltage to GND	-0.3 V to VLOGIC + 0.3 V
Operating temperature range:	-55°C to +125°C
Storage temperature range	-65°C to 150°C
Junction temperature	135°C
Case outline X, θ_{JA} Thermal Impedance, 0 Airflow (4-Layer Board)	70°C/W
Reflow soldering peak temperature, lead (Pb) free (J-STD-020)	260°C
Electrostatic discharge sensitivity (ESD):	
Human body model (HBM)	4 kV
Field induced charged device model (FICDM)	1.25 kV

2. APPLICABLE DOCUMENTS

JEDEC Solid State Technology Association

- JEDEC J STD-020 – Moisture/Reflow Sensitivity Classification for Non-Hermetic Solid State Surface Mount Devices
- JESD22-C101 – Field-Induced Charged-Device Model Test Method for Electrostatic-Discharge-Withstand Thresholds of Microelectronics Components
- JEDEC PUB 95 – Registered and Standard Outlines for Semiconductor Devices

(Copies of these documents are available online at <https://www.jedec.org>.)

1/ Stresses beyond those listed under “absolute maximum rating” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 3

3. REQUIREMENTS

3.1 Marking. Parts shall be permanently and legibly marked with the manufacturer's part number as shown in 6.3 herein and as follows:

- A. Manufacturer's name, CAGE code, or logo
- B. Pin 1 identifier
- C. ESDS identification (optional)

3.2 Unit container. The unit container shall be marked with the manufacturer's part number and with items A and C (if applicable) above.

3.3 Electrical characteristics. The maximum and recommended operating conditions and electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.4 Design, construction, and physical dimension. The design, construction, and physical dimensions are as specified herein.

3.5 Diagrams.

3.5.1 Case outline. The case outline shall be as shown in 1.2.2 and figure 1.

3.5.2 Terminal connections. The terminal connections shall be as shown in figure 2.

3.5.3 Terminal function. The terminal function shall be as shown in figure 3.

3.5.4 Functional block diagram. The functional block diagram shall be as shown in figure 4.

3.5.5 Serial write operation. The serial write operation shall be as shown in figure 5.

3.5.6 Load circuit for Digital Output (SDO) timing specification. The load circuit for Digital Output (SDO) timing specification shall be as shown in figure 6.

3.5.7 Daisy Chain timing tiagram. The Daisy Chain timing diagram shall be as shown in figure 7.

3.5.8 Readback timing diagram. The Readback timing diagram shall be as shown in figure 8.

3.5.9 Headroom/Footroom versus load current. The Headroom/Footroom versus load current shall be as shown in figure 9.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 4

TABLE I. Electrical performance characteristics. 1/

Test	Test conditions 2/	Limits			Unit
		Min	Typ	Max	
Static performance 3/					
Resolution		16			Bits
Relative accuracy	Gain = 2		±1	±4	LSB
	Gain = 1		±1	±5	LSB
Differential nonlinearity (DNL)	Guaranteed monotonic by design			±1	LSB
Zero-code error	All zeros loaded to DAC register		0.4	1.5	mV
Offset error			±0.1	±0.5	mV
Full-scale error	All ones loaded to DAC register		+0.01	+0.1	% of FSR
Gain error	Gain = 2		±0.02	±0.1	% of FSR
	Gain = 1		±0.02	±0.15	% of FSR
Total unadjusted error	External reference; gain = 2		±0.01	±0.1	% of FSR
	Internal reference; gain = 1			±0.2	% of FSR
Offset error drift 4/			±1		μV/°C
Gain temperature coefficient (TC) 4/	Of FSR/°C		±1		ppm
DC power supply rejection Ratio 4/	DAC code = midscale, VDD = 5 V ± 10%		0.15		mV/V
DC crosstalk 4/	Due to single channel, full-scale output change		±2		μV
	Due to load current change		±3		μV/mA
	Due to powering down (per channel)		±2		μV
Output characteristics 4/					
Output voltage range	Gain = 1	0		VREF	V
	Gain = 2, see Figure 9	0		2 × VREF	V
Capacitive load stability	R _L = ∞		2		nF
	R _L = 1 kΩ		10		nF
Resistive load 5/		1			kΩ
Load regulation	5 V ± 10%, DAC code = midscale, -30 mA ≤ I _{OUT} ≤ 30 mA		80		μV/mA
	3 V ± 10%, DAC code = midscale, -20 mA ≤ I _{OUT} ≤ 20 mA		80		μV/mA
Short-circuit current 6/			40		mA
Load impedance at rails 7/	See Figure 9		25		Ω
Power-up time	Coming out of power-down mode; VDD = 5 V		2.5		μs

See footnote at end of table.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 5

TABLE I. Electrical performance characteristics - Continued. 1/

Test	Test conditions 2/	Limits			Unit
		Min	Typ	Max	
Reference output					
Output voltage 8/	At ambient	2.4975		2.5025	V
Reference TC 9/ 10/			4	13	ppm/°C
Output impedance 4/			0.04		Ω
Output voltage noise 4/	0.1 Hz to 10 Hz		12		μV p-p
Output voltage noise density 4/	At ambient; f = 10 kHz, C _L = 10 nF		240		nV/√Hz
Load regulation sourcing 4/	At ambient		20		μV/mA
Load regulation sinking 4/	At ambient		40		μV/mA
Output current load capability 4/	V _{DD} ≥ 3 V		±5		mA
Line regulation 4/	At ambient		100		μV/V
Thermal hysteresis 4/	First cycle		125		ppm
	Additional cycles		25		ppm
Logic inputs 4/					
Input current	Per pin			±2	μA
Input voltage, low (VINL)				0.3 × V _{LOGIC}	V
Input voltage, high (VINH)		0.7 × V _{LOGIC}			V
Pin capacitance			2		pF
Logic outputs (SDO) 4/					
Output voltage, low (VOL)	ISINK = 200 μA			0.4	V
Output voltage, high (VOH)	ISOURCE = 200 μA	V _{LOGIC} - 0.4			V
Floating state output capacitance			4		pF
Power requirements					
V _{LOGIC}		1.62		5.5	V
I _{LOGIC}				3	μA
V _{DD}	Gain = 1	2.7		5.5	V
V _{DD}	Gain = 2	V _{REF} + 1.5		5.5	V
I _{DD}	V _{IH} = V _{DD} , V _{IL} = GND, V _{DD} = 2.7 V to 5.5 V				
Normal mode 11/	Internal reference off		0.59	0.7	mA
	Internal reference on at full scale		1.1	1.3	mA
All power-down modes 12/	-40°C to +85°C		1	4	μA
	-55°C to +125°C			6	μA

See footnote at end of table.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 6

TABLE I. Electrical performance characteristics - Continued. 1/

Test	Test conditions	Limits			Unit
		Min	Typ	Max	
AC characteristics <u>13/ 14/ 15/</u>					
Output voltage settling time	1/4 to 3/4 scale settling to ± 2 LSB		5	8	μ s
Slew rate			0.8		V/ μ s
Digital-to-analog glitch impulse	1 LSB change around major carry		0.5		nV-sec
Digital feedthrough			0.13		nV-sec
Digital crosstalk			0.1		nV-sec
Analog crosstalk			0.2		nV-sec
DAC-to-DAC crosstalk			0.3		nV-sec
Total harmonic distortion (THD) <u>16/</u>	At ambient, BW = 20 kHz, VDD = 5 V, fOUT = 1 kHz		-80		dB
Output noise spectral density (NSD)	DAC code = midscale, 10 kHz; gain = 2		300		nV/ $\sqrt{\text{Hz}}$
Output noise	0.1 Hz to 10 Hz		6		μ V p-p
Signal-to-noise ratio (SNR)	At ambient, BW = 20 kHz, VDD = 5 V, fOUT = 1 kHz		90		dB
Spurious free dynamic range (SFDR)	At ambient, BW = 20 kHz, VDD = 5 V, fOUT = 1 kHz		83		dB
Signal-to-noise-and-distortion ratio (SINAD)	At ambient, BW = 20 kHz, VDD = 5 V, fOUT = 1 kHz		80		dB

See footnote at end of table.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 7

TABLE I. Electrical performance characteristics - Continued. 1/

Test	Symbol	Test conditions	Limits				Unit
			1.62 V ≤ V _{LOGIC} ≤ 2.7 V		2.7 V ≤ V _{LOGIC} ≤ 5.5 V		
			Min	Max	Min	Max	
Timing characteristics 17/ 18/		(See Figure 5)					
SCLK cycle time	t ₁		20		20		ns
SCLK high time	t ₂		10		10		ns
SCLK low time	t ₃		10		10		ns
$\overline{\text{SYNC}}$ to SCLK falling edge setup time	t ₄		15		10		ns
Data setup time	t ₅		5		5		ns
Data hold time	t ₆		5		5		ns
SCLK falling edge to $\overline{\text{SYNC}}$ rising edge	t ₇		10		10		ns
Minimum $\overline{\text{SYNC}}$ high time	t ₈		20		20		ns
$\overline{\text{SYNC}}$ rising edge to $\overline{\text{SYNC}}$ rising edge (DAC register update/s)	t ₉		870		830		ns
$\overline{\text{SYNC}}$ falling edge to SCLK fall ignore	t ₁₀		16		10		ns
$\overline{\text{LDAC}}$ pulse width low	t ₁₁		15		15		ns
$\overline{\text{SYNC}}$ rising edge to $\overline{\text{LDAC}}$ rising edge	t ₁₂		20		20		ns
$\overline{\text{SYNC}}$ rising edge to $\overline{\text{LDAC}}$ falling edge	t ₁₃		30		30		ns
$\overline{\text{LDAC}}$ falling edge to $\overline{\text{SYNC}}$ rising edge	t ₁₄		840		800		ns
Minimum pulse width low	t ₁₅		30		30		ns
Pulse activation time	t ₁₆		30		30		ns
Power-up time 19/			4.5		4.5		μs

See footnote at end of table.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 8

TABLE I. Electrical performance characteristics - Continued. 1/

Test	Symbol	Test conditions 20/	Limits				Unit
			1.62 V ≤ V _{LOGIC} ≤ 2.7 V		2.7 V ≤ V _{LOGIC} ≤ 5.5 V		
			Min	Max	Min	Max	
Daisy-chain and readback timing characteristics 21/ (See Figures 6, 7, 8)							
SCLK cycle time	t ₁		66		40		ns
SCLK high time	t ₂		33		20		ns
SCLK low time	t ₃		33		20		ns
$\overline{\text{SYNC}}$ to SCLK falling edge	t ₄		33		20		ns
Data setup time	t ₅		5		5		ns
Data hold time	t ₆		5		5		ns
SCLK falling edge to $\overline{\text{SYNC}}$ rising edge	t ₇		15		10		ns
Minimum $\overline{\text{SYNC}}$ high time	t ₈		60		30		ns
SDO data valid from SCLK rising edge	t ₉			40		30	ns
$\overline{\text{SYNC}}$ rising edge to SCLK rising edge	t ₁₀		15		10		ns
$\overline{\text{SYNC}}$ rising edge to SDO disable	t ₁₁		60		60		ns

See footnote at end of table.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 9

TABLE I. Electrical performance characteristics - Continued. 1/

- 1/ Testing and other quality control techniques are used to the extent deemed necessary to assure product performance over the specified temperature range. Product may not necessarily be tested across the full temperature range and all parameters may not necessarily be tested. In the absence of specific parametric testing, product performance is assured by characterization and/or design.
- 2/ VDD = 2.7 V to 5.5 V; 1.62 V ≤ VLOGIC ≤ 5.5 V; all specifications TMIN to TMAX, unless otherwise noted. RL = 2 kΩ; CL = 200 pF.
- 3/ DC specifications tested with the outputs unloaded, unless otherwise noted. Upper dead band = 10 mV and exists only when VREF = VDD with gain = 1 or when VREF/2 = VDD with gain = 2. Linearity is calculated using a reduced code range of 256 to 65,280.
- 4/ Guaranteed by design, not subject to production test.
- 5/ Channel A can have an output current of up to 15 mA. Similarly, Channel B can have an output current of up to 15 mA, up to a junction temperature of 135°C.
- 6/ VDD = 5 V. The device includes current limiting that is intended to protect the device during temporary overload conditions. Junction temperature may be exceeded during current limit, but operation above the specified maximum operation junction temperature can impair device reliability.
- 7/ When drawing a load current at either rail, the output voltage headroom, with respect to that rail, is limited by the 25 Ω typical channel resistance of the output device. For example, when sinking 1 mA, the minimum output voltage = 25 Ω × 1 mA = 25 mV (see Figure 9).
- 8/ Initial accuracy presolder reflow is ±750 μV; output voltage includes the effects of preconditioning drift. See manufacturer data sheet for more information.
- 9/ Reference is trimmed and tested at two temperatures and is characterized from -55°C to +125°C.
- 10/ Reference temperature coefficient is calculated as per the box method. See manufacturer data sheet for more information.
- 11/ Interface inactive. Both DACs active. DAC outputs unloaded.
- 12/ Both DACs powered down.
- 13/ VDD = 2.7 V to 5.5 V; RL = 2 kΩ to GND; CL = 200 pF to GND; 1.62 V ≤ VLOGIC ≤ 5.5 V; all specifications TMIN to TMAX, unless otherwise noted. Guaranteed by design and characterization; not production tested.
- 14/ Temperature range is -55°C to +125°C, typical at 25°C.
- 15/ See manufacturer data sheet.
- 16/ Digitally generated sine wave at 1 kHz.
- 17/ All input signals are specified with tR = tF = 1 ns/V (10% to 90% of VDD) and timed from a voltage level of (VIL + VIH)/2. See Figure 5. VDD = 2.7 V to 5.5 V, 1.62 V ≤ VLOGIC ≤ 5.5 V; VREF = 2.5 V. All specifications TMIN to TMAX, unless otherwise noted.
- 18/ Maximum SCLK frequency is 50 MHz at VDD = 2.7 V to 5.5 V, 1.62 V ≤ VLOGIC ≤ VDD. Guaranteed by design and characterization; not production tested.
- 19/ Time to exit power-down to normal mode of device operation, 32nd clock edge to 90% of DAC midscale value, with output unloaded.
- 20/ All input signals are specified with tR = tF = 1 ns/V (10% to 90% of VDD) and timed from a voltage level of (VIL + VIH)/2. See Figure 7 and Figure 8. VDD = 2.7 V to 5.5 V, 1.62 V ≤ VLOGIC ≤ 5.5 V; VREF = 2.5 V. All specifications TMIN to TMAX, unless otherwise noted. VDD = 2.7 V to 5.5 V.
- 21/ Guaranteed by design and characterization; not production tested.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 10

Case X




FIGURE 1. Case outline.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 11

Case X - continued

Symbol	Dimensions					
	Inches			Millimeters		
	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum
A	.027	.029	.031	0.70	0.75	0.80
A1	---	.001	.002	---	0.02	0.05
A2	.008 REF			0.20 REF		
b	.007	.009	.012	0.18	0.23	0.30
D/E	.114	.118	.122	2.90	3.00	3.10
E1	.057	.063	.069	1.45	1.60	1.75
E2	.008	---	---	0.20	---	---
e	.020 BSC			0.50 BSC		
s	.012	.016	.020	0.30	0.40	0.50

NOTES:

1. Controlling dimensions are millimeter, inch dimensions are given for reference only.
2. For proper connection of the exposed pad, refer to the pin configuration and function descriptions section of the manufacturer's datasheet.
3. Falls within reference to JEDEC MO-220-WEED-6.

FIGURE 1. Case outline - Continued.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 12

Device type	01
Case outline	X
Terminal number	Terminal symbol
1	VOUTA
2	GND
3	VDD
4	NC
5	VOUTB
6	SDO
7	$\overline{\text{LDAC}}$
8	GAIN
9	VLOGIC
10	SCLK
11	$\overline{\text{SYNC}}$
12	SDIN
13	$\overline{\text{RESET}}$
14	RSTSEL
15	VREF
16	NC

NOTES

1. The exposed PAD must be tied to GND.
2. NC = No Connect. Do not Connect to this PIN.

FIGURE 2. Terminal connections.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 13

Terminal Number	Terminal Symbol	Description
1	VOUTA	Analog output voltage from DAC A. The output amplifier has rail-to-rail operation.
2	GND	Ground reference point for all circuitry on the device.
3	VDD	Power supply input. The device can be operated from 2.7 V to 5.5 V. Decouple the supply with a 10 μ F capacitor in parallel with a 0.1 μ F capacitor to GND.
4	NC	No connect. Do not connect to this pin.
5	VOUTB	Analog output voltage from DAC B. The output amplifier has rail-to-rail operation.
6	SDO	Serial data output. SDO can be used to daisy-chain a number of devices together, or it can be used for readback. The serial data is transferred on the rising edge of SCLK and is valid on the falling edge of the clock.
7	$\overline{\text{LDAC}}$	$\overline{\text{LDAC}}$ can be operated in two modes: asynchronously and synchronously. Pulsing this pin low allows either or both DAC registers to be updated if the input registers have new data; both DAC outputs can be updated simultaneously. This pin can also be tied permanently low.
8	GAIN	Gain select. When this pin is tied to GND, both DACs output a span from 0 V to VREF. If this pin is tied to VLOGIC, both DACs output a span of 0 V to 2 \times VREF.
9	VLOGIC	Digital power supply. Voltage ranges from 1.8 V to 5.5 V.
10	SCLK	Serial clock input. Data is clocked into the input shift register on the falling edge of the serial clock input. Data can be transferred at rates of up to 50 MHz.
11	$\overline{\text{SYNC}}$	Active low control input. This is the frame synchronization signal for the input data. When $\overline{\text{SYNC}}$ goes low, data is transferred in on the falling edges of the next 24 clocks.
12	SDIN	Serial data input. This device has a 24-bit input shift register. Data is clocked into the register on the falling edge of the serial clock input.
13	$\overline{\text{RESET}}$	Asynchronous Reset Input. The $\overline{\text{RESET}}$ input is falling edge sensitive. When $\overline{\text{RESET}}$ is low, all $\overline{\text{LDAC}}$ pulses are ignored. When $\overline{\text{RESET}}$ activated, the input register and the DAC register are updated with zero scale or midscale, depending on the state of the RSTSEL pin.
14	RSTSEL	Power-on reset select. Tying this pin to GND powers up both DACs to zero scale. Tying this pin to VLOGIC powers up both DACs to midscale.
15	VREF	Reference voltage. The device has a common reference pin. When using the internal reference, this is the reference output pin. When using an external reference, this is the reference input pin. The default for this pin is as a reference output.
16	NC	No connect. Do not connect to this pin.
17	EPAD	Exposed pad. The exposed pad must be tied to GND.

FIGURE 3. Terminal function.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 14




FIGURE 4. Functional block diagram.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 15




FIGURE 5. Serial Write Operation.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 16




FIGURE 6. Load Circuit for Digital Output (SDO) Timing Specifications.




FIGURE 7. Daisy-Chain Timing Diagram.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 17




FIGURE 8. Readback Timing Diagram.




FIGURE 9. Headroom/Footroom versus Load Current.

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 18

4. VERIFICATION

4.1 Product assurance requirements. The manufacturer is responsible for performing all inspection and test requirements as indicated in their internal documentation. Such procedures should include proper handling of electrostatic sensitive devices, classification, packaging, and labeling of moisture sensitive devices, as applicable.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Preservation, packaging, labeling, and marking shall be in accordance with the manufacturer's standard commercial practices for electrostatic discharge sensitive devices.

6. NOTES

6.1 ESDS. Devices are electrostatic discharge sensitive and are classified as ESDS class 1 minimum.

6.2 Configuration control. The data contained herein is based on the salient characteristics of the device manufacturer's data book. The device manufacturer reserves the right to make changes without notice. This drawing will be modified as changes are provided.

6.3 Suggested source(s) of supply. Identification of the suggested source(s) of supply herein is not to be construed as a guarantee of present or continued availability as a source of supply for the item. DLA Land and Maritime maintains an online database of all current sources of supply at <https://landandmaritimeapps.dla.mil/programs/smcr/>.

Vendor item drawing administrative control number <u>1/</u>	Device manufacturer CAGE code	Mode of transportation and quantity	Vendor part number
V62/14634-01XE	24355	Reel, 1500 units	AD5689RTCPZ-EP-RL7

1/ The vendor item drawing establishes an administrative control number for identifying the item on the engineering documentation.

CAGE code

24355

Source of supply

Analog Devices
 Route 1 Industrial Park
 P.O. Box 9106
 Norwood, MA 02062
 Point of contact: 20 Alpha Road
 Chelmsford, MA 01824-4123

DLA LAND AND MARITIME COLUMBUS, OHIO	SIZE A	CAGE CODE 16236	DWG NO. V62/14634
		REV A	PAGE 19