

**DLA Land and Maritime - VQ  
Supplemental Information Sheet for Electronic QPL-19**

Date: 1/25/2021

**Specification Details:**

Specification: MIL-PRF-19  
 Title: Resistor, Variable, Wire Wound (Low Operating Temperature)  
 Federal Supply Class (FSC): 5905  
 Conventional: Yes  
 Specification contains quality assurance program: No  
 MIL-STD-790 Established Reliability & High Reliability: No  
 MIL-STD-690 Failure Rate Sampling Plans & Procedures: No  
 Weibull Graded: No  
 Specification contains space level reliability requirements: No  
 Specification allows test optimization: No

**Contact Information:**

Office of Primary Involvement: Passive Devices Branch, DLA Land and Maritime - VQP  
 Primary Qualifying Activity Contact: 614-692-3757, e-mail: vqp.dl@dla.mil  
 Secondary Qualifying Activity Contact: 614-692-0609, e-mail: vqp.do@dla.mil

**Notes:**

N/A

**Part Configuration:**

RA30NASK103A

| Style | Bushing | Switch | Operating shaft and length | Resistance | Resistance Characteristic |
|-------|---------|--------|----------------------------|------------|---------------------------|
| RA30  | N       | A      | SK                         | 103        | A                         |

**PART LISTINGS**

| GOVERNMENT DESIGNATION | MANUFACTURER'S DESIGNATION OR TYPE NUMBER | TEST OR QUALIFICATION REFERENCE | SPECIFICATION SHEET | SUPPLIER'S NAME (ADDRESS ON LAST PAGE) |
|------------------------|---|---------------------------------|---------------------|--|
|------------------------|---|---------------------------------|---------------------|--|

|   |           |                      |    |              |
|---|-----------|----------------------|----|--------------|
| <b>RA20</b><br>Bushings L, N, S, T; with and without a switch; operating shafts SA, SB, SD, SG, SK; res. values 3 ohms thru 15 kilohms; res. chars. A, C, E | 43M, 43MS | 19-488-74; 19-489-74 | /2 | Strube, Inc. |
| <b>RA30</b><br>Bushings L, N, S, T; with and without a switch; operating shafts SA, SB, SD, SG, SK; res. values 3 ohms thru 25 kilohms; res. chars. A, C, E | 58M       | 19-3-59              | /3 | Strube, Inc. |

---

**Manufacturer and Supplier Location Information**

---

**Manufacturer: Strube, Inc. (CAGE Code: 54034)**

Location: 629 W. Market Street, Marietta, PA 17547-9998, US

Plants:

1. P.O. Box 247, 307 Front Street, Richmond, ME 04357-1374,