



QUALIFICATIONS VALIDATED
EVERY TWO YEARS

QPL-93-109
09-Nov-04
SUPERSEDING
QPL-93-108
29-Nov-02

QUALIFIED PRODUCTS LIST
OF
PRODUCTS QUALIFIED UNDER MILITARY SPECIFICATION
MIL-R-93
RESISTORS, FIXED, WIRE-WOUND (ACCURATE),
GENERAL SPECIFICATION FOR

Effective 22 November 1968, MIL-R-93 has been declared "Inactive for New Design" with no superseding specification. This is applicable on all acquisitions to which MIL-R-93 is applied.

This list has been prepared for use by or for the Government in the acquisition of products covered by Specification MIL-R-93. Listing of a product is not intended to and does not connote endorsement of the product by the Department of Defense. All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. This list is subject to change without notice; revision or amendment of this list will be issued as necessary. The listing of a product does not release the supplier from compliance with the specification requirements.

THE ACTIVITY RESPONSIBLE FOR THIS QPL IS THE DEFENSE SUPPLY CENTER COLUMBUS (DSCC-VQ), COLUMBUS, OH 43218-3990.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFICATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RB52				
Char. C; res. values 0.1 ohms thru 1 megohms; tols. D, F	VA36, VAS3	93-443-66	/10	IRC Shallcross, Inc.
Char. C; res. values 10 ohms thru 1 megohms; tols. B	VA36, VAS3	93-443-66	/10	IRC Shallcross, Inc.
Char. C; res. values 100 ohms thru 1 megohms; tols. A	VA36, VAS3	93-443-66	/10	IRC Shallcross, Inc.
RB53				
Char. C; res. values 0.1 ohms thru 604 kilohms; tols. D, F	VA34	93-443-66	/11	IRC Shallcross, Inc.
Char. C; res. values 10 ohms thru 604 kilohms; tols. B	VA34	93-443-66	/11	IRC Shallcross, Inc.
Char. C; res. values 100 ohms thru 604 kilohms; tols. A	VA34	93-443-66	/11	IRC Shallcross, Inc.
RB54				
Char. C; res. values 0.1 ohms thru 226 kilohms; tols. D, F	VA14, VAS1	93-443-66	/12	IRC Shallcross, Inc.
Char. C; res. values 10 ohms thru 226 kilohms; tols. B	VA14, VAS1	93-443-66	/12	IRC Shallcross, Inc.
Char. C; res. values 100 ohms thru 221 kilohms; tols. A	VA14, VAS1	93-443-66	/12	IRC Shallcross, Inc.
RB55				
Char. C; res. values 0.1 ohms thru 176 kilohms; tols. D, F	VA12, VAS1	93-443-66	/13	IRC Shallcross, Inc.
Char. C; res. values 10 ohms thru 176 kilohms; tols. B	VA12, VAS1	93-443-66	/13	IRC Shallcross, Inc.
Char. C; res. values 100 ohms thru 176 kilohms; tols. A	VA12, VAS1	93-443-66	/13	IRC Shallcross, Inc.
RB56				
Char. C; res. values 0.1 ohms thru 127 kilohms; tols. D, F	VA10, VAS1	93-443-66	/14	IRC Shallcross, Inc.
Char. C; res. values 10 ohms thru 127 kilohms; tols. B	VA10, VAS1	93-443-66	/14	IRC Shallcross, Inc.
Char. C; res. values 100 ohms thru 127 kilohms; tols. A	VA10, VAS1	93-443-66	/14	IRC Shallcross, Inc.
RB70				
Char. C; res. values 10 ohms thru 301 kilohms; tols. B, D, F	4065	93-56-90	/19	IRC Shallcross, Inc.
Char. C; res. values 100 ohms thru 301 kilohms; tols. A	4065	93-56-90	/19	IRC Shallcross, Inc.
RB71				
Char. C, W; res. values 0.1 ohms thru 100 kilohms; tols. D, F	PC8	93-873-69	/20	IRC Shallcross, Inc.
Char. C, W; res. values 10 ohms thru 100 kilohms; tols. B	PC8	93-873-69	/20	IRC Shallcross, Inc.
Char. C, W; res. values 100 ohms thru 100 kilohms; tols. A	PC8	93-873-69	/20	IRC Shallcross, Inc.

Manufacturer and Supplier Location Information

Manufacturer: IRC Shallcross, Inc. (CAGE Code: 54294)

Location: P.O. Box 2240, U.S. 70 East, Smithfield, NC 27577, US

Plant Location: Same Address as Manufacturer