

**Specification Details:**

Specification: MIL-PRF-31032  
 Title: Printed Circuit Board/Printed Wiring Board  
 Federal Supply Class (FSC): 5998  
 Conventional: No  
 Specification contains quality assurance program: Yes  
 MIL-STD-790 Established Reliability & High Reliability: No  
 MIL-STD-690 Failure Rate Sampling Plans & Procedures: No  
 Weibull Graded: No  
 Specification contains space level reliability requirements: No  
 Specification allows test optimization: Yes

**Contact Information:**

DSCC Office of Primary Involvement: Electronic Devices Team, DSCC-VQE  
 Primary DSCC-VQ Contact: 614-692-0627, e-mail: vqe.ls@dla.mil  
 Secondary DSCC-VQ Contact: 614-692-0631, e-mail: vqe.bw@dla.mil

**Notes:**

If a manufacturer desires to have test data considered for qualification, it must be certified and meet all qualification test requirements of MIL-PRF-31032 and the applicable associated specification.

The listing of printed board manufacturing lines in the QML applies only to printed boards produced in the plant(s) specified herein. Therefore, only those printed boards that have been manufactured and tested on the certified/qualified lines listed herein can be supplied as QML printed boards.

DSCC contacts for QML companies can be located in the file ¿31032 main points-of-contact¿ at website:  
[http://www.dsccl.dla.mil/offices/sourcing and qualification/offices.asp?section=VQE](http://www.dsccl.dla.mil/offices/sourcing%20and%20qualification/offices.asp?section=VQE)

QML is a definition of a manufacturer's verified capabilities. Manufacturers may use the add-on qualification process to qualify capabilities that are not currently listed on the QML. The user is encouraged to contact the manufacturer or DSCC to make arrangements for QML availability.

The following abbreviations are used in this listing:

Ag: Silver  
 Au: Gold  
 CAGE: Commercial and Government Entity (Code)  
 Cu: Copper  
 ENIG: Electroless Nickel Immersion Gold  
 HASL: Hot Air Solder Level  
 ImmAg: Immersion Silver  
 IR: Infrared  
 LPI: Liquid Photoimageable  
 MIX: Mix of SMT and THM  
 Ni: Nickel  
 OSP: Organic Surface Protection  
 Pb: Lead  
 Pd: Palladium  
 PTH: Plated Thru Hole  
 SMOBC: Solder Mask Over Bare Copper  
 SMT: Surface-Mount Technology  
 Sn: Tin  
 THM: Through-Hole Mounting

**SECTION I  
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION: <b>Accurate Circuit Engineering</b> 3019 S. Kilson Drive Santa Ana, CA 92707, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 0MNN9  Contact: James Hofer Phone: 714-546-162 Fax: 714-433-7418 EMail: James@ace-pcb.com</p>
---	---	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-07-12577
Panel Size:	20" X 26"	VQE-06-12150
Max./Min. Board Thickness:	0.22"/Not Specified	
Max./Min. Base CU Thickness:	0.006"/Not Specified	
Max./Min. Through Hole Size:	0.025"/0.008" ((after plating))	
Aspect Ratio:	11:1 (Through Hole)	
Max. Number of Layers:	24	
Min. Conductor Width:	0.003"	
Min. Conductor Space:	0.003" (+/-10%)	
Part Mounting:	SMT, THM, MIX	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant	
Flex Base Material:	N/A	
Finish System:	ENIG	
Hole Preparation:	Permanganate Desmear/Etchback	
Alternate Construction:	Buried Vias, Sequential Lamination, Blind Vias	
Copper Plating:	Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	Characteristic, Differential 50, 75, 100 ohms +/-10%	
Hole Fill/Via Plug:	Non-conductive Hole Fill/Via Plug	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>American Standard Circuits</b> RF Division, 475 Industrial Drive West Chicago, IL 60185, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	CAGE Code: 4AA34  Contact: Lori Ryan Phone: 603-639-5438 Fax: EMail: lori@asc-i.com
--	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 12" X 18" Max./Min. Board Thickness: 0.062"/Not Specified Max./Min. Base CU Thickness: 0.006"/Not Specified ((1/2 oz.)) Max./Min. Through Hole Size: 0.052"/0.009" ((after plating)) Aspect Ratio: 7:1 (Through Hole) Max. Number of Layers: 10 Min. Conductor Width: 0.004" Min. Conductor Space: 0.004" (+/-10%) Part Mounting: THM, SMT, MIX Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: N/A Finish System: HASL Hole Preparation: Permanganate Desmear Alternate Construction: N/A Copper Plating: Acid Copper Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Through Hole Metallization: N/A	VQE-08-015934

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Amphenol TCS</b> 91 Northeastern Boulevard Nashua, NH 03062, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 3T000  <b>Contact:</b> Denise Chevalier <b>Phone:</b> 603-879-3268 <b>Fax:</b> 603-879-2818 <b>EMail:</b> denise.chevalier@amphenol-tcs.com
--	--	--

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2
Panel Size:	24" X 36"
Max./Min. Board Thickness:	0.322"/Not Specified
Max./Min. Base CU Thickness:	N/A
Max./Min. Through Hole Size:	Not Specified/0.016"
Aspect Ratio:	8:1 (Through Hole) 0.5:1 (Blind Via)
Max. Number of Layers:	27
Min. Conductor Width:	0.004"
Min. Conductor Space:	0.004"
Part Mounting:	THM, Compliant Pin, SMT, MIX
Rigid Base Material:	Hybrid Built (GF/Hydrocarbon Ceramic) GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant
Flex Base Material:	N/A
Finish System:	Fused SnB, Nickel, Electrolytic Hard & Soft Gold, Electrolytic Nickel
Hole Preparation:	Permanganate Desmear/Etchback, Plasma Desmear
Alternate Construction:	Blind Vias (Mechanicall Drilled)
Copper Plating:	Acid Copper, DC Plate, Pulse Plate
Solder Resist:	thermal cured Soldermask, LPI, SMOBC
Controlled Impedance:	50 ohms ± 10%
Hole Fill/Via Plug:	Non-conductive
Flex Usage:	N/A
Through Hole Metallization:	N/A

VQE-97-0649  
 VQE-97-0721  
 VQE-06-10054

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Calumet Electronics Corp.</b> 25830 Depot Street Calumet, MI 49913-1985, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 65337  <b>Contact:</b> Robert Hall <b>Phone:</b> 906-337-1305 <b>Fax:</b> 906-337-5359 <b>EMail:</b> rhall@cec-up.com
--	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-03-4657
		VQE-04-6280
Panel Size:	18" X 24"	
Max./Min. Board Thickness:	0.125"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	0.125"/0.016"	
Aspect Ratio:	8:1 (Through Hole)	
Max. Number of Layers:	10	
Min. Conductor Width:	0.006"	
Min. Conductor Space:	0.003"	
Part Mounting:	THM, SMT	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant	
	GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, Au, Ni	
Hole Preparation:	FR4: Chemical Etchback, Non FR4: Plasma Etchback	
Alternate Construction:	N/A	
Copper Plating:	Electro-deposited Acid Copper	
Solder Resist:	N/A	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I  
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION: <b>Calumet Electronics Corp.</b> 25830 Depot Street Calumet, MI 49913-1985, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 65337  Contact: Robert Hall Phone: 906-337-1305 Fax: 906-337-5359 EMail: rhall@cec-up.com</p>
---	---	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<p>Specification: MIL-PRF-31032/3, MIL-PRF-31032/4            Panel Size: 12" X 180"            Max./Min. Board Thickness: 0.035"/Not Specified            Max./Min. Base CU Thickness: N/A            Max./Min. Through Hole Size: 0.011"/Not Specified            Aspect Ratio: 3:1 (Through Hole)            Max. Number of Layers: 7            Min. Conductor Width: 0.007"            Min. Conductor Space: 0.007"            Part Mounting: SMT, THM            Rigid Base Material: N/A            Flex Base Material: FR4-IPC-4101/21                                              Flexible Polyimide Clad (IPC-4204/1)                                              Flexible Polyimide Film (PIC-4202/1)                                              Flexible Polyimide Film/Acrylic (IPC-4203/1)            Finish System: HASL            Hole Preparation: Plasma Desmear/Etchback            Alternate Construction: N/A            Copper Plating: Acid Copper            Solder Resist: N/A            Controlled Impedance: N/A            Hole Fill/Via Plug: N/A            Flex Usage: N/A            Through Hole Metallization: N/A</p>	<p>VQE-04-5354</p>



**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Cirex International</b> 791 Nuttman Street Santa Clara, CA 95054,	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 4MEG7  <b>Contact:</b> Don Angulo <b>Phone:</b> 408-988-3980 <b>Fax:</b> 408-988-4534 <b>EMail:</b> dangulo@cirexxintl.com
--	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification: Panel Size: Max./Min. Board Thickness: Max./Min. Base CU Thickness: Max./Min. Through Hole Size: Aspect Ratio: Max. Number of Layers: Min. Conductor Width: Min. Conductor Space: Part Mounting: Rigid Base Material:  Flex Base Material: Finish System: Hole Preparation: Alternate Construction: Copper Plating: Solder Resist: Controlled Impedance: Hole Fill/Via Plug: Flex Usage: Through Hole Metallization:	MIL-PRF-31032/1 12" X 18" 0.125"/Not Specified N/A Not Specified/0.01" ((Mechanical)) 12.5:1 22 0.004" 0.004" THM, MIX, SMT GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant N/A HASL, ENIG Plasma Etchback, Permanganate Desmear N/A Acid Copper LPI 50 ohms +/- 10%, 100 ohms +/- 10% N/A N/A N/A	VQ-08-016602

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification: Panel Size: Max./Min. Board Thickness: Max./Min. Base CU Thickness: Max./Min. Through Hole Size: Aspect Ratio: Max. Number of Layers: Min. Conductor Width: Min. Conductor Space: Part Mounting: Rigid Base Material:  Flex Base Material: Finish System: Hole Preparation: Alternate Construction: Copper Plating: Solder Resist: Controlled Impedance: Hole Fill/Via Plug: Flex Usage: Through Hole Metallization:	MIL-PRF-31032/4 12" X 18" 0.125"/Not Specified N/A Not Specified/0.01" ((Mechanical)) 10:1 16 0.004" 0.004" SMT, THM, MIX GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Copper Clad Adhesiveless Polyimide Acrylic Adhesive ENIG, HASL Plasma Etchback, Permanganate Desmear N/A Acid Copper LPI 50 ohms +/- 10%, 100 ohms +/- 10% N/A Class A (Flex-to-Install) N/A	VQ-08-016602

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION:  <b>Colonial Circuits, Inc.</b>          1026 Warrenton Road          Fredericksburg, VA 22406-6200, US</p>	<p>PLANT LOCATION:          Same Address as Manufacturer</p>	<p>CAGE Code: 6T499           Contact: Mike Hill          Phone: 540-753-5511, x125          Fax: 540-752-2109          EMail: quality@colonialcircuits.com</p>
--	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<p>Specification: MIL-PRF-31032/1            Panel Size: 18" X 24"            Max./Min. Board Thickness: 0.127"/Not Specified            Max./Min. Base CU Thickness: N/A            Max./Min. Through Hole Size: 0.228"/0.015"            Aspect Ratio: 8.5:1 (Through Hole)            Max. Number of Layers: 12            Min. Conductor Width: 0.008"            Min. Conductor Space: 0.005"            Part Mounting: PTH, SMT            Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant            Flex Base Material: N/A            Finish System: Tin/Lead HASL            Hole Preparation: Plasma Desmear            Alternate Construction: N/A            Copper Plating: Electrolytic Acid Copper            Solder Resist: LPI            Controlled Impedance: 55 Ohms (± 10%)            Hole Fill/Via Plug: N/A            Flex Usage: N/A            Through Hole Metallization: N/A</p>	<p>VQE-04-6002</p>

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<p>Specification: MIL-PRF-31032/1            Panel Size: 18" X 24"            Max./Min. Board Thickness: 0.088"/Not Specified            Max./Min. Base CU Thickness: N/A            Max./Min. Through Hole Size: 0.052"/0.021"            Aspect Ratio: 4.2:1 (Through Hole)            Max. Number of Layers: 14            Min. Conductor Width: 0.006"            Min. Conductor Space: 0.005"            Part Mounting: PTH, SMT            Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant            Flex Base Material: N/A            Finish System: Tin/Lead HASL            Hole Preparation: Plasma Desmear            Alternate Construction: N/A            Copper Plating: Electrolytic Acid Copper            Solder Resist: LPI            Controlled Impedance: N/A            Hole Fill/Via Plug: N/A            Flex Usage: N/A            Through Hole Metallization: N/A</p>	<p>VQE-04-6002</p>

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION:  <b>Colonial Circuits, Inc.</b>          1026 Warrenton Road          Fredericksburg, VA 22406-6200, US</p>	<p>PLANT LOCATION:          Same Address as Manufacturer</p>	<p>CAGE Code: 6T499           Contact: Mike Hill          Phone: 540-753-5511, x125          Fax: 540-752-2109          EMail: quality@colonialcircuits.com</p>
--	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<p>Specification: MIL-PRF-31032/4            Panel Size: 12" X 18"            Max./Min. Board Thickness: 0.093"/Not Specified            Max./Min. Base CU Thickness: N/A            Max./Min. Through Hole Size: 0.045"/0.025"            Aspect Ratio: 3.7:1 (Through Hole)            Max. Number of Layers: 10            Min. Conductor Width: 0.005"            Min. Conductor Space: 0.005"            Part Mounting: PTH, SMT            Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant            Flex Base Material: IPC-4204/1 (Acrylic Adhesive)            Finish System: Tin/Lead Reflow            Hole Preparation: Plasma Desmear/Etchback            Alternate Construction: N/A            Copper Plating: Electrolytic Acid Copper            Solder Resist: LPI            Controlled Impedance: N/A            Hole Fill/Via Plug: N/A            Flex Usage: N/A            Through Hole Metallization: N/A</p>	<p>VQE-04-6002</p>

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<p>Specification: MIL-PRF-31032/Custom            Panel Size: 12" X 18"            Max./Min. Board Thickness: 0.083"/Not Specified            Max./Min. Base CU Thickness: N/A            Max./Min. Through Hole Size: 0.045"/0.02"            Aspect Ratio: 4.15:1 (Through Hole)            Max. Number of Layers: 4            Min. Conductor Width: 0.01"            Min. Conductor Space: 0.011"            Part Mounting: PTH, SMT            Rigid Base Material: Rogers 4003            Flex Base Material: N/A            Finish System: Tin/Lead HASL            Hole Preparation: Plasma Desmear            Alternate Construction: N/A            Copper Plating: Electrolytic Acid Copper            Solder Resist: LPI            Controlled Impedance: N/A            Hole Fill/Via Plug: N/A            Flex Usage: N/A            Through Hole Metallization: N/A</p>	<p>VQE-04-6002</p>

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Colonial Circuits, Inc.</b> 1026 Warrenton Road Fredericksburg, VA 22406-6200, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 6T499  <b>Contact:</b> Mike Hill <b>Phone:</b> 540-753-5511, x125 <b>Fax:</b> 540-752-2109 <b>EMail:</b> quality@colonialcircuits.com
--	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification: Panel Size: Max./Min. Board Thickness: Max./Min. Base CU Thickness: Max./Min. Through Hole Size: Aspect Ratio: Max. Number of Layers: Min. Conductor Width: Min. Conductor Space: Part Mounting: Rigid Base Material:  Flex Base Material: Finish System: Hole Preparation: Alternate Construction: Copper Plating: Solder Resist: Controlled Impedance: Hole Fill/Via Plug: Flex Usage: Through Hole Metallization:	MIL-PRF-31032/Custom 12" X 18" 0.031"/Not Specified N/A 0.117"/0.02" 1.55:1 (Through Hole) 2 0.025" 0.01" SMT PTFE Resin with Ceramic Filler With or Without Woven E-Glass N/A Tin/Lead HASL Plasma Desmear N/A Electrolytic Acid Copper LPI N/A N/A N/A N/A	VQE-04-6002

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification: Panel Size: Max./Min. Board Thickness: Max./Min. Base CU Thickness: Max./Min. Through Hole Size: Aspect Ratio: Max. Number of Layers: Min. Conductor Width: Min. Conductor Space: Part Mounting: Rigid Base Material:  Flex Base Material: Finish System: Hole Preparation: Alternate Construction: Copper Plating: Solder Resist: Controlled Impedance: Hole Fill/Via Plug: Flex Usage: Through Hole Metallization:	MIL-PRF-31032/1, MIL-PRF-31032/2 12" X 18" 0.09"/Not Specified N/A 0.139"/0.021" 4.29:1 (Through Hole) 8 0.005" 0.005" PTH, SMT Woven E-Glass Hydrocarbon Resin with Ceramic Filler N/A Tin/Lead HASL, Tin/Lead Reflow Plasma Desmear, Plasma Etchback N/A Electrolytic Acid Copper LPI 55 ohms ±10% N/A N/A N/A	VQE-04-6002 VQE-06-010192

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Coretec Cleveland, Inc.</b> 7 Ascot Parkway Cuyahoga Falls, OH 44223, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 7Z463  <b>Contact:</b> Mark Kasting <b>Phone:</b> 330-572-3400 <b>Fax:</b> 330-572-3434 <b>EMail:</b> mark_kasting/coretec@coretec-inc.com
---	--	---

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

<b>Specification:</b> MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-05-008414
<b>Panel Size:</b> 18" X 24"	VQE-06-010963
<b>Max./Min. Board Thickness:</b> 0.126"/Not Specified	VQE-00-0289
<b>Max./Min. Base CU Thickness:</b> N/A	VQE-01-0910
<b>Max./Min. Through Hole Size:</b> Not Specified/0.014"	
<b>Aspect Ratio:</b> 5:1 (Through Hole)	
<b>Max. Number of Layers:</b> 16	
<b>Min. Conductor Width:</b> 0.004"	
<b>Min. Conductor Space:</b> 0.004"	
<b>Part Mounting:</b> SMT, THM	
<b>Rigid Base Material:</b> AF: Aramid Fabric, Woven, Majority Polyfunctional Epoxy Resin GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant BI: Aramid Fabric, Nonwoven, Polyimide Resin	
<b>Flex Base Material:</b> N/A	
<b>Finish System:</b> HASL, Fused Tin Lead late, Selective Solder Strip-Tin Lead Plate	
<b>Hole Preparation:</b> Plasma Etchback	
<b>Alternate Construction:</b> Sequential Lamination for Blind & Buried Vias (8 layer max)	
<b>Copper Plating:</b> Acid Copper	
<b>Solder Resist:</b> N/A	
<b>Controlled Impedance:</b> 100/50 ohm (±5%)	
<b>Hole Fill/Via Plug:</b> N/A	
<b>Flex Usage:</b> N/A	
<b>Through Hole Metallization:</b> N/A	

VQE-05-008414  
 VQE-06-010963  
 VQE-00-0289  
 VQE-01-0910

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Coretec Cleveland, Inc.</b> 7 Ascot Parkway Cuyahoga Falls, OH 44223, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 7Z463  <b>Contact:</b> Mark Kasting <b>Phone:</b> 330-572-3400 <b>Fax:</b> 330-572-3434 <b>EMail:</b> mark_kasting/coretec@coretec-inc.com
---	--	---

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

<b>Specification:</b> MIL-PRF-31032/3, MIL-PRF-31032/4	VQE-06-010963
<b>Panel Size:</b> 18" X 24"	VQE-01-0909
<b>Max./Min. Board Thickness:</b> 0.126"/Not Specified	
<b>Max./Min. Base CU Thickness:</b> N/A	
<b>Max./Min. Through Hole Size:</b> Not Specified/0.017"	
<b>Aspect Ratio:</b> 10:1 (Through Hole)	
<b>Max. Number of Layers:</b> 11	
<b>Min. Conductor Width:</b> 0.003"	
<b>Min. Conductor Space:</b> 0.003"	
<b>Part Mounting:</b> SMT, THM	
<b>Rigid Base Material:</b> GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
<b>Flex Base Material:</b> IPC-4204/1 (Acrylic Adhesive) IPC-4204/11 (Adhesiveless)	
<b>Finish System:</b> HASL	
<b>Hole Preparation:</b> Plasma Etchback	
<b>Alternate Construction:</b> N/A	
<b>Copper Plating:</b> Acid Copper	
<b>Solder Resist:</b> N/A	
<b>Controlled Impedance:</b> N/A	
<b>Hole Fill/Via Plug:</b> N/A	
<b>Flex Usage:</b> Class A (Flex to Install)	
<b>Through Hole Metallization:</b> N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Coretec Denver, Inc.</b> 10570 Bradford Road Littleton, CO 80127, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 75815  <b>Contact:</b> Douglas N. Berry <b>Phone:</b> 303-904-6119 <b>Fax:</b> 303-933-2934 <b>EMail:</b> dberry@coretec-denver.com
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-02-0317 VQE-05-9014 VQE-05-7627
Panel Size:	18" X 24"	
Max./Min. Board Thickness:	0.125"/Not Specified	
Max./Min. Base CU Thickness:	0.001"/Not Specified	
Max./Min. Through Hole Size:	0.109"/0.015"	
Aspect Ratio:	7:1 (Through Hole)	
Max. Number of Layers:	16	
Min. Conductor Width:	0.006"	
Min. Conductor Space:	0.006"	
Part Mounting:	SMT, MIX, THM	
Rigid Base Material:	GM: Glass Base, Woven, Triazine and/or Bismaleimide Modified Epoxy Resin, Flame Resistant GF: Woven E-Glass, Epoxy Resin, Flame Resistant Gl: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, IR Reflow Following SnPb Plate, ENIG	
Hole Preparation:	Permanganate Desmear/Etchback	
Alternate Construction:	N/A	
Copper Plating:	Acid Copper	
Solder Resist:	LPI, Dry Film	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	Conductive Epoxy, Non-conductive Epoxy	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Coretec, Inc.</b> 8150 Sheppard Avenue East Scarborough, Ontario, Canada M1B 5K2	<b>PLANT LOCATIONS:</b> 1. Same Address as Manufacturer 2. Coretec, Inc., CAGE Code: 3AF82, 2020 Ellesmere Road, Scarborough, Ontario, Canada M1H 2Z8	CAGE Code: 3AF82 Contact: Noor Al-Shaikh Phone: 416-208-2100 Fax: 416-439-1582 EMail: alshaikh@coretec-inc.com
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-04-006240
		VQE-08-015407
Panel Size:	18" X 24"	
Max./Min. Board Thickness:	0.08"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.01" ((as drilled))	
Aspect Ratio:	7:1 (Through Hole)	
Max. Number of Layers:	14	
Min. Conductor Width:	0.005"	
Min. Conductor Space:	0.005"	
Part Mounting:	MIX, SMT, THM	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant	
Flex Base Material:	N/A	
Finish System:	ENIG, HASL	
Hole Preparation:	Chemical desmear	
Alternate Construction:	N/A	
Copper Plating:	Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	Characteristics ( $\pm 10\%$ ), Differential ( $\pm 10\%$ )	
Hole Fill/Via Plug:	Non-conductive Via Plug	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-08-015407
		VQE-04-006240
Panel Size:	18" X 24"	
Max./Min. Board Thickness:	0.08"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.01" ((as drilled))	
Aspect Ratio:	7:1 (Through Hole)	
Max. Number of Layers:	14	
Min. Conductor Width:	0.005"	
Min. Conductor Space:	0.005"	
Part Mounting:	THM, SMT, MIX	
Rigid Base Material:	GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, ENIG	
Hole Preparation:	Plasma Etchback, Desmear	
Alternate Construction:	N/A	
Copper Plating:	Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	Characteristics (+/-10%), Differential (+/-10%)	
Hole Fill/Via Plug:	Non-conductive Via Plug	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Cosmotronic, Inc.</b> 16721 Noyes Avenue Irvine, CA 92606, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 63695  <b>Contact:</b> Alan Exley <b>Phone:</b> 949-660-0740 <b>Fax:</b> 949-553-8371 <b>E-Mail:</b> alan_exley@cosmotronic.com
--	--	--

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2
Panel Size:	18" X 24"
Max./Min. Board Thickness:	0.335"/Not Specified
Max./Min. Base CU Thickness:	N/A
Max./Min. Through Hole Size:	Not Specified/0.014"
Aspect Ratio:	15:1 (Through Hole)
Max. Number of Layers:	36
Min. Conductor Width:	0.005"
Min. Conductor Space:	0.004"
Part Mounting:	SMT, THM, MIX
Rigid Base Material:	GM: Glass Base, Woven, Triazine and/or Bismaleimide Modified Epoxy Resin, Flame Resistant GF: Woven E-Glass, Epoxy Resin, Flame Resistant AF: Aramid Fabric, Woven, Majority Polyfunctional Epoxy Resin GI: Glass Base, Woven, Polyimide Resin, Heat Resistant BF: Aramid Fabric, Nonwoven, Epoxy Resin BI: Aramid Fabric, Nonwoven, Polyimide Resin
Flex Base Material:	N/A
Finish System:	Fused SnPB, HASL, Selective Solder Strip-Tin Lead Plate, ENIG
Hole Preparation:	Plasma Desmear/Etchback
Alternate Construction:	Blind Vias, Sequential Lamination
Copper Plating:	Electro-deposited Acid Copper
Solder Resist:	LPI, SMOBC
Controlled Impedance:	50 ohms ± 10% (nominal/tolerance)
Hole Fill/Via Plug:	N/A
Flex Usage:	N/A
Through Hole Metallization:	N/A

VQE-05-009107  
 VQE-04-006966  
 VQE-06-010085  
 VQE-06-011248

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Cosmotronic, Inc.</b> 16721 Noyes Avenue Irvine, CA 92606, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 63695  <b>Contact:</b> Alan Exley <b>Phone:</b> 949-660-0740 <b>Fax:</b> 949-553-8371 <b>EMail:</b> alan_exley@cosmotronic.com
--	--	---

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

Specification:	MIL-PRF-31032/3, MIL-PRF-31032/4
Panel Size:	18" X 24"
Max./Min. Board Thickness:	0.165"/Not Specified
Max./Min. Base CU Thickness:	N/A
Max./Min. Through Hole Size:	Not Specified/0.012"
Aspect Ratio:	8:1 (Through Hole)
Max. Number of Layers:	22
Min. Conductor Width:	0.006"
Min. Conductor Space:	0.008"
Part Mounting:	SMT, THM
Rigid Base Material:	GM: Glass Base, Woven, Triazine and/or Bismaleimide Modified Epoxy Resin, Flame Resistant GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant GI/GM Composite Material
Flex Base Material:	IPC-4204/1 (Acrylic Adhesive) IPC-4204/11 (Adhesiveless)
Finish System:	Fused SnPB, HASL, Selective Solder Strip-Tin Lead Plate, ENIG,
Hole Preparation:	N/A
Alternate Construction:	N/A
Copper Plating:	Electro-deposited Acid Copper
Solder Resist:	LPI, SMOBC
Controlled Impedance:	N/A
Hole Fill/Via Plug:	N/A
Flex Usage:	Class A (Flex to Install) Class B (Continuous Flex)
Through Hole Metallization:	N/A

VQE-05-009107  
 VQE-04-006966  
 VQE-06-010085

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Cosmotronic, Inc.</b> 16721 Noyes Avenue Irvine, CA 92606, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 63695  <b>Contact:</b> Alan Exley <b>Phone:</b> 949-660-0740 <b>Fax:</b> 949-553-8371 <b>EMail:</b> alan_exley@cosmotronic.com
--	--	---

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

Specification:	MIL-PRF-31032/Custom
Panel Size:	12" X 18"
Max./Min. Board Thickness:	0.225"/Not Specified
Max./Min. Base CU Thickness:	N/A
Max./Min. Through Hole Size:	Not Specified/0.02"
Aspect Ratio:	10:1 (Through Hole)
Max. Number of Layers:	16
Min. Conductor Width:	0.011"
Min. Conductor Space:	0.007"
Part Mounting:	SMT
Rigid Base Material:	Rogers 4003 (Ceramic-Filled Thermoset Resin) Rogers 4003/GI Composite
Flex Base Material:	N/A
Finish System:	HASL, ENIG
Hole Preparation:	Plasma Desmear/Etchback
Alternate Construction:	Blind Vias, Sequential Lamination
Copper Plating:	Electro-deposited Acid Copper
Solder Resist:	LPI, SMOBC
Controlled Impedance:	N/A
Hole Fill/Via Plug:	N/A
Flex Usage:	N/A
Through Hole Metallization:	N/A

VQE-05-009107  
 VQE-04-006966  
 VQE-06-010085

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION:  <b>Diversified Systems</b>          3939 West 56th Street          Indianapolis, IN 46254, US</p>	<p>PLANT LOCATION:          Same Address as Manufacturer</p>	<p>CAGE Code: 5S706           Contact: Linda Bell          Phone: 317-299-9547, x238          Fax: 317-298-2061          EMail: linda.bell@divsys.com</p>
---	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-01-0309
Panel Size:	18" X 24"	VQE-02-0015
Max./Min. Board Thickness:	0.11"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.012"	
Aspect Ratio:	5.5:1 (Through Hole)	
Max. Number of Layers:	14	
Min. Conductor Width:	0.005"	
Min. Conductor Space:	0.005"	
Part Mounting:	SMT, THM	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL	
Hole Preparation:	Permanganate Desmear/Etchback	
Alternate Construction:	Foil Lamination	
Copper Plating:	Electro-deposited Acid Copper	
Solder Resist:	Dry Film, LPI	
Controlled Impedance:	Embedded Stripline & Microstrip	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Dynaco Corp.</b> 1000 South Priest Drive Tempe, AZ 85281-5238, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 61642  <b>Contact:</b> Ted Edwards <b>Phone:</b> 480-736-3728 <b>Fax:</b> 480-921-9830 <b>EMail:</b> tedwards@dynacocorp.com
--	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification: Panel Size: Max./Min. Board Thickness: Max./Min. Base CU Thickness: Max./Min. Through Hole Size: Aspect Ratio: Max. Number of Layers: Min. Conductor Width: Min. Conductor Space: Part Mounting: Rigid Base Material:  Flex Base Material: Finish System: Hole Preparation: Alternate Construction: Copper Plating: Solder Resist: Controlled Impedance: Hole Fill/Via Plug: Flex Usage: Through Hole Metallization:	MIL-PRF-31032/1, MIL-PRF-31032/2 18" X 24" 0.1"/Not Specified 0.001"/Not Specified 0.045"/0.032" 3:1 (Through Hole) 10 0.01" 0.01" THM GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant N/A HASL Permanganate Desmear/Etchback N/A Acid Copper N/A N/A N/A N/A N/A	VQE-05-9356

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification: Panel Size: Max./Min. Board Thickness: Max./Min. Base CU Thickness: Max./Min. Through Hole Size: Aspect Ratio: Max. Number of Layers: Min. Conductor Width: Min. Conductor Space: Part Mounting: Rigid Base Material: Flex Base Material: Finish System: Hole Preparation: Alternate Construction: Copper Plating: Solder Resist: Controlled Impedance: Hole Fill/Via Plug: Flex Usage: Through Hole Metallization:	MIL-PRF-31032/3, MIL-PRF-31032/4 18" X 24", 12" X 18" 0.12"/Not Specified 0.001"/Not Specified 0.045"/0.01" 12:1 (Through Hole) 20 0.004" 0.006" THM GI: Glass Base, Woven, Polyimide Resin, Heat Resistant IPC-4204/1 (Acrylic Adhesive) HASL, Fused Sn/Pb Permanganate Desmear/Etchback, Plasma Etchback N/A Electroless Acid Copper, Electroplated Acid Copper N/A N/A N/A N/A N/A	VQE-05-9356 VQE-06-10600

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Dynaco Corp.</b> 1000 South Priest Drive Tempe, AZ 85281-5238, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 61642  <b>Contact:</b> Ted Edwards <b>Phone:</b> 480-736-3728 <b>Fax:</b> 480-921-9830 <b>EMail:</b> tedwards@dynacocorp.com
--	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
Specification: MIL-PRF-31032/3, MIL-PRF-31032/4 Panel Size: 12" X 18", 18" X 24" Max./Min. Board Thickness: 0.1"/Not Specified Max./Min. Base CU Thickness: 0.001"/Not Specified Max./Min. Through Hole Size: 0.045"/0.032" Aspect Ratio: 3:1 (Through Hole) Max. Number of Layers: 10 Min. Conductor Width: 0.01" Min. Conductor Space: 0.01" Part Mounting: THM Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: IPC-241/11 (Adhesiveless) IPC-4204/11 (Adhesiveless) Finish System: HASL Hole Preparation: Permanganate Desmear/Etchback Alternate Construction: Foil Lamination Copper Plating: Acid Copper Solder Resist: N/A Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: Class A (Flex to Install) Class B (Continuous Flex) Through Hole Metallization: N/A	VQE-05-9356

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Dynamic &amp; Proto Circuits, Inc.</b> 869 Barton Street Stoney Creek, Ontario, Canada L8E 5G6	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 38898  <b>Contact:</b> Stephen Hazell <b>Phone:</b> 905-643-9900 <b>Fax:</b> 905-643-9911 <b>E-Mail:</b> stephenhazell@dapc.com
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-98-1143 VQE-00-0007 VQE-01-0311 VQE-03-0818
Panel Size:	16" X 18"	
Max./Min. Board Thickness:	0.125"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	0.039"/0.018" (0.0135" Drilled)	
Aspect Ratio:	9.3:1 (Through Hole)	
Max. Number of Layers:	16	
Min. Conductor Width:	0.005"	
Min. Conductor Space:	0.005"	
Part Mounting:	SMT, THM, MIX	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL	
Hole Preparation:	Plasma Etchback	
Alternate Construction:	N/A	
Copper Plating:	Acid Copper	
Solder Resist:	LPI, Dry Film Solder Resist Plugs	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	



**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Electro Plate Circuitry</b> 1430 Century Drive Carrollton, TX 75006, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 79616  <b>Contact:</b> James McNeal <b>Phone:</b> 972-466-0818 <b>Fax:</b> 972-466-9078 <b>EMail:</b> jimm@eplate.com
--	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<b>Specification:</b> MIL-PRF-31032/1, MIL-PRF-31032/2  <b>Panel Size:</b> 18" X 16", 18" X 24" <b>Max./Min. Board Thickness:</b> 0.12"/0.03" <b>Max./Min. Base CU Thickness:</b> N/A <b>Max./Min. Through Hole Size:</b> Not Specified/0.008" <b>Aspect Ratio:</b> 9.3:1 (Through Hole) <b>Max. Number of Layers:</b> 14 <b>Min. Conductor Width:</b> 0.004" <b>Min. Conductor Space:</b> 0.004" <b>Part Mounting:</b> SMT, THM, MIX <b>Rigid Base Material:</b> GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant <b>Flex Base Material:</b> N/A <b>Finish System:</b> HASL, Reflowed SnPb, ENIG, Hard Gold <b>Hole Preparation:</b> Plasma Desmear/Etchback <b>Alternate Construction:</b> Sequential Lamination, Blind/Buried Vias, Filled Vias, Foil Lamination <b>Copper Plating:</b> Acid Copper <b>Solder Resist:</b> LPI, Dry Film <b>Controlled Impedance:</b> ± 3% Tolerance <b>Hole Fill/Via Plug:</b> CB100 (conductive), UVP100 (non-conductive) <b>Flex Usage:</b> N/A <b>Through Hole Metallization:</b> N/A	VQE-06-011433 VQE-06-010333

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Electrotek Corp.</b> 7745 S. 10th Street Oak Creek, WI 53154, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 66030  <b>Contact:</b> Tom Tikusis <b>Phone:</b> 414-762-1390 <b>Fax:</b> 414-762-1510 <b>EMail:</b> sales@boards4u.com
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQ-06-011451
Panel Size:	18" X 24"	VQ-08-014513
Max./Min. Board Thickness:	0.115"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.012"	
Aspect Ratio:	9:1 (Through Hole)	
Max. Number of Layers:	18	
Min. Conductor Width:	0.003"	
Min. Conductor Space:	0.003"	
Part Mounting:	SMT, THM, MIX	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, ENIG, ImmAg	
Hole Preparation:	Permanganate Desmear, Plasma Etchback	
Alternate Construction:	Via-fill Technology, 0.016" ( ±25%) Diameter	
Copper Plating:	Electroplated Acid Copper	
Solder Resist:	LPI, Dry Film	
Controlled Impedance:	GF: 100 ohms/50 ohms ± 10%, GI: 100 ohms ± 10%	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I  
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Endicott Interconnect Technologies, Inc.</b> 1701 North Street P.O. Box 658, Endicott, NY 13760, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 3ECL3  <b>Contact:</b> Jose Rios <b>Phone:</b> 607-755-5896 <b>Fax:</b> 607-755-4649 <b>EMail:</b> JoseA.Rios@eitny.com
--	--	--

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

<b>Specification:</b> MIL-PRF-31032/1, MIL-PRF-31032/2  <b>Panel Size:</b> 24" X 28" <b>Max./Min. Board Thickness:</b> 0.116"/Not Specified <b>Max./Min. Base CU Thickness:</b> N/A <b>Max./Min. Through Hole Size:</b> Not Specified/0.01" <b>Aspect Ratio:</b> 12:1 (Through Hole) <b>Max. Number of Layers:</b> 30 <b>Min. Conductor Width:</b> 0.003" <b>Min. Conductor Space:</b> 0.004" <b>Part Mounting:</b> MIX, THM, SMT <b>Rigid Base Material:</b> GF: Woven E-Glass, Epoxy Resin, Flame Resistant <b>Flex Base Material:</b> N/A <b>Finish System:</b> HASL, ENIG <b>Hole Preparation:</b> Permanganate Desmear, Plasma Etchback, Glass Etch <b>Alternate Construction:</b> Foil-Lamination, Cap-Lamination <b>Copper Plating:</b> Electroplated Acid Copper <b>Solder Resist:</b> LPI <b>Controlled Impedance:</b> N/A <b>Hole Fill/Via Plug:</b> N/A <b>Flex Usage:</b> N/A <b>Through Hole Metallization:</b> N/A	VQE-04-005311 VQE-07-013506 VQE-07-012236 VQE-08-015922
---	--

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Endicott Interconnect Technologies, Inc.</b> 1701 North Street P.O. Box 658, Endicott, NY 13760, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 3ECL3  <b>Contact:</b> Jose Rios <b>Phone:</b> 607-755-5896 <b>Fax:</b> 607-755-4649 <b>EMail:</b> JoseA.Rios@eitny.com
--	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-04-005311 VQE-07-013506 VQE-07-012236
Panel Size:	18" X 24"	
Max./Min. Board Thickness:	0.084"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.012"	
Aspect Ratio:	7:1 (Through Hole)	
Max. Number of Layers:	12	
Min. Conductor Width:	0.004"	
Min. Conductor Space:	0.004"	
Part Mounting:	MIX, THM, SMT	
Rigid Base Material:	GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, ENIG	
Hole Preparation:	Pemanganate Desmear, Plasma Etchback	
Alternate Construction:	Foil-Lamination, Cap-Lamination	
Copper Plating:	Electroplated Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/Custom	VQE-04-005311 VQE-07-013506 VQE-07-012236
Panel Size:	19.5" X 24"	
Max./Min. Board Thickness:	0.153"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.02"	
Aspect Ratio:	7.6:1 (Through Hole)	
Max. Number of Layers:	19	
Min. Conductor Width:	0.005"	
Min. Conductor Space:	0.005"	
Part Mounting:	MIX	
Rigid Base Material:	GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	ENIG	
Hole Preparation:	Pemanganate Desmear, Plasma Etchback	
Alternate Construction:	Foil-Lamination, Copper Core	
Copper Plating:	Electroplated Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Firan Technology Group</b> 250 Finchdene Square Scarborough, Ontario, Canada M1X 1A5	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> L2665  <b>Contact:</b> Bryan Clark <b>Phone:</b> 416-299-4000 <b>Fax:</b> 416-292-4308 <b>E-Mail:</b> byanclark@firantechnology.com
---	--	--

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2
Panel Size:	18" X 24"
Max./Min. Board Thickness:	0.22"/Not Specified
Max./Min. Base CU Thickness:	N/A
Max./Min. Through Hole Size:	0.025"/0.008" (Mechanical Drill) Not Specified/0.005" (Laser Control Depth) Not Specified/0.006" (Buried Via Mechanical Drill)
Aspect Ratio:	7:1 (Through Hole)
Max. Number of Layers:	20
Min. Conductor Width:	0.004"
Min. Conductor Space:	0.004"
Part Mounting:	MIX, SMT, THM
Rigid Base Material:	GM: Glass Base, Woven, Triazine and/or Bismaleimide Modified Epoxy Resin, Flame Resistant GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant BI: Aramid Fabric, Nonwoven, Polyimide Resin GX: Glass Base, Woven, Polytetrafluoroethylene Resin, Flame Resistant
Flex Base Material:	N/A
Finish System:	HASL, Reflow Solder, Immersion Tin, Silver, ENIG
Hole Preparation:	Permanganate Desmear, Plasma Etchback
Alternate Construction:	Sequential Lamination for Blind & Buried Vias and Micro Vias
Copper Plating:	Electroless Acid Copper, Electrolytic Acid Copper
Solder Resist:	LPI, Hole Fill
Controlled Impedance:	Characteristic ( $\pm 10\%$ ), Differential ( $\pm 10\%$ )
Hole Fill/Via Plug:	N/A
Flex Usage:	N/A
Through Hole Metallization:	N/A

VQE-05-009339  
 VQE-06-010764  
 VQE-06-010889



**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION:  <b>Global Innovation Corp.</b>            901 Hensley Drive            Wylie, TX 75098, US</p>	<p>PLANT LOCATION:            Same Address as Manufacturer</p>	<p>CAGE Code: 04RV5             Contact: Bob Noland            Phone: 214-291-1427            Fax:            EMail: b noland@globalinnovationcorp.com</p>
--	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-04-4957
Panel Size:	18" X 24"	VQE-05-7288
Max./Min. Board Thickness:	0.074"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.012"	
Aspect Ratio:	6.2:1 (Through Hole)	
Max. Number of Layers:	12	
Min. Conductor Width:	0.005"	
Min. Conductor Space:	0.005"	
Part Mounting:	MIX	
Rigid Base Material:	GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL	
Hole Preparation:	Plasma Etchback	
Alternate Construction:	N/A	
Copper Plating:	Electro-deposited Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	62/37.5 ohms (±10%)	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Hamby Corporation</b> 27704 Avenue Scott Valencia, CA 91355, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 07248  <b>Contact:</b> Sue Sharp <b>Phone:</b> 661-257-1924 <b>Fax:</b> 661-257-1213 <b>EMail:</b> suesharp@hambycorp.com
--	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
Specification: MIL-PRF-31032/3, MIL-PRF-31032/4 Panel Size: 18" X 24" Max./Min. Board Thickness: 0.085"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: 0.035"/0.018" Not Specified/" Aspect Ratio: 5:1 (Through Hole) Max. Number of Layers: 11 Min. Conductor Width: 0.004" Min. Conductor Space: 0.004" Part Mounting: SMT, THM, MIX Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: IPC-4204/1 (Acrylic Adhesive) IPC-4204/11 (Adhesiveless) Finish System: HASL, Ni/Au Hole Preparation: Plasma Etchback/Desmear Alternate Construction: N/A Copper Plating: Electrodeposited Acid Copper Solder Resist: N/A Controlled Impedance: Characteristic: 35-50 ohms +/-10%, Differential: 100 ohms +/-10% Hole Fill/Via Plug: N/A Flex Usage: N/A Through Hole Metallization: N/A	VQE-08-014596

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Hans Brockstedt GmbH</b> Leiterplattenschnelldienst, Clara-Immerwahr-Str. 7 24145, Kiel, Germany	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> C4831  <b>Contact:</b> Hilmar Klammer <b>Phone:</b> 0049-431-71966-0, -30 <b>Fax:</b> 0049-431-71966-29 <b>EMail:</b> klammer@brockstedt.de
---	--	--

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2
Panel Size:	9" X 13", 13" X 20", 15" X 21", 18" X 24"
Max./Min. Board Thickness:	0.2"/Not Specified
Max./Min. Base CU Thickness:	N/A
Max./Min. Through Hole Size:	Not Specified/0.01" (Mech. Drilled) Not Specified/0.004" (Laser Drilled)
Aspect Ratio:	1:1 (Blind Vias) 7:1 (Through Hole)
Max. Number of Layers:	12
Min. Conductor Width:	0.004"
Min. Conductor Space:	0.004"
Part Mounting:	SMT, THM, MIX
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant
Flex Base Material:	N/A
Finish System:	Fused SnPb, HASL, Electroless Sn, Electroplated Nickel/Gold, Electroless Nickel/Gold, Electroplated SnPb
Hole Preparation:	Plasma Desmear/Etchback
Alternate Construction:	Blind Vias, Buried Vias, Laser Drilled Vias
Copper Plating:	Acid Copper
Solder Resist:	LPI
Controlled Impedance:	N/A
Hole Fill/Via Plug:	N/A
Flex Usage:	N/A
Through Hole Metallization:	N/A

VQE-03-2619  
VQE-05-7480

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Hans Brockstedt GmbH</b> Leiterplattenschnelldienst, Clara-Immerwahr-Str. 7 24145, Kiel, Germany	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> C4831  <b>Contact:</b> Hilmar Klammer <b>Phone:</b> 0049-431-71966-0, -30 <b>Fax:</b> 0049-431-71966-29 <b>EMail:</b> klammer@brockstedt.de
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/3, MIL-PRF-31032/4	VQE-03-2619
		VQE-05-7480
Panel Size:	9" X 13", 13" X 20"	
Max./Min. Board Thickness:	0.2"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.01" (Mech. Drilled)	
	Not Specified/0.004" (Laser Drilled)	
Aspect Ratio:	1:1 (Blind Vias)	
	7:1 (Through Hole)	
Max. Number of Layers:	12	
Min. Conductor Width:	0.004"	
Min. Conductor Space:	0.004"	
Part Mounting:	SMT, THM, MIX	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant	
	GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	IPC-4204/1 (Acrylic Adhesive)	
	IPC-4204/11 (Adhesiveless)	
Finish System:	Fused SnPb, HASL, Electroless Sn, Electroplated Nickel/Gold, Electroless	
	Nickel/Gold, Electroplated SnPb	
Hole Preparation:	Plasma Desmear/Etchback	
Alternate Construction:	Blind Vias, Buried Vias, Laser Drilled Vias	
Copper Plating:	Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	Class A (Flex to Install)	
Through Hole Metallization:	N/A	



**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Lockheed Martin Systems Integration-Owego</b> 1801 State Route 17C Owego, NY 13827, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 03640  <b>Contact:</b> Melita Nagerl <b>Phone:</b> 607-751-4665 <b>Fax:</b> 607-751-7714 <b>EMail:</b> melita.nagerl@lmco.com
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-99-0130
		VQE-00-0961
Panel Size:	18" X 24"	
Max./Min. Board Thickness:	0.2"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.02"	
Aspect Ratio:	8:1 (Through Hole)	
Max. Number of Layers:	16	
Min. Conductor Width:	0.004"	
Min. Conductor Space:	0.004"	
Part Mounting:	SMT, THM	
Rigid Base Material:	AF: Aramid Fabric, Woven, Majority Polyfunctional Epoxy Resin	
Flex Base Material:	N/A	
Finish System:	Fused SnPb, HASL, NiAu	
Hole Preparation:	Permanganate Desmear, Plasma Etchback	
Alternate Construction:	N/A	
Copper Plating:	Electro-deposited Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-01-0539
Panel Size:	18" X 24"	
Max./Min. Board Thickness:	0.095"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.014"	
Aspect Ratio:	6.8:1 (Through Hole)	
Max. Number of Layers:	14	
Min. Conductor Width:	0.004"	
Min. Conductor Space:	0.004"	
Part Mounting:	SMT, THM	
Rigid Base Material:	BI: Aramid Fabric, Nonwoven, Polyimide Resin	
Flex Base Material:	N/A	
Finish System:	Fused SnPb, HASL, NiAu	
Hole Preparation:	Permanganate Desmear	
Alternate Construction:	N/A	
Copper Plating:	Electro-deposited Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I  
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION: <b>Lockheed Martin Systems Integration-Owego</b> 1801 State Route 17C Owego, NY 13827, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 03640  Contact: Melita Nagerl Phone: 607-751-4665 Fax: 607-751-7714 EMail: melita.nagerl@lmco.com</p>
--	---	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<p>Specification: MIL-PRF-31032/1, MIL-PRF-31032/2</p> <p>Panel Size:</p> <p>Max./Min. Board Thickness: 0.2"/Not Specified</p> <p>Max./Min. Base CU Thickness: N/A</p> <p>Max./Min. Through Hole Size: Not Specified/0.018"</p> <p>Aspect Ratio: 8:1 (Through Hole)</p> <p>Max. Number of Layers: 24</p> <p>Min. Conductor Width: 0.004"</p> <p>Min. Conductor Space: 0.004"</p> <p>Part Mounting: SMT, THM</p> <p>Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant</p> <p>Flex Base Material: N/A</p> <p>Finish System: Fused SnPb, HASL, NiAu</p> <p>Hole Preparation: Permanganate Desmear, Plasma Etchback</p> <p>Alternate Construction: N/A</p> <p>Copper Plating: Electro-deposited Acid Copper</p> <p>Solder Resist: LPI</p> <p>Controlled Impedance: N/A</p> <p>Hole Fill/Via Plug: N/A</p> <p>Flex Usage: N/A</p> <p>Through Hole Metallization: N/A</p>	<p>VQE-99-0130 VQE-00-0961 VQE-07-013268 VQE-07-013459</p>

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Lockheed Martin Systems Integration-Owego</b> 1801 State Route 17C Owego, NY 13827, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 03640  <b>Contact:</b> Melita Nagerl <b>Phone:</b> 607-751-4665 <b>Fax:</b> 607-751-7714 <b>EMail:</b> melita.nagerl@lmco.com
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-99-0130 VQE-00-0961 VQE-07-013459
Panel Size:	24" X 30"	
Max./Min. Board Thickness:	0.2"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.018"	
Aspect Ratio:	8:1 (Through Hole)	
Max. Number of Layers:	16	
Min. Conductor Width:	0.004"	
Min. Conductor Space:	0.004"	
Part Mounting:	SMT, THM	
Rigid Base Material:	GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	Fused SnPb, HASL, NiAu	
Hole Preparation:	Permanganate Desmear, Plasma Etchback	
Alternate Construction:	N/A	
Copper Plating:	Electro-deposited Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Lockheed Martin Systems Integration-Owego</b> 1801 State Route 17C Owego, NY 13827, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 03640  <b>Contact:</b> Melita Nagerl <b>Phone:</b> 607-751-4665 <b>Fax:</b> 607-751-7714 <b>E-Mail:</b> melita.nagerl@lmco.com
---	--	---

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

Specification:	MIL-PRF-31032/3, MIL-PRF-31032/4
Panel Size:	18" X 24"
Max./Min. Board Thickness:	0.11"/Not Specified
Max./Min. Base CU Thickness:	N/A
Max./Min. Through Hole Size:	Not Specified/0.016"
Aspect Ratio:	6:1 (Through Hole)
Max. Number of Layers:	18
Min. Conductor Width:	0.003"
Min. Conductor Space:	0.004"
Part Mounting:	SMT, THM
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant
Flex Base Material:	IPC-4204/4 IC-4204/11 (Adhesiveless) IPC-4204/2 IPC-4204/1 (Acrylic Adhesiveless) IPC-4204/3
Finish System:	Fused SnPb, HASL
Hole Preparation:	Permanganate Desmear, Plasma Etchback
Alternate Construction:	N/A
Copper Plating:	Electro-deposited Acid Copper
Solder Resist:	LPI
Controlled Impedance:	N/A
Hole Fill/Via Plug:	N/A
Flex Usage:	N/A
Through Hole Metallization:	N/A

VQE-00-0684  
VQE-07-013459

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION:  <b>Merix Corp.</b>          355 Turtle Creek Court          San Jose, CA 95125-1316, US</p>	<p>PLANT LOCATION:          Same Address as Manufacturer</p>	<p>CAGE Code: 0MHG5           Contact: Dave Williams          Phone: 408-280-0422          Fax: 408-280-0641          EMail: david.williams@sj.merix.com</p>
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-08-016481
Panel Size:	18" X 24"	VQE-08-016632
Max./Min. Board Thickness:	0.13"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	0.25"/0.008" ((mechanical)) 0.004"/0.008" ((laser drilled))	
Aspect Ratio:	10:1 (Through Hole) 0.8:1 ((blind vias))	
Max. Number of Layers:	20	
Min. Conductor Width:	0.004"	
Min. Conductor Space:	0.004"	
Part Mounting:	THM, SMT, MIX	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, Nickel, Hard Gold, ENIG	
Hole Preparation:	Plasma Etchback, Desmear, Chemical Desmear	
Alternate Construction:	Sequential Lamination, Blind Vias, Buried Vias	
Copper Plating:	Electrodeposited Acid Copper	
Solder Resist:	LPI	
Controlled Impedance:	25-125 ohms +/-10%	
Hole Fill/Via Plug:	Non-conductive Filled Vias	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Micom Corp.</b> 475 Old Highway 8 NW New Brighton, MN 55112, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 34076  <b>Contact:</b> Larry Leonard <b>Phone:</b> 651-604-2639 <b>Fax:</b> 651-636-1352 <b>E-Mail:</b> lleonard@micomcircuits.com
--	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-03-2980
Panel Size:	18" X 24"	VQE-02-002780
Max./Min. Board Thickness:	0.239"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.007"	
Aspect Ratio:	11:1 (Through Hole)	
Max. Number of Layers:	28	
Min. Conductor Width:	0.004"	
Min. Conductor Space:	0.004"	
Part Mounting:	SMT, THM	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	Fuse Following SnPb Plate, HASL	
Hole Preparation:	Permanganate Desmear/Etchback, Plasma Desmear/Etchback	
Alternate Construction:	Blind & Buried Vias	
Copper Plating:	Acid Copper	
Solder Resist:	LPI, Dry Film	
Controlled Impedance:	Characteristic ( $\pm 10\%$ ), Differential ( $\pm 10\%$ )	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	





**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Sanmina-SCI (San Jose)</b> 2050 Bering Drive San Jose, CA 95131, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 3DR67  <b>Contact:</b> Darrell Myers <b>Phone:</b> 408-964-6515 <b>Fax:</b> 408-964-6453 <b>EMail:</b> darrell.myers@sanmina-sci.com
--	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: 0.062"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: 0.25"/0.01" Aspect Ratio: 6:1 (Through Hole) Max. Number of Layers: 8 Min. Conductor Width: 0.003" Min. Conductor Space: 0.003" Part Mounting: SMT, THM Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: N/A Finish System: HASL, ImmAg, ENIG, OSP Hole Preparation: Plasma Desmear Alternate Construction: Foil Lamination Copper Plating: Acid Copper Solder Resist: LPI, Dry Film Controlled Impedance: 50-110 ohms (± 5%) Hole Fill/Via Plug: N/A Flex Usage: N/A Through Hole Metallization: N/A	VQE-06-011137	

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: 0.04"/Not Specified (for Plasma Etchback) 0.25"/Not Specified (for Plasma Desmear) Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: 0.25"/0.008" Aspect Ratio: 15:1 (Through Hole) 1:2 (Microvias, Laser) Max. Number of Layers: 30 Min. Conductor Width: 0.003" Min. Conductor Space: 0.003" Part Mounting: SMT, THM, MIX Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: N/A Finish System: HASL, ENIG, Electrolytic Nickel Gold, Reflowed Solder Hole Preparation: Plasma Desmear//Etchback Alternate Construction: Min. Blind Via: 0.005" Laser, Min. Buried Via: 0.010" Mechanical Drill, Foil Lamination, Sequential Lamination Copper Plating: Electrolytic Acid Copper Solder Resist: LPI, Dry Film Controlled Impedance: 50-110 ohms (± 5%) Hole Fill/Via Plug: Epoxy, Silver Flex Usage: N/A Through Hole Metallization: N/A	VQE-06-011137	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Sovereign Circuits, Inc.</b> 12080 DeBartolo Drive North Jackson, OH 44451, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 0GN71  <b>Contact:</b> Cynthia Savakis <b>Phone:</b> 330-538-3900, x211 <b>Fax:</b> 330-538-3820 <b>EMail:</b> quality@sovereign-circuits.com
---	--	--

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

Specification:	MIL-PRF-31032/3, MIL-PRF-31032/4
Panel Size:	18" X 24"
Max./Min. Board Thickness:	0.25"/Not Specified
Max./Min. Base CU Thickness:	0.005"/Not Specified
Max./Min. Through Hole Size:	0.008"/"
Aspect Ratio:	15:1 (Through Hole)
Max. Number of Layers:	24
Min. Conductor Width:	0.003"
Min. Conductor Space:	0.003"
Part Mounting:	THM, SMT, MIX, Press Fit
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant
Flex Base Material:	IPC-4204/1 (Acrylic Adhesive) IPC-4204/11 (Adhesiveless)
Finish System:	HASL, Fused SnPb, Immersion White tin, Immersion Ag, Ni/Au, OSP, Reflowed Pure Tin
Hole Preparation:	Permanganate Desmear/Etchback, Plasma Desmear/Etchback
Alternate Construction:	Blind Via, Buried Via, Foil Lamination, Cap Lamination
Copper Plating:	Electroless Acid Copper, Electroplated Acid Copper
Solder Resist:	LPI, Dry Film
Controlled Impedance:	Characteristic & Differential, 50, 75, 100 ohms ± 10%
Hole Fill/Via Plug:	Non-Conductive
Flex Usage:	N/A
Through Hole Metallization:	N/A

VQE-03-003214  
 VQE-03-003121  
 VQE-07-012925

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Sovereign Circuits, Inc.</b> 12080 DeBartolo Drive North Jackson, OH 44451, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 0GN71  <b>Contact:</b> Cynthia Savakis <b>Phone:</b> 330-538-3900, x211 <b>Fax:</b> 330-538-3820 <b>EMail:</b> quality@sovereign-circuits.com
---	--	--

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2
Panel Size:	18" X 24"
Max./Min. Board Thickness:	0.25"/Not Specified
Max./Min. Base CU Thickness:	N/A
Max./Min. Through Hole Size:	0.008"/Not Specified
Aspect Ratio:	15:1 (Through Hole)
Max. Number of Layers:	24
Min. Conductor Width:	0.003"
Min. Conductor Space:	0.003"
Part Mounting:	SMT, THM, MIX, Press Fit
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant BI: Aramid Fabric, Nonwoven, Polyimide Resin
Flex Base Material:	N/A
Finish System:	HASL, Fused SnPb, Immersion White Tin, Ni/Au, Ni/Pd/Au, OSP, Reflowed Pure Tin, Immersion Ag
Hole Preparation:	Plasma Desmear/Etchback, Permanganate Desmear/Etchback
Alternate Construction:	Blind Vias, Buried Vias, Foil Lamination, Cap Lamination
Copper Plating:	Electroless Acid Copper, Electroplated Acid Copper
Solder Resist:	LPI, Dry Film
Controlled Impedance:	Range 30-150 ohms ( $\pm 10\%$ ), Microstrip, Embedded Microstrip, Dual Stripline, Characteristic, Differential
Hole Fill/Via Plug:	Conductive, Non-conductive
Flex Usage:	N/A
Through Hole Metallization:	N/A

VQE-07-012925  
 VQE-03-003214  
 VQE-03-003121

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION:  <b>Speedy Circuits</b>                      5331 McFadden Avenue                      Huntington Beach, CA 92649-1204, US</p>	<p>PLANT LOCATION:                      Same Address as Manufacturer</p>	<p>CAGE Code: 66982                       Contact: Jan Lesky                      Phone: 714-766-6243                      Fax: 714-899-7074                      EMail:</p>
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
<p>Specification:                      Panel Size:                      Max./Min. Board Thickness:                      Max./Min. Base CU Thickness:                      Max./Min. Through Hole Size:                      Aspect Ratio:                      Max. Number of Layers:                      Min. Conductor Width:                      Min. Conductor Space:                      Part Mounting:                      Rigid Base Material:                       Flex Base Material:                      Finish System:                       Hole Preparation:                      Alternate Construction:                      Copper Plating:                      Solder Resist:                      Controlled Impedance:                      Hole Fill/Via Plug:                      Flex Usage:                      Through Hole Metallization:</p>	<p>MIL-PRF-31032/1, MIL-PRF-31032/2                      18" X 24"                      0.11"/Not Specified                      N/A                      0.048"/0.02"                      4:1 (Through Hole)                      10                      0.005"                      0.005"                      SMT, THM                      GF: Woven E-Glass, Epoxy Resin, Flame Resistant                      GI: Glass Base, Woven, Polyimide Resin, Heat Resistant                      N/A                      HASL, Electro-deposited Fused SnPb, Electrolytic Hard Gold, Electrolytic Soft Gold, Electrolytic Nickel                      Plasma Desmear, Etchback                      Foil Lamination                      Acid Copper                      LPI                      100/50 ohms +/-10% Characteristic, 100/50 ohms +/-10% Differential                      N/A                      N/A                      N/A</p>	<p>VQE-08-016434</p>

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
<p>Specification:                      Panel Size:                      Max./Min. Board Thickness:                      Max./Min. Base CU Thickness:                      Max./Min. Through Hole Size:                      Aspect Ratio:                      Max. Number of Layers:                      Min. Conductor Width:                      Min. Conductor Space:                      Part Mounting:                      Rigid Base Material:                      Flex Base Material:                      Finish System:                       Hole Preparation:                      Alternate Construction:                      Copper Plating:                      Solder Resist:                      Controlled Impedance:                      Hole Fill/Via Plug:                      Flex Usage:                      Through Hole Metallization:</p>	<p>MIL-PRF-31032/3, MIL-PRF-31032/4                      18" X 24"                      0.11"/Not Specified                      N/A                      0.048"/0.02"                      4:1 (Through Hole)                      10                      0.005"                      0.005"                      SMT, THM                      GI: Glass Base, Woven, Polyimide Resin, Heat Resistant                      Adhesiveless Polyimide                      HASL, Electro-deposited Fused SnPb, Electrolytic Hard Gold, Electrolytic Soft Gold, Electrolytic Nickel                      Plasma Desmear, Etchback                      Foil Lamination                      Electro-deposited Acid Copper                      LPI                      100/50 ohms +/-10% Characteristic, 100/50 ohms +/-10% Differential                      N/A                      Class A (Flex to Install)                      Class B (Continuous)                      N/A</p>	<p>VQE-08-016434</p>

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION:  <b>Speedy Circuits</b>                      5331 McFadden Avenue                      Huntington Beach, CA 92649-1204, US</p>	<p>PLANT LOCATION:                      Same Address as Manufacturer</p>	<p>CAGE Code: 66982                       Contact: Jan Lesky                      Phone: 714-766-6243                      Fax: 714-899-7074                      EMail:</p>
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<p>Specification: MIL-PRF-31032/6                      Panel Size: 12" X 18"                      Max./Min. Board Thickness: 0.036"/Not Specified                      Max./Min. Base CU Thickness: N/A                      Max./Min. Through Hole Size: 0.048"/0.02"                      Aspect Ratio: 2:1 (Through Hole)                      Max. Number of Layers: 2                      Min. Conductor Width: 0.005"                      Min. Conductor Space: 0.005"                      Part Mounting: SMT                      Rigid Base Material: GR: Glass Base, Nonwoven, Polytetrafluoroethylene Resin, Flame Resistant                      GY: Glass Base, Woven, Polytetrafluoroethylene Resin, Flame Resistant, for Microwave Application                       Flex Base Material: N/A                      Finish System: Electro-deposited fused SnPb                      Hole Preparation: N/A                      Alternate Construction: N/A                      Copper Plating: Acid Copper                      Solder Resist: N/A                      Controlled Impedance: N/A                      Hole Fill/Via Plug: N/A                      Flex Usage: N/A                      Through Hole Metallization: N/A</p>	<p>VQE-08-016434</p>

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Strataflex Corp.</b> 11 Dohme Avenue Toronto, Ontario, Canada M4B 1Y7	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 38661  <b>Contact:</b> Peter Pialis <b>Phone:</b> 416-752-2224 <b>Fax:</b> 416-752-6719 <b>E-Mail:</b> ppialis@strataflex.ca
--	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<b>Specification:</b> MIL-PRF-31032/3, MIL-PRF-31032/4  <b>Panel Size:</b> 12" X 18" <b>Max./Min. Board Thickness:</b> 0.035"/Not Specified <b>Max./Min. Base CU Thickness:</b> N/A <b>Max./Min. Through Hole Size:</b> 0.011"/Not Specified <b>Aspect Ratio:</b> 3:1 (Through Hole) <b>Max. Number of Layers:</b> 7 <b>Min. Conductor Width:</b> 0.007" <b>Min. Conductor Space:</b> 0.007" <b>Part Mounting:</b> SM, THM <b>Rigid Base Material:</b> N/A <b>Flex Base Material:</b> Flexible Polyimide Film (IPC-4202/1) FR4 (IPC-4101/21) Flexible Polyimide Clad (IPC-4204/1) Woven E-Glass, Polyimide Resin (IPC-4101/41) Flexible Polyimide Film/Acrylic (IPC-4203/1)  <b>Finish System:</b> HASL <b>Hole Preparation:</b> Plasma Etchback <b>Alternate Construction:</b> N/A <b>Copper Plating:</b> Electrodeposited Acid Copper <b>Solder Resist:</b> N/A <b>Controlled Impedance:</b> N/A <b>Hole Fill/Via Plug:</b> N/A <b>Flex Usage:</b> N/A <b>Through Hole Metallization:</b> N/A	VQE-04-005354 VQE-08-015729



**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Strataflex Corp.</b> 11 Dohme Avenue Toronto, Ontario, Canada M4B 1Y7	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 38661  <b>Contact:</b> Peter Pialis <b>Phone:</b> 416-752-2224 <b>Fax:</b> 416-752-6719 <b>EMail:</b> ppialis@strataflex.ca
--	--	--

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

<b>Specification:</b> MIL-PRF-31032/3, MIL-PRF-31032/4  <b>Panel Size:</b> 12" X 18" <b>Max./Min. Board Thickness:</b> 0.094"/Not Specified <b>Max./Min. Base CU Thickness:</b> N/A <b>Max./Min. Through Hole Size:</b> Not Specified/0.008" <b>Aspect Ratio:</b> 12:1 (Through Hole) <b>Max. Number of Layers:</b> 12 <b>Min. Conductor Width:</b> 0.006" <b>Min. Conductor Space:</b> 0.004" <b>Part Mounting:</b> N/A <b>Rigid Base Material:</b> N/A <b>Flex Base Material:</b> Woven E-Glass, Polyimide Resin (IPC-4101/40) Woven E-Glass, Polyimide Resin (IPC-4101/41) Woven E-Glass, Polyimide Resin (IPC-4101/42) Flexible Polyimide (IPC-4204/11) Flexible Polyimide Film/Acrylic (IC-4203/1)  <b>Finish System:</b> HASL <b>Hole Preparation:</b> Plasma Etchback <b>Alternate Construction:</b> N/A <b>Copper Plating:</b> Electrodeposited Acid Copper <b>Solder Resist:</b> TA140 PSR-4000 HG <b>Controlled Impedance:</b> N/A <b>Hole Fill/Via Plug:</b> N/A <b>Flex Usage:</b> N/A <b>Through Hole Metallization:</b> N/A	VQE-04-005354 VQE-08-015729
---	--------------------------------

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Titan PCB East, Inc.</b> 2 Industrial Way Amesbury, MA 01913, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	CAGE Code: 0BX48  Contact: Lance Arlander Phone: 978-388-5740 Fax: 978-388-5538 EMail: larlander@titaneast.com
---	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-05-7439
Panel Size:	18" X 24"	VQE-04-6518
Max./Min. Board Thickness:	0.012"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.012"	
Aspect Ratio:	10:1 (Through Hole)	
Max. Number of Layers:	14	
Min. Conductor Width:	0.004"	
Min. Conductor Space:	0.004"	
Part Mounting:	SMT, THM, MIX	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, ENIG, Electroplated Gold	
Hole Preparation:	Plasma Etchback	
Alternate Construction:	N/A	
Copper Plating:	Electrolytic Acid Copper	
Solder Resist:	LPI, Dry Film	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/3, MIL-PRF-31032/4	VQE-05-7439
Panel Size:	18" X 24"	VQE-04-6518
Max./Min. Board Thickness:	0.012"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.012"	
Aspect Ratio:	10:1 (Through Hole)	
Max. Number of Layers:	14	
Min. Conductor Width:	0.004"	
Min. Conductor Space:	0.004"	
Part Mounting:	SMT, THM, MIX	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, Immersion Ni/Au, ENIG, Electroplated Gold	
Hole Preparation:	Plasma Etchback	
Alternate Construction:	N/A	
Copper Plating:	Electrodeposited Acid Copper	
Solder Resist:	LPI, Dry Film	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I  
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION: <b>Titan PCB East, Inc.</b> 2 Industrial Way Amesbury, MA 01913, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 0BX48  Contact: Lance Arlander Phone: 978-388-5740 Fax: 978-388-5538 EMail: larlander@titaneast.com</p>
--	---	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<p>Specification: MIL-PRF-31032/3, MIL-PRF-31032/3                      Panel Size: 12" X 18", 18" X 24"                      Max./Min. Board Thickness: 0.12"/Not Specified                      Max./Min. Base CU Thickness: N/A                      Max./Min. Through Hole Size: N/A                      Aspect Ratio: N/A                      Max. Number of Layers: N/A                      Min. Conductor Width: N/A                      Min. Conductor Space: N/A                      Part Mounting: N/A                      Rigid Base Material: N/A                      Flex Base Material: N/A                      Finish System: N/A                      Hole Preparation: N/A                      Alternate Construction: N/A                      Copper Plating: N/A                      Solder Resist: N/A                      Controlled Impedance: N/A                      Hole Fill/Via Plug: N/A                      Flex Usage: N/A                      Through Hole Metallization: N/A</p>	<p>VQE-01-0024</p>

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>TTM Technologies (Redmond)</b> 17550 NE 67th Court Redmond, WA 98052-4939, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 3EDZ0  <b>Contact:</b> Margaret Schlosser <b>Phone:</b> 425-883-7575 <b>Fax:</b> <b>EMail:</b> mschlosser@ttmtech.com
--	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-06-011027
Panel Size:	21.5" X 24.5"	VQE-06-011656
Max./Min. Board Thickness:	0.063"/Not Specified (nominal)	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	Not Specified/0.01"	
Aspect Ratio:	6.3:1 (Through Hole)	
Max. Number of Layers:	12	
Min. Conductor Width:	0.005"	
Min. Conductor Space:	0.003"	
Part Mounting:	SMT, THM	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	ENIG	
Hole Preparation:	Desmear/Etchback	
Alternate Construction:	N/A	
Copper Plating:	Acid Copper	
Solder Resist:	N/A	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>TTM Technologies (Santa Ana)</b> 2630 South Harbor Boulevard Santa Ana, CA 92704, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 1WQ42  <b>Contact:</b> Terry Lichte <b>Phone:</b> 714-241-0303, x3127 <b>Fax:</b> 714-241-0708 <b>EMail:</b> tlichte@ttmtech.comca
---	--	---

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-05-8644
		VQE-06-011211
Panel Size:	21" X 28"	
Max./Min. Board Thickness:	0.2"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	0.044"/0.013"	
Aspect Ratio:	14:1 (Through Hole)	
Max. Number of Layers:	24	
Min. Conductor Width:	0.003"	
Min. Conductor Space:	0.003"	
Part Mounting:	SMT, THM	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, ENIG, OSP, ImmAg, Fused SnPb	
Hole Preparation:	Desmear Etchback	
Alternate Construction:	Min. Blind Via: 0.005" Laser, Min. Buried Via: 0.0135" Mechanical Drill, Sequential Lamination, Aspect Ratio Microvias: 1:1	
Copper Plating:	Acid Copper	
Solder Resist:	LPI, Dry Film	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-05-8644
Panel Size:	18" X 24"	VQE-06-011211
Max./Min. Board Thickness:	0.2"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	0.044"/0.013"	
Aspect Ratio:	14:1 (Through Hole)	
Max. Number of Layers:	24	
Min. Conductor Width:	0.003"	
Min. Conductor Space:	0.003"	
Part Mounting:	SMT, THM	
Rigid Base Material:	GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, ENIG, OSP, ImmAg, Fused SnPb	
Hole Preparation:	Desmear Etchback	
Alternate Construction:	Min. Blind Via: 0.005" Laser, Min. Buried Via: 0.0135" Mechanical Drill, Sequential Lamination, Aspect Ratio Microvias: 1:1	
Copper Plating:	Acid Copper	
Solder Resist:	LPI, Dry Film	
Controlled Impedance:	N/A	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION:  <b>TTM Technologies (Santa Clara)</b>          400 Matthew Street          Santa Clara, CA 95050, US</p>	<p>PLANT LOCATION:          Same Address as Manufacturer</p>	<p>CAGE Code: 65916           Contact: Nellie Gutierrez          Phone: 408-486-3184          Fax: 408-727-1003          EMail: nellie.gutierrez@ttmtech.com</p>
--	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>		<b>QUALIFICATION LETTERS:</b>
Specification:	MIL-PRF-31032/1, MIL-PRF-31032/2	VQE-03-3888
Panel Size:	18" X 24"	VQE-04-5823
Max./Min. Board Thickness:	0.12"/Not Specified	
Max./Min. Base CU Thickness:	N/A	
Max./Min. Through Hole Size:	0.191"/0.012"	
Aspect Ratio:	9:1 (Through Hole)	
Max. Number of Layers:	20	
Min. Conductor Width:	0.004"	
Min. Conductor Space:	0.004"	
Part Mounting:	SMT, THM, MIX	
Rigid Base Material:	GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant	
Flex Base Material:	N/A	
Finish System:	HASL, Immersion Ni/Au	
Hole Preparation:	Plasma Desmear/Etchback	
Alternate Construction:	Blind Vias	
Copper Plating:	Electrolytic Acid Copper	
Solder Resist:	LPI, Screen Printed	
Controlled Impedance:	Characteristic, Differential +/-10%	
Hole Fill/Via Plug:	N/A	
Flex Usage:	N/A	
Through Hole Metallization:	N/A	



**SECTION I  
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<p>MANUFACTURER INFORMATION: <b>TTM Technologies (Santa Clara)</b> 400 Matthew Street Santa Clara, CA 95050, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 65916  Contact: Nellie Guitierrez Phone: 408-486-3184 Fax: 408-727-1003 EMail: nellie.guitierrez@ttmtech.com</p>
---	---	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
<p>Specification: MIL-PRF-31032/Custom Panel Size: 18" X 24" Max./Min. Board Thickness: 0.62"/0.006" Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: 0.076"/0.015" ((drilled)) 0.02"/0.015" ((drilled)) Aspect Ratio: 4:1 (Through Hole) Max. Number of Layers: 6 Min. Conductor Width: 0.007" Min. Conductor Space: 0.008" Part Mounting: MIX, SMT, THM Rigid Base Material: IPC-4103/10 Construction GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: N/A Finish System: ENIG Hole Preparation: Chemical Desmear Alternate Construction: Blind vias Copper Plating: Electroless, Electrolytic Acid Copper Solder Resist: LPI, SMOBC Controlled Impedance: 50 ohms +/-10% Hole Fill/Via Plug: N/A Flex Usage: N/A Through Hole Metallization: N/A</p>	<p>VQE-07-13211</p>

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>TTM Technologies (Stafford)</b> 4 Old Monson Road P.O. Box 145, Stafford, TX 77497, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 5L706  <b>Contact:</b> Michelle Herbert <b>Phone:</b> 860-684-5881 <b>Fax:</b> 860-684-7425 <b>EMail:</b> michele.hebert@tycoelectronics.com
---	--	---

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

Specification: Panel Size: Max./Min. Board Thickness: Max./Min. Base CU Thickness: Max./Min. Through Hole Size: Aspect Ratio: Max. Number of Layers: Min. Conductor Width: Min. Conductor Space: Part Mounting: Rigid Base Material: Flex Base Material: Finish System: Hole Preparation: Alternate Construction: Copper Plating: Solder Resist: Controlled Impedance: Hole Fill/Via Plug: Flex Usage: Through Hole Metallization:	MIL-PRF-31032/3, MIL-PRF-31032/4 30" X 54" 0.3"/0.003" N/A 0.221"/0.009" (drilled) 9:1 (Through Hole) 28 0.004" 0.004" SMT, THM, MIX GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant IPC-4204/1 (Acrylic Adhesive) IPC-4204/11 (Adhesiveless) HASL, SMOBC, Reflowed Solder, Electroless Nickel/Immersion Gold, Electrolytic Hard & Soft Gold, Electrolytic Nickel, Bright Tin, Immersion Tin Plasma Etchback Buried Via Aspect Ratio: 5:1, Copper Invar Copper, Blind and Buried Vias, Micro Vias, Buried Resistors, Multiple Laminations Acid Copper LPI, Dy Film, Wet Mask, Hole Fill, Hole Plug Range 30-150 (±10%), Microstrip, Embedded Microstrip, Dual Stripline, Characteristic, Differential N/A Class A (Flex to Install) Class B (Continuous) N/A
--	---

VQE-03-3349

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>TTM Technologies (Stafford)</b> 4 Old Monson Road P.O. Box 145, Stafford, TX 77497, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 5L706  <b>Contact:</b> Michelle Herbert <b>Phone:</b> 860-684-5881 <b>Fax:</b> 860-684-7425 <b>E-Mail:</b> michele.hebert@tycoelectronics.com
---	--	--

**CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION** **QUALIFICATION LETTERS:**

<b>Specification:</b> MIL-PRF-31032/1, MIL-PRF-31032/2 <b>Panel Size:</b> 30" X 54" <b>Max./Min. Board Thickness:</b> 1.088"/Not Specified <b>Max./Min. Base CU Thickness:</b> N/A <b>Max./Min. Through Hole Size:</b> 0.095"/0.221" (drilled) <b>Aspect Ratio:</b> 10:1 (Through Hole) <b>Max. Number of Layers:</b> 68 <b>Min. Conductor Width:</b> 0.004" <b>Min. Conductor Space:</b> 0.004" <b>Part Mounting:</b> SMT, THM, MIX, Press Fit <b>Rigid Base Material:</b> GM: Glass Base, Woven, Triazine and/or Bismaleimide Modified Epoxy Resin, Flame Resistant AF: Aramid Fabric, Woven, Majority Polyfunctional Epoxy Resin GF: Woven E-Glass, Epoxy Resin, Flame Resistant SC: Glass Base, Woven S-2, Fiber, Majority Cyanate Ester, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant BF: Aramid Fabric, Nonwoven, Epoxy Resin BI: Aramid Fabric, Nonwoven, Polyimide Resin  <b>Flex Base Material:</b> N/A <b>Finish System:</b> HASL, SMOBC, Reflowed Solder, Electroless Nickel/Immersion Gold, Electrolytic Hard & Soft Gold, Electrolytic Nickel, Bright Tin, Immersion Tin <b>Hole Preparation:</b> Plasma Etchback <b>Alternate Construction:</b> Buried Via Aspect Ratio: 1:1, Copper Invar Copper, Blind and Buried Vias, Micro Vias, Buried Resistors, Multiple Laminations <b>Copper Plating:</b> Acid Copper <b>Solder Resist:</b> LPI, Dry Film, Wet Mask, Hole Fill, Hole Plug <b>Controlled Impedance:</b> Range 30-150 ( $\pm 10\%$ ), Microstrip, Embedded Microstrip, Dual Stripline, Characteristic, Differential  <b>Hole Fill/Via Plug:</b> N/A <b>Flex Usage:</b> N/A <b>Through Hole Metallization:</b> N/A	VQE-03-3348
---	-------------

**SECTION I**  
**LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

<b>MANUFACTURER INFORMATION:</b> <b>Unicircuit, Inc.</b> 8192 Southpark Lane Littleton, CO 80120, US	<b>PLANT LOCATION:</b> Same Address as Manufacturer	<b>CAGE Code:</b> 66311  <b>Contact:</b> Bob Lageman <b>Phone:</b> 303-730-0505, x110 <b>Fax:</b> <b>EMail:</b> blageman@unicircuit.com
---	--	--

<b>CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION</b>	<b>QUALIFICATION LETTERS:</b>
Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 12" X 18" Max./Min. Board Thickness: 0.12"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: 0.02"/0.129" (Drilled Through Hole) Aspect Ratio: 6:1 (Through Hole) Max. Number of Layers: 16 Min. Conductor Width: 0.005" Min. Conductor Space: 0.005" Part Mounting: SMT, THM Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: N/A Finish System: HASL, Reflowed Tin Lead Hole Preparation: Plasma Etchback Alternate Construction: Sequential Lamination, Blind Via, Bured Via, Laser-drilled Microvias, Foil Lamination  Copper Plating: Electrodeposited Acid Copper Solder Resist: LPI Controlled Impedance: 55 ohms characteristic, 100 ohms differential +/-10% Hole Fill/Via Plug: N/A Flex Usage: N/A Through Hole Metallization: N/A Laser Via Hole Size .006 +/- .001	VQE-07-13789

**SECTION II**  
**LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION**

**MIL-PRF-31032/1**

**Accurate Circuit Engineering**

3019 S. Kilson Drive, Santa Ana, CA 92707, US

**American Standard Circuits**

RF Division, 475 Industrial Drive, West Chicago, IL 60185, US

**Amphenol TCS**

91 Northeastern Boulevard, Nashua, NH 03062, US

**Calumet Electronics Corp.**

25830 Depot Street, Calumet, MI 49913-1985, US

**Cirexx International**

791 Nuttman Street, Santa Clara, CA 95054,

**Colonial Circuits, Inc.**

1026 Warrenton Road, Fredericksburg, VA 22406-6200, US

**Coretec Cleveland, Inc.**

7 Ascot Parkway, Cuyahoga Falls, OH 44223, US

**Coretec Denver, Inc.**

10570 Bradford Road, Littleton, CO 80127, US

**Coretec, Inc.**

8150 Sheppard Avenue East, Scarborough, Ontario, Canada M1B 5K2

**Cosmotronic, Inc.**

16721 Noyes Avenue, Irvine, CA 92606, US

**Diversified Systems**

3939 West 56th Street, Indianapolis, IN 46254, US

**Dynaco Corp.**

1000 South Priest Drive, Tempe, AZ 85281-5238, US

**Dynamic & Proto Circuits, Inc.**

869 Barton Street, Stoney Creek, Ontario, Canada L8E 5G6

**Dynamic Details, Inc.**

1200 Severn Way, Dulles, VA 20166-8904, US

**Electro Plate Circuitry**

1430 Century Drive, Carrollton, TX 75006, US

**Electrotek Corp.**

7745 S. 10th Street, Oak Creek, WI 53154, US

**Endicott Interconnect Technologies, Inc.**

1701 North Street, P.O. Box 658, Endicott, NY 13760, US

**Firan Technology Group**

250 Finchdene Square, Scarborough, Ontario, Canada M1X 1A5

**Global Innovation Corp.**

901 Hensley Drive, Wylie, TX 75098, US

**Hans Brockstedt GmbH**

Leiterplattenschnelldienst, Clara-Immerwahr-Str. 7, 24145, Kiel, Germany

**Hughes Circuits**

540 S. Pacific Street, San Marcos, CA 92078-4056, US

**Lockheed Martin Systems Integration-Owego**

1801 State Route 17C, Owego, NY 13827, US

**Merix Corp.**

355 Turtle Creek Court, San Jose, CA 95125-1316, US

**Micom Corp.**

475 Old Highway 8 NW, New Brighton, MN 55112, US

**Philway Products, Inc.**

701 Virginia Avenue, Ashland, OH 44806, US

**Sanmina-SCI (San Jose)**

2050 Bering Drive, San Jose, CA 95131, US

**Sovereign Circuits, Inc.**

12080 DeBartolo Drive, North Jackson, OH 44451, US

**SECTION II**  
**LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION**

**MIL-PRF-31032/1**

**Speedy Circuits**

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

**Titan PCB East, Inc.**

2 Industrial Way, Amesbury, MA 01913, US

**TTM Technologies (Redmond)**

17550 NE 67th Court, Redmond, WA 98052-4939, US

**TTM Technologies (Santa Ana)**

2630 South Harbor Boulevard, Santa Ana, CA 92704, US

**TTM Technologies (Santa Clara)**

400 Matthew Street, Santa Clara, CA 95050, US

**TTM Technologies (Stafford)**

4 Old Monson Road, P.O. Box 145, Stafford, TX 77497, US

**Unicircuit, Inc.**

8192 Southpark Lane, Littleton, CO 80120, US

**SECTION II**  
**LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION**

**MIL-PRF-31032/2**

**Accurate Circuit Engineering**

3019 S. Kilson Drive, Santa Ana, CA 92707, US

**American Standard Circuits**

RF Division, 475 Industrial Drive, West Chicago, IL 60185, US

**Amphenol TCS**

91 Northeastern Boulevard, Nashua, NH 03062, US

**Calumet Electronics Corp.**

25830 Depot Street, Calumet, MI 49913-1985, US

**Cirexx International**

791 Nuttman Street, Santa Clara, CA 95054,

**Colonial Circuits, Inc.**

1026 Warrenton Road, Fredericksburg, VA 22406-6200, US

**Coretec Cleveland, Inc.**

7 Ascot Parkway, Cuyahoga Falls, OH 44223, US

**Coretec Denver, Inc.**

10570 Bradford Road, Littleton, CO 80127, US

**Coretec, Inc.**

8150 Sheppard Avenue East, Scarborough, Ontario, Canada M1B 5K2

**Cosmotronic, Inc.**

16721 Noyes Avenue, Irvine, CA 92606, US

**Diversified Systems**

3939 West 56th Street, Indianapolis, IN 46254, US

**Dynaco Corp.**

1000 South Priest Drive, Tempe, AZ 85281-5238, US

**Dynamic & Proto Circuits, Inc.**

869 Barton Street, Stoney Creek, Ontario, Canada L8E 5G6

**Dynamic Details, Inc.**

1200 Severn Way, Dulles, VA 20166-8904, US

**Electro Plate Circuitry**

1430 Century Drive, Carrollton, TX 75006, US

**Electrotek Corp.**

7745 S. 10th Street, Oak Creek, WI 53154, US

**Endicott Interconnect Technologies, Inc.**

1701 North Street, P.O. Box 658, Endicott, NY 13760, US

**Firan Technology Group**

250 Finchdene Square, Scarborough, Ontario, Canada M1X 1A5

**Global Innovation Corp.**

901 Hensley Drive, Wylie, TX 75098, US

**Hans Brockstedt GmbH**

Leiterplattenschnelldienst, Clara-Immerwahr-Str. 7, 24145, Kiel, Germany

**Hughes Circuits**

540 S. Pacific Street, San Marcos, CA 92078-4056, US

**Lockheed Martin Systems Integration-Owego**

1801 State Route 17C, Owego, NY 13827, US

**Merix Corp.**

355 Turtle Creek Court, San Jose, CA 95125-1316, US

**Micom Corp.**

475 Old Highway 8 NW, New Brighton, MN 55112, US

**Sanmina-SCI (San Jose)**

2050 Bering Drive, San Jose, CA 95131, US

**Sovereign Circuits, Inc.**

12080 DeBartolo Drive, North Jackson, OH 44451, US

**Speedy Circuits**

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

**SECTION II**  
**LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION**

**MIL-PRF-31032/2**

**Titan PCB East, Inc.**

2 Industrial Way, Amesbury, MA 01913, US

**TTM Technologies (Redmond)**

17550 NE 67th Court, Redmond, WA 98052-4939, US

**TTM Technologies (Santa Ana)**

2630 South Harbor Boulevard, Santa Ana, CA 92704, US

**TTM Technologies (Santa Clara)**

400 Matthew Street, Santa Clara, CA 95050, US

**TTM Technologies (Stafford)**

4 Old Monson Road, P.O. Box 145, Stafford, TX 77497, US

**Unicircuit, Inc.**

8192 Southpark Lane, Littleton, CO 80120, US

**SECTION II**  
**LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION**

**MIL-PRF-31032/3**

**Calumet Electronics Corp.**

25830 Depot Street, Calumet, MI 49913-1985, US

**Cirexx International**

791 Nuttman Street, Santa Clara, CA 95054,

**Coretec Cleveland, Inc.**

7 Ascot Parkway, Cuyahoga Falls, OH 44223, US

**Cosmotronic, Inc.**

16721 Noyes Avenue, Irvine, CA 92606, US

**Dynaco Corp.**

1000 South Priest Drive, Tempe, AZ 85281-5238, US

**Hamby Corporation**

27704 Avenue Scott, Valencia, CA 91355, US

**Hans Brockstedt GmbH**

Leiterplattenschnelldienst, Clara-Immerwahr-Str. 7, 24145, Kiel, Germany

**Lockheed Martin Systems Integration-Owego**

1801 State Route 17C, Owego, NY 13827, US

**Printed Circuits, Inc.**

1200 West 96th Street, Bloomington, MN 55431, US

**Sovereign Circuits, Inc.**

12080 DeBartolo Drive, North Jackson, OH 44451, US

**Speedy Circuits**

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

**Strataflex Corp.**

11 Dohme Avenue, Toronto, Ontario, Canada M4B 1Y7

**Titan PCB East, Inc.**

2 Industrial Way, Amesbury, MA 01913, US

**TTM Technologies (Santa Clara)**

400 Matthew Street, Santa Clara, CA 95050, US

**TTM Technologies (Stafford)**

4 Old Monson Road, P.O. Box 145, Stafford, TX 77497, US

**SECTION II**  
**LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION**

**MIL-PRF-31032/4**

**Calumet Electronics Corp.**

25830 Depot Street, Calumet, MI 49913-1985, US

**Cirexx International**

791 Nuttman Street, Santa Clara, CA 95054,

**Colonial Circuits, Inc.**

1026 Warrenton Road, Fredericksburg, VA 22406-6200, US

**Coretec Cleveland, Inc.**

7 Ascot Parkway, Cuyahoga Falls, OH 44223, US

**Cosmotronic, Inc.**

16721 Noyes Avenue, Irvine, CA 92606, US

**Dynaco Corp.**

1000 South Priest Drive, Tempe, AZ 85281-5238, US

**Hamby Corporation**

27704 Avenue Scott, Valencia, CA 91355, US

**Hans Brockstedt GmbH**

Leiterplattenschnelldienst, Clara-Immerwahr-Str. 7, 24145, Kiel, Germany

**Lockheed Martin Systems Integration-Owego**

1801 State Route 17C, Owego, NY 13827, US

**Printed Circuits, Inc.**

1200 West 96th Street, Bloomington, MN 55431, US

**Sovereign Circuits, Inc.**

12080 DeBartolo Drive, North Jackson, OH 44451, US

**Speedy Circuits**

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

**Strataflex Corp.**

11 Dohme Avenue, Toronto, Ontario, Canada M4B 1Y7

**Titan PCB East, Inc.**

2 Industrial Way, Amesbury, MA 01913, US

**TTM Technologies (Santa Clara)**

400 Matthew Street, Santa Clara, CA 95050, US

**TTM Technologies (Stafford)**

4 Old Monson Road, P.O. Box 145, Stafford, TX 77497, US

**SECTION II**  
**LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION**

**MIL-PRF-31032/6**

**Speedy Circuits**

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

**SECTION II**  
**LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION**

**MIL-PRF-31032/Custom**

**Colonial Circuits, Inc.**

1026 Warrenton Road, Fredericksburg, VA 22406-6200, US

**Cosmotronic, Inc.**

16721 Noyes Avenue, Irvine, CA 92606, US

**Endicott Interconnect Technologies, Inc.**

1701 North Street, P.O. Box 658, Endicott, NY 13760, US

**TTM Technologies (Santa Clara)**

400 Matthew Street, Santa Clara, CA 95050, US

**SECTION III**  
**ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS**

<p>MANUFACTURER INFORMATION: <b>Accurate Circuit Engineering</b> 3019 S. Kilson Drive Santa Ana, CA 92707, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 0MNN9  Contact: James Hofer Phone: 714-546-162 Fax: 714-433-7418 EMail: James@ace-pcb.com</p>
<p>MANUFACTURER INFORMATION: <b>American Standard Circuits</b> RF Division, 475 Industrial Drive West Chicago, IL 60185, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 4AA34  Contact: Lori Ryan Phone: 603-639-5438 Fax: EMail: lori@asc-i.com</p>
<p>MANUFACTURER INFORMATION: <b>Amphenol TCS</b> 91 Northeastern Boulevard Nashua, NH 03062, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 3T000  Contact: Denise Chevalier Phone: 603-879-3268 Fax: 603-879-2818 EMail: denise.chevalier@amphenol-tcs.com</p>
<p>MANUFACTURER INFORMATION: <b>Calumet Electronics Corp.</b> 25830 Depot Street Calumet, MI 49913-1985, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 65337  Contact: Robert Hall Phone: 906-337-1305 Fax: 906-337-5359 EMail: rhall@cec-up.com</p>
<p>MANUFACTURER INFORMATION: <b>Cirexx International</b> 791 Nuttman Street Santa Clara, CA 95054,</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 4MEG7  Contact: Don Angulo Phone: 408-988-3980 Fax: 408-988-4534 EMail: dangulo@cirexxintl.com</p>
<p>MANUFACTURER INFORMATION: <b>Colonial Circuits, Inc.</b> 1026 Warrenton Road Fredericksburg, VA 22406-6200, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 6T499  Contact: Mike Hill Phone: 540-753-5511, x125 Fax: 540-752-2109 EMail: quality@colonialcircuits.com</p>
<p>MANUFACTURER INFORMATION: <b>Coretec Cleveland, Inc.</b> 7 Ascot Parkway Cuyahoga Falls, OH 44223, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 7Z463  Contact: Mark Kasting Phone: 330-572-3400 Fax: 330-572-3434 EMail: mark_kasting/coretec@coretec-inc.com</p>

**SECTION III**  
**ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS**

<p>MANUFACTURER INFORMATION: <b>Coretec Denver, Inc.</b> 10570 Bradford Road Littleton, CO 80127, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 75815  Contact: Douglas N. Berry Phone: 303-904-6119 Fax: 303-933-2934 EMail: dberry@coretec-denver.com</p>
<p>MANUFACTURER INFORMATION: <b>Coretec, Inc.</b> 8150 Sheppard Avenue East Scarborough, Ontario, Canada M1B 5K2</p>	<p>PLANT LOCATIONS: 1. Same Address as Manufacturer 2. Coretec, Inc., CAGE Code: 3AF82, 2020 Ellesmere Road, Scarborough, Ontario, Canada M1H 2Z8</p>	<p>CAGE Code: 3AF82  Contact: Noor Al-Shaikh Phone: 416-208-2100 Fax: 416-439-1582 EMail: alshaikh@coretec-inc.com</p>
<p>MANUFACTURER INFORMATION: <b>Cosmotronic, Inc.</b> 16721 Noyes Avenue Irvine, CA 92606, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 63695  Contact: Alan Exley Phone: 949-660-0740 Fax: 949-553-8371 EMail: alan_exley@cosmotronic.com</p>
<p>MANUFACTURER INFORMATION: <b>Diversified Systems</b> 3939 West 56th Street Indianapolis, IN 46254, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 5S706  Contact: Linda Bell Phone: 317-299-9547, x238 Fax: 317-298-2061 EMail: linda.bell@divsys.com</p>
<p>MANUFACTURER INFORMATION: <b>Dynaco Corp.</b> 1000 South Priest Drive Tempe, AZ 85281-5238, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 61642  Contact: Ted Edwards Phone: 480-736-3728 Fax: 480-921-9830 EMail: tedwards@dynacocorp.com</p>
<p>MANUFACTURER INFORMATION: <b>Dynamic &amp; Proto Circuits, Inc.</b> 869 Barton Street Stoney Creek, Ontario, Canada L8E 5G6</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 38898  Contact: Stephen Hazell Phone: 905-643-9900 Fax: 905-643-9911 EMail: stephenhazell@dapc.com</p>
<p>MANUFACTURER INFORMATION: <b>Dynamic Details, Inc.</b> 1200 Severn Way Dulles, VA 20166-8904, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 0K703  Contact: Tony Trnka Phone: 703-652-2266 Fax: 703-652-2271 EMail: atrnka@va.ddiglobal.com</p>
<p>MANUFACTURER INFORMATION: <b>Electro Plate Circuitry</b> 1430 Century Drive Carrollton, TX 75006, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 79616  Contact: James McNeal Phone: 972-466-0818 Fax: 972-466-9078 EMail: jimm@eplate.com</p>

**SECTION III**  
**ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS**

<p>MANUFACTURER INFORMATION: <b>Electrotek Corp.</b> 7745 S. 10th Street Oak Creek, WI 53154, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 66030  Contact: Tom Tikusis Phone: 414-762-1390 Fax: 414-762-1510 EMail: sales@boards4u.com</p>
<p>MANUFACTURER INFORMATION: <b>Endicott Interconnect Technologies, Inc.</b> 1701 North Street P.O. Box 658, Endicott, NY 13760, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 3ECL3  Contact: Jose Rios Phone: 607-755-5896 Fax: 607-755-4649 EMail: JoseA.Rios@eitny.com</p>
<p>MANUFACTURER INFORMATION: <b>Firan Technology Group</b> 250 Finchdene Square Scarborough, Ontario, Canada M1X 1A5</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: L2665  Contact: Bryan Clark Phone: 416-299-4000 Fax: 416-292-4308 EMail: byanclark@firantechnology.com</p>
<p>MANUFACTURER INFORMATION: <b>Global Innovation Corp.</b> 901 Hensley Drive Wylie, TX 75098, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 04RV5  Contact: Bob Noland Phone: 214-291-1427 Fax: EMail: bnoland@globalinnovationcorp.com</p>
<p>MANUFACTURER INFORMATION: <b>Hamby Corporation</b> 27704 Avenue Scott Valencia, CA 91355, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 07248  Contact: Sue Sharp Phone: 661-257-1924 Fax: 661-257-1213 EMail: suesharp@hambycorp.com</p>
<p>MANUFACTURER INFORMATION: <b>Hans Brockstedt GmbH</b> Leiterplattenschnelldienst, Clara-Immerwahr- Str. 7 24145, Kiel, Germany</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: C4831  Contact: Hilmar Klammer Phone: 0049-431-71966-0, -30 Fax: 0049-431-71966-29 EMail: klammer@brockstedt.de</p>
<p>MANUFACTURER INFORMATION: <b>Hughes Circuits</b> 540 S. Pacific Street San Marcos, CA 92078-4056, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 1KXU6  Contact: Joe Hughes Phone: 760-744-0300 Fax: 760-744-6388 EMail: joe@hughescircuits.com</p>
<p>MANUFACTURER INFORMATION: <b>Lockheed Martin Systems Integration-Owego</b> 1801 State Route 17C Owego, NY 13827, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 03640  Contact: Melita Nagerl Phone: 607-751-4665 Fax: 607-751-7714 EMail: melita.nagerl@lmco.com</p>

**SECTION III**  
**ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS**

<p>MANUFACTURER INFORMATION: <b>Merix Corp.</b> 355 Turtle Creek Court San Jose, CA 95125-1316, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 0MHG5  Contact: Dave Williams Phone: 408-280-0422 Fax: 408-280-0641 EMail: david.williams@sj.merix.com</p>
<p>MANUFACTURER INFORMATION: <b>Micom Corp.</b> 475 Old Highway 8 NW New Brighton, MN 55112, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 34076  Contact: Larry Leonard Phone: 651-604-2639 Fax: 651-636-1352 EMail: lleonard@micomcircuits.com</p>
<p>MANUFACTURER INFORMATION: <b>Philway Products, Inc.</b> 701 Virginia Avenue Ashland, OH 44806, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 21971  Contact: Tom School Phone: 419-281-7777 Fax: 419-289-3447 EMail: quality@philway.com</p>
<p>MANUFACTURER INFORMATION: <b>Printed Circuits, Inc.</b> 1200 West 96th Street Bloomington, MN 55431, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 65114  Contact: Jim Smith Phone: 612-888-7900 Fax: 612-888-2719 EMail: jsmith@printedcircuits.com</p>
<p>MANUFACTURER INFORMATION: <b>Sanmina-SCI (San Jose)</b> 2050 Bering Drive San Jose, CA 95131, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 3DR67  Contact: Darrell Myers Phone: 408-964-6515 Fax: 408-964-6453 EMail: darrell.myers@sanmina-sci.com</p>
<p>MANUFACTURER INFORMATION: <b>Sovereign Circuits, Inc.</b> 12080 DeBartolo Drive North Jackson, OH 44451, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 0GN71  Contact: Cynthia Savakis Phone: 330-538-3900, x211 Fax: 330-538-3820 EMail: quality@sovereign-circuits.com</p>
<p>MANUFACTURER INFORMATION: <b>Speedy Circuits</b> 5331 McFadden Avenue Huntington Beach, CA 92649-1204, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 66982  Contact: Jan Lesky Phone: 714-766-6243 Fax: 714-899-7074 EMail:</p>
<p>MANUFACTURER INFORMATION: <b>Strataflex Corp.</b> 11 Dohme Avenue Toronto, Ontario, Canada M4B 1Y7</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 38661  Contact: Peter Pialis Phone: 416-752-2224 Fax: 416-752-6719 EMail: ppialis@strataflex.ca</p>

**SECTION III**  
**ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS**

<p>MANUFACTURER INFORMATION: <b>Titan PCB East, Inc.</b> 2 Industrial Way Amesbury, MA 01913, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 0BX48  Contact: Lance Arlander Phone: 978-388-5740 Fax: 978-388-5538 EMail: larlander@titaneast.com</p>
<p>MANUFACTURER INFORMATION: <b>TTM Technologies (Redmond)</b> 17550 NE 67th Court Redmond, WA 98052-4939, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 3EDZ0  Contact: Margaret Schlosser Phone: 425-883-7575 Fax: EMail: mschlosser@ttmtech.com</p>
<p>MANUFACTURER INFORMATION: <b>TTM Technologies (Santa Ana)</b> 2630 South Harbor Boulevard Santa Ana, CA 92704, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 1WQ42  Contact: Terry Lichte Phone: 714-241-0303, x3127 Fax: 714-241-0708 EMail: tlichte@ttmtech.comca</p>
<p>MANUFACTURER INFORMATION: <b>TTM Technologies (Santa Clara)</b> 400 Matthew Street Santa Clara, CA 95050, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 65916  Contact: Nellie Guitierrez Phone: 408-486-3184 Fax: 408-727-1003 EMail: nellie.guitierrez@ttmtech.com</p>
<p>MANUFACTURER INFORMATION: <b>TTM Technologies (Stafford)</b> 4 Old Monson Road P.O. Box 145, Stafford, TX 77497, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 5L706  Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 EMail: michele.hebert@tycoelectronics.com</p>
<p>MANUFACTURER INFORMATION: <b>Unicircuit, Inc.</b> 8192 Southpark Lane Littleton, CO 80120, US</p>	<p>PLANT LOCATION: Same Address as Manufacturer</p>	<p>CAGE Code: 66311  Contact: Bob Lageman Phone: 303-730-0505, x110 Fax: EMail: blageman@unicircuit.com</p>