

DLA Land and Maritime - VQ
Supplemental Information Sheet for Electronic QML-31032

Date: 1/25/2011

Specification Details:

Specification: MIL-PRF-31032
Title: Printed Circuit Board/Printed Wiring Board
Federal Supply Class (FSC): 5998
Conventional: No
Specification contains quality assurance program: Yes
MIL-STD-790 Established Reliability & High Reliability: No
MIL-STD-690 Failure Rate Sampling Plans & Procedures: No
Weibull Graded: Yes
Specification contains space level reliability requirements: No
Specification allows test optimization: Yes

Contact Information:

Office of Primary Involvement: Electronic Devices Branch, DLA Land and Maritime - VQE
Primary Qualifying Activity Contact: 614-692-0627, e-mail: vqe.ls@dla.mil
Secondary Qualifying Activity Contact: 614-692-0631, e-mail: vqe.bw@dla.mil

Notes:

If a manufacturer desires to have test data considered for qualification, it must be certified and meet all qualification test requirements of MIL-PRF-31032 and the applicable associated specification.

The listing of printed board manufacturing lines in the QML applies only to printed boards produced in the plant(s) specified herein. Therefore, only those printed boards that have been manufactured and tested on the certified/qualified lines listed herein can be supplied as QML printed boards.

The DLA Land and Maritime - VQE contacts for QML companies can be located in the file "31032 main points-of-contact" at website: http://www.dsc.dla.mil/offices/sourcing_and_qualification/offices.asp?section=VQE

QML is a definition of a manufacturer's verified capabilities. Manufacturers may use the add-on qualification process to qualify capabilities that are not currently listed on the QML. The user is encouraged to contact the manufacturer or Qualifying Activity to make arrangements for QML availability.

The following abbreviations are used in this listing:

Ag: Silver
Au: Gold
CAGE: Commercial and Government Entity (Code)
Cu: Copper
ENIG: Electroless Nickel Immersion Gold
HASL: Hot Air Solder Level
ImmAg: Immersion Silver
IR: Infrared
LPI: Liquid Photoimageable
MIX: Mix of SMT and THM
Ni: Nickel
OSP: Organic Surface Protection
Pb: Lead
Pd: Palladium
PTH: Plated Thru Hole
SMOBC: Solder Mask Over Bare Copper
SMT: Surface-Mount Technology
Sn: Tin
THM: Through-Hole Mounting

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|--|--|--|
| MANUFACTURER INFORMATION: Accurate Circuit Engineering 3019 S. Kilson Drive Santa Ana, CA 92707, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 0MNN9 Contact: James Hofer Phone: 714-546-162 Fax: 714-433-7418 EMail: James@ace-pcb.com |
|--|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 20" X 26" |
| Max./Min. Board Thickness: | .22"/Not Specified |
| Max./Min. Base CU Thickness: | .0056"/Not Specified |
| Max./Min. Through Hole Size: | .075"/.008" (after plating) |
| | .247"/Not Specified (mounting-after plating) |
| Aspect Ratio: | 11:1 (Through Hole) |
| Max. Number of Layers: | 24 |
| Min. Conductor Width: | .003" |
| Min. Conductor Space: | .003" (+/-10%) |
| Part Mounting: | MIX, SM, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Electrolytic Ni-Au, HASL |
| Hole Preparation: | Permanganate Desmear, Permanganate Etchback |
| Alternate Construction: | Blind Vias, Buried Vias, Foil Lamination, Sequential Lamination |
| Copper Plating: | Acid Copper |
| Solder Resist: | LPI |
| Controlled Impedance: | Characteristic, Differential 50, 75, 100 ohms +/-10% |
| Hole Fill/Via Plug: | Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-06-12150
 VQE-07-12577
 VQE-09-18384

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| <p>MANUFACTURER INFORMATION: American Standard Circuits RF Division, 475 Industrial Drive West Chicago, IL 60185, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 4AA34 Contact: Lori Ryan Phone: 603-639-5438 Fax: EMail: lori@asc-i.com</p> |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|---|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-08-015934 |
| Panel Size: | 12" X 18" | VQE-11-021830 |
| Max./Min. Board Thickness: | .062"/Not Specified | |
| Max./Min. Base CU Thickness: | .006"/Not Specified (1/2 oz.) | |
| Max./Min. Through Hole Size: | .052"/.009" (Drilled Through Hole (before plating)) | |
| Aspect Ratio: | 7:1 (Through Hole) | |
| Max. Number of Layers: | 10 | |
| Min. Conductor Width: | .004" | |
| Min. Conductor Space: | .004" (+/-10%) | |
| Part Mounting: | MIX, SMT, THM | |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | Electrolytic Ni-Au Tab Plating, HASL, Immersion Ag | |
| Hole Preparation: | Permanganate Desmear | |
| Alternate Construction: | N/A | |
| Copper Plating: | Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|--|---|---|
| <p>MANUFACTURER INFORMATION: Amphenol Printed Circuits 91 Northeastern Boulevard Nashua, NH 03062, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 57034 Contact: Denise Chevalier Phone: 603-879-3268 Fax: 603-879-2818 EMail: denise.chevalier@amphenol-tcs.com</p> |
|--|---|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|--|-------------------------------|
| <p>Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 21" X 24" Max./Min. Board Thickness: .078"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: ".026" Aspect Ratio: 3:1 Max. Number of Layers: 10 Min. Conductor Width: .004" Min. Conductor Space: .004" Part Mounting: Compliant Pin, MIX, SMT, THM Rigid Base Material: GM (Woven E-Glass, Triazine/Bismaleimide Modified Epoxy Resin) Flex Base Material: N/A Finish System: ENIG, Electrolytic Hard and Soft Gold, Electrolytic Nickel, Fused SnPb, HASL Hole Preparation: Plasma Desmear Alternate Construction: N/A Copper Plating: Acid Copper: DC Plate, Pulse Plate Solder Resist: N/A Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper</p> | <p>VQE-09-018717</p> |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Amphenol Printed Circuits 91 Northeastern Boulevard Nashua, NH 03062, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 57034 Contact: Denise Chevalier Phone: 603-879-3268 Fax: 603-879-2818 E-Mail: denise.chevalier@amphenol-tcs.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 24" X 36", 30" X 36" |
| Max./Min. Board Thickness: | .322"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | Not Specified/.008" |
| Aspect Ratio: | 0.5:1 (Blind Via) 11:1 (Through Hole) |
| Max. Number of Layers: | 28 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .004" |
| Part Mounting: | Compliant Pin, MIX, SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Hybrid Built GF/Hydrocarbon Ceramic Hydrocarbon Ceramic |
| Flex Base Material: | N/A |
| Finish System: | Electrolytic Hard & Soft Gold, Electrolytic Nickel, Fused SnB, Nickel |
| Hole Preparation: | Permanganate Desmear, Permanganate Etchback, Plasma Desmear |
| Alternate Construction: | Blind Vias Mechanicall Drilled |
| Copper Plating: | Acid Copper, DC Plate, Pulse Plate |
| Solder Resist: | Dry Film Soldermask, LPI, SMOBC, Thermal Cured Soldermask |
| Controlled Impedance: | 120 ohms ± 10%, 50 ohms ± 10% |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | N/A |

VQE-06-010054
 VQE-09-017008
 VQE-10-020582
 VQE-97-000649

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: Amphenol Printed Circuits 91 Northeastern Boulevard Nashua, NH 03062, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 57034 Contact: Denise Chevalier Phone: 603-879-3268 Fax: 603-879-2818 EMail: denise.chevalier@amphenol-tcs.com |
|---|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|---|---------------|-------------------------------|
| Specification: MIL-PRF-31032/3, MIL-PRF-31032/4 Panel Size: 18" X 24" ((max)) Max./Min. Board Thickness: .031"/Not Specified Max./Min. Base CU Thickness: 1"/" Max./Min. Through Hole Size: ".055" ((drilled)) Aspect Ratio: 0.7:1 ((Through Hole)) Max. Number of Layers: 4 Min. Conductor Width: .005" Min. Conductor Space: .005" Part Mounting: MIX, SM, THM Rigid Base Material: N/A (types 1, 2 & 3 only) Flex Base Material: 4203/1 Acrylic Adhesive Polyimide Coverlayer 4204/1 Acrylic Adhesive Finish System: HASL, Hot Oil Reflow following SnPb plate Hole Preparation: Plasma Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Acid Copper Solder Resist: Dru Film Soldermask Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: Use A (Flex to Install), Use B (Dynamic Flex) Hole Wall Conductive Coating: Direct Metallization Max. Base Cu Weight 1 oz. | VQE-10-019533 | |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|---------------|-------------------------------|
| Specification: MIL-PRF-31032/3, MIL-PRF-31032/4 Panel Size: 18" X 24" ((max)) Max./Min. Board Thickness: .125"/Not Specified Max./Min. Base CU Thickness: 1"/" Max./Min. Through Hole Size: ".012" ((drilled)) Aspect Ratio: 7.75:1 ((Through Hole)) Max. Number of Layers: 15 Min. Conductor Width: .006" Min. Conductor Space: .005" Part Mounting: MIX, SM, THM Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: 4203/1 Acrylic Adhesive Polyimide Coverlayer 4204/11 Adhesiveless Polyimide Finish System: HASL, Hot Oil Reflow following SnPb plate Hole Preparation: Plasma Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Acid Copper (DC and Pulse Plate) Solder Resist: N/A Controlled Impedance: Characteristic, Differential, Range 50-100 ohms (+/- 10%) Hole Fill/Via Plug: N/A Flex Usage: Use A (Flex to Install) Hole Wall Conductive Coating: Direct Metallization Max. Base Cu Weight 1 oz. | VQE-10-019533 | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Cirex International, Inc. 791 Nuttman Street Santa Clara, CA 95054, | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 4MEG7 Contact: Don Angulo Phone: 408-988-3980 Fax: 408-988-4534 EMail: dangulo@cirexxintl.com |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|---|-------------------------------|
| Specification: MIL-PRF-31032/3 Panel Size: 12" X 18" Max./Min. Board Thickness: .1"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: Not Specified/.01" Aspect Ratio: 10:1 (Through Hole) Max. Number of Layers: 2 Min. Conductor Width: .004" Min. Conductor Space: .004" Part Mounting: MIX, SMT, THM Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: Acrylic Adhesive Polyimide Copper-Clad Adhesiveless Polyimide Finish System: ENIG, HASL, Ni/Au Hole Preparation: Plasma Desmear Alternate Construction: N/A Copper Plating: Acid Copper Solder Resist: Kapton Covelay Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: Class A Flex-to-Install, Class B Continuous Flex Hole Wall Conductive Coating: N/A | VQE-07-014176 |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|---|-------------------------------|
| Specification: MIL-PRF-31032/4 Panel Size: 12" X 18" Max./Min. Board Thickness: .125"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: Not Specified/.01" (Mechanical) Aspect Ratio: 10:1 Max. Number of Layers: 16 Min. Conductor Width: .004" Min. Conductor Space: .004" Part Mounting: MIX, SMT, THM Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: Acrylic Adhesie Copper Clad Adhesiveless Polyimide Finish System: ENIG, HASL Hole Preparation: Permanganate Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Acid Coper Solder Resist: LPI Controlled Impedance: 100 ohms +/-10%, 50 ohms +/- 10% Hole Fill/Via Plug: N/A Flex Usage: Class A Flex-to-Install Hole Wall Conductive Coating: N/A | VQ-08-016602 |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| MANUFACTURER INFORMATION: Colonial Circuits, Inc. 1026 Warrenton Road Fredericksburg, VA 22406-6200, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 6T499 Contact: Mike Hill Phone: 540-753-5511, x125 Fax: 540-752-2109 EMail: quality@colonialcircuits.com |
|--|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|-------------------------------|
| Specification: MIL-PRF-31032/1 Panel Size: 18" X 24" Max./Min. Board Thickness: .088"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .052"/.021" Aspect Ratio: 4.2:1 (Through Hole) Max. Number of Layers: 14 Min. Conductor Width: .006" Min. Conductor Space: .005" Part Mounting: PTH, SMT Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: N/A Finish System: Tin/Lead HASL Hole Preparation: Plasma Desmear Alternate Construction: N/A Copper Plating: Electrolytic Acid Copper Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: N/A | | VQE-04-6002 |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|---|--|-------------------------------|
| Specification: MIL-PRF-31032/1 Panel Size: 18" X 24" Max./Min. Board Thickness: .127"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .228"/.015" Aspect Ratio: 8.5:1 (Through Hole) Max. Number of Layers: 12 Min. Conductor Width: .008" Min. Conductor Space: .005" Part Mounting: PTH, SMT Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: N/A Finish System: Tin/Lead HASL Hole Preparation: Plasma Desmear Alternate Construction: N/A Copper Plating: Electrolytic Acid Copper Solder Resist: LPI Controlled Impedance: 55 Ohms ± 10% Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: N/A | | VQE-04-6002 |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Colonial Circuits, Inc. 1026 Warrenton Road Fredericksburg, VA 22406-6200, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 6T499 Contact: Mike Hill Phone: 540-753-5511, x125 Fax: 540-752-2109 E-Mail: quality@colonialcircuits.com |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-04-6002 |
| Panel Size: | 12" X 18" | VQE-06-010192 |
| Max./Min. Board Thickness: | .09"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | .139"/.021" | |
| Aspect Ratio: | 4.29:1 (Through Hole) | |
| Max. Number of Layers: | 8 | |
| Min. Conductor Width: | .005" | |
| Min. Conductor Space: | .005" | |
| Part Mounting: | PTH, SMT | |
| Rigid Base Material: | Hydrocarbon Resin with Ceramic Filler Woven E-Glass | |
| Flex Base Material: | N/A | |
| Finish System: | Tin/Lead HASL, Tin/Lead Reflow | |
| Hole Preparation: | Plasma Desmear, Plasma Etchback | |
| Alternate Construction: | N/A | |
| Copper Plating: | Electrolytic Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | 55 ohms ±10% | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | N/A | |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|---|-------------------------------|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 | VQ-10-019425 |
| Panel Size: | 18" X 24" | |
| Max./Min. Board Thickness: | .093"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | .15"/.01" | |
| Aspect Ratio: | 8.6:1 | |
| Max. Number of Layers: | 10 | |
| Min. Conductor Width: | .005" | |
| Min. Conductor Space: | .005" | |
| Part Mounting: | PTH, SMT | |
| Rigid Base Material: | Rigid Flex/Kapton Adhesive | |
| Flex Base Material: | IPC-FC-241/11 (Adhesiveless) | |
| Finish System: | N/A | |
| Hole Preparation: | Plasma Desmear, Plasma Etchback | |
| Alternate Construction: | N/A | |
| Copper Plating: | Electrolytic Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | Class A (Flex During Installation), Class B (Dynamic) | |
| Hole Wall Conductive Coating: | Immersion Tin, Tin/Lead Reflow | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| MANUFACTURER INFORMATION: Colonial Circuits, Inc. 1026 Warrenton Road Fredericksburg, VA 22406-6200, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 6T499 Contact: Mike Hill Phone: 540-753-5511, x125 Fax: 540-752-2109 EMail: quality@colonialcircuits.com |
|--|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|--|-------------------------------|
| Specification: MIL-PRF-31032/Custom Panel Size: 12" X 18" Max./Min. Board Thickness: .083"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .045"/.02" Aspect Ratio: 4.15:1 (Through Hole) Max. Number of Layers: 4 Min. Conductor Width: .01" Min. Conductor Space: .011" Part Mounting: PTH, SMT Rigid Base Material: Rogers 4003 Flex Base Material: N/A Finish System: Tin/Lead HASL Hole Preparation: Plasma Desmear Alternate Construction: N/A Copper Plating: Electrolytic Acid Copper Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: N/A | VQE-04-6002 |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Cosmotronic, Inc. 16721 Noyes Avenue Irvine, CA 92606, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 63695 Contact: Alan Exley Phone: 949-660-0740 Fax: 949-553-8371 EMail: alan_exley@cosmotronic.com |
|--|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .335"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | Not Specified/.014" |
| Aspect Ratio: | 15:1 (Through Hole) |
| Max. Number of Layers: | 36 |
| Min. Conductor Width: | .005" |
| Min. Conductor Space: | .004" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | AF: Aramid Fabric, Woven, Majority Polyfunctional Epoxy Resin BF: Aramid Fabric, Nonwoven, Epoxy Resin BI: Aramid Fabric, Nonwoven, Polyimide Resin GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant GM: Glass Base, Woven, Triazine and/or Bismaleimide Modified Epoxy Resin, Flame Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Fused SnPB, HASL, Selective Solder Strip-Tin Lead Plate |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind Vias, Sequential Lamination |
| Copper Plating: | Electro-deposited Acid Copper |
| Solder Resist: | LPI, SMOBC |
| Controlled Impedance: | 50 ohms ± 10% nominal/tolerance |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | N/A |

VQE-04-006966
 VQE-05-009107
 VQE-06-010085
 VQE-06-011248

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Cosmotronic, Inc. 16721 Noyes Avenue Irvine, CA 92606, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 63695 Contact: Alan Exley Phone: 949-660-0740 Fax: 949-553-8371 EMail: alan_exley@cosmotronic.com |
|--|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|--|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .165"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | Not Specified/.012" |
| Aspect Ratio: | 8:1 (Through Hole) |
| Max. Number of Layers: | 22 |
| Min. Conductor Width: | .006" |
| Min. Conductor Space: | .008" |
| Part Mounting: | SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant GI/GM Composite Material GM: Glass Base, Woven, Triazine and/or Bismaleimide Modified Epoxy Resin, Flame Resistant |
| Flex Base Material: | IPC-4204/1 Acrylic Adhesive IPC-4204/11 Adhesiveless |
| Finish System: | ENIG, Fused SnPB, HASL, Selective Solder Strip-Tin Lead Plate |
| Hole Preparation: | N/A |
| Alternate Construction: | N/A |
| Copper Plating: | Electro-deposited Acid Copper |
| Solder Resist: | LPI, SMOBC |
| Controlled Impedance: | N/A |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | Class A Flex to Install, Class B Continuous Flex |
| Hole Wall Conductive Coating: | N/A |

VQE-04-006966
 VQE-05-009107
 VQE-06-010085

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Cosmotronic, Inc. 16721 Noyes Avenue Irvine, CA 92606, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 63695 Contact: Alan Exley Phone: 949-660-0740 Fax: 949-553-8371 EMail: alan_exley@cosmotronic.com |
|--|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|---|---|
| Specification: MIL-PRF-31032/Custom Panel Size: 12" X 18" Max./Min. Board Thickness: .225"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: Not Specified/.02" Aspect Ratio: 10:1 (Through Hole) Max. Number of Layers: 16 Min. Conductor Width: .011" Min. Conductor Space: .007" Part Mounting: SMT Rigid Base Material: Rogers 4003 Ceramic-Filled Thermoset Resin Rogers 4003/GI Composite Flex Base Material: N/A Finish System: ENIG, HASL Hole Preparation: Plasma Desmear, Plasma Etchback Alternate Construction: Blind Vias, Sequential Lamination Copper Plating: Electro-deposited Acid Copper Solder Resist: LPI, SMOBC Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: N/A | VQE-04-006966 VQE-05-009107 VQE-06-010085 |
|---|---|

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: DDi Cleveland Corp. 7 Ascot Parkway Cuyahoga Falls, OH 44223, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 7Z463 Contact: Mark Kasting Phone: 330-572-3400 Fax: 330-572-3434 EMail: mark_kasting/coretec@coretec-inc.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|--|---------------|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-00-000289 |
| Panel Size: 18" X 24" | VQE-01-000910 |
| Max./Min. Board Thickness: .126"/Not Specified | VQE-05-008414 |
| Max./Min. Base CU Thickness: 1"/Not Specified | VQE-06-010963 |
| Max./Min. Through Hole Size: .021"/.015" | |
| Aspect Ratio: 5:1 | |
| Max. Number of Layers: 10 | |
| Min. Conductor Width: .004" | |
| Min. Conductor Space: .004" | |
| Part Mounting: MIX, SM, THM | |
| Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant | |
| Flex Base Material: N/A | |
| Finish System: Fused SnPb, HASL, Selective SnPb Plate | |
| Hole Preparation: Plasma Desmear, Plasma Etchback | |
| Alternate Construction: Sequential Lamination for Blind & Buried Vias 8 layer max | |
| Copper Plating: Acid Copper | |
| Solder Resist: Dry Film, LPI | |
| Controlled Impedance: 100/50 ohm ±10% | |
| Hole Fill/Via Plug: N/A | |
| Flex Usage: N/A | |
| Hole Wall Conductive Coating: Electroless Copper | |

VQE-00-000289
 VQE-01-000910
 VQE-05-008414
 VQE-06-010963

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: DDi Cleveland Corp. 7 Ascot Parkway Cuyahoga Falls, OH 44223, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 7Z463 Contact: Mark Kasting Phone: 330-572-3400 Fax: 330-572-3434 EMail: mark_kasting/coretec@coretec-inc.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|--|---------------|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-00-000289 |
| Panel Size: 18" X 24" | VQE-01-000910 |
| Max./Min. Board Thickness: .126"/Not Specified | VQE-05-008414 |
| Max./Min. Base CU Thickness: 2"/" | VQE-06-010963 |
| Max./Min. Through Hole Size: .045"/.013" | |
| Aspect Ratio: 5:1 | |
| Max. Number of Layers: 16 | |
| Min. Conductor Width: .004" | |
| Min. Conductor Space: .004" | |
| Part Mounting: MIX, SMT, THM | |
| Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: N/A | |
| Finish System: Fused SnPb, HASL, Selective SnPb Plate | |
| Hole Preparation: Plasma Desmear, Plasma Etchback | |
| Alternate Construction: Sequential Lamination for Blind & Buried Vias 8 layer max | |
| Copper Plating: Acid Copper | |
| Solder Resist: N/A | |
| Controlled Impedance: 100/50 ohms +/- 10% | |
| Hole Fill/Via Plug: N/A | |
| Flex Usage: N/A | |
| Hole Wall Conductive Coating: Electroless Copper | |

VQE-00-000289
 VQE-01-000910
 VQE-05-008414
 VQE-06-010963

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: DDi Cleveland Corp. 7 Ascot Parkway Cuyahoga Falls, OH 44223, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 7Z463 Contact: Mark Kasting Phone: 330-572-3400 Fax: 330-572-3434 EMail: mark_kasting/coretec@coretec-inc.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .126"/Not Specified |
| Max./Min. Base CU Thickness: | 2"/" |
| Max./Min. Through Hole Size: | .039"/.013" |
| Aspect Ratio: | 10:1 |
| Max. Number of Layers: | 11 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .004" |
| Part Mounting: | MIX, SM, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | IPC-4204/11 Adhesiveless |
| Finish System: | HASL |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | N/A |
| Copper Plating: | Acid Copper |
| Solder Resist: | N/A |
| Controlled Impedance: | N/A |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |
| Flex Usage: | Class A Flex to Install |

VQE-01-000909
 VQE-06-010963

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: DDi Cleveland Corp. 7 Ascot Parkway Cuyahoga Falls, OH 44223, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 7Z463 Contact: Mark Kasting Phone: 330-572-3400 Fax: 330-572-3434 EMail: mark_kasting/coretec@coretec-inc.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|--------------------------------------|---|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .07"/Not Specified |
| Max./Min. Base CU Thickness: | 1"/Not Specified |
| Max./Min. Through Hole Size: | Not Specified/.026" |
| Aspect Ratio: | 2.6:1 |
| Max. Number of Layers: | 7 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .004" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | IPC-4204/1 Acrylic Adhesive |
| Finish System: | HASL |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | N/A |
| Copper Plating: | Acid Copper |
| Solder Resist: | N/A |
| Controlled Impedance: | N/A |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | Class A Flex to Install |
| Hole Wall Conductive Coating: | Electroless Copper |
| Flex Usage: | Class A Flex to Install |

VQE-01-000909
 VQE-06-010963

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: DDi Denver Corp. 10570 Bradford Road Littleton, CO 80127, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 75815 Contact: Douglas N. Berry Phone: 303-972-4105 Fax: 303-933-2934 EMail: dberry@ddiglobal.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|--|--|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: .125"/Not Specified Max./Min. Base CU Thickness: .001"/Not Specified Max./Min. Through Hole Size: .109"/.013" Aspect Ratio: 7:1 Max. Number of Layers: 20 Min. Conductor Width: .004" Min. Conductor Space: .004" Part Mounting: MIX, SMT, THM Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: N/A Finish System: ENIG, HASL, IR Reflow Following SnPb Plate Hole Preparation: Plasma Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Acid Copper Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: Non-conductive Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper Max. Base Cu Weight 2 oz. | VQE-02-0317 VQE-05-7627 VQE-05-9014 VQE-09-18719 VQE-10-020224 |
|--|--|

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: DDi Denver Corp. 10570 Bradford Road Littleton, CO 80127, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 75815 Contact: Douglas N. Berry Phone: 303-972-4105 Fax: 303-933-2934 E-Mail: dberry@ddiglobal.com |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|--|--|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: .125"/Not Specified Max./Min. Base CU Thickness: .001"/" Max./Min. Through Hole Size: .109"/.013" Aspect Ratio: 10:1 Max. Number of Layers: 20 Min. Conductor Width: .004" Min. Conductor Space: .004" Part Mounting: MIX, SMT, THM Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: N/A Finish System: ENIG, HASL, IR Reflow following SnPb plate Hole Preparation: Plasma Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Acid Copper Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: Non-conductive Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper Max. Base Cu Weight 2 oz. | VQE-02-0217 VQE-05-7626 VQE-05-9014 VQE-09-18719 VQE-10-020224 |
|--|--|

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| MANUFACTURER INFORMATION: DDi North Jackson Corp. 12080 DeBartolo Drive North Jackson, OH 44451, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 0GN71 Contact: Cynthia Savakis Phone: 330-538-3900, x211 Fax: 330-538-3820 EMail: quality@sovereign-circuits.com |
|--|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .25"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .008"/Not Specified |
| Aspect Ratio: | 15:1 (Through Hole) |
| Max. Number of Layers: | 24 |
| Min. Conductor Width: | .003" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, Press Fit, SMT, THM |
| Rigid Base Material: | BI: Aramid Fabric, Nonwoven, Polyimide Resin GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Fused SnPb, HASL, Immersion Ag, Immersion White Tin, Ni/Au, Ni/Pd/Au, OSP, Reflowed Pure Tin |
| Hole Preparation: | Permanganate Desmear, Permanganate Etchback, Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind Vias, Buried Vias, Cap Lamination, Foil Lamination |
| Copper Plating: | Electroless Acid Copper, Electroplated Acid Copper |
| Solder Resist: | Dry Film, LPI |
| Controlled Impedance: | Characteristic, Differential, Dual Stripline, Embedded Microstrip, Microstrip, Range 30-150 ohms ±10% |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-03-003121
 VQE-03-003214
 VQE-07-012925
 VQE-10-020405

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| MANUFACTURER INFORMATION: DDi North Jackson Corp. 12080 DeBartolo Drive North Jackson, OH 44451, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 0GN71 Contact: Cynthia Savakis Phone: 330-538-3900, x211 Fax: 330-538-3820 EMail: quality@sovereign-circuits.com |
|--|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|--|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .25"/Not Specified |
| Max./Min. Base CU Thickness: | .005"/Not Specified |
| Max./Min. Through Hole Size: | .008"/Not Specified |
| Aspect Ratio: | 15:1 (Through Hole) |
| Max. Number of Layers: | 24 |
| Min. Conductor Width: | .003" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, Press Fit, SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant |
| | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | IPC-4204/1 Acrylic Adhesive |
| | IPC-4204/11 Adhesiveless |
| Finish System: | ENIG, Fused SnPb, HASL, Immersion Ag, Immersion White tin, Ni/Au, OSP, Reflowed Pure Tin |
| Hole Preparation: | Permanganate Desmear, Permanganate Etchback, Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind Via, Buried Via, Cap Lamination, Foil Lamination |
| Copper Plating: | Electroless Acid Copper, Electroplated Acid Copper |
| Solder Resist: | Dry Film, LPI |
| Controlled Impedance: | 30 - 150 ohms ± 10% |
| Hole Fill/Via Plug: | Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-03-003121
 VQE-03-003214
 VQE-07-012925
 VQE-10-020405

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: DDi Ontario 8150 Sheppard Avenue East Scarborough, Ontario, Canada M1B 5K2 | PLANT LOCATIONS: 1. Same Address as Manufacturer 2. Coretec, Inc., CAGE Code: 3AF82, 2020 Ellesmere Road, Scarborough, Ontario, Canada M1H 2Z8 | CAGE Code: 3AF82 Contact: Noor Al-Shaikh Phone: 416-208-2100 Fax: 416-439-1582 EMail: alshaikh@coretec-inc.com |
|---|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-04-006240 |
| Panel Size: | 18" X 24" | VQE-08-015407 |
| Max./Min. Board Thickness: | .08"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | Not Specified/.01" (as drilled) | |
| Aspect Ratio: | 7:1 (Through Hole) | |
| Max. Number of Layers: | 14 | |
| Min. Conductor Width: | .005" | |
| Min. Conductor Space: | .005" | |
| Part Mounting: | MIX, SMT, THM | |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG, HASL | |
| Hole Preparation: | Plasma Desmear, Plasma Etchback | |
| Alternate Construction: | N/A | |
| Copper Plating: | Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | Characteristics +/-10%, Differential +/-10% | |
| Hole Fill/Via Plug: | Non-conductive | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|---|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-04-006240 |
| Panel Size: | 18" X 24" | VQE-08-015407 |
| Max./Min. Board Thickness: | .08"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | Not Specified/.01" (as drilled) | |
| Aspect Ratio: | 7:1 (Through Hole) | |
| Max. Number of Layers: | 14 | |
| Min. Conductor Width: | .005" | |
| Min. Conductor Space: | .005" | |
| Part Mounting: | MIX, SMT, THM | |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG, HASL | |
| Hole Preparation: | Chemical Desmear | |
| Alternate Construction: | N/A | |
| Copper Plating: | Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | Characteristics ± 10%, Differential ± 10% | |
| Hole Fill/Via Plug: | Non-conductive | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Dynaco Corp. 1000 South Priest Drive Tempe, AZ 85281-5238, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 61642 Contact: Ted Edwards Phone: 480-736-3728 Fax: 480-921-9830 EMail: tedwards@dynacocorp.com |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|-------------------------------|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 | VQE-05-9356 |
| Panel Size: | 12" X 18", 18" X 24" | VQE-06-10600 |
| Max./Min. Board Thickness: | .12"/Not Specified | |
| Max./Min. Base CU Thickness: | .001"/Not Specified | |
| Max./Min. Through Hole Size: | .045"/.01" | |
| Aspect Ratio: | 12:1 (Through Hole) | |
| Max. Number of Layers: | 20 | |
| Min. Conductor Width: | .004" | |
| Min. Conductor Space: | .006" | |
| Part Mounting: | THM | |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: | IPC-4204/1 Acrylic Adhesive | |
| Finish System: | Fused Sn/Pb, HASL | |
| Hole Preparation: | Permanganate Desmear, Permanganate Etchback, Plasma Etchback | |
| Alternate Construction: | N/A | |
| Copper Plating: | Electroless Acid Copper, Electroplated Acid Copper | |
| Solder Resist: | N/A | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | N/A | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| <p>MANUFACTURER INFORMATION: Dynamic & Proto Circuits, Inc. 869 Barton Street Stoney Creek, Ontario, Canada L8E 5G6</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 38898 Contact: Stephen Hazell Phone: 905-643-9900 Fax: 905-643-9911 EMail: stephenhazell@dapc.com</p> |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|---|---|
| <p>Specification: MIL-PRF-31032/1, MIL-PRF-31032/2</p> <p>Panel Size: 16" X 18"</p> <p>Max./Min. Board Thickness: .125"/Not Specified</p> <p>Max./Min. Base CU Thickness: N/A</p> <p>Max./Min. Through Hole Size: .039"/.018" (0.0135" Drilled)</p> <p>Aspect Ratio: 9.3:1 (Through Hole)</p> <p>Max. Number of Layers: 16</p> <p>Min. Conductor Width: .005"</p> <p>Min. Conductor Space: .005"</p> <p>Part Mounting: MIX, SMT, THM</p> <p>Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant</p> <p>Flex Base Material: N/A</p> <p>Finish System: HASL</p> <p>Hole Preparation: Plasma Etchback</p> <p>Alternate Construction: N/A</p> <p>Copper Plating: Acid Copper</p> <p>Solder Resist: Dry Film Solder Resist Plugs, LPI</p> <p>Controlled Impedance: N/A</p> <p>Hole Fill/Via Plug: N/A</p> <p>Flex Usage: N/A</p> <p>Hole Wall Conductive Coating: N/A</p> | <p>VQE-00-0007 VQE-01-0311 VQE-03-0818 VQE-98-1143</p> |
|---|---|

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Electro Plate Circuitry, Inc. 1430 Century Drive Carrollton, TX 75006, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 79616 Contact: James McNeal Phone: 972-466-0818 Fax: 972-466-9078 EMail: jjimm@eplate.com |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-06-010333 VQE-06-011433 VQE-10-020352 |
| Panel Size: | 18" X 24", 18" X 16" | |
| Max./Min. Board Thickness: | .12"/.03" | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | ".008" | |
| Aspect Ratio: | 9.3:1 (Through Hole) | |
| Max. Number of Layers: | 14 | |
| Min. Conductor Width: | .004" | |
| Min. Conductor Space: | .004" | |
| Part Mounting: | MIX, SMT, THM | |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG, HASL, Hard Au, Reflowed SnPb | |
| Hole Preparation: | Plasma Desmear, Plasma Etchback | |
| Alternate Construction: | Blind/Buried Vias, Filled Vias, Foil Lamination, Sequential Lamination | |
| Copper Plating: | Acid Copper | |
| Solder Resist: | Dry Film, LPI | |
| Controlled Impedance: | ± 3% Tolerance | |
| Hole Fill/Via Plug: | Conductive, Non-conductive | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-06-010333 VQE-06-011433 VQE-10-020352 |
| Panel Size: | 18" X 16", 18" X 24" | |
| Max./Min. Board Thickness: | .17"/.03" | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | ".008" | |
| Aspect Ratio: | 9.3:1 ((Through Hole)) | |
| Max. Number of Layers: | 18 | |
| Min. Conductor Width: | .004" | |
| Min. Conductor Space: | .004" | |
| Part Mounting: | MIX, SMT, THM | |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG, HASL, Hard Au, Reflowed SnPb | |
| Hole Preparation: | Plasma Desmear, Plasma Etchback | |
| Alternate Construction: | Blind/Buried Vias, Filled Vias, Foil Lamination, Sequential Lamination | |
| Copper Plating: | Acid Copper | |
| Solder Resist: | Dry Film, LPI | |
| Controlled Impedance: | ± 3% Tolerance | |
| Hole Fill/Via Plug: | Conductive, Non-conductive | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Electro Plate Circuitry, Inc. 1430 Century Drive Carrollton, TX 75006, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 79616 Contact: James McNeal Phone: 972-466-0818 Fax: 972-466-9078 EMail: jjimm@eplate.com |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|--|-------------------------------|
|--|-------------------------------|

| | |
|---|---------------|
| Specification: MIL-PRF-31032/5, MIL-PRF-31032/6 Panel Size: 12" X 18", 18" X 24" Max./Min. Board Thickness: .18"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: ".008" Aspect Ratio: 6:1 Max. Number of Layers: 6 Min. Conductor Width: .004" Min. Conductor Space: .004" Part Mounting: MIX, SMT, THM Rigid Base Material: GT: Woven E-Glass, PTFE Resin GX: Glass Base, Non-Woven, PTFE Resin, Flame Resistant GY: Glass Base, Woven, PTFE Resin, Flame Resistant, for Microwave Application With or Without Woven or Non-Woven E-Glass, Polytetrafluoroethylene (PTFE) Resin, Ceramic Filler Flex Base Material: N/A Finish System: ENIG, Electrolytic Nickel with Electrolytic Hard/Soft Gold, HASL, Hot Oil Reflow of Plated SnPb, Tin Lead Plate Hole Preparation: Plasma Desmear Alternate Construction: Blind Vias, Cavity, Exposed Inner Layer, Foil Lamination, Sequential Lamination Copper Plating: Acid Copper Solder Resist: Dry Film, LPI Controlled Impedance: ± 3% Characteristic, ± 3% Differential Hole Fill/Via Plug: Conductive, Non-conductive Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper | VQE-10-021161 |
|---|---------------|

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| <p>MANUFACTURER INFORMATION: Electro Plate Circuitry, Inc. 1430 Century Drive Carrollton, TX 75006, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 79616 Contact: James McNeal Phone: 972-466-0818 Fax: 972-466-9078 EMail: jjimm@eplate.com</p> |
|--|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|---|-------------------------------|
| <p>Specification: N/A Panel Size: N/A Max./Min. Board Thickness: N/A Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: N/A Aspect Ratio: N/A Max. Number of Layers: N/A Min. Conductor Width: N/A Min. Conductor Space: N/A Part Mounting: N/A Rigid Base Material: N/A Flex Base Material: N/A Finish System: N/A Hole Preparation: N/A Alternate Construction: N/A Copper Plating: N/A Solder Resist: N/A Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: N/A</p> | <p>N/A</p> |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: Electrotek Corp. 7745 S. 10th Street Oak Creek, WI 53154, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 66030 Contact: Tom Tikusis Phone: 414-762-1390 Fax: 414-762-1510 EMail: sales@boards4u.com |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|---|---|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 | VQ-06-011451 VQ-08-014513 VQE-09-018692 |
| Panel Size: 18" X 24" | |
| Max./Min. Board Thickness: .115"/Not Specified | |
| Max./Min. Base CU Thickness: N/A | |
| Max./Min. Through Hole Size: ".012" | |
| Aspect Ratio: 9:1 (Through Hole) | |
| Max. Number of Layers: 18 | |
| Min. Conductor Width: .003" | |
| Min. Conductor Space: .003" | |
| Part Mounting: MIX, SMT, THM | |
| Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: N/A | |
| Finish System: ENIG, Electrolytic Nickel/Gold, HASL, ImmAg | |
| Hole Preparation: Permanganate Desmear, Plasma Etchback | |
| Alternate Construction: Cap Lamination, Foil Lamination | |
| Copper Plating: Electroplated Acid Copper | |
| Solder Resist: Dry Film, LPI | |
| Controlled Impedance: GF: 100 ohms/50 ohms ± 10%, GI: 100 ohms ± 10% | |
| Hole Fill/Via Plug: Via-fill Technology, 0.016" ±25% Diameter | |
| Flex Usage: N/A | |
| Hole Wall Conductive Coating: Electroless Copper | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| MANUFACTURER INFORMATION: Endicott Interconnect Technologies, Inc. Dept. 0069/014-3, 1093 Clark Street Endicott, NY 13760, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 3ECL3 Contact: Jose Rios Phone: 607-755-5896 Fax: 607-755-4649 EMail: JoseA.Rios@eitny.com |
|--|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|---|--|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 24" X 28" Max./Min. Board Thickness: .116"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: ".01" Aspect Ratio: 12:1 (Through Hole) Max. Number of Layers: 30 Min. Conductor Width: .003" Min. Conductor Space: .004" Part Mounting: MIX, SMT, THM Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: N/A Finish System: ENIG, HASL Hole Preparation: Glass Etch, Permanganate Desmear, Plasma Etchback Alternate Construction: Cap-Lamination, Foil-Lamination Copper Plating: Electroplated Acid Copper Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: N/A | VQE-04-005311 VQE-07-012236 VQE-07-013506 VQE-08-015922 |
|---|--|

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Endicott Interconnect Technologies, Inc. Dept. 0069/014-3, 1093 Clark Street Endicott, NY 13760, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 3ECL3 Contact: Jose Rios Phone: 607-755-5896 Fax: 607-755-4649 EMail: JoseA.Rios@eitny.com |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-04-005311 VQE-07-012236 VQE-07-013506 |
| Panel Size: | 18" X 24" | |
| Max./Min. Board Thickness: | .084"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | Not Specified/.012" | |
| Aspect Ratio: | 7:1 (Through Hole) | |
| Max. Number of Layers: | 12 | |
| Min. Conductor Width: | .004" | |
| Min. Conductor Space: | .004" | |
| Part Mounting: | MIX, SMT, THM | |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG, HASL | |
| Hole Preparation: | Permanganate Desmear, Plasma Etchback | |
| Alternate Construction: | Cap-Lamination, Foil-Lamination | |
| Copper Plating: | Electroplated Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | N/A | |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|---|
| Specification: | MIL-PRF-31032/Custom | VQE-04-005311 VQE-07-012236 VQE-07-013506 |
| Panel Size: | 19.5" X 24" | |
| Max./Min. Board Thickness: | .153"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | Not Specified/.02" | |
| Aspect Ratio: | 7.6:1 (Through Hole) | |
| Max. Number of Layers: | 19 | |
| Min. Conductor Width: | .005" | |
| Min. Conductor Space: | .005" | |
| Part Mounting: | MIX | |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG | |
| Hole Preparation: | Permanganate Desmear, Plasma Etchback | |
| Alternate Construction: | Foil-Lamination, Copper Core | |
| Copper Plating: | Electroplated Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | N/A | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: Firan Technology Group 250 Finchdene Square Scarborough, Ontario, Canada M1X 1A5 | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: L2665 Contact: Bryan Clark Phone: 416-299-4000 Fax: 416-292-4308 E-Mail: byanclark@firantechnology.com |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|--------------------------------------|--|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .22"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | Not Specified/.005" (Laser Control Depth) Not Specified/.006" (Buried Via Mechanical Drill) .025"/.008" (Mechanical Drill) |
| Aspect Ratio: | 7:1 (Through Hole) |
| Max. Number of Layers: | 20 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .004" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | BI: Aramid Fabric, Nonwoven, Polyimide Resin GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant GM: Glass Base, Woven, Triazine and/or Bismaleimide Modified Epoxy Resin, Flame Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, HASL, Immersion Tin, Silver, Reflow Solder |
| Hole Preparation: | Permanganate Desmear, Plasma Etchback |
| Alternate Construction: | Sequential Lamination for Blind & Buried Vias and Micro Vias |
| Copper Plating: | Electroless Acid Copper, Electrolytic Acid Copper |
| Solder Resist: | Hole Fill, LPI |
| Controlled Impedance: | Characteristic \pm 10%, Differential \pm 10% |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | N/A |

VQE-05-009339
 VQE-06-010764
 VQE-06-010889

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Global Innovations Corp. 901 Hensley Drive Wylie, TX 75098, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 04RV5 Contact: Bob Noland Phone: 214-291-1427 Fax: E-Mail: bnoland@globalinnovationcorp.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|---|--|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: .119"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: Not Specified/.01" Aspect Ratio: 7.5:1 (Through Hole) Max. Number of Layers: 18 Min. Conductor Width: .004" Min. Conductor Space: .005" Part Mounting: MIX Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: N/A Finish System: HASL Hole Preparation: Permanganate Desmear, Plasma Etchback Alternate Construction: Foil Lamination Copper Plating: Electro-deposited Acid Copper Solder Resist: Dry Film, LPI Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper | VQE-03-4341 VQE-04-5599 VQE-04-5891 VQE-05-7288 |
|---|--|

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: Global Innovations Corp. 901 Hensley Drive Wylie, TX 75098, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 04RV5 Contact: Bob Noland Phone: 214-291-1427 Fax: EMail: bnoland@globalinnovationcorp.com |
|---|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|---|---|-------------------------------|
| Specification: Panel Size: Max./Min. Board Thickness: Max./Min. Base CU Thickness: Max./Min. Through Hole Size: Aspect Ratio: Max. Number of Layers: Min. Conductor Width: Min. Conductor Space: Part Mounting: Rigid Base Material: Flex Base Material: Finish System: Hole Preparation: Alternate Construction: Copper Plating: Solder Resist: Controlled Impedance: Hole Fill/Via Plug: Flex Usage: Hole Wall Conductive Coating: | MIL-PRF-31032/1, MIL-PRF-31032/2 18" X 24" .074"/Not Specified N/A Not Specified/.012" 6.2:1 (Through Hole) 12 .005" .005" MIX GI: Glass Base, Woven, Polyimide Resin, Heat Resistant N/A HASL Plasma Etchback N/A Electro-deposited Acid Copper LPI 62/37.5 ohms ±10% N/A N/A Electroless Copper | VQE-04-4957 VQE-05-7288 |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|---|--|---|
| Specification: Panel Size: Max./Min. Board Thickness: Max./Min. Base CU Thickness: Max./Min. Through Hole Size: Aspect Ratio: Max. Number of Layers: Min. Conductor Width: Min. Conductor Space: Part Mounting: Rigid Base Material: Flex Base Material: Finish System: Hole Preparation: Alternate Construction: Copper Plating: Solder Resist: Controlled Impedance: Hole Fill/Via Plug: Flex Usage: Hole Wall Conductive Coating: | MIL-PRF-31032/6 9" X 16" .098"/Not Specified N/A Not Specified/.031" 3.2:1 (Through Hole) 2 .005" .005" MIX GR: Glass Base, Nonwoven, Polytetrafluoroethylene Resin, Flame Resistant N/A HASL, Ni/Au Fluoroetch N/A Electro-deposited Acid Copper LPI N/A N/A N/A Electroless Copper | VQE-07-013270 VQE-09-017797 VQE-10-020600 |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Hamby Corporation 27704 Avenue Scott Valencia, CA 91355, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 07284 Contact: Sue Sharp Phone: 661-257-1924 Fax: 661-257-1213 E-Mail: suesharp@hambycorp.com |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|--|-------------------------------|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 12" X 18" Max./Min. Board Thickness: .035"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .05"/.02" (drilled) Aspect Ratio: 2:1 (Through Hole) Max. Number of Layers: 6 Min. Conductor Width: .009" Min. Conductor Space: .009" Part Mounting: MIX, SMT, THM Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: N/A Finish System: HASL, Ni/Au Hole Preparation: Plasma Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Electrodeposited Acid Copper Solder Resist: N/A Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper | VQE-09-017349 |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|---|-------------------------------|
| Specification: MIL-PRF-31032/3, MIL-PRF-31032/4 Panel Size: 18" X 24" Max./Min. Board Thickness: .085"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .035"/.018" Aspect Ratio: 5:1 (Through Hole) Max. Number of Layers: 11 Min. Conductor Width: .004" Min. Conductor Space: .004" Part Mounting: MIX, SMT, THM Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: IPC-4204/1 Acrylic Adhesive IPC-4204/11 Adhesiveless Finish System: HASL, Ni/Au Hole Preparation: Plasma Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Electrodeposited Acid Copper Solder Resist: N/A Controlled Impedance: Characteristic: 35-50 ohms +/-10%, Differential: 100 ohms +/-10% Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper | VQE-08-014596 |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Hans Brockstedt GmbH Clara-Immerwahr Strasse 7 24145 Kiel, Germany | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: C4831 Contact: Hilmar Klammer Phone: 0049-431-71966-0, -30 Fax: 0049-431-71966-29 EMail: klammer@brockstedt.de |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 9" X 13", 13" X 20", 15" X 21", 18" X 24" |
| Max./Min. Board Thickness: | .2"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | Not Specified/.004" (Laser Drilled) Not Specified/.01" (Mech. Drilled) |
| Aspect Ratio: | 1:1 (Blind Vias) 7:1 (Through Hole) |
| Max. Number of Layers: | 12 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .004" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | N/A |
| Finish System: | Electroless Nickel/Gold, Electroplated Nickel/Gold, Electroplated SnPb, Fused SnPb, HASL |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind Vias, Buried Vias, Foil Lamination, Laser Drilled Vias |
| Copper Plating: | Acid Copper |
| Solder Resist: | LPI |
| Controlled Impedance: | N/A |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-03-2619
 VQE-05-7480

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Hans Brockstedt GmbH Clara-Immerwahr Strasse 7 24145 Kiel, Germany | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: C4831 Contact: Hilmar Klammer Phone: 0049-431-71966-0, -30 Fax: 0049-431-71966-29 E-Mail: klammer@brockstedt.de |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 9" X 13", 13" X 20" |
| Max./Min. Board Thickness: | .2"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | Not Specified/.004" (Laser Drilled) Not Specified/.01" (Mech. Drilled) |
| Aspect Ratio: | 1:1 (Blind Vias) 7:1 (Through Hole) |
| Max. Number of Layers: | 12 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .004" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | IPC-4204/1 Acrylic Adhesive IPC-4204/11 Adhesiveless |
| Finish System: | Electroless Nickel/Gold, Electroplated Nickel/Gold, Electroplated SnPb, Fused SnPb, HASL |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind Vias, Buried Vias, Foil Lamination, Laser Drilled Vias |
| Copper Plating: | Acid Copper |
| Solder Resist: | LPI |
| Controlled Impedance: | N/A |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | Use A (Flex to Install), Use B (Continuous Flex) |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-03-2619
VQE-05-7480

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: KCA Electronics, Inc. 223 North Crescent Way Anaheim, CA 92801, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 1VUH8 Contact: Mr. Jeffrey Frost Phone: 714-239-2433 Fax: 714-239-2455 EMail: |
|---|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|---|-------------------------------|
| Specification: MIL-PRF-31032/3 Panel Size: 12" X 18" Max./Min. Board Thickness: .008"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: N/A Aspect Ratio: N/A Max. Number of Layers: 1 Min. Conductor Width: .004" Min. Conductor Space: .006" Part Mounting: THM Rigid Base Material: N/A Flex Base Material: Acrylic Adhesive Polyimide Coverlayer Copper Clad Polyimide with Acrylic Adhesive Finish System: HASL Hole Preparation: N/A Alternate Construction: N/A Copper Plating: N/A Solder Resist: N/A Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: Use A (Flex During Installation), Use B (Dynamic Flex) Hole Wall Conductive Coating: N/A | VQE-11-021796 |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|--|-------------------------------|
| Specification: MIL-PRF-31032/3, MIL-PRF-31032/4 Panel Size: 12" X 18" Max./Min. Board Thickness: .074"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: ".01" (Drilled Through Hole (before plating)) Aspect Ratio: 7:1 Max. Number of Layers: 16 Min. Conductor Width: .005" Min. Conductor Space: .004" Part Mounting: SMT Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: Acrylic Adhesive Polyimide Coverlayer Copper Clad Adhesiveless Polyimide Finish System: HASL Hole Preparation: Plasma Etchback/Desmear Alternate Construction: Blind Vias, Foil Lamination, Sequential Lamination Copper Plating: Acid Copper: DC Plate Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: Non-conductive Flex Usage: Use A (Flex During Installation) Hole Wall Conductive Coating: Electroless Copper | VQE-11-021796 |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: Lockheed Martin Systems Integration 1801 State Route 17C Owego, NY 13827, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 03640 Contact: Melita Nagerl Phone: 607-751-4665 Fax: 607-751-7714 EMail: melita.nagerl@lmco.com |
|---|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|---|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-00-0961 |
| Panel Size: | 18" X 24" | VQE-99-0130 |
| Max./Min. Board Thickness: | .2"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | Not Specified/.02" | |
| Aspect Ratio: | 8:1 (Through Hole) | |
| Max. Number of Layers: | 16 | |
| Min. Conductor Width: | .004" | |
| Min. Conductor Space: | .004" | |
| Part Mounting: | SMT, THM | |
| Rigid Base Material: | AF: Aramid Fabric, Woven, Majority Polyfunctional Epoxy Resin | |
| Flex Base Material: | N/A | |
| Finish System: | Fused SnPb, HASL, NiAu | |
| Hole Preparation: | Permanganate Desmear, Plasma Etchback | |
| Alternate Construction: | N/A | |
| Copper Plating: | Electro-deposited Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-01-0539 |
| Panel Size: | 18" X 24" | |
| Max./Min. Board Thickness: | .095"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | Not Specified/.014" | |
| Aspect Ratio: | 6.8:1 (Through Hole) | |
| Max. Number of Layers: | 14 | |
| Min. Conductor Width: | .004" | |
| Min. Conductor Space: | .004" | |
| Part Mounting: | SMT, THM | |
| Rigid Base Material: | BI: Aramid Fabric, Nonwoven, Polyimide Resin | |
| Flex Base Material: | N/A | |
| Finish System: | Fused SnPb, HASL, NiAu | |
| Hole Preparation: | Permanganate Desmear | |
| Alternate Construction: | N/A | |
| Copper Plating: | Electro-deposited Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Lockheed Martin Systems Integration 1801 State Route 17C Owego, NY 13827, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 03640 Contact: Melita Nagerl Phone: 607-751-4665 Fax: 607-751-7714 EMail: melita.nagerl@lmco.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|--|--|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 24" X 30" Max./Min. Board Thickness: .2"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: Not Specified/.018" Aspect Ratio: 8:1 (Through Hole) Max. Number of Layers: 24 Min. Conductor Width: .004" Min. Conductor Space: .004" Part Mounting: SMT, THM Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: N/A Finish System: Fused SnPb, HASL, NiAu Hole Preparation: Permanganate Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Electro-deposited Acid Copper Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper | VQE-00-0961 VQE-07-013268 VQE-07-013459 VQE-99-0130 |
|--|--|

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Lockheed Martin Systems Integration 1801 State Route 17C Owego, NY 13827, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 03640 Contact: Melita Nagerl Phone: 607-751-4665 Fax: 607-751-7714 EMail: melita.nagerl@lmco.com |
|---|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-00-0961 VQE-07-013459 VQE-99-0130 |
| Panel Size: | 24" X 30" | |
| Max./Min. Board Thickness: | .2"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | Not Specified/.018" | |
| Aspect Ratio: | 8:1 (Through Hole) | |
| Max. Number of Layers: | 16 | |
| Min. Conductor Width: | .004" | |
| Min. Conductor Space: | .004" | |
| Part Mounting: | SMT, THM | |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | Fused SnPb, HASL, NiAu | |
| Hole Preparation: | Permanganate Desmear, Plasma Etchback | |
| Alternate Construction: | N/A | |
| Copper Plating: | Electro-deposited Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: Lockheed Martin Systems Integration 1801 State Route 17C Owego, NY 13827, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 03640 Contact: Melita Nagerl Phone: 607-751-4665 Fax: 607-751-7714 EMail: melita.nagerl@lmco.com |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .11"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | Not Specified/.016" |
| Aspect Ratio: | 6:1 (Through Hole) |
| Max. Number of Layers: | 18 |
| Min. Conductor Width: | .003" |
| Min. Conductor Space: | .004" |
| Part Mounting: | SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | IC-4204/11 Adhesiveless IPC-4204/1 Acrylic Adhesive IPC-4204/2 IPC-4204/3 IPC-4204/4 |
| Finish System: | Fused SnPb, HASL |
| Hole Preparation: | Permanganate Desmear, Plasma Etchback |
| Alternate Construction: | N/A |
| Copper Plating: | Electro-deposited Acid Copper |
| Solder Resist: | LPI |
| Controlled Impedance: | N/A |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-00-0684
VQE-07-013459

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| MANUFACTURER INFORMATION: Micom Corp. 475 Old Highway 8 NW New Brighton, MN 55112, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 34076 Contact: Larry Leonard Phone: 651-604-2639 Fax: 651-636-1352 EMail: lleonard@micomcircuits.com |
|--|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .239"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | Not Specified/.007" |
| Aspect Ratio: | 11:1 (Through Hole) |
| Max. Number of Layers: | 28 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .004" |
| Part Mounting: | SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | N/A |
| Finish System: | Fuse Following SnPb Plate, HASL |
| Hole Preparation: | Permanganate Desmear, Permanganate Etchback, Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind & Buried Vias |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry Film, LPI |
| Controlled Impedance: | Characteristic $\pm 10\%$, Differential $\pm 10\%$ |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | N/A |

VQE-02-002780
 VQE-03-2980

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| <p>MANUFACTURER INFORMATION: Pioneer Circuits, Inc. 3000 S. Shannon Street Santa Ana, CA 92704-6321, US</p> | | <p>CAGE Code: 65723 Contact: Elias Gabriel Phone: 714-641-3132 x234 Fax: 714-641-3120 EMail:</p> |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .177"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .206"/.0135" |
| Aspect Ratio: | 11:1 |
| Max. Number of Layers: | 22 |
| Min. Conductor Width: | .0035" |
| Min. Conductor Space: | .0035" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | G1: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Electrolytic Ni/Au Bondable, HASL, Reflowed Tin/Lead Fused, SMOBC, Selective Tin/Lead Strip |
| Hole Preparation: | Permanganate Desmear, Plasma Etchback |
| Alternate Construction: | Blind/Buried Vias, Filled Via Holes, Plated Sub-Assemblies, Sequential Lamination |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry Film, LPI |
| Controlled Impedance: | Characteristic & Differential \pm 10% |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-09-017323
VQE-09-017656

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|--|--|---|
| <p>MANUFACTURER INFORMATION: Pioneer Circuits, Inc. 3000 S. Shannon Street Santa Ana, CA 92704-6321, US</p> | | <p>CAGE Code: 65723 Contact: Elias Gabriel Phone: 714-641-3132 x234 Fax: 714-641-3120 EMail:</p> |
|--|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .275"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .252"/.012" |
| Aspect Ratio: | 11:1 |
| Max. Number of Layers: | 20 |
| Min. Conductor Width: | .0035" |
| Min. Conductor Space: | .0035" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Electrolytic Ni/Au Bondable, HASL, Reflowed Tin/Lead Fused, SMOBC, Selective Tin/Lead Strip |
| Hole Preparation: | Permanganate Desmear, Plasma Etchback |
| Alternate Construction: | Blind/Buried Vias, Filled Via Holes, Plated Sub-Assemblies, Sequential Lamination |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry Film, LPI |
| Controlled Impedance: | Characteristic & Differential \pm 10% |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-09-017323
VQE-09-017656

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| <p>MANUFACTURER INFORMATION: Pioneer Circuits, Inc. 3000 S. Shannon Street Santa Ana, CA 92704-6321, US</p> | | <p>CAGE Code: 65723 Contact: Elias Gabriel Phone: 714-641-3132 x234 Fax: 714-641-3120 EMail:</p> |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 18" X 26" |
| Max./Min. Board Thickness: | .231"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .169"/.02" |
| Aspect Ratio: | 8.5:1 |
| Max. Number of Layers: | 22 |
| Min. Conductor Width: | .003" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | GF (Epoxy Glass) |
| Flex Base Material: | Adhesiveless Epoxy |
| Finish System: | ENIG, Electrolytic Ni/Au (Bondable), HASL, Reflowed Tin/Lead (Fused), SMOBC, Selective Tin/Lead Strip |
| Hole Preparation: | Permanganate Desmear, Plasma Etchback |
| Alternate Construction: | Blind/Buried Vias, Filled Via Holes, Plated Sub-Assemblies, Sequential Lamination |
| Copper Plating: | Acid Copper |
| Solder Resist: | LPI |
| Controlled Impedance: | Characteristic & Differential +/- 10% |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | Class A (Flex During Installation) |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-09-017323
VQE-09-017656
VQE-10-020651

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| <p>MANUFACTURER INFORMATION: Pioneer Circuits, Inc. 3000 S. Shannon Street Santa Ana, CA 92704-6321, US</p> | | <p>CAGE Code: 65723 Contact: Elias Gabriel Phone: 714-641-3132 x234 Fax: 714-641-3120 EMail:</p> |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .1"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .193"/.016" |
| Aspect Ratio: | 6:1 |
| Max. Number of Layers: | 10 |
| Min. Conductor Width: | .003" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | Adhesive Polyimide |
| Finish System: | ENIG, Electrolytic Ni/Au Bondable, HASL, Reflowed Tin/Lead Fused, SMOBC, Selective Tin/Lead Strip |
| Hole Preparation: | Permanganate Copper, Plasma Etchback |
| Alternate Construction: | Blind/Buried Vias, Filled Via Holes, Plated Sub-Assemblies, Sequential Lamination |
| Copper Plating: | Acid Copper |
| Solder Resist: | LPI |
| Controlled Impedance: | Characteristic & Differential \pm 10% |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | Class A Flex During Installation, Class B Dynamic |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-09-017323
VQE-09-017656

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| <p>MANUFACTURER INFORMATION: Pioneer Circuits, Inc. 3000 S. Shannon Street Santa Ana, CA 92704-6321, US</p> | | <p>CAGE Code: 65723 Contact: Elias Gabriel Phone: 714-641-3132 x234 Fax: 714-641-3120 EMail:</p> |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 24" X 36" |
| Max./Min. Board Thickness: | .185"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .167"/.013" |
| Aspect Ratio: | 11:1 |
| Max. Number of Layers: | 26 |
| Min. Conductor Width: | .003" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | G1: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | Adhesiveless Polyimide |
| Finish System: | ENIG, Electrolytic Ni/Au Bondable, HASL, Reflowed Tin/Lead Fused, SMOBC, Selective Tin/Lead Strip |
| Hole Preparation: | Permanganate Desmear, Plasma Etchback |
| Alternate Construction: | Blind/Buried Vias, Bood Binder, Filled Via Holes, Plated Sub-Assemblies, Sequential Lamination |
| Copper Plating: | Acid Copper |
| Solder Resist: | LPI |
| Controlled Impedance: | Characteristic & Differential \pm 10% |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | Class A Flex During Installation, Class B Dynamic |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-09-017323
VQE-09-017656

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| <p>MANUFACTURER INFORMATION:</p> <p>PNC, Inc. 115 East Centre Street Nutley, NJ 07110, US</p> | | <p>CAGE Code: 66766</p> <p>Contact: Carmela Conte Phone: 973-284-1600 Fax: EMail: carmela@pnconline.com</p> |
|--|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|---|-------------------------------|
| <p>Specification: MIL-PRF-31032/1, MIL-PRF-31032/2</p> <p>Panel Size: 18" X 22"</p> <p>Max./Min. Board Thickness: .093"/Not Specified</p> <p>Max./Min. Base CU Thickness: N/A</p> <p>Max./Min. Through Hole Size: .12"/.014"</p> <p>Aspect Ratio: 6.6:1</p> <p>Max. Number of Layers: 10</p> <p>Min. Conductor Width: .008"</p> <p>Min. Conductor Space: .008"</p> <p>Part Mounting: MIX, SMT, THM</p> <p>Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant</p> <p>Flex Base Material: N/A</p> <p>Finish System: HASL</p> <p>Hole Preparation: Permanganate Desmear</p> <p>Alternate Construction: Foil Lamination</p> <p>Copper Plating: Electroplated Acid Copper</p> <p>Solder Resist: LPI</p> <p>Controlled Impedance: N/A</p> <p>Hole Fill/Via Plug: N/A</p> <p>Flex Usage: N/A</p> <p>Hole Wall Conductive Coating: Electroless Copper</p> | <p>VQE-10-19440</p> |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Printed Circuits, Inc. 1200 West 96th Street Bloomington, MN 55431, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 65114 Contact: Jim Smith Phone: 612-888-7900 Fax: 612-888-2719 E-Mail: jsmith@printedcircuits.com |
|---|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|--|-------------------------------|
| Specification: MIL-PRF-31032/3, MIL-PRF-31032/4 Panel Size: 12" X 18", 18" X 24" Max./Min. Board Thickness: .12"/Not Specified Max./Min. Base CU Thickness: (1/2 oz.) Max./Min. Through Hole Size: Not Specified/.01" Aspect Ratio: 10:1 (Through Hole) Max. Number of Layers: 16 Min. Conductor Width: .004" Min. Conductor Space: .005" (+/- 10%) Part Mounting: MIX, SMT, THM Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: IPC-4204/1 Acrylic Adhesive IPC-4204/11 Adhesiveless Finish System: Electroless Ni/Au, Electrolytic Ni/Au, Fused SnPb, HASL, SMOBC Hole Preparation: Plasma Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Electrolytic Acid Copper Solder Resist: Dry Film, LPI, Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: Class A Flex to Install, Class B Continuous Flex Hole Wall Conductive Coating: Electroless Copper | VQE-01-0024 |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: Pro-Tech Interconnect Solutions 4300 Peavey Road Chaska, MN 55318-2351, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 3CP65 Contact: Harland Kooda Phone: 952-442-2189 Fax: 952-442-2472 E-Mail: |
|---|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|---|-------------------------------|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: .1"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: ".024" ((drilled)) Aspect Ratio: 4:1 Max. Number of Layers: 10 Min. Conductor Width: .005" Min. Conductor Space: .005" Part Mounting: N/A Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: N/A Finish System: HASL Hole Preparation: Plasma Desmear, Etchback Alternate Construction: N/A Copper Plating: Direct Current Plate Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Direct Metallization | VQE-11-021704 |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|--|-------------------------------|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: .1"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: ".024" ((drilled)) Aspect Ratio: 4:1 Max. Number of Layers: 10 Min. Conductor Width: .005" Min. Conductor Space: .005" Part Mounting: N/A Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: N/A Finish System: HASL Hole Preparation: Plasma Desmear, Etchback Alternate Construction: N/A Copper Plating: Direct Current Plate Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Direct Metallization | VQE-11-021704 |

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|--|--|--|
| <p>MANUFACTURER INFORMATION: Sanmina-SCI (Owego) 1200 Taylor Road Owega, NY 13827, US</p> | | <p>CAGE Code: 4GZ84 Contact: Rick Sylvain Phone: 607-689-5543 Fax: EMail: rick.sylvain@sanmina-sci.com</p> |
|--|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|---|-------------------------------|
| <p>Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: .11"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .13"/.012" Aspect Ratio: 9.3:1 Max. Number of Layers: 12 Min. Conductor Width: .008" Min. Conductor Space: .0045" Part Mounting: MIX, SMT, THM Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: N/A Finish System: HASL Hole Preparation: Plasma Etchback Alternate Construction: Foil Lamination Copper Plating: Electroplated Acid Copper Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper</p> | <p>VQE-11-021597</p> |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Sanmina-SCI (San Jose) 2050 Bering Drive San Jose, CA 95131, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 3DR67 Contact: Darrell Myers Phone: 408-964-6515 Fax: 408-964-6453 EMail: darrell.myers@sanmina-sci.com |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|---|--------------------------------|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: .062"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .25"/.01" Aspect Ratio: 6:1 (Through Hole) Max. Number of Layers: 8 Min. Conductor Width: .003" Min. Conductor Space: .003" Part Mounting: SMT, THM Rigid Base Material: GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: N/A Finish System: ENIG, HASL, ImmAg, OSP Hole Preparation: Plasma Desmear Alternate Construction: Buried Via Mechanical Drill, Foil Lamination, Sequential Lamination Copper Plating: Acid Copper Solder Resist: Dry Film, LPI Controlled Impedance: 50-110 ohms ± 5% Hole Fill/Via Plug: Epoxy, Silver Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper | VQE-06-011137 VQE-10-019381 |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Sanmina-SCI (San Jose) 2050 Bering Drive San Jose, CA 95131, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 3DR67 Contact: Darrell Myers Phone: 408-964-6515 Fax: 408-964-6453 EMail: darrell.myers@sanmina-sci.com |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|--|-------------------------------|
| Specification: N/A Panel Size: N/A Max./Min. Board Thickness: N/A Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: N/A Aspect Ratio: N/A Max. Number of Layers: N/A Min. Conductor Width: N/A Min. Conductor Space: N/A Part Mounting: N/A Rigid Base Material: N/A Flex Base Material: N/A Finish System: N/A Hole Preparation: N/A Alternate Construction: N/A Copper Plating: N/A Solder Resist: N/A Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: N/A | N/A |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Speedy Circuits, Inc. 5331 McFadden Avenue Huntington Beach, CA 92649-1204, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 66982 Contact: Jan Lesky Phone: 714-766-6243 Fax: 714-899-7074 EMail: |
|---|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-08-016434 |
| | | VQE-10-021007 |
| Panel Size: | 18" X 24" | |
| Max./Min. Board Thickness: | .11"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | .194"/.015" | |
| Aspect Ratio: | 7:1 | |
| Max. Number of Layers: | 14 | |
| Min. Conductor Width: | .005" | |
| Min. Conductor Space: | .005" | |
| Part Mounting: | SMT, THM | |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant | |
| | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | Electroless Nickel Immersion Gold, HASL | |
| Hole Preparation: | Plasma Desmear, Plasma Etchback | |
| Alternate Construction: | Foil Lamination | |
| Copper Plating: | Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | 100/50 ohms +/-10% Characteristic, 100/50 ohms +/-10% Differential | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Speedy Circuits, Inc. 5331 McFadden Avenue Huntington Beach, CA 92649-1204, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 66982 Contact: Jan Lesky Phone: 714-766-6243 Fax: 714-899-7074 EMail: |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .13"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .048"/.02" |
| Aspect Ratio: | 7:1 |
| Max. Number of Layers: | 18 |
| Min. Conductor Width: | .005" |
| Min. Conductor Space: | .005" |
| Part Mounting: | SMT, THM |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | Adhesiveless Polyimide |
| Finish System: | Electro-deposited Fused SnPb, Electrolytic Hard Gold, Electrolytic Nickel, Electrolytic Soft Gold, HASL |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Foil Lamination |
| Copper Plating: | Electro-deposited Acid Copper |
| Solder Resist: | Dry Film, LPI |
| Controlled Impedance: | 100/50 ohms +/-10% Characteristic, 100/50 ohms +/-10% Differential |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | Class A (Flex During Installation), Class B (Dynamic) |
| Hole Wall Conductive Coating: | Electroless Copper |

VQE-08-016434
 VQE-10-019157
 VQE-10-021007

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: Speedy Circuits, Inc. 5331 McFadden Avenue Huntington Beach, CA 92649-1204, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 66982 Contact: Jan Lesky Phone: 714-766-6243 Fax: 714-899-7074 E-Mail: |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/5 |
| Panel Size: | 12" X 18" |
| Max./Min. Board Thickness: | .068"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .125"/.01" |
| Aspect Ratio: | 6:1 |
| Max. Number of Layers: | 10 |
| Min. Conductor Width: | .005" |
| Min. Conductor Space: | .005" |
| Part Mounting: | SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | N/A |
| Finish System: | Electro-deposited Fused SnPb, Electrolytic Hard Gold, Electrolytic Nickel, Electrolytic Soft Gold, HASL |
| Hole Preparation: | Plasma Desmear |
| Alternate Construction: | Electro-deposited Fused SnPb, Electrolytic Hard and Soft Gold, Electrolytic Nickel, HASL |
| Copper Plating: | Acid Copper |
| Solder Resist: | LPI, |
| Controlled Impedance: | 50 ohms +/- 10% (Characteristic, Differential) |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Ceramic Filler, Epoxy Resin - Mixed, PTFE Resin, With or Without Woven or Non-woven E-Glass, Woven E-Glass |

VQE-09-018657
 VQE-10-021007

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: Speedy Circuits, Inc. 5331 McFadden Avenue Huntington Beach, CA 92649-1204, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 66982 Contact: Jan Lesky Phone: 714-766-6243 Fax: 714-899-7074 E-Mail: |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|---|---|
| Specification: Panel Size: Max./Min. Board Thickness: Max./Min. Base CU Thickness: Max./Min. Through Hole Size: Aspect Ratio: Max. Number of Layers: Min. Conductor Width: Min. Conductor Space: Part Mounting: Rigid Base Material: Flex Base Material: Finish System: Hole Preparation: Alternate Construction: Copper Plating: Solder Resist: Controlled Impedance: Hole Fill/Via Plug: Flex Usage: Hole Wall Conductive Coating: | MIL-PRF-31032/5, MIL-PRF-31032/6 12" X 18" .1"/Not Specified N/A .048"/.02" .125"/.01" 10:1 10 .005" .005" SMT, THM GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant N/A Electro-deposited Fused SnPb, Electrolytic Hard and Soft Gold, Electrolytic Nickel, HASL Plasma Desmear N/A Acid Copper LPI 100/50 ohms +/-10% Characteristic, Differential N/A N/A Electroless Copper |
|---|---|

VQE-09-018657

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|--|---|--|
| <p>MANUFACTURER INFORMATION: Speedy Circuits, Inc. 5331 McFadden Avenue Huntington Beach, CA 92649-1204, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 66982 Contact: Jan Lesky Phone: 714-766-6243 Fax: 714-899-7074 EMail:</p> |
|--|---|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|--|-------------------------------|
| <p>Specification: MIL-PRF-31032/6 Panel Size: 12" X 18" Max./Min. Board Thickness: .036"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .048"/.02" Aspect Ratio: 2:1 (Through Hole) Max. Number of Layers: 2 Min. Conductor Width: .005" Min. Conductor Space: .005" Part Mounting: SMT Rigid Base Material: GR: Glass Base, Nonwoven, Polytetrafluoroethylene Resin, Flame Resistant GY: Glass Base, Woven, Polytetrafluoroethylene Resin, Flame Resistant, for Microwave Application Flex Base Material: N/A Finish System: Electro-deposited fused SnPb Hole Preparation: N/A Alternate Construction: N/A Copper Plating: Acid Copper Solder Resist: N/A Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper</p> | <p>VQE-08-016434</p> |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Strataflex Corp. 11 Dohme Avenue Toronto, Ontario, Canada M4B 1Y7 | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 38661 Contact: Peter Pialis Phone: 416-752-2224 Fax: 416-752-6719 E-Mail: ppialis@strataflex.ca |
|--|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|---|--------------------------------|
| Specification: MIL-PRF-31032/3, MIL-PRF-31032/4 Panel Size: 12" X 18" Max./Min. Board Thickness: .035"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .011"/Not Specified Aspect Ratio: 3:1 (Through Hole) Max. Number of Layers: 7 Min. Conductor Width: .007" Min. Conductor Space: .007" Part Mounting: SM, THM Rigid Base Material: N/A Flex Base Material: FR4 IPC-4101/21 Flexible Polyimide Clad IPC-4204/1 Flexible Polyimide Film IPC-4202/1 Flexible Polyimide Film/Acrylic IPC-4203/1 Woven E-Glass, Polyimide Resin IPC-4101/41 Finish System: HASL Hole Preparation: Plasma Etchback Alternate Construction: N/A Copper Plating: Electrodeposited Acid Copper Solder Resist: N/A Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: N/A | VQE-04-005354 VQE-08-015729 |
|---|--------------------------------|

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| MANUFACTURER INFORMATION: Strataflex Corp. 11 Dohme Avenue Toronto, Ontario, Canada M4B 1Y7 | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 38661 Contact: Peter Pialis Phone: 416-752-2224 Fax: 416-752-6719 EMail: ppialis@strataflex.ca |
|--|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 12" X 18" |
| Max./Min. Board Thickness: | .094"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | Not Specified/.008" |
| Aspect Ratio: | 12:1 (Through Hole) |
| Max. Number of Layers: | 12 |
| Min. Conductor Width: | .006" |
| Min. Conductor Space: | .004" |
| Part Mounting: | N/A |
| Rigid Base Material: | N/A |
| Flex Base Material: | Flexible Polyimide Film/Acrylic IC-4203/1 Flexible Polyimide IPC-4204/11 Woven E-Glass, Polyimide Resin IPC-4101/40 Woven E-Glass, Polyimide Resin IPC-4101/41 Woven E-Glass, Polyimide Resin IPC-4101/42 |
| Finish System: | HASL |
| Hole Preparation: | Plasma Etchback |
| Alternate Construction: | N/A |
| Copper Plating: | Electrodeposited Acid Copper |
| Solder Resist: | TA140 PSR-4000 HG |
| Controlled Impedance: | N/A |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Direct Metallization |

VQE-04-005354
 VQE-08-015729

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| <p>MANUFACTURER INFORMATION: Strataflex Corp. 11 Dohme Avenue Toronto, Ontario, Canada M4B 1Y7</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 38661 Contact: Peter Pialis Phone: 416-752-2224 Fax: 416-752-6719 EMail: ppialis@strataflex.ca</p> |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|---|-------------------------------|
| <p>Specification: MIL-PRF-31032/3, MIL-PRF-31032/4 Panel Size: 12" X 18" Max./Min. Board Thickness: .035"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .011"/Not Specified Aspect Ratio: 3:1 (Through Hole) Max. Number of Layers: 7 Min. Conductor Width: .007" Min. Conductor Space: .007" Part Mounting: SMT, THM Rigid Base Material: FR4-IPC-4101/21 Flexible Polyimide Clad IPC-4204/1 Flexible Polyimide Film IPC-4202/1 Flexible Polyimide Film/Acylic IPC-4203/1 Flex Base Material: N/A Finish System: HASL Hole Preparation: Plasma Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Acid Copper Solder Resist: N/A Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: N/A</p> | <p>VQE-04-5354</p> |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Santa Ana) 2630 South Harbor Boulevard Santa Ana, CA 92704, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 1WQ42 Contact: Terry Lichte Phone: 714-241-0303, x3127 Fax: 714-241-0708 EMail: tlichte@ttmtech.comca |
|---|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|---|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-05-8644 |
| | | VQE-06-011211 |
| Panel Size: | 18" X 24" | |
| Max./Min. Board Thickness: | .2"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | .044"/.013" | |
| Aspect Ratio: | 14:1 (Through Hole) | |
| Max. Number of Layers: | 24 | |
| Min. Conductor Width: | .003" | |
| Min. Conductor Space: | .003" | |
| Part Mounting: | SMT, THM | |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG, Fused SnPb, HASL, ImmAg, OSP | |
| Hole Preparation: | Plasma Desmear, Plasma Etchback | |
| Alternate Construction: | Aspect Ratio Microvias: 1:1, Min. Blind Via: 0.005" Laser, Min. Buried Via: 0.0135" Mechanical Drill, Sequential Lamination | |
| Copper Plating: | Acid Copper | |
| Solder Resist: | Dry Film, LPI | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | N/A | |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|---|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-05-8644 |
| | | VQE-06-011211 |
| Panel Size: | 21" X 28" | |
| Max./Min. Board Thickness: | .2"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | .044"/.013" | |
| Aspect Ratio: | 14:1 (Through Hole) | |
| Max. Number of Layers: | 24 | |
| Min. Conductor Width: | .003" | |
| Min. Conductor Space: | .003" | |
| Part Mounting: | SMT, THM | |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG, Fused SnPb, HASL, ImmAg, OSP | |
| Hole Preparation: | Plasma Desmear, Plasma Etchback | |
| Alternate Construction: | Aspect Ratio Microvias: 1:1, Min. Blind Via: 0.005" Laser, Min. Buried Via: 0.0135" Mechanical Drill, Sequential Lamination | |
| Copper Plating: | Acid Copper | |
| Solder Resist: | Dry Film, LPI | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | N/A | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Santa Clara) 400 Matthew Street Santa Clara, CA 95050, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 65916 Contact: Nellie Guitierrez Phone: 408-486-3184 Fax: 408-727-1003 EMail: nellie.guitierrez@ttmtech.com |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|----------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-03-003888 VQE-10-020500 VQE-10-020581 |
| Panel Size: | 18" X 24" | |
| Max./Min. Board Thickness: | .12"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | .191"/.012" | |
| Aspect Ratio: | 9:1 (Through Hole) | |
| Max. Number of Layers: | 20 | |
| Min. Conductor Width: | .004" | |
| Min. Conductor Space: | .004" | |
| Part Mounting: | MIX, SM, THM | |
| Rigid Base Material: | GF (Woven E-Glass, Epoxy Resin) | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG, Electrolytic Ni, HASL | |
| Hole Preparation: | Plasma Desmear, Plasma Etchback | |
| Alternate Construction: | Blind Vias | |
| Copper Plating: | Electrolytic Acid Copper | |
| Solder Resist: | LPI, Screen Printed | |
| Controlled Impedance: | +/-10% tolerance | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|-------------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-03-003888 VQE-10-020500 VQE-10-020581 |
| Panel Size: | 18" X 24" | |
| Max./Min. Board Thickness: | .12"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | .191"/.012" | |
| Aspect Ratio: | 9:1 | |
| Max. Number of Layers: | 12 | |
| Min. Conductor Width: | .004" | |
| Min. Conductor Space: | .004" | |
| Part Mounting: | MIX, SM, THM | |
| Rigid Base Material: | GI (Woven E-Glass, Polyimide Resin) | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG, Electrolytic Ni, HASL | |
| Hole Preparation: | Plasma Desmear, Plasma Etchback | |
| Alternate Construction: | Blind Vias | |
| Copper Plating: | Electrolytic Acid Copper | |
| Solder Resist: | LPI, Screen Printed | |
| Controlled Impedance: | +/- 10% tolerance | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Santa Clara) 400 Matthew Street Santa Clara, CA 95050, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 65916 Contact: Nellie Guitierrez Phone: 408-486-3184 Fax: 408-727-1003 EMail: nellie.guitierrez@ttmtech.com |
|--|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

Specification: MIL-PRF-31032/1, MIL-PRF-31032/2, MIL-PRF-31032/3, MIL-PRF-31032/4

Panel Size: 18" X 24", 18" X 24"

Max./Min. Board Thickness: .12"/Not Specified
.12"/Not Specified

Max./Min. Base CU Thickness: N/A

Max./Min. Through Hole Size: .191"/.012"
.191"/.012"

Aspect Ratio: 6.45:1
9:1

Max. Number of Layers: 11, 16

Min. Conductor Width: .004"
.004"

Min. Conductor Space: .004"
.004"

Part Mounting: MIX, MIX, SM, SM, THM, THM

Rigid Base Material: BI (Aramid Fabric, Non-Woven, Polyimide Resin)
GF (Woven E-Glass, Epoxy Resin)
GI (Woven E-Glass, Polyimide Resin)

Flex Base Material: IPC-4203/1 (Acrylic Adhesive Coverlay)
IPC-4204/11 (Adhesiveless Polyimide)

Finish System: ENIG, ENIG, Electrolytic Ni, Electrolytic Ni, HASL, HASL

Hole Preparation: Plasma Desmear, Plasma Etchback

Alternate Construction: Blind Vias

Copper Plating: Electrolytic Acid Copper, Electrolytic Acid Copper

Solder Resist: LPI, Screen Printed

Controlled Impedance: +/- 10% tolerance

Hole Fill/Via Plug: N/A

Flex Usage: N/A

Hole Wall Conductive Coating: Electroless Copper, Electroless Copper

VQE-03-003888
 VQE-03-003895
 VQE-10-020500
 VQE-10-020500
 VQE-10-020581
 VQE-10-020581
 VQE-11-021181

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Santa Clara) 400 Matthew Street Santa Clara, CA 95050, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 65916 Contact: Nellie Guitierrez Phone: 408-486-3184 Fax: 408-727-1003 EMail: nellie.guitierrez@ttmtech.com |
|--|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|--|---|
| Specification: MIL-PRF-31032/3, MIL-PRF-31032/4 Panel Size: 18" X 24" Max./Min. Board Thickness: .1"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .045"/.031" Aspect Ratio: 9:1 (Through Hole) Max. Number of Layers: 10 Min. Conductor Width: .004" Min. Conductor Space: .004" Part Mounting: MIX, SM, THM Rigid Base Material: GF (Woven E-Glass, Epoxy Resin) GI (Woven E-Glass, Polyimide Resin) Flex Base Material: IPC-4203/1 (Acrylic Adhesive Coverlay) IPC-4204/1 (Adhesive Polyimide) Finish System: ENIG, Electrolytic Ni, HASL Hole Preparation: Plasma Desmear, Plasma Etchback Alternate Construction: N/A Copper Plating: Electrolytic Acid Copper Solder Resist: N/A Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper | VQE-03-003895 VQE-10-020500 VQE-10-020581 |
|--|---|

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Stafford) 4 Old Monson Road P.O. Box 145, Stafford, CT 77497, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 5L706 Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 EMail: michele.hebert@tycoelectroni cs.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|--|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 30" X 32" |
| Max./Min. Board Thickness: | .1"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .067"/.032" (drilled) |
| Aspect Ratio: | 3:1 (Through hole) |
| Max. Number of Layers: | 10 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, Press Fit, SM, THM |
| Rigid Base Material: | GC: Glass Base, Woven E, Reinforcement, Majority Cyanate Ester, Flame Resistant SC: Glass Base, Woven S-2, Fiber, Majority Cyanate Ester, Flame Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Electrolytic Nickel, Electrolytic Soft & Hard Gold, HASL, Hot Oil Reflow following SnPb plate |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind and Buried Vias, Buried Resistors, Micro Vias, Multiple Laminations |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry-Film, LPI, Wet Mask |
| Controlled Impedance: | Characteristic, Differential, Dual Stripline, Embedded Microstrip, Microstrip, Range 30-150 ohms (+/- 10%) |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |
| Max. Base Cu Weight | 1 oz. |

VQE-03-003348
 VQE-09-18855

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Stafford) 4 Old Monson Road P.O. Box 145, Stafford, CT 77497, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 5L706 Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 EMail: michele.hebert@tycoelectroni cs.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|--|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .1"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .045"/.032" (drilled) |
| Aspect Ratio: | 3:1 (Through hole) |
| Max. Number of Layers: | 10 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, Press Fit, SM, THM |
| Rigid Base Material: | GM: Glass Base, Woven, Triazine and/or Bismaleimide Modified Epoxy Resin, Flame Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Electrolytic Nickel, Electrolytic Soft & Hard Gold, HASL, Hot Oil Reflow following SnPb plate |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind and Buried Vias, Buried Resistors, Micro Vias, Multiple Laminations |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry-Film, LPI, Wet Mask |
| Controlled Impedance: | Characteristic, Differential, Dual Stripline, Embedded Microstrip, Microstrip, Range 30-150 ohms (+/- 10%) |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |
| Max. Base Cu Weight | 1 oz. |

VQE-03-003348
 VQE-09-18855

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Stafford) 4 Old Monson Road P.O. Box 145, Stafford, CT 77497, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 5L706 Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 EMail: michele.hebert@tycoelectroni cs.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|--|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 30" X 54" |
| Max./Min. Board Thickness: | .4"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .195"/.0079" (drilled) |
| Aspect Ratio: | 14:1 (Through Hole) |
| | 2.5:1 (Buried Vias) |
| Max. Number of Layers: | 50 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, Press Fit, SM, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Electrolytic Nickel, Electrolytic Soft & Hard Gold, HASL, Hot Oil Reflow following SnPb plate, Reflowed Solder |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind and Buried Vias, Buried Resistors, Copper Invar Copper, Micro Vias, Multiple Laminations |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry Film, LPI, Wet Mask |
| Controlled Impedance: | Characteristic, Differential, Dual Stripline, Embedded Microstrip, Microstrip, Range 30-150 ohms (+/- 10%) |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |
| Max. Base Cu Weight | 1 oz. |

VQE-03-3348
 VQE-09-18855

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Stafford) 4 Old Monson Road P.O. Box 145, Stafford, CT 77497, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 5L706 Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 EMail: michele.hebert@tycoelectroni cs.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|--|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .13"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .133"/.0118" (drilled) |
| Aspect Ratio: | 11:1 (Through hole) 2.5:1 (Buried Vias) |
| Max. Number of Layers: | 32 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, Press Fit, SM, THM |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Electrolytic Nickel, Electrolytic Soft & Hard Gold, HASL, Hot Oil Reflow following SnPb plate |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind and Buried Vias, Buried Resistors, Copper Invar Copper, Micro Vias, Multiple Laminations |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry-Film, LPI, Wet Mask |
| Controlled Impedance: | Characteristic, Differential, Dual Stripline, Embedded Microstrip, Microstrip, Range 30-150 ohms (+/- 10%) |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |
| Max. Base Cu Weight | 1 oz. |

VQE-03-003348
 VQE-09-18855

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Stafford) 4 Old Monson Road P.O. Box 145, Stafford, CT 77497, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 5L706 Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 EMail: michele.hebert@tycoelectroni cs.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|--------------------------------------|--|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 16" X 18" |
| Max./Min. Board Thickness: | .1"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .045"/.0118" (drilled) |
| Aspect Ratio: | 6:1 (Through hole) |
| Max. Number of Layers: | 10 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, Press Fit, SM, THM |
| Rigid Base Material: | BI: Aramid Fabric, Nonwoven, Polyimide Resin |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Electrolytic Nickel, Electrolytic Soft & Hard Gold, HASL, Hot Oil Reflow following SnPb plate |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind and Buried Vias, Buried Resistors, Micro Vias, Multiple Laminations |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry-Film, LPI, Wet Mask |
| Controlled Impedance: | Characteristic, Differential, Dual Stripline, Embedded Microstrip, Microstrip, Range 30-150 ohms (+/- 10%) |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |
| Max. Base Cu Weight | 1 oz. |

VQE-03-003348
 VQE-09-18855

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| <p>MANUFACTURER INFORMATION: TTM Technologies (Stafford) 4 Old Monson Road P.O. Box 145, Stafford, CT 77497, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 5L706 Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 EMail: michele.hebert@tycoelectroni cs.com</p> |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|--|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .1"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .045"/.032" (drilled) |
| Aspect Ratio: | 3:1 (Through hole) |
| Max. Number of Layers: | 10 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, Press Fit, SM, THM |
| Rigid Base Material: | AF: Aramid Fabric, Woven, Majority Polyfunctional Epoxy Resin |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Electrolytic Nickel, Electrolytic Soft & Hard Gold, HASL, Hot Oil Reflow following SnPb plate |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind and Buried Vias, Buried Resistors, Micro Vias, Multiple Laminations |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry-Film, LPI, Wet Mask |
| Controlled Impedance: | Characteristic, Differential, Dual Stripline, Embedded Microstrip, Microstrip, Range 30-150 ohms (+/- 10%) |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |
| Max. Base Cu Weight | 1 oz. |

VQE-03-003348
VQE-09-18855

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Stafford) 4 Old Monson Road P.O. Box 145, Stafford, CT 77497, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 5L706 Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 EMail: michele.hebert@tycoelectroni cs.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|--|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | N/A |
| Max./Min. Base CU Thickness: | .002"/" |
| Max./Min. Through Hole Size: | .045"/.0118" (drilled) |
| Aspect Ratio: | 7:1 (Through hole) |
| Max. Number of Layers: | 10 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, Press Fit, SM, THM |
| Rigid Base Material: | BF: Aramid Fabric, Nonwoven, Epoxy Resin |
| Flex Base Material: | N/A |
| Finish System: | ENIG, Electrolytic Nickel, Electrolytic Soft & Hard Gold, HASL, Hot Oil Reflow following SnPb plate |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind and Buried Vias, Buried Resistors, Micro Vias, Multiple Laminations |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry-Film, LPI, Wey Mask |
| Controlled Impedance: | Characteristic, Differential, Dual Stripline, Embedded Microstrip, Microstrip, Range 30-150 ohms (+/- 10%) |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |
| Max. Base Cu Weight | 1 oz. |

VQE-03-003348
 VQE-09-18855

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|--|
| MANUFACTURER INFORMATION: TTM Technologies (Stafford) 4 Old Monson Road P.O. Box 145, Stafford, CT 77497, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 5L706 Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 E-Mail: michele.hebert@tycoelectroni cs.com |
|---|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|--|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .125"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .063"/.013" (drilled) |
| Aspect Ratio: | 9:1 (Through Hole) |
| Max. Number of Layers: | 24 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .003" |
| Part Mounting: | MIX, Press Fit, SM, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | 4201/11 Acrylic Adhesive Coverlayer 4204/11 Adhesive Polyimide |
| Finish System: | ENIG, Electrolytic Nickel, Electrolytic Soft & Hard Gold, HASL, Hot Oil Reflow following SnPb plate |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind and Buried Vias, Buried Resistors, Micro Vias, Multiple Laminations |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dy Film, LPI, Wet Mask |
| Controlled Impedance: | Characteristic, Differential, Dual Stripline, Embedded Microstrip, Microstrip, Range 30-150 ohms (+/- 10%) |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | Class A Flex to Install, Class B Continuous |
| Hole Wall Conductive Coating: | Electroless Copper |
| Max. Base Cu Weight | 1 oz. |

VQE-03-003349
 VQE-09-18855
 VQE-10-19456

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: TTM Technologies (Stafford) 4 Old Monson Road P.O. Box 145, Stafford, CT 77497, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 5L706 Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 EMail: michele.hebert@tycoelectroni cs.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/3, MIL-PRF-31032/4, MIL-PRF-31032/Custom |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .07"/Not Specified .11"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | Not Specified/.035" (drilled) .0413"/.0197" (drilled) |
| Aspect Ratio: | 2:1 3.3:1 ((through hole)) |
| Max. Number of Layers: | 11, 12 |
| Min. Conductor Width: | .004" .006" |
| Min. Conductor Space: | .003" .004" |
| Part Mounting: | MIX, Press Fit, SM, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Hydrocarbon with Ceramic Filler PTFE Resin with Ceramic Filler, |
| Flex Base Material: | 4204/1 Acrylic Adhesive |
| Finish System: | ENIG, Electrolytic Nickel, Electrolytic Soft & Hard Gold, HASL, Hot Oil Reflow following SnPb plate |
| Hole Preparation: | Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind and Buried Vias, Buried Resistors, Micro Vias, Multiple Laminations |
| Copper Plating: | Acid Copper |
| Solder Resist: | Dry-Film, LPI, LPI, Dry-Film, Wet Mask, Wet Mask |
| Controlled Impedance: | Characteristic, Differential, Dual Stripline, Embedded Microstrip, Microstrip, Range 30-150 ohms (+/- 10%) |
| Hole Fill/Via Plug: | Conductive, Non-conductive |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Electroless Copper |
| Max. Base Cu Weight | 1 oz. |

VQE-03-003348
 VQE-03-003349
 VQE-10-19456
 VQE-10-19855

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Unicircuit, Inc. 8192 Southpark Lane Littleton, CO 80120, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 66311 Contact: Bob Lageman Phone: 303-730-0505, x110 Fax: EMail: blageman@unicircuit.com |
|---|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|---|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-07-13789 |
| Panel Size: | 12" X 18" | VQE-09-17422 |
| Max./Min. Board Thickness: | .12"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | .129"/.02" | |
| Aspect Ratio: | 6:1 (Through Hole) | |
| Max. Number of Layers: | 16 | |
| Min. Conductor Width: | .005" | |
| Min. Conductor Space: | .005" | |
| Part Mounting: | SMT, THM | |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | HASL, Reflowed Tin Lead | |
| Hole Preparation: | Plasma Etchback | |
| Alternate Construction: | Blind Via, Bured Via, Foil Lamination, Laser-drilled Microvias, Sequential Lamination | |
| Copper Plating: | Electrodeposited Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | 100 ohms differential +/-10%, 53 ohms characteristic +/-7% | |
| Hole Fill/Via Plug: | Conductive, Non-conductive | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |
| Laser Via Hole Size | .006 +/- .001 | |

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-09-17422 |
| Panel Size: | 20" X 26" | |
| Max./Min. Board Thickness: | .19"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | .252"/.029" | |
| Aspect Ratio: | 6.5:1 ((thru hole)) | |
| Max. Number of Layers: | 24 | |
| Min. Conductor Width: | .005" | |
| Min. Conductor Space: | .005" | |
| Part Mounting: | SMT, THM | |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | HASL, Reflowed Tin Lead | |
| Hole Preparation: | Plasma Etchback | |
| Alternate Construction: | N/A | |
| Copper Plating: | Electrodeposited Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | 100 ohms differential +/-10%, 53 ohms characteristic +/-7% | |
| Hole Fill/Via Plug: | Conductive, Non-conductive | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Electroless Copper | |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|---|
| MANUFACTURER INFORMATION: Universal Circuits, Inc. 8860 Zachary Lane North Maple Grove, MN 55369-4524, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 45032 Contact: Phone: Fax: EMail: |
|--|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|---|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .125"/Not Specified .18"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | ".008" ".021" |
| Aspect Ratio: | 7.75:1 8.57:1 |
| Max. Number of Layers: | 16, 18 |
| Min. Conductor Width: | .0032" .005" |
| Min. Conductor Space: | .0032" .005" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant Hybrid GF Hydrocarbon/Ceramic |
| Flex Base Material: | N/A |
| Finish System: | ENIG, HASL |
| Hole Preparation: | Chemical Desmear, Plasma Etchback |
| Alternate Construction: | Blind Vias, Foil Lamination, Sequential Lamination |
| Copper Plating: | Acid Copper |
| Solder Resist: | LPI |
| Controlled Impedance: | Differential 77.5 +/- 7.5, 90 +/- 13.5, 98 +/- 13, 100 +/- 10, 120 +/- 12, 150 +/- 7 ohms, Single-ended 50 +/- 2.5, 55 +/- 5 ohms |
| Hole Fill/Via Plug: | Acid Copper |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | Direct Metallization |
| Through Hole Metallization | Direct Metallization |

VQE-10-019530
 VQE-10-020323

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| MANUFACTURER INFORMATION: Universal Circuits, Inc. 8860 Zachary Lane North Maple Grove, MN 55369-4524, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 45032 Contact: Phone: Fax: EMail: |
|--|--|--|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | | QUALIFICATION LETTERS: |
|--|--|-------------------------------|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 | VQE-10-019530 |
| Panel Size: | 18" X 24" | VQE-11-021326 |
| Max./Min. Board Thickness: | .062"/Not Specified | |
| Max./Min. Base CU Thickness: | N/A | |
| Max./Min. Through Hole Size: | ".0138" | |
| Aspect Ratio: | 4.5:1 | |
| Max. Number of Layers: | 8 | |
| Min. Conductor Width: | .007" | |
| Min. Conductor Space: | .006" | |
| Part Mounting: | SMT | |
| Rigid Base Material: | GI: Glass Base, Woven, Polyimide Resin, Heat Resistant | |
| Flex Base Material: | N/A | |
| Finish System: | ENIG, Electrolytic Ni/Au, HASL | |
| Hole Preparation: | Chemical Desmear, Plasma Etchback | |
| Alternate Construction: | Foil Lamination | |
| Copper Plating: | Acid Copper | |
| Solder Resist: | LPI | |
| Controlled Impedance: | N/A | |
| Hole Fill/Via Plug: | N/A | |
| Flex Usage: | N/A | |
| Hole Wall Conductive Coating: | Direct Metallization | |

**SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY**

| | | |
|--|--|---|
| <p>MANUFACTURER INFORMATION: Vermont Circuits, Inc. 76 Technology Drive P.O. Box 1890, Brattleboro, VT 05302-1890, US</p> | | <p>CAGE Code: 65200 Contact: Bob Downing Phone: 802-257-4571 Fax: 802-257-0011 EMail: Bob.Downing@vtcircuits.com</p> |
|--|--|---|

| CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION | QUALIFICATION LETTERS: |
|--|-------------------------------|
| <p>Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: .1"/Not Specified Max./Min. Base CU Thickness: 1"/.5" Max./Min. Through Hole Size: .04"/.008" ((.0453/.012 Drilled)) Aspect Ratio: 7.5:1 Max. Number of Layers: 10 Min. Conductor Width: .005" Min. Conductor Space: .005" Part Mounting: THM Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant Flex Base Material: N/A Finish System: ENIG, HASL Hole Preparation: Permanganate Desmear, Plasma Desmear, Plasma Etchback Alternate Construction: Foil Lamination Copper Plating: Acid Copper: DC Plate Solder Resist: LPI Controlled Impedance: N/A Hole Fill/Via Plug: N/A Flex Usage: N/A Hole Wall Conductive Coating: Electroless Copper</p> | <p>VQE-10-019275</p> |

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|---|--|---|
| MANUFACTURER INFORMATION: Viasystems Corp. (CA) 355 Turtle Creek Court San Jose, CA 95125-1316, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 0MHG5 Contact: Dave Williams Phone: 408-280-0422 Fax: 408-280-0641 EMail: david.williams@viasystems.com |
|---|--|---|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|---|--------------------------------|
| Specification: MIL-PRF-31032/1, MIL-PRF-31032/2 Panel Size: 18" X 24" Max./Min. Board Thickness: .13"/Not Specified Max./Min. Base CU Thickness: N/A Max./Min. Through Hole Size: .004"/.008" (laser drilled) .25"/.008" (mechanical) Aspect Ratio: 0.8:1 (Blind Vias) 10:1 (Through Hole) Max. Number of Layers: 20 Min. Conductor Width: .004" Min. Conductor Space: .004" Part Mounting: MIX, SMT, THM Rigid Base Material: GF: Woven E-Glass, Epoxy Resin, Flame Resistant GI: Glass Base, Woven, Polyimide Resin, Heat Resistant Flex Base Material: N/A Finish System: ENIG, HASL, Hard Gold, Nickel Hole Preparation: Chemical Desmear, Plasma Desmear, Plasma Etchback Alternate Construction: Blind Vias, Buried Vias, Sequential Lamination Copper Plating: Electrodeposited Acid Copper Solder Resist: LPI Controlled Impedance: 25-125 ohms +/-10% Hole Fill/Via Plug: Non-conductive Flex Usage: N/A Hole Wall Conductive Coating: N/A | VQE-08-016481 VQE-08-016632 |
|---|--------------------------------|

SECTION I
LIST OF MANUFACTURERS' QUALIFIED CAPABILITIES FOR EACH TECHNOLOGY

| | | |
|--|--|--|
| MANUFACTURER INFORMATION: Viasystems Corp. (OR) 1521 Poplar Lane Forest Grove, OR 97116, US | PLANT LOCATION: Same Address as Manufacturer | CAGE Code: 01KV9 Contact: Roger Michalowski Phone: 781-639-5410 Fax: E-Mail: Customerservice@viasystems.com |
|--|--|--|

CAPABILITIES BY TECHNOLOGY/ASSOCIATED SPECIFICATION **QUALIFICATION LETTERS:**

| | |
|-------------------------------|--|
| Specification: | MIL-PRF-31032/1, MIL-PRF-31032/2 |
| Panel Size: | 18" X 24" |
| Max./Min. Board Thickness: | .13"/Not Specified |
| Max./Min. Base CU Thickness: | N/A |
| Max./Min. Through Hole Size: | .003"/Not Specified (Laser Via) ".008" (Mechanical) |
| Aspect Ratio: | 0.8:1 (Blind Vias) 10:1 (Through Hole) |
| Max. Number of Layers: | 26 |
| Min. Conductor Width: | .004" |
| Min. Conductor Space: | .004" |
| Part Mounting: | MIX, SMT, THM |
| Rigid Base Material: | GF: Woven E-Glass, Epoxy Resin, Flame Resistant G: Glass Base, Woven, Polyimide Resin, Heat Resistant |
| Flex Base Material: | N/A |
| Finish System: | ENIG, HASL, Immersion Ag, Ni/Hard-Au |
| Hole Preparation: | Chemical Desmear Permanganate, Plasma Desmear, Plasma Etchback |
| Alternate Construction: | Blind Vias, Laser Drilled Vias |
| Copper Plating: | Electrodeposited Acid Copper |
| Solder Resist: | LPI |
| Controlled Impedance: | Differential Methods $\pm 5\%$ at 50 ohms, Microstrip, Single Ended, Single Line |
| Hole Fill/Via Plug: | N/A |
| Flex Usage: | N/A |
| Hole Wall Conductive Coating: | N/A |

VQ-09-017325

SECTION II
LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION

MIL-PRF-31032/1

Accurate Circuit Engineering

3019 S. Kilson Drive, Santa Ana, CA 92707, US

American Standard Circuits

RF Division, 475 Industrial Drive, West Chicago, IL 60185, US

Amphenol Printed Circuits

91 Northeastern Boulevard, Nashua, NH 03062, US

Calumet Electronics Corp.

25830 Depot Street, Calumet, MI 49913-1985, US

Cirexx International, Inc.

791 Nuttman Street, Santa Clara, CA 95054,

Colonial Circuits, Inc.

1026 Warrenton Road, Fredericksburg, VA 22406-6200, US

Cosmotronic, Inc.

16721 Noyes Avenue, Irvine, CA 92606, US

DDi Cleveland Corp.

7 Ascot Parkway, Cuyahoga Falls, OH 44223, US

DDi Denver Corp.

10570 Bradford Road, Littleton, CO 80127, US

DDi Global Corp. - Anaheim

1220 N. Simon Circle, Anaheim, CA 92806, US

DDi Global Corp. - Sterling, VA

1200 Severn Way, Dulles, VA 20166-8904, US

DDi North Jackson Corp.

12080 DeBartolo Drive, North Jackson, OH 44451, US

DDi Ontario

8150 Sheppard Avenue East, Scarborough, Ontario, Canada M1B 5K2

Dynaco Corp.

1000 South Priest Drive, Tempe, AZ 85281-5238, US

Dynamic & Proto Circuits, Inc.

869 Barton Street, Stoney Creek, Ontario, Canada L8E 5G6

Electro Plate Circuitry, Inc.

1430 Century Drive, Carrollton, TX 75006, US

Electrotek Corp.

7745 S. 10th Street, Oak Creek, WI 53154, US

Endicott Interconnect Technologies, Inc.

Dept. 0069/014-3, 1093 Clark Street, Endicott, NY 13760, US

Firan Technology Group

250 Finchdene Square, Scarborough, Ontario, Canada M1X 1A5

Global Innovations Corp.

901 Hensley Drive, Wylie, TX 75098, US

Hamby Corporation

27704 Avenue Scott, Valencia, CA 91355, US

Hans Brockstedt GmbH

Clara-Immerwahr Strasse 7, 24145 Kiel, Germany

Hughes Circuits

540 S. Pacific Street, San Marcos, CA 92078-4056, US

Lockheed Martin Systems Integration

1801 State Route 17C, Owego, NY 13827, US

Micom Corp.

475 Old Highway 8 NW, New Brighton, MN 55112, US

Philway Products, Inc.

701 Virginia Avenue, Ashland, OH 44806, US

Pioneer Circuits, Inc.

3000 S. Shannon Street, Santa Ana, CA 92704-6321, US

SECTION II
LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION

MIL-PRF-31032/1

PNC, Inc.

115 East Centre Street, Nutley, NJ 07110, US

Pro-Tech Interconnect Solutions

4300 Peavey Road, Chaska, MN 55318-2351, US

Sanmina-SCI (Owego)

1200 Taylor Road, Owego, NY 13827, US

Sanmina-SCI (San Jose)

2050 Bering Drive, San Jose, CA 95131, US

Speedy Circuits, Inc.

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

TTM Technologies (Santa Ana)

2630 South Harbor Boulevard, Santa Ana, CA 92704, US

TTM Technologies (Santa Clara)

400 Matthew Street, Santa Clara, CA 95050, US

TTM Technologies (Stafford)

4 Old Monson Road, P.O. Box 145, Stafford, CT 77497, US

Unicircuit, Inc.

8192 Southpark Lane, Littleton, CO 80120, US

Universal Circuits, Inc.

8860 Zachary Lane North, Maple Grove, MN 55369-4524, US

Vermont Circuits, Inc.

76 Technology Drive, P.O. Box 1890, Brattleboro, VT 05302-1890, US

Viasystems Corp. (CA)

355 Turtle Creek Court, San Jose, CA 95125-1316, US

Viasystems Corp. (OR)

1521 Poplar Lane, Forest Grove, OR 97116, US

SECTION II
LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION

MIL-PRF-31032/2

Accurate Circuit Engineering

3019 S. Kilson Drive, Santa Ana, CA 92707, US

American Standard Circuits

RF Division, 475 Industrial Drive, West Chicago, IL 60185, US

Amphenol Printed Circuits

91 Northeastern Boulevard, Nashua, NH 03062, US

Calumet Electronics Corp.

25830 Depot Street, Calumet, MI 49913-1985, US

Cirexx International, Inc.

791 Nuttman Street, Santa Clara, CA 95054,

Colonial Circuits, Inc.

1026 Warrenton Road, Fredericksburg, VA 22406-6200, US

Cosmotronic, Inc.

16721 Noyes Avenue, Irvine, CA 92606, US

DDi Cleveland Corp.

7 Ascot Parkway, Cuyahoga Falls, OH 44223, US

DDi Denver Corp.

10570 Bradford Road, Littleton, CO 80127, US

DDi Global Corp. - Anaheim

1220 N. Simon Circle, Anaheim, CA 92806, US

DDi Global Corp. - Sterling, VA

1200 Severn Way, Dulles, VA 20166-8904, US

DDi North Jackson Corp.

12080 DeBartolo Drive, North Jackson, OH 44451, US

DDi Ontario

8150 Sheppard Avenue East, Scarborough, Ontario, Canada M1B 5K2

Dynaco Corp.

1000 South Priest Drive, Tempe, AZ 85281-5238, US

Dynamic & Proto Circuits, Inc.

869 Barton Street, Stoney Creek, Ontario, Canada L8E 5G6

Electro Plate Circuitry, Inc.

1430 Century Drive, Carrollton, TX 75006, US

Electrotek Corp.

7745 S. 10th Street, Oak Creek, WI 53154, US

Endicott Interconnect Technologies, Inc.

Dept. 0069/014-3, 1093 Clark Street, Endicott, NY 13760, US

Firan Technology Group

250 Finchdene Square, Scarborough, Ontario, Canada M1X 1A5

Global Innovations Corp.

901 Hensley Drive, Wylie, TX 75098, US

Hamby Corporation

27704 Avenue Scott, Valencia, CA 91355, US

Hans Brockstedt GmbH

Clara-Immerwahr Strasse 7, 24145 Kiel, Germany

Hughes Circuits

540 S. Pacific Street, San Marcos, CA 92078-4056, US

Lockheed Martin Systems Integration

1801 State Route 17C, Owego, NY 13827, US

Micom Corp.

475 Old Highway 8 NW, New Brighton, MN 55112, US

Pioneer Circuits, Inc.

3000 S. Shannon Street, Santa Ana, CA 92704-6321, US

PNC, Inc.

115 East Centre Street, Nutley, NJ 07110, US

SECTION II
LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION

MIL-PRF-31032/2

Pro-Tech Interconnect Solutions

4300 Peavey Road, Chaska, MN 55318-2351, US

Sanmina-SCI (Owego)

1200 Taylor Road, Owego, NY 13827, US

Sanmina-SCI (San Jose)

2050 Bering Drive, San Jose, CA 95131, US

Speedy Circuits, Inc.

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

TTM Technologies (Santa Ana)

2630 South Harbor Boulevard, Santa Ana, CA 92704, US

TTM Technologies (Santa Clara)

400 Matthew Street, Santa Clara, CA 95050, US

TTM Technologies (Stafford)

4 Old Monson Road, P.O. Box 145, Stafford, CT 77497, US

Unicircuit, Inc.

8192 Southpark Lane, Littleton, CO 80120, US

Universal Circuits, Inc.

8860 Zachary Lane North, Maple Grove, MN 55369-4524, US

Vermont Circuits, Inc.

76 Technology Drive, P.O. Box 1890, Brattleboro, VT 05302-1890, US

Viasystems Corp. (CA)

355 Turtle Creek Court, San Jose, CA 95125-1316, US

Viasystems Corp. (OR)

1521 Poplar Lane, Forest Grove, OR 97116, US

SECTION II
LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION

MIL-PRF-31032/3

Amphenol Printed Circuits

91 Northeastern Boulevard, Nashua, NH 03062, US

Cirexx International, Inc.

791 Nuttman Street, Santa Clara, CA 95054,

Colonial Circuits, Inc.

1026 Warrenton Road, Fredericksburg, VA 22406-6200, US

Cosmotronic, Inc.

16721 Noyes Avenue, Irvine, CA 92606, US

DDi Cleveland Corp.

7 Ascot Parkway, Cuyahoga Falls, OH 44223, US

DDi North Jackson Corp.

12080 DeBartolo Drive, North Jackson, OH 44451, US

Dynaco Corp.

1000 South Priest Drive, Tempe, AZ 85281-5238, US

Hamby Corporation

27704 Avenue Scott, Valencia, CA 91355, US

Hans Brockstedt GmbH

Clara-Immerwahr Strasse 7, 24145 Kiel, Germany

KCA Electronics, Inc.

223 North Crescent Way, Anaheim, CA 92801, US

Lockheed Martin Systems Integration

1801 State Route 17C, Owego, NY 13827, US

Pioneer Circuits, Inc.

3000 S. Shannon Street, Santa Ana, CA 92704-6321, US

Printed Circuits, Inc.

1200 West 96th Street, Bloomington, MN 55431, US

Speedy Circuits, Inc.

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

Strataflex Corp.

11 Dohme Avenue, Toronto, Ontario, Canada M4B 1Y7

TTM Technologies (Santa Clara)

400 Matthew Street, Santa Clara, CA 95050, US

TTM Technologies (Stafford)

4 Old Monson Road, P.O. Box 145, Stafford, CT 77497, US

SECTION II
LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION

MIL-PRF-31032/4

Amphenol Printed Circuits

91 Northeastern Boulevard, Nashua, NH 03062, US

Cirexx International, Inc.

791 Nuttman Street, Santa Clara, CA 95054,

Colonial Circuits, Inc.

1026 Warrenton Road, Fredericksburg, VA 22406-6200, US

Cosmotronic, Inc.

16721 Noyes Avenue, Irvine, CA 92606, US

DDi Cleveland Corp.

7 Ascot Parkway, Cuyahoga Falls, OH 44223, US

DDi North Jackson Corp.

12080 DeBartolo Drive, North Jackson, OH 44451, US

Dynaco Corp.

1000 South Priest Drive, Tempe, AZ 85281-5238, US

Hamby Corporation

27704 Avenue Scott, Valencia, CA 91355, US

Hans Brockstedt GmbH

Clara-Immerwahr Strasse 7, 24145 Kiel, Germany

KCA Electronics, Inc.

223 North Crescent Way, Anaheim, CA 92801, US

Lockheed Martin Systems Integration

1801 State Route 17C, Owego, NY 13827, US

Pioneer Circuits, Inc.

3000 S. Shannon Street, Santa Ana, CA 92704-6321, US

Printed Circuits, Inc.

1200 West 96th Street, Bloomington, MN 55431, US

Speedy Circuits, Inc.

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

Strataflex Corp.

11 Dohme Avenue, Toronto, Ontario, Canada M4B 1Y7

TTM Technologies (Santa Clara)

400 Matthew Street, Santa Clara, CA 95050, US

TTM Technologies (Stafford)

4 Old Monson Road, P.O. Box 145, Stafford, CT 77497, US

SECTION II
LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION

MIL-PRF-31032/5

Electro Plate Circuitry, Inc.

1430 Century Drive, Carrollton, TX 75006, US

Sanmina-SCI (San Jose)

2050 Bering Drive, San Jose, CA 95131, US

Speedy Circuits, Inc.

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

SECTION II
LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION

MIL-PRF-31032/6

Electro Plate Circuitry, Inc.

1430 Century Drive, Carrollton, TX 75006, US

Global Innovations Corp.

901 Hensley Drive, Wylie, TX 75098, US

Speedy Circuits, Inc.

5331 McFadden Avenue, Huntington Beach, CA 92649-1204, US

SECTION II
LIST OF MANUFACTURERS BY ASSOCIATED SPECIFICATION

MIL-PRF-31032/Custom

Colonial Circuits, Inc.

1026 Warrenton Road, Fredericksburg, VA 22406-6200, US

Cosmotronic, Inc.

16721 Noyes Avenue, Irvine, CA 92606, US

Endicott Interconnect Technologies, Inc.

Dept. 0069/014-3, 1093 Clark Street, Endicott, NY 13760, US

TTM Technologies (Santa Clara)

400 Matthew Street, Santa Clara, CA 95050, US

TTM Technologies (Stafford)

4 Old Monson Road, P.O. Box 145, Stafford, CT 77497, US

SECTION III
ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS

| | | |
|---|---|---|
| <p>MANUFACTURER INFORMATION: Accurate Circuit Engineering 3019 S. Kilson Drive Santa Ana, CA 92707, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 0MNN9 Contact: James Hofer Phone: 714-546-162 Fax: 714-433-7418 EMail: James@ace-pcb.com</p> |
| <p>MANUFACTURER INFORMATION: American Standard Circuits RF Division, 475 Industrial Drive West Chicago, IL 60185, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 4AA34 Contact: Lori Ryan Phone: 603-639-5438 Fax: EMail: lori@asc-i.com</p> |
| <p>MANUFACTURER INFORMATION: Amphenol Printed Circuits 91 Northeastern Boulevard Nashua, NH 03062, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 57034 Contact: Denise Chevalier Phone: 603-879-3268 Fax: 603-879-2818 EMail: denise.chevalier@amphenol-tcs.com</p> |
| <p>MANUFACTURER INFORMATION: Calumet Electronics Corp. 25830 Depot Street Calumet, MI 49913-1985, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 65337 Contact: Robert Hall Phone: 906-337-1305 Fax: 906-337-5359 EMail: rhall@cec-up.com</p> |
| <p>MANUFACTURER INFORMATION: Cirexx International, Inc. 791 Nuttman Street Santa Clara, CA 95054,</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 4MEG7 Contact: Don Angulo Phone: 408-988-3980 Fax: 408-988-4534 EMail: dangulo@cirexxintl.com</p> |
| <p>MANUFACTURER INFORMATION: Colonial Circuits, Inc. 1026 Warrenton Road Fredericksburg, VA 22406-6200, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 6T499 Contact: Mike Hill Phone: 540-753-5511, x125 Fax: 540-752-2109 EMail: quality@colonialcircuits.com</p> |
| <p>MANUFACTURER INFORMATION: Cosmotronic, Inc. 16721 Noyes Avenue Irvine, CA 92606, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 63695 Contact: Alan Exley Phone: 949-660-0740 Fax: 949-553-8371 EMail: alan_exley@cosmotronic.com</p> |
| <p>MANUFACTURER INFORMATION: DDi Cleveland Corp. 7 Ascot Parkway Cuyahoga Falls, OH 44223, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 7Z463 Contact: Mark Kasting Phone: 330-572-3400 Fax: 330-572-3434 EMail: mark_kasting/coretec@coretec-inc.com</p> |

**SECTION III
ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS**

| | | |
|--|---|---|
| <p>MANUFACTURER INFORMATION: DDi Denver Corp. 10570 Bradford Road Littleton, CO 80127, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 75815 Contact: Douglas N. Berry Phone: 303-972-4105 Fax: 303-933-2934 EMail: dberry@ddiglobal.com</p> |
| <p>MANUFACTURER INFORMATION: DDI Global Corp. - Anaheim 1220 N. Simon Circle Anaheim, CA 92806, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 0BSG1 Contact: Rick Sylvain Phone: 714-688-7371 Fax: EMail: rsylvain@ddiglobal.com</p> |
| <p>MANUFACTURER INFORMATION: DDi Global Corp. - Sterling, VA 1200 Severn Way Dulles, VA 20166-8904, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 0K703 Contact: Juan Vasquez Phone: 703-652-2200 Fax: 703-652-2272 EMail: jvasquez@ddiglobal.com</p> |
| <p>MANUFACTURER INFORMATION: DDi North Jackson Corp. 12080 DeBartolo Drive North Jackson, OH 44451, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 0GN71 Contact: Cynthia Savakis Phone: 330-538-3900, x211 Fax: 330-538-3820 EMail: quality@sovereign-circuits.com</p> |
| <p>MANUFACTURER INFORMATION: DDi Ontario 8150 Sheppard Avenue East Scarborough, Ontario, Canada M1B 5K2</p> | <p>PLANT LOCATIONS: 1. Same Address as Manufacturer 2. Coretec, Inc., CAGE Code: 3AF82, 2020 Ellesmere Road, Scarborough, Ontario, Canada M1H 2Z8</p> | <p>CAGE Code: 3AF82 Contact: Noor Al-Shaikh Phone: 416-208-2100 Fax: 416-439-1582 EMail: alshaikh@coretec-inc.com</p> |
| <p>MANUFACTURER INFORMATION: Dynaco Corp. 1000 South Priest Drive Tempe, AZ 85281-5238, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 61642 Contact: Ted Edwards Phone: 480-736-3728 Fax: 480-921-9830 EMail: tedwards@dynacocorp.com</p> |
| <p>MANUFACTURER INFORMATION: Dynamic & Proto Circuits, Inc. 869 Barton Street Stoney Creek, Ontario, Canada L8E 5G6</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 38898 Contact: Stephen Hazell Phone: 905-643-9900 Fax: 905-643-9911 EMail: stephenhazell@dapc.com</p> |
| <p>MANUFACTURER INFORMATION: Electro Plate Circuitry, Inc. 1430 Century Drive Carrollton, TX 75006, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 79616 Contact: James McNeal Phone: 972-466-0818 Fax: 972-466-9078 EMail: jimmm@eplate.com</p> |

SECTION III
ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS

| | | |
|---|---|---|
| <p>MANUFACTURER INFORMATION: Electrotek Corp. 7745 S. 10th Street Oak Creek, WI 53154, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 66030 Contact: Tom Tikusis Phone: 414-762-1390 Fax: 414-762-1510 EMail: sales@boards4u.com</p> |
| <p>MANUFACTURER INFORMATION: Endicott Interconnect Technologies, Inc. Dept. 0069/014-3, 1093 Clark Street Endicott, NY 13760, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 3ECL3 Contact: Jose Rios Phone: 607-755-5896 Fax: 607-755-4649 EMail: JoseA.Rios@eitny.com</p> |
| <p>MANUFACTURER INFORMATION: Firan Technology Group 250 Finchdene Square Scarborough, Ontario, Canada M1X 1A5</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: L2665 Contact: Bryan Clark Phone: 416-299-4000 Fax: 416-292-4308 EMail: byanclark@firantechnology.com</p> |
| <p>MANUFACTURER INFORMATION: Global Innovations Corp. 901 Hensley Drive Wylie, TX 75098, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 04RV5 Contact: Bob Noland Phone: 214-291-1427 Fax: EMail: b noland@globalinnovationcorp.com</p> |
| <p>MANUFACTURER INFORMATION: Hamby Corporation 27704 Avenue Scott Valencia, CA 91355, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 07284 Contact: Sue Sharp Phone: 661-257-1924 Fax: 661-257-1213 EMail: suesharp@hambycorp.com</p> |
| <p>MANUFACTURER INFORMATION: Hans Brockstedt GmbH Clara-Immerwahr Strasse 7 24145 Kiel, Germany</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: C4831 Contact: Hilmar Klammer Phone: 0049-431-71966-0, -30 Fax: 0049-431-71966-29 EMail: klammer@brockstedt.de</p> |
| <p>MANUFACTURER INFORMATION: Hughes Circuits 540 S. Pacific Street San Marcos, CA 92078-4056, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 1KXU6 Contact: Joe Hughes Phone: 760-744-0300 Fax: 760-744-6388 EMail: joe@hughescircuits.com</p> |
| <p>MANUFACTURER INFORMATION: KCA Electronics, Inc. 223 North Crescent Way Anaheim, CA 92801, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 1VUH8 Contact: Mr. Jeffrey Frost Phone: 714-239-2433 Fax: 714-239-2455 EMail:</p> |

SECTION III
ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS

| | | |
|--|---|---|
| <p>MANUFACTURER INFORMATION: Lockheed Martin Systems Integration 1801 State Route 17C Owego, NY 13827, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 03640 Contact: Melita Nagerl Phone: 607-751-4665 Fax: 607-751-7714 EMail: melita.nagerl@lmco.com</p> |
| <p>MANUFACTURER INFORMATION: Micom Corp. 475 Old Highway 8 NW New Brighton, MN 55112, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 34076 Contact: Larry Leonard Phone: 651-604-2639 Fax: 651-636-1352 EMail: lleonard@micomcircuits.com</p> |
| <p>MANUFACTURER INFORMATION: Philway Products, Inc. 701 Virginia Avenue Ashland, OH 44806, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 21971 Contact: Tom School Phone: 419-281-7777 Fax: 419-289-3447 EMail: quality@philway.com</p> |
| <p>MANUFACTURER INFORMATION: Pioneer Circuits, Inc. 3000 S. Shannon Street Santa Ana, CA 92704-6321, US</p> | | <p>CAGE Code: 65723 Contact: Elias Gabriel Phone: 714-641-3132 x234 Fax: 714-641-3120 EMail:</p> |
| <p>MANUFACTURER INFORMATION: PNC, Inc. 115 East Centre Street Nutley, NJ 07110, US</p> | | <p>CAGE Code: 66766 Contact: Carmela Conte Phone: 973-284-1600 Fax: EMail: carmela@pnconline.com</p> |
| <p>MANUFACTURER INFORMATION: Printed Circuits, Inc. 1200 West 96th Street Bloomington, MN 55431, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 65114 Contact: Jim Smith Phone: 612-888-7900 Fax: 612-888-2719 EMail: jsmith@printedcircuits.com</p> |
| <p>MANUFACTURER INFORMATION: Pro-Tech Interconnect Solutions 4300 Peavey Road Chaska, MN 55318-2351, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 3CP65 Contact: Harland Kooda Phone: 952-442-2189 Fax: 952-442-2472 EMail:</p> |
| <p>MANUFACTURER INFORMATION: Sanmina-SCI (Owego) 1200 Taylor Road Owega, NY 13827, US</p> | | <p>CAGE Code: 4GZ84 Contact: Rick Sylvain Phone: 607-689-5543 Fax: EMail: rick.sylvain@sanmina-sci.com</p> |

SECTION III
ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS

| | | |
|--|---|--|
| <p>MANUFACTURER INFORMATION: Sanmina-SCI (San Jose) 2050 Bering Drive San Jose, CA 95131, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 3DR67 Contact: Darrell Myers Phone: 408-964-6515 Fax: 408-964-6453 EMail: darrell.myers@sanmina-sci.com</p> |
| <p>MANUFACTURER INFORMATION: Speedy Circuits, Inc. 5331 McFadden Avenue Huntington Beach, CA 92649-1204, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 66982 Contact: Jan Lesky Phone: 714-766-6243 Fax: 714-899-7074 EMail:</p> |
| <p>MANUFACTURER INFORMATION: Strataflex Corp. 11 Dohme Avenue Toronto, Ontario, Canada M4B 1Y7</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 38661 Contact: Peter Pialis Phone: 416-752-2224 Fax: 416-752-6719 EMail: ppialis@strataflex.ca</p> |
| <p>MANUFACTURER INFORMATION: TTM Technologies (Santa Ana) 2630 South Harbor Boulevard Santa Ana, CA 92704, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 1WQ42 Contact: Terry Lichte Phone: 714-241-0303, x3127 Fax: 714-241-0708 EMail: tlichte@ttmtech.comca</p> |
| <p>MANUFACTURER INFORMATION: TTM Technologies (Santa Clara) 400 Matthew Street Santa Clara, CA 95050, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 65916 Contact: Nellie Guitierrez Phone: 408-486-3184 Fax: 408-727-1003 EMail: nellie.guitierrez@ttmtech.com</p> |
| <p>MANUFACTURER INFORMATION: TTM Technologies (Stafford) 4 Old Monson Road P.O. Box 145, Stafford, CT 77497, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 5L706 Contact: Michelle Herbert Phone: 860-684-5881 Fax: 860-684-7425 EMail: michele.hebert@tycoelectronics.com</p> |
| <p>MANUFACTURER INFORMATION: Unicircuit, Inc. 8192 Southpark Lane Littleton, CO 80120, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 66311 Contact: Bob Lageman Phone: 303-730-0505, x110 Fax: EMail: blageman@unicircuit.com</p> |
| <p>MANUFACTURER INFORMATION: Universal Circuits, Inc. 8860 Zachary Lane North Maple Grove, MN 55369-4524, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 45032 Contact: Phone: Fax: EMail:</p> |

SECTION III
ALPHABETICAL LIST OF QUALIFIED MANUFACTURERS

| | | |
|--|---|--|
| <p>MANUFACTURER INFORMATION: Vermont Circuits, Inc. 76 Technology Drive P.O. Box 1890, Brattleboro, VT 05302-1890, US</p> | | <p>CAGE Code: 65200 Contact: Bob Downing Phone: 802-257-4571 Fax: 802-257-0011 EMail: Bob.Downing@vtcircuits.com</p> |
| <p>MANUFACTURER INFORMATION: Viasystems Corp. (CA) 355 Turtle Creek Court San Jose, CA 95125-1316, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 0MHG5 Contact: Dave Williams Phone: 408-280-0422 Fax: 408-280-0641 EMail: david.williams@viasystems.com</p> |
| <p>MANUFACTURER INFORMATION: Viasystems Corp. (OR) 1521 Poplar Lane Forest Grove, OR 97116, US</p> | <p>PLANT LOCATION: Same Address as Manufacturer</p> | <p>CAGE Code: 01KV9 Contact: Roger Michalowski Phone: 781-639-5410 Fax: EMail: Customerservice@viasystems.com</p> |