

Specification Details:

Specification: MIL-PRF-39023
 Title: Resistors, Variable, Non-Wire-Wound, Precision
 Federal Supply Class (FSC): 5905
 Conventional: Yes
 Specification contains quality assurance program: No
 MIL-STD-790 Established Reliability & High Reliability: No
 MIL-STD-690 Failure Rate Sampling Plans & Procedures: No
 Weibull Graded: No
 Specification contains space level reliability requirements: No
 Specification allows test optimization: No

Contact Information:

Office of Primary Involvement: Passive Devices Branch, DLA Land and Maritime - VQP
 Primary Qualifying Activity Contact: 614-692-0597, e-mail: vqp.jz@dla.mil
 Secondary Qualifying Activity Contact: 614-692-0609, e-mail: vqp.do@dla.mil

Notes:

N/A

Part Configuration:

RQ090AA12AB103

Style	Temp Character	Shaft Length	Moisture Resistance	Life Character	Tolerance Character	Output-Smoothness Character	Resistance
RQ090	A	A	1	2	A	B	103

PART LISTINGS

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFICATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RQ051* Res. temp. char. C; shaft length G; life char. 5; moist. res. char. 2; func. conformity tol. chars. A; output-smoothness char. F; nom. total res. value 5 kilohms	1020-561-3	39023-192-86	/10	BEI Sensors
RQ051 Res. temp. char. C; shaft length G; life char. 5; moist. res. char. 2; func. conformity tol. chars. A; output-smoothness char. F; nom. total res. value 5 kilohms	55FL1-130-01	39023-846-83	/10	Honeywell - New England Instruments Div.
RQ090* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	2211	39023-803-76	/1	BEI Sensors
RQ090* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	1221	39023-4-77	/1	BEI Sensors
RQ090* Res. temp. char. A; shaft length A, B, C, D; life char. 1, 2, 3, 4; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	78FLI, 78FS, 78SF	39023-526-77	/1	Honeywell - New England Instruments Div.
RQ090* Res. temp. char. A, B; shaft length A, B, C, D; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	WP7/8M	39023-308-73	/1	Honeywell S&C

PART LISTINGS

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFICATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RQ091* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	2212	39023-803-76	/9	BEI Sensors
RQ091* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	1222	39023-4-77	/9	BEI Sensors
RQ091* Res. temp. char. A; shaft length A, B, C, D, E, F; life char. 1, 2, 3, 4; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	78BF, 78FL,	39023-526-77	/9	Honeywell - New England Instruments Div.
RQ091* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	WP7/8M	39023-308-73	/9	Honeywell S&C
RQ100* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E; output-smoothness char. A, B, C, D, E; nom. total res. values 1 ohm thru 1 megohm	4211	39023-804-76	/6	BEI Sensors
RQ110* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	2311	39023-803-76	/2	BEI Sensors
RQ110 Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	1321	39023-4-77	/2	BEI Sensors
RQ110* Res. temp. char. A; shaft length A, B, C, D; life char. 1, 2, 3, 4; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	116FL, 116FTS, 116SF	39023-526-77	/2	Honeywell - New England Instruments Div.
RQ150* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	2511	39023-803-76	/3	BEI Sensors
RQ150* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 2; func. conformity tol. chars. A, B, C, D, E; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	1521	39023-4-77	/3	BEI Sensors
RQ150* Res. temp. char. A; shaft length A, B, C, D, E, F; life char. 1, 2, 3, 4; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	176FL, 176FTS, 176SF	39023-526-77	/3	Honeywell - New England Instruments Div.
RQ150* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	WP1 7/16-M	39023-309-73	/3	Honeywell S&C

PART LISTINGS

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFICATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RQ160* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E; output-smoothness char. A, B, C, D, E; nom. total res. values 1 kilohm thru 3 megohms	4511	39023-804-76	/7	BEI Sensors
RQ200* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3, 4; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E, F; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	2711	2711	/4	BEI Sensors
RQ200* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3, 4; moist. res. char. 2; func. conformity tol. chars. A, B, C, D, E, F; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	1721	39023-4-77	/4	BEI Sensors
RQ200* Res. temp. char. A; shaft length A, B, C, D, E, F; life char. 1, 2, 3, 4; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E, F; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	200FL, 200FTS, 200SF	39023-526-77	/4	Honeywell - New England Instruments Div.
RQ200* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E, F; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	WP2-M	39023-309-73	/4	Honeywell S&C
RQ210* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 2, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E, F; output-smoothness char. A, B, C, D, E; nom. total res. values 1 kilohm thru 3 megohms	4711	39023-804-76	/8	BEI Sensors
RQ300* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E, F; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	2811	39023-803-76	/5	BEI Sensors
RQ300* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 3; moist. res. char. 2; func. conformity tol. chars. A, F; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	1821	39023-4-77	/5	BEI Sensors
RQ300* Res. temp. char. A; shaft length A, B, C, D, E, F; life char. 1, 4; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E, F; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	300FL, 300FTS, 300SF	39023-526-77	/5	Honeywell - New England Instruments Div.
RQ300* Res. temp. char. A, B; shaft length A, B, C, D, E, F; life char. 1, 3; moist. res. char. 1, 2; func. conformity tol. chars. A, B, C, D, E, F; output-smoothness char. A, B, C, D, E; nom. total res. values 100 ohms thru 1 megohm	WP3-M	39023-309-73	/5	Honeywell S&C

Manufacturer and Supplier Location Information

Manufacturer: BEI Sensors (CAGE Code: 11534)

Location: 7230 Hollister Avenue, Goleta, CA 93117, US

Plants:

1. Plant: Same Address as Manufacturer

Manufacturer: Honeywell - New England Instruments Div. (CAGE Code: 08815)

Location: 245 Railroad Steet, Woonsocket, RI 02895, US

Plants:

1. Plant: Same Address as Manufacturer

Manufacturer: Honeywell S&C (CAGE Code: 12697)

Location: 12220 Rojos Drive, Suite SC, El Paso, TX 79936-7713, US

Plants:

1. Honeywell Optoelectronica S DE RL DE CV, Parque Industrial Juarez #3328, Cd. Juarez, Mex. C.P. 32630, Mexico