



DEFENSE LOGISTICS AGENCY
 DEFENSE SUPPLY CENTER, COLUMBUS
 3990 EAST BROAD STREET
 COLUMBUS, OH 43216-5000

IN REPLY
 REFER TO
 2003

DSCC-VQ (VQP-03-003030 revised /Mr. Parshall/614-692-0666)

April 14,

SUBJECT: Notification of Qualification, MIL-PRF-55681/9, FSC 5910

Ms. Christine Pollock
 Presidio Components, Inc.
 P.O. Box 81576
 San Diego, CA 92138-1576

Dear Ms. Pollock:

Qualification of your products is granted under the current issue of the subject specification as a result of successful qualification testing in accordance with the test report number listed in the Qualification Reference section below. Therefore, your products will be listed as shown below on Qualified Products List (QPL) 55681.

Government Designation	Manufacturer's Designation	Test or Qualification Reference	Manufacturer's Name and Address
CDR04 1200 thru 3300pf. tols. J, and K , 100 volts BP rated temp. and volt. temp. limits term M, S, U, Z life failure rate M, P, R, S 39000 thru 180000pf. tols. K, M , 50 and 100 volts BX rated temp. and volt. temp. limits term M, S, U, Z life failure rate M, P, R, S	55681-04	55681-049-00	Presidio Component, Inc. P. O Box 81576 San Diego, CA 92138-1576
CDR05 3900 thru 5600pf. tols. J, and K , 100 volts BP rated temp. and volt. temp. limits term M, S, U, Z life failure rate M, P, R, S 68000 thru 330000pf. tols. K, M , 50 and 100 volts BX rated temp. and volt. temp. limits term M, S, U, Z life failure rate M, P, R, S	55681-05	55681-049-00	
CDR34 2200 thru 4700pf. tols. J, and K , 100 volts BP rated temp. and volt. temp. limits term M, S, U, Z life failure rate M, P, R, S 27000 thru 180000pf. tols. K, M , 50 and 100 volts	55681-34	55681-049-00	

BX rated temp. and volt. temp. limits
term M, S, U, Z life failure rate M, P, R, S

2

<u>Government Designation</u>	<u>Manufacturer's Designation</u>	<u>Test or Qualification Reference</u>	<u>Manufacturer's Name and Address</u>
CDR35	55681-35	55681-049-00	

4700 thru 22000pf. tols. F,J,K , 50 and 100 volts
BP rated temp. and volt. temp. limits
term M, S, U, Z life failure rate M, P, R, S
180000 thru 470000pf. tols. K, M , 50 volts
BX rated temp. and volt. temp. limits
term M, S, U, Z life failure rate M, P, R, S

This qualification approval is subject to the conditions as stated in DoD 4120.3M and SD-6.

To maintain the listing of the products on QPL 55681, you are required to submit a report at six (6) month intervals to DSCC-VQP. This report shall consist of a summary of the results of the tests performed for inspection of product for delivery (Groups A) and a summary of the results of tests performed for verification of qualification inspection (Group C). This is in accordance with paragraph 4.4.5 of MIL-PRF-55681. In the event there is no production during the reporting periods, you are required to submit a report of no production.

The standard reporting period is from October 1 through March 31. Your first reporting period for these products is from the date of this letter through March 31, 2003. A report is required for each of your products qualified to the subject military specification. The original data must be retained by your company and is to be made available to authorized government representatives upon request. Please coordinate your summary with your government quality representative and submit it directly to us in time to arrive by April 30, 2003.

Because we are held responsible for the accuracy and currency of this QPL, please let us know if your company discontinues production of the products listed above. No changes are to be made in the design and construction of the products qualified without approval of the Defense Supply Center, Columbus.

This letter acts as a letter of delegation for your local QAR to survey your facility for compliance as necessary.

Sincerely,

/Signed/

L. DARRELL HILL
Chief

Sourcing and Qualifications Unit