

REVISIONS

LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Make changes to V _{OS} , I _{IB} , and I _{OS} test limits as specified under Table IA. Add new footnote 3/ to TC _{VOS} , TC _{IIB} , TC _{IOS} parameters as specified under Table IA. Make changes to V _{OS} and I _S tests as specified under Table IIB. - ro	15-12-14	C. SAFFLE
B	Make change to the Input offset current (I _{OS}) post radiation limit by deleting 10 nA and replacing with 6 nA as specified under Table IA. - ro	16-05-17	C. SAFFLE
C	Drawing updated to reflect current MIL-PRF-38535 requirements. -rrp	21-05-24	J. ESCHMEYER




REV																				
SHEET																				
REV	C	C	C	C																
SHEET	15	16	17	18																
REV STATUS OF SHEETS	REV			C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	
	SHEET			1	2	3	4	5	6	7	8	9	10	11	12	13	14			

PMIC N/A	PREPARED BY RICK OFFICER	<p align="center">DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990 https://www.dla.mil/LandandMaritime</p>																	
<p align="center">STANDARD MICROCIRCUIT DRAWING</p> <p>THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE</p> <p align="center">AMSC N/A</p>	CHECKED BY RAJESH PITHADIA																		
	APPROVED BY CHARLES F. SAFFLE	<p align="center">MICROCIRCUIT, LINEAR, OPERATIONAL AMPLIFIER, QUAD, 40 V, LOW POWER, MONOLITHIC SILICON</p>																	
	DRAWING APPROVAL DATE 12-09-04																		
	REVISION LEVEL C	SIZE A	CAGE CODE 67268	5962-12228															
		SHEET		1 OF 18															

1. SCOPE

1.1 Scope. This drawing documents two product assurance class levels consisting of high reliability (device class Q) and space application (device class V). A choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). When available, a choice of Radiation Hardness Assurance (RHA) levels is reflected in the PIN.

1.2 PIN. The PIN is as shown in the following example:



1.2.1 RHA designator. Device classes Q and V RHA marked devices meet the MIL-PRF-38535 specified RHA levels and are marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	ISL70417SEH	Quad, 40 V, low power operational amplifier

1.2.3 Device class designator. The device class designator is a single letter identifying the product assurance level as follows:

<u>Device class</u>	<u>Device requirements documentation</u>
Q or V	Certification and qualification to MIL-PRF-38535

1.2.4 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

<u>Outline letter</u>	<u>Descriptive designator</u>	<u>Terminals</u>	<u>Package style</u>
X	CDFP3-F14	14	Flat pack

1.2.5 Lead finish. The lead finish is as specified in MIL-PRF-38535 for device classes Q and V.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 2

1.3 Absolute maximum ratings. 1/

Maximum supply voltage	42 V 2/
Maximum differential Input current	20 mA
Maximum differential input voltage	20 V
Minimum/maximum input voltage	-VS – 0.5 V to +VS + 0.5 V
Maximum/minimum input current for input voltage > +VS or < -VS	±20 mA
Output short circuit duration (1 output at a time)	Indefinite
Power dissipation (PD) :	
At +25°C	1.19 W
At +125°C	238 mW
Maximum junction temperature (TJ)	+150°C
Lead temperature (soldering, 10 seconds)	+300°C
Storage temperature range	-65°C to +150°C
Thermal resistance, junction-to-ambient (θJA)	105°C/W 3/
Thermal resistance, junction-to-case (θJC)	15°C/W 4/

1.4 Recommended operating conditions.

Supply voltage	4.5 V to 30 V
Split supply voltage (-VS, +VS)	± 2.25 V to ±15 V
Ambient operating temperature range (TA)	-55°C to +125°C

1.5 Radiation features.

Maximum total dose available (dose rate = 50 – 300 rads(Si)/s)	300 krads(Si) 5/
Maximum total dose available (dose rate ≤ 0.01 rads(Si)/s)	50 krad(Si) 5/
Single event phenomenon (SEP) features:	
No Single event latchup (SEL) occurs at effective LET (see 4.4.4.2)	≤ 73.9 MeV/mg/cm ² 6/
No Single event burnout (SEB) occur at effective LET (see 4.4.4.2)	≤ 73.9 MeV/mg/cm ² 6/

1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.

2/ For applications that operate in a heavy ion environment, the 42 V absolute maximum rating decreases to 40 V.

3/ θJA is measured with the component mounted on a low effective thermal conductivity test board in free air.

4/ For θJC, the case temperature location is the center of the exposed metal pad on the package underside.

5/ The device type 01 radiation end point limits for the noted parameters are guaranteed only for the conditions as specified in MIL-STD-883, method 1019, condition A to a maximum total dose of 300 krads(Si), and condition D to a maximum total dose of 50 krads(Si).

6/ Limits are characterized at initial qualification and after any design or process changes which may affect the SEP characteristics but are not production tested unless specified by the customer through the purchase order or contract. For more information on SEE test results customers are requested to contact manufacturer.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 3

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-883 - Test Method Standard Microcircuits.
 MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

DEPARTMENT OF DEFENSE HANDBOOKS

MIL-HDBK-103 - List of Standard Microcircuit Drawings.
 MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these documents are available online at <https://quicksearch.dla.mil>).

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL (ASTM)

ASTM F1192 - Standard Guide for the Measurement of Single Event Phenomena (SEP) Induced by Heavy Ion Irradiation of semiconductor Devices.

(Copies of these documents are available online at <https://www.astm.org>).

2.3 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 as specified herein, or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein.

3.1.1 Microcircuit die. For the requirements of microcircuit die, see appendix A to this document.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein for device classes Q and V.

3.2.1 Case outline. The case outline shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.3 Radiation exposure circuit. The radiation exposure circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing and acquiring activity upon request.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table IA and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table IIA. The electrical tests for each subgroup are defined in table IA.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 4

TABLE IA. Electrical performance characteristics.

Test	Symbol	Conditions <u>1/</u> <u>2/</u> -55°C ≤ TA ≤ +125°C ±VS = ±15 V unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Offset voltage	VOS		1	01		85	μV
			2,3			110	
			M,D,P,L,R,F		1	110	
Offset voltage drift	TCVOS	<u>3/</u>	2,3	01		1	μV/°C
Input bias current	IIB		1	01	-2.5	+2.5	nA
			2,3		-5	+5	
			M,D,P,L,R,F		1	-15	
Input bias current temperature coefficient	TCIIB	<u>3/</u>	2,3	01	-5	+5	pA/°C
Input offset current	IOS		1	01	-2.5	2.5	nA
			2,3		-3	3	
			M,D,P,L,R,F		1	-6	
Input offset current temperature coefficient	TCIOS	<u>3/</u>	2,3	01	-3	+3	pA/°C
Input voltage range	VCM	Guaranteed by CMRR	1,2,3	01	-13	13	V
Common mode rejection ratio	CMRR	VCM = -13 V to +13 V	1,2,3	01	120		dB
Power supply rejection ratio	PSRR	VS = ±2.25 V to ±20 V	1,2,3	01	120		dB
Open loop gain	AOL	VO = -13 V to +13 V, RL = 10 kΩ to ground	1,2,3	01	3000		V/mV
Output voltage high	VOH	RL = 10 kΩ to ground	1	01	13.5		V
			2,3		13.2		
			M,D,P,L,R,F		1	13.2	
		RL = 2 kΩ to ground	1		13.3		
			2,3		13.0		
			M,D,P,L,R,F		1	13.0	

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 5

TABLE IA. Electrical performance characteristics – Continued.

Test	Symbol	Conditions <u>1/ 2/</u> -55°C ≤ TA ≤ +125°C ±VS = ±15 V unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Output voltage low	VOL	RL = 10 kΩ to ground	1	01		-13.5	V
			2,3			-13.2	
			M,D,P,L,R,F		1		
		RL = 2 kΩ to ground	1			-13.3	
			2,3			-13.0	
			M,D,P,L,R,F		1		
Supply current/amplifier	IS		1	01		0.53	mA
			2,3			0.68	
			M,D,P,L,R,F		1		
Supply voltage range	VSUPPLY	Guaranteed by PSRR	1,2,3	01	±2.25	±20	V
Transient response section							
Slew rate	SR	AV = 11 , RL = 2 kΩ, VO = 4 VPP	4	01	0.3		V/μs
			5,6		0.2		
			M,D,P,L,R,F		4	0.2	
Small signal rise time, 10% to 90% of VOUT	tr	AV = -1, VOUT = 50 mVPP, RL = 10 kΩ to VCM	9	01		450	ns
			10,11			625	
			M,D,P,L,R,F		9		
Small signal fall time, 90% to 10% of VOUT	tf	AV = -1, VOUT = 50 mVPP, RL = 10 kΩ to VCM	9	01		600	ns
			10,11			700	
			M,D,P,L,R,F		9		
Positive overshoot	+OS	AV = 1, VOUT = 10 VPP, Rf = 0 Ω, RL = 2 kΩ to VCM	4,5,6	01		33	%
Negative overshoot	-OS	AV = 1, VOUT = 10 VPP, Rf = 0 Ω, RL = 2 kΩ to VCM	4,5,6	01		33	%

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 6

TABLE IA. Electrical performance characteristics – Continued.

Test	Symbol	Conditions <u>1/ 2/</u> -55°C ≤ TA ≤ +125°C ±Vs = ±5 V unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Offset voltage	VOS		1	01		150	μV
			2,3			250	
			M,D,P,L,R,F		1	250	
Offset voltage drift	TCVOS	<u>3/</u>	2,3	01		1	μV/°C
Input bias current	IIB		1	01	-2.5	+2.5	nA
			2,3		-5	+5	
			M,D,P,L,R,F		1	-15	
Input bias current temperature coefficient	TCIIB	<u>3/</u>	2,3	01	-5	+5	pA/°C
Input offset current	IOS		1	01	-2.5	2.5	nA
			2,3		-3	3	
			M,D,P,L,R,F		1	-10	
Input offset current temperature coefficient	TCIOS	<u>3/</u>	2,3	01	-3	+3	pA/°C
Input voltage range	VCM	Guaranteed by CMRR	1,2,3	01	-3	3	V
Common mode rejection ratio	CMRR	VCM = -3 V to +3 V	1,2,3	01	120		dB
Power supply rejection ratio	PSRR	Vs = ±2.25 V to ±5 V	1,2,3	01	120		dB
Open loop gain	AOL	VO = -3 V to +3 V, RL = 10 kΩ to ground	1,2,3	01	3000		V/mV
Output voltage high	VOH	RL = 10 kΩ to ground	1	01	3.5		V
			2,3		3.2		
			M,D,P,L,R,F		1	3.2	
		RL = 2 kΩ to ground	1		3.3		
			2,3		3.0		
			M,D,P,L,R,F		1	3.0	

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 7

TABLE IA. Electrical performance characteristics – Continued.

Test	Symbol	Conditions <u>1/ 2/</u> -55°C ≤ TA ≤ +125°C ±Vs = ±5 V unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Output voltage low	VOL	RL = 10 kΩ to ground	1	01		-3.5	V
			2,3			-3.2	
		M,D,P,L,R,F	1			-3.2	
		RL = 2 kΩ to ground	1			-3.3	
			2,3			-3.0	
			M,D,P,L,R,F		1	-3.0	
Supply current/amplifier	IS		1	01		0.53	mA
			2,3			0.68	
			M,D,P,L,R,F		1		

1/ Unless otherwise specified, V_{CM} = 0 V, V_O = 0 V.

2/ RHA devices supplied to this drawing meet levels L, R, and F of irradiation for condition A and levels P and L for condition D. However, devices are only tested at the F level in accordance with MIL-STD-883, method 1019, condition A and the L level in accordance with MIL-STD-883, method 1019, condition D (see 1.5 herein).
When performing post irradiation electrical measurements for any RHA level, TA = +25°C (see 1.5 herein).

3/ This parameter is guaranteed but not tested. The limits are characterized at initial qualification and after any design or process changes which may affect the product characteristics but are not production tested.

TABLE IB. SEP test limits. 1/ 2/ 3/ 4/

Device type	SEP	Temperature (Tc)	Bias Vs	Linear energy transfer (LET)
01	No SEL	125°C	20 V	Effective LET ≤ 73.9 MeV/mg/cm ²
	No SEB	125°C	20 V	LET ≤ 73.9 MeV/mg/cm ²

1/ For single event phenomena (SEP) test conditions, see 4.4.4.2 herein.

2/ Technology characterization and model verification supplemented by in-line data may be used in lieu of end of line testing. Test plan must be approved by the technical review board and qualifying activity.

3/ For SEB test Xe ion is used at angle 45° and fluence = 2.0 x10⁶ particles/cm² and cross section = 5.0x10⁻⁷ cm².

4/ Limits are characterized at initial qualification and after any design or process changes which may affect the SEP characteristics but, not production tested unless specified by the customer through the purchase order or contract. For more information on SEE test results, customers are requested to contact manufacturer.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 8

Device type	01	
Case outline	X	
Terminal number	Terminal symbol	Description
1	OUTPUT A	Amplifier A output.
2	-INPUT A	Amplifier A inverting input.
3	+INPUT A	Amplifier A non-inverting input.
4	+Vs	Positive power supply.
5	+INPUT B	Amplifier B non-inverting input.
6	-INPUT B	Amplifier B inverting input.
7	OUTPUT B	Amplifier B output.
8	OUTPUT C	Amplifier C output.
9	-INPUT C	Amplifier C inverting input.
10	+INPUT C	Amplifier C non-inverting input.
11	-Vs	Negative power supply.
12	+INPUT D	Amplifier D non-inverting input.
13	-INPUT D	Amplifier D inverting input.
14	OUTPUT D	Amplifier D output.

FIGURE 1. Terminal connections.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 9

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked. For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device. For RHA product using this option, the RHA designator shall still be marked. Marking for device classes Q and V shall be in accordance with MIL-PRF-38535.

3.5.1 Certification/compliance mark. The certification mark for device classes Q and V shall be a "QML" or "Q" as required in MIL-PRF-38535.

3.6 Certificate of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.6.1 herein). The certificate of compliance submitted to DLA Land and Maritime-VA prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and herein.

3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 shall be provided with each lot of microcircuits delivered to this drawing.

4. VERIFICATION

4.1 Sampling and inspection. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein.

4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection.

4.2.1 Additional criteria for device classes Q and V.

- a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.
- b. Interim and final electrical test parameters shall be as specified in table IIA herein.
- c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in MIL-PRF-38535, appendix B.

4.3 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-PRF-38535. Inspections to be performed shall be those specified in MIL-PRF-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4 Conformance inspection. Technology conformance inspection for classes Q and V shall be in accordance with MIL-PRF-38535 including groups A, B, C, D, and E inspections, and as specified herein.

4.4.1 Group A inspection.

- a. Tests shall be as specified in table IIA herein.
- b. Subgroups 7 and 8 in table I, method 5005 of MIL-STD-883 shall be omitted.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 10

TABLE IIA. Electrical test requirements.

Test requirements	Subgroups (in accordance with MIL-PRF-38535, table III)	
	Device class Q	Device class V
Interim electrical parameters (see 4.2)	1,4,9	1,4,9
Final electrical parameters (see 4.2)	1,2,3,4,5,6, <u>1/</u> 9,10,11	1,2,3,4,5,6, <u>1/ 2/</u> 9,10,11
Group A test requirements (see 4.4)	1,2,3,4,5,6, 9,10,11	1,2,3,4,5,6, 9,10,11
Group C end-point electrical parameters (see 4.4)	1,2,3,4,5,6, 9,10,11	1,2,3,4,5,6, <u>2/</u> 9,10,11
Group D end-point electrical parameters (see 4.4)	1,4,9	1,4,9
Group E end-point electrical parameters (see 4.4)	1,4,9	1,4,9

1/ PDA applies to subgroup 1 for class Q and subgroups 1 and Δ for class V.

2/ Delta limits as specified in table IIB shall be required where specified, and the delta limits shall be completed with reference to the zero hour electrical parameters (see table IA).

TABLE IIB. Burn-in and operating life test delta parameters. T_A = +25°C. 1/

Parameters	Symbol	Delta limits		Units
		Min	Max	
Offset voltage	VOS	-40	+40	μV
Input bias current	IIB	-1	+1	nA
Input offset current	IOS	-1	+1	nA
Supply current	IS	-200	+200	μA

1/ Deltas are performed at room temperature.

4.4.2 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table IIA herein.

4.4.2.1 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.

4.4.3 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table IIA herein.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 11

4.4.4 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein).

- a. End-point electrical parameters shall be as specified in table IIA herein.
- b. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535 for the RHA level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table IA at $T_A = +25^{\circ}\text{C} \pm 5^{\circ}\text{C}$, after exposure, to the subgroups specified in table IIA herein.

4.4.4.1 Total dose irradiation testing. Total dose irradiation testing shall be performed in accordance with MIL-STD-883 method 1019 condition A and D as specified herein.

4.4.4.2 Single event phenomena (SEP). When specified in the purchase order or contract, SEP testing shall be performed on class V devices. SEP testing shall be performed on the Standard Evaluation Circuit (SEC) or alternate SEP test vehicle as approved by the qualifying activity at initial qualification and after any design or process changes which may affect the upset or latchup characteristics. Test four devices with zero failures. ASTM F1192 may be used as a guideline when performing SEP testing. The test conditions for SEP are as follows:

- a. The ion beam angle of incidence shall be between normal to the die surface and 60° to the normal, inclusive (i.e. $0^{\circ} \leq \text{angle} \leq 60^{\circ}$). No shadowing of the ion beam due to fixturing or package related affects is allowed.
- b. The fluence shall be ≥ 100 errors or $\geq 8 \times 10^6$ ions/cm².
- c. The flux shall be between 10^2 and 10^5 ions/cm²/s. The cross-section shall be verified to be flux independent by measuring the cross-section at two flux rates which differ by at least an order of magnitude.
- d. The particle range shall be ≥ 20 micron in silicon.
- e. The test temperature shall be $125^{\circ}\text{C} \pm 10\%$ for SEB and SEL.
- f. Bias conditions shall be $V_S = 20$ V maximum for the latchup measurements.
- g. For SEL and SEB test limits, see Table IB herein.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535 for device classes Q and V.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor prepared specification or drawing.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

6.3 Record of users. Military and industrial users should inform DLA Land and Maritime when a system application requires configuration control and which SMD's are applicable to that system. DLA Land and Maritime will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DLA Land and Maritime-VA, telephone (614) 692-8108.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 12

6.4 Comments. Comments on this drawing should be directed to DLA Land and Maritime-VA, Columbus, Ohio 43218-3990, or telephone (614) 692-0540.

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535 and MIL-HDBK-1331.

6.6 Sources of supply.

6.6.1 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in MIL-HDBK-103 and QML-38535. The vendors listed in MIL-HDBK-103 and QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DLA Land and Maritime-VA and have agreed to this drawing.

6.7 Additional information. When applicable, a copy of the following additional data shall be maintained and available from the device manufacturer:

- a. RHA upset levels.
- b. Test conditions (SEP).
- c. Occurrence of latchup (SEL).
- d. Number of burnouts (SEB).


STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 13

APPENDIX A
APPENDIX A FORMS A PART OF SMD 5962-12228

A.1 SCOPE

A.1.1 Scope. This appendix establishes minimum requirements for microcircuit die to be supplied under the Qualified Manufacturers List (QML) Program. QML microcircuit die meeting the requirements of MIL-PRF-38535 and the manufacturers approved QM plan for use in monolithic microcircuits, multi-chip modules (MCMs), hybrids, electronic modules, or devices using chip and wire designs in accordance with MIL-PRF-38534 are specified herein. Two product assurance classes consisting of military high reliability (device class Q) and space application (device class V) are reflected in the Part or Identification Number (PIN). When available, a choice of Radiation Hardness Assurance (RHA) levels are reflected in the PIN.

A.1.2 PIN. The PIN is as shown in the following example:



A.1.2.1 RHA designator. Device classes Q and V RHA identified die meet the MIL-PRF-38535 specified RHA levels. A dash (-) indicates a non-RHA die.

A.1.2.2 Device type(s). The device type(s) identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	ISL70417SEH	Quad, 40 V, low power operational amplifier

A.1.2.3 Device class designator.

<u>Device class</u>	<u>Device requirements documentation</u>
Q or V	Certification and qualification to the die requirements of MIL-PRF-38535

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 14

APPENDIX A
APPENDIX A FORMS A PART OF SMD 5962-12228

A.1.2.4 Die details. The die details designation is a unique letter which designates the die's physical dimensions, bonding pad location(s) and related electrical function(s), interface materials, and other assembly related information, for each product and variant supplied to this appendix.

A.1.2.4.1 Die physical dimensions.

<u>Die type</u>	<u>Figure number</u>
01	A-1

A.1.2.4.2 Die bonding pad locations and electrical functions.

<u>Die type</u>	<u>Figure number</u>
01	A-1

A.1.2.4.3 Interface materials.

<u>Die type</u>	<u>Figure number</u>
01	A-1

A.1.2.4.4 Assembly related information.

<u>Die type</u>	<u>Figure number</u>
01	A-1

A.1.3 Absolute maximum ratings. See paragraph 1.3 herein for details.

A.1.4 Recommended operating conditions. See paragraph 1.4 herein for details.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 15

APPENDIX A
APPENDIX A FORMS A PART OF SMD 5962-12228

A.2 APPLICABLE DOCUMENTS.

A.2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

DEPARTMENT OF DEFENSE STANDARD

MIL-STD-883 - Test Method Standard Microcircuits.

DEPARTMENT OF DEFENSE HANDBOOKS

MIL-HDBK-103 - List of Standard Microcircuit Drawings.

MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these documents are available online at <https://quicksearch.dla.mil>).

A.2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

A.3 REQUIREMENTS

A.3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 and as specified herein or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein.

A.3.2 Design, construction and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein and the manufacturer's QM plan for device classes Q and V.

A.3.2.1 Die physical dimensions. The die physical dimensions shall be as specified in A.1.2.4.1 and on figure A-1.

A.3.2.2 Die bonding pad locations and electrical functions. The die bonding pad locations and electrical functions shall be as specified in A.1.2.4.2 and on figure A-1.

A.3.2.3 Interface materials. The interface materials for the die shall be as specified in A.1.2.4.3 and on figure A-1.

A.3.2.4 Assembly related information. The assembly related information shall be as specified in A.1.2.4.4 and on figure A-1.

A.3.2.5 Radiation exposure circuit. The radiation exposure circuit shall be as defined in paragraph 3.2.3 herein.

A.3.3 Electrical performance characteristics and post-irradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and post-irradiation parameter limits are as specified in table IA of the body of this document.

A.3.4 Electrical test requirements. The wafer probe test requirements shall include functional and parametric testing sufficient to make the packaged die capable of meeting the electrical performance requirements in table IA.

A.3.5 Marking. As a minimum, each unique lot of die, loaded in single or multiple stack of carriers, for shipment to a customer, shall be identified with the wafer lot number, the certification mark, the manufacturer's identification and the PIN listed in A.1.2 herein. The certification mark shall be a "QML" or "Q" as required by MIL-PRF-38535.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 16

APPENDIX A
APPENDIX A FORMS A PART OF SMD 5962-12228

A.3.6 Certification of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see A.6.4 herein). The certificate of compliance submitted to DLA Land and Maritime -VA prior to listing as an approved source of supply for this appendix shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and the requirements herein.

A.3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 shall be provided with each lot of microcircuit die delivered to this drawing.

A.4 VERIFICATION

A.4.1 Sampling and inspection. For device classes Q and V, die sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modifications in the QM plan shall not affect the form, fit, or function as described herein.

A.4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and as defined in the manufacturer's QM plan. As a minimum, it shall consist of:

- a. Wafer lot acceptance for class V product using the criteria defined in MIL-STD-883, method 5007.
- b. 100% wafer probe (see paragraph A.3.4 herein).
- c. 100% internal visual inspection to the applicable class Q or V criteria defined in MIL-STD-883, method 2010 or the alternate procedures allowed in MIL-STD-883, method 5004.

A.4.3 Conformance inspection.

A.4.3.1 Group E inspection. Group E inspection is required only for parts intended to be identified as radiation assured (see A.3.5 herein). RHA levels for device classes Q and V shall be as specified in MIL-PRF-38535. End point electrical testing of packaged die shall be as specified in table II herein. Group E tests and conditions are as specified in paragraphs 4.4.4, 4.4.4.1, and 4.4.4.2 herein.

A.5 DIE CARRIER

A.5.1 Die carrier requirements. The requirements for the die carrier shall be accordance with the manufacturer's QM plan or as specified in the purchase order by the acquiring activity. The die carrier shall provide adequate physical, mechanical and electrostatic protection.

A.6 NOTES

A.6.1 Intended use. Microcircuit die conforming to this drawing are intended for use in microcircuits built in accordance with MIL-PRF-38535 or MIL-PRF-38534 for government microcircuit applications (original equipment), design applications, and logistics purposes.


A.6.2 Comments. Comments on this appendix should be directed to DLA Land and Maritime -VA, Columbus, Ohio, 43218-3990 or telephone (614)-692-0540.

A.6.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535 and MIL-HDBK-1331.

A.6.4 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed within MIL-HDBK-103 and QML-38535 have submitted a certificate of compliance (see A.3.6 herein) to DLA Land and Maritime -VA and have agreed to this drawing.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 17

APPENDIX A
 APPENDIX A FORMS A PART OF SMD 5962-12228



Die bonding pad locations and electrical functions

Die physical dimensions.

Die size: 2028 μm x 2568 μm (80 mils x 101 mils)

Die thickness: 483 μm \pm 25 μm (19 mils \pm 1 mil)

Interface materials.

Top metallization: AlCu (99.5% / 0.5%)

Backside metallization: Silicon

Glassivation.

Type: Nitrox

Thickness: 15 kÅ

Top metallization:

Type AlCu (99.5% / 0.5%)

Thickness: 30 kÅ

Substrate: Single crystal silicon

Assembly related information.

Substrate potential: Floating

Special assembly instructions: None

FIGURE A-1. Die bonding pad locations and electrical functions - continued.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-12228
		REVISION LEVEL C	SHEET 18

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 21-05-24

Approved sources of supply for SMD 5962-12228 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DLA Land and Maritime-VA. This information bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535. DLA Land and Maritime maintains an online database of all current sources of supply at <https://landandmaritimeapps.dla.mil/programs/smcr/>.

Standard microcircuit drawing PIN <u>1/</u>	Vendor CAGE number	Vendor similar PIN <u>2/</u>
5962F1222801VXC	34371	ISL70417SEHVF
5962F1222801V9A	34371	ISL70417SEHVX

- 1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.
- 2/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE number

34371

Vendor name and address

Renesas Electronics America, Inc.
1650 Robert J. Conlan Blvd. NE
Palm Bay, FL 32905-3406

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.